

The **tugboat** package*

The *TUGboat* team
(Distributed by Robin Fairbairns)

2007/09/19

Contents

1	Document preambles	2
2	Introduction	2
2.1	Summary of control sequences	2
3	\LaTeX 2ϵ <i>TUGboat</i> class file	6
3.1	Setup and options	6
3.2	Resetting at start of paper	9
3.3	Helpful shorthand (common code with Plain styles)	9
3.4	Abbreviations and logos	11
3.5	General typesetting rules	14
3.6	Utility registers and definitions	15
3.7	Ragged right and friends	17
3.8	Reviews	19
3.9	Dates, volume and issue numbers, etc.	20
3.10	Page dimensions, glue, penalties etc	24
3.11	Messing about with the \LaTeX logo	24
3.12	Authors, contributors, addresses, signatures	25
3.13	Section titles	32
3.14	Headings	35
3.15	Appendices	38
3.16	References	39
3.17	Title references	40
3.18	Float captions	41
3.19	Size changing commands	41
3.20	Lists and other text inclusions	42
3.21	Some fun with <code>verbatim</code>	42
3.22	Bibliography	44
3.23	Registration marks	47

*This file has version number v2.4, last revised 2007/09/19

3.24	Running heads	48
3.25	Output routine	48
3.26	Font-related definitions and machinery	49
3.27	Miscellaneous definitions	50
3.28	Initialization	51
4	L^AT_EX 2_ε Proceedings class	52
4.1	Proceedings titles	54
4.2	Section divisions	59
5	Plain T_EX styles	60
6	The L^AT_EX 2_ε compatibility-mode style files	60
	tugboat.dtx - main source for LaTeX TUGboat classes.	

1 Document preambles

```

1 <|tugboatcls | ltugproccls | ltugcomn>\NeedsTeXFormat{LaTeX2e}[1994/12/01]
2 <*dtx>
3 \ProvidesFile                {tugboat.dtx}
4 </dtx>
5 <|tugboatcls>\ProvidesClass  {ltugboat}
6 <|tugproccls>\ProvidesClass  {ltugproc}
7 <|tugboatsty>\ProvidesPackage{ltugboat}
8 <|tugprocsty>\ProvidesPackage{ltugproc}
9 <|tugcomn>   \ProvidesPackage{ltugcomn}
10              [2007/09/19 v2.4
11 <|tugboatcls>                TUGboat journal class%
12 <|tugproccls>                TUG conference proceedings class%
13 <|tugboatsty | ltugprocsty>   TUG compatibility package%
14 <|tugcomn>                   TUGboat 'common macros' package%
15 <*dtx>
16                               TUG macros source file%
17 </dtx>
18 ]
19 <*dtx>
20 \newif\ifoldlongtable
21 </dtx>

```

2 Introduction

This file contains all the macros for typesetting *TUGboat* with both plain T_EX and L^AT_EX 2_ε.

2.1 Summary of control sequences

Abbreviations. Just a listing with indications of expansion where that may not be obvious. For full definitions, see real code below (Section 3.4).

<code>\AllTeX</code>	(\mathbb{A}) $\mathrm{T}_{\mathrm{E}}\mathrm{X}$
<code>\AMS</code>	American Mathematical Society
<code>\AmSTeX</code>	
<code>\aw</code>	A-W (abbreviation for Addison-Wesley)
<code>\AW</code>	Addison-Wesley
<code>\BibTeX</code>	
<code>\CandT</code>	Computers & Typesetting
<code>\ConTeXt</code>	Con $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ t
<code>\Cplusplus</code>	C++
<code>\DTD</code>	
<code>\DVI</code>	
<code>\DVD</code>	
<code>\DVIPDFMx</code>	DVIPDFM <i>x</i>
<code>\DVItOVDU</code>	DVItOVDU
<code>\eTeX</code>	ε - $\mathrm{T}_{\mathrm{E}}\mathrm{X}$
<code>\Ghostscript</code>	
<code>\Hawaii</code>	Hawai'i
<code>\HTML</code>	
<code>\ISBN</code>	ISBN
<code>\ISO</code>	
<code>\ISSN</code>	ISSN
<code>\JTeX</code>	
<code>\JoT</code>	The Joy of $\mathrm{T}_{\mathrm{E}}\mathrm{X}$
<code>\LaTeX</code>	
<code>\MacOSX</code>	Mac OS X
<code>\MathML</code>	
<code>\Mc</code>	M with raised c
<code>\MF</code>	METAFONT
<code>\mf</code>	METAFONT
<code>\MFB</code>	The Metafont book
<code>\MP</code>	METAPOST
<code>\mp</code>	MetaPost (in text only: remains ‘ \mp ’ in maths)
<code>\OMEGA</code>	Omega ‘logo’ (Ω)
<code>\OCP</code>	Omega compiled process
<code>\OTP</code>	Omega translation process
<code>\mtex</code>	multilingual $\mathrm{T}_{\mathrm{E}}\mathrm{X}$
<code>\NTS</code>	New Typesetting System
<code>\pcMF</code>	pcMF
<code>\PCTeX</code>	
<code>\pcTeX</code>	
<code>\Pas</code>	Pascal
<code>\PiCTeX</code>	
<code>\plain</code>	plain (in typewriter font)
<code>\POBox</code>	P. O. Box
<code>\PS</code>	PostScript (with hyphenation)
<code>\SC</code>	Steering Committee

<code>\SGML</code>	SGML
<code>\SliTeX</code>	
<code>\slMF</code>	Metafont (slanted) — deprecated: use <code>\textsl</code> instead
<code>\stTeX</code>	T _E X for the Atari ST
<code>\SVG</code>	
<code>\TANGLE</code>	
<code>\TB</code>	The T _E Xbook
<code>\TeX</code>	(Although nearly every package defines this, most — including plain — are missing the space-factor adjustment)
<code>\TeXhax</code>	
<code>\TeXMaG</code>	(defunct)
<code>\TeXtures</code>	
<code>\TeXXeT</code>	
<code>\Thanh</code>	
<code>\TFM</code>	TFM
<code>\TUB</code>	<i>TUGboat</i>
<code>\TUG</code>	T _E X Users Group
<code>\UNIX</code>	
<code>\UTF</code>	
<code>\VAX</code>	
<code>\VorTeX</code>	
<code>\XeT</code>	
<code>\XeTeX</code>	reflected and lowered first ‘E’
<code>\XeLaTeX</code>	with extra space before ‘L’
<code>\XML</code>	
<code>\WEB</code>	
<code>\WEAVE</code>	

Macros for things that are slightly more significant.

<code>\NoBlackBoxes</code>	turns off marginal rules marking overfull boxes
<code>\BlackBoxes</code>	turns them back on
<code>\newline</code>	horizontal glue plus a break
<code>\ifundefined#1</code>	checks argument with <code>\csname</code> against <code>\relax</code>
<code>\topsmash</code>	smashes above baseline (from AMSTeX)
<code>\botsmash</code>	smashes below baseline (from AMSTeX)
<code>\smash</code>	smashes both (from plain)
<code>\ulap</code>	lap upwards
<code>\dlap</code>	lap downwards
<code>\xlap</code>	reference point at center horizontally; 0 width
<code>\ylap</code>	reference point at center vertically; 0 height, depth
<code>\zlap</code>	combination <code>\xlap</code> and <code>\ylap</code>
<code>\basezero</code>	to avoid insertion of <code>baselineskip</code> and <code>lineskip</code> glue

<code>\nullhrule</code>	empty <code>\hrule</code>
<code>\nullvrule</code>	empty <code>\vrule</code>
<code>\makestrut[#1;#2]</code>	ad hoc struts; #1=height, #2=depth
<code>\today</code>	today's date
<code>\SetTime</code>	converts <code>\time</code> to hours, minutes
<code>\now</code>	displays time in hours and minutes
<code>\Now</code>	shows current date and time
<code>\ifPrelimDraft</code>	flag to indicate status as preliminary draft
<code>\rtitlex</code>	<i>TUGboat</i> volume and number info for running head
<code>\midrttitle</code>	information for center of running head
<code>\HorzR@gisterRule</code>	pieces of registration marks ('trimmarks')
<code>\DownShortR@gisterRule</code>	
<code>\UpShortR@gisterRule</code>	
<code>\ttopregister</code>	top registration line with 'T' in center
<code>\tbotregister</code>	bottom registration line with inverted 'T' in center
<code>\topregister</code>	register actually used
<code>\botregister</code>	
<code>\raggedskip</code>	parameters used for ragged settings
<code>\raggedstretch</code>	
<code>\raggedparfill</code>	
<code>\raggedspaces</code>	
<code>\raggedright</code>	
<code>\raggedleft</code>	
<code>\raggedcenter</code>	
<code>\normalspaces</code>	
<code>\raggedbottom</code>	
<code>\bull</code>	square bullet
<code>\cents</code>	'cents' sign
<code>\Dag</code>	superscripted dagger
<code>\careof</code>	c/o
<code>\sfrac</code>	slashed fraction (arguments optionally separated by a slash)
<code>\cs</code>	control sequence name <code>\cs{name}→\name</code>
<code>\env</code>	environment name <code>\env{name}→\begin{name}</code>
<code>\meta</code>	meta-argument name <code>\meta{name}→⟨name⟩</code>
<code>\dash</code>	en-dash surrounded by thinspaces; only breakable AFTER
<code>\Dash</code>	em-dash, as above
<code>\hyph</code>	permit automatic hyphenation after an actual hyphen
<code>\slash</code>	'breakable' slash

<code>\nth</code>	for obtaining ‘1 st ’, ‘2 nd ’, 3 rd , etc.
<code>\tubissue</code>	gets <code>\TUB</code> followed by volume and issue numbers
<code>\xEdNote</code>	Editor’s Note:
<code>\Review:</code>	Review: (for title of book review article)
<code>\reviewitem</code>	begin data for item being reviewed
<code>\revauth</code>	with one argument, author(s) of item being reviewed
<code>\revtitle</code>	with one argument, title of ...
<code>\revpubinfo</code>	with one argument, other info pertaining to ...
<code>\endreviewitem</code>	end data for item being reviewed
<code>\booktitle</code>	with one argument, format book title in text
<code>\Input</code>	<code>\input</code> with some other bookkeeping for case where multiple articles are put together
<code>\TBremark</code>	reminder to <i>TUGboat</i> editorial staff
<code>\TBEnableRemarks</code>	enable <code>\TBremarks</code> (normally suppressed)
<code>\pagexref</code>	used to write out page numbers to screen and external files
<code>\pagexrefON</code>	
<code>\pagexrefOFF</code>	
<code>\xref to</code>	used for symbolic cross-reference to other pages
<code>\xref toON</code>	in <i>TUGboat</i>
<code>\xref toOFF</code>	
<code>\TBdriver</code>	marks code which only takes effect when articles are run together in a driver file
<code>\signaturemark</code>	items for signatures
<code>\signaturewidth</code>	

3 L^AT_EX 2_ε *TUGboat* class file

3.1 Setup and options

Check for reloading. Hmm... Does this happen with L^AT_EX 2_ε classes? Probably, in fact, as well that it doesn’t, since the `\tugstyinit` referenced here doesn’t exist; however, it’s possible that we might need a similar mechanism in the future, so we retain its skeleton, without fleshing out the `\tugstyinit` bones.

```

22 <*\tugboatcls>
23 \csname tugstyloaded@ \endcsname
24 \def\tugstyloaded@{\tugstyinit\endinput}

```

Acquire a name for this class if we don’t already have one (by virtue of having been loaded by `tugproc.cls`). This name will be used in error messages and the like.

```

25 \providecommand{\@tugclass}{\tugboat}

```

Warnings/error messages/information messages — if we’re using L^AT_EX 2_ε we can use the `\Class*` commands:

```

26 \def\TBInfo{\ClassInfo{\@tugclass}}

```

```

27 \def\TError{\ClassError{\@tugclass}}
28 \def\TWarning{\ClassWarning{\@tugclass}}
29 \def\TWarningNL{\ClassWarningNoLine{\@tugclass}}

```

Some trivial options, just flicking switches, etc.

```

30 \newif\ifpreprint
31 \def\preprint{\preprinttrue}
32 \DeclareOption{draft}{%
33   \AtEndOfClass{%
34     \setcounter{page}{1001}%
35     \BlackBoxes
36     \def\MakeRegistrationMarks{}%
37     \PrelimDrafttrue
38   }%
39 }
40 \DeclareOption{preprint}{%
41   \preprinttrue
42 }
43 \DeclareOption{final}{%
44   \AtEndOfClass{%
45     \NoBlackBoxes
46     \PrelimDraftfalse
47   }%
48 }

```

The rules dictate that the output should be set using a 10pt base font.

```

49 \DeclareOption{11pt}{%
50   \TWarning{The \@tugclass\space class only supports 10pt fonts:
51     \MessageBreak option \CurrentOption\space ignored}%
52 }
53 \DeclareOption{12pt}{\csname ds@11pt\endcsname}

```

Similarly, ignore one/two-side/column

```

54 \DeclareOption{oneside}{\TWarning{Option \CurrentOption\space ignored}}
55 \DeclareOption{twoside}{\ds@oneside}
56 \DeclareOption{onecolumn}{\ds@oneside}
57 \DeclareOption{twocolumn}{\ds@oneside}

```

There are these people who seem to think `tugproc` is an option rather than a class... (Note that it's already been filtered out if we were calling from `ltugproc`.)

```

58 \DeclareOption{tugproc}{%
59   \TWarning{Option \CurrentOption\space ignored: use class ltugproc
60     instead of \@tugclass}%
61 }

```

Option `rawcite` (the default) specifies the default citation mechanism (as built-in to \LaTeX); option `harvardcite` specifies the author-date citation mechanism defined in section 3.22 below.

```

62 \DeclareOption{rawcite}{\let\if@Harvardcite\iffalse}
63 \DeclareOption{harvardcite}{\let\if@Harvardcite\iftrue}

```

Option `extralabel` (the default) specifies that the publication years of two successive references with otherwise identical labels will be tagged with distinguishing letters; option `noextralabel` causes those letters to be suppressed. Note that (a) no two references will in any case have the same labels in the default (plain) `rawcite` setup, and that (b) the distinguishing letters appear in the labels themselves — the even remotely intelligent reader should be able to work out the correspondence one with the other...

```
64 \DeclareOption{extralabel}{\let\UseExtraLabel\@firstofone}
65 \DeclareOption{noextralabel}{\let\UseExtraLabel\@gobble}
```

The section-numbering style, so that we can allow the same heading layout as in the plain macros.

```
66 \DeclareOption{numbersec}{\let@if@numbersec@iftrue}
67 \DeclareOption{nonumber}{\let@if@numbersec@iffalse}
```

Any other options, we pass on to `article.cls` before we load it:

```
68 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
```

Request default options (draft mode, standard citation, double-sided printing), process all options, and then get the base document class on top of which we reside.

```
69 \ExecuteOptions{draft,extralabel,numbersec,rawcite}
70 \ProcessOptions
71 \LoadClass[twoside]{article}
```

Various fonts used throughout. Some effort has been made to suppress these things with explicit sizes in the macro name (`\tensl` is an example below), but keeping in step with the documentation is one thing that restricts such a move.

```
72 \def\sectitlefont{\fontfamily\sfddefault\fontseries{bx}\fontshape{n}%
73     \fontsize\@xviipt\stbaselineskip\selectfont}
74 \def\tensl{\fontseries{m}\fontshape{sl}\fontsize\@xpt\@xipt
75     \selectfont}
```

This font selection command is used *only* for the ‘Editor’s Note’ introduction to notes; sadly it makes explicit reference to CMR, and Barbara Beeton has agreed that the reference may be constructed to use the current family such that, if no upright italic is defined, ordinary italics are used. A project for later...

```
76 \def\EdNoteFont{\fontfamily{cmr}\fontseries{m}\fontshape{ui}%
77     \selectfont}
78 \ltugboatcls
```

If Ulrik Vieth’s `mflogo.sty` is around, we’ll use it. Otherwise (pro tem, at least) we’ll warn the user and define the absolute minimum of machinery that *TUGboat* requires (that which was used prior to the invention of L^AT_EX 2_ε).

```
79 \<common>
80 \IfFileExists{mflogo.sty}%
81     {\RequirePackage{mflogo}}%
82 \ltugcomn {\TBWarning
```



```

83 <ltugcomn> {\PackageWarning{ltugcomn}
84     {Package mflogo.sty not available --\MessageBreak
85     Proceeding to emulate mflogo.sty}
86 \DeclareRobustCommand\logofamily{%
87     \not@math@alphabet\logofamily\relax
88     \fontencoding{U}\fontfamily{logo}\selectfont}
89 \DeclareTextFontCommand{\textlogo}{\logofamily}
90 \def\MF{\textlogo{META}}\-\textlogo{FONT}\@}
91 \def\MP{\textlogo{META}}\-\textlogo{POST}\@}
92 \DeclareFontFamily{U}{logo}{-}
93 \DeclareFontShape{U}{logo}{m}{n}{%
94     <8><9>gen*logo%
95     <10><10.95><12><14.4><17.28><20.74><24.88>logo10%
96 }{}
97 \DeclareFontShape{U}{logo}{m}{sl}{%
98     <8><9>gen*logosl%
99     <10><10.95><12><14.4><17.28><20.74><24.88>logosl10%
100 }{}
101 \DeclareFontShape{U}{logo}{m}{it}{%
102     <->ssub*logo/m/sl%
103 }{}%
104 }

```

3.2 Resetting at start of paper

`\ResetCommands` We store a set of commands that should be executed at the start of each paper, before any paper-specific customisation. These commands (stored in the token register `\ResetCommands`) include things such as resetting section and footnote numbers, re-establishing default settings of typesetting parameters, and so on. The user (or more typically, editor) may execute the commands by using the command `\StartNewPaper`. Things I've not yet thought of may be added to the list of commands, by

```

105 \newtoks\ResetCommands
106 \ResetCommands{%
107     \setcounter{part}{0}%
108     \setcounter{section}{0}%
109     \setcounter{footnote}{0}%
110     \authornumber\z@
111 }
112 \newcommand{\AddToResetCommands}[1]{%
113     \AddToResetCommands\expandafter{\AddToResetCommands#1}%
114 }

```

3.3 Helpful shorthand (common code with Plain styles)

`\makescape`, ..., `\makecomment` allow users to change the category code of a single character a little more easily. These require that the character be addressed as a control sequence: e.g., `\makescape\` will make `'/'` an escape character.

```

115 <!\latex>
116 \def\makeescape#1{\catcode'#1=0 }
117 \def\makebgroup#1{\catcode'#1=1 }
118 \def\makeegroup#1{\catcode'#1=2 }
119 \def\makemath #1{\catcode'#1=3 }
120 </!\latex>
121 <!\latex>
122 \def\makeescape#1{\catcode'#1=\z@}
123 \def\makebgroup#1{\catcode'#1=\@ne}
124 \def\makeegroup#1{\catcode'#1=\tw@}
125 \def\makemath #1{\catcode'#1=\thr@@}
126 </!\latex>
127 \def\makealign #1{\catcode'#1=4 }
128 \def\makeeol #1{\catcode'#1=5 }
129 \def\makeparm #1{\catcode'#1=6 }
130 \def\makesup #1{\catcode'#1=7 }
131 \def\makesub #1{\catcode'#1=8 }
132 \def\makeignore#1{\catcode'#1=9 }
133 \def\makespace #1{\catcode'#1=10 }
134 \def\makeletter#1{\catcode'#1=11 }
135 \chardef\other=12
136 \let\makeother\@makeother
137 \def\makeactive#1{\catcode'#1=13 }
138 \def\makecomment#1{\catcode'#1=14 }

```

`\savecat#1` and `\restorecat#1` will save and restore the category of a given character. These are useful in cases where one doesn't wish to localize the settings and therefore be required to globally define or set things.

```

139 \def\savecat#1{%
140   \expandafter\xdef\csname\string#1savedcat\endcsname{\the\catcode'#1}}
141 \def\restorecat#1{\catcode'#1=\csname\string#1savedcat\endcsname}
142 <!\latex>\savecat\@
143 <!\latex>\makeletter\@

```

`\SaveCS#1` and `\RestoreCS#1` save and restore 'meanings' of control sequences. Again this is useful in cases where one doesn't want to localize or where global definitions clobber a control sequence which is needed later with its 'old' definition.

```

144 \def\SaveCS#1{\expandafter\let\csname saved@@#1\expandafter\endcsname
145   \csname#1\endcsname}
146 \def\RestoreCS#1{\expandafter\let\csname#1\expandafter\endcsname
147   \csname saved@@#1\endcsname}

```

To distinguish between macro files loaded

```

148 \def\plaintubstyle{plain}
149 \def\largetubstyle{latex}

```

Control sequences that were first defined in L^AT_EX 2_ε of 1995/06/01 (or later), but which we merrily use. Only define if necessary:

```

150 \providecommand\hb@xt@{\hbox to}

```

```

151 \providecommand\textsuperscript[1]{\ensuremath{\m@th
152             ^{\mbox{\fontsize\sf@size\z@
153             \selectfont #1}}}}

```

(Note that that definition of `\textsuperscript` isn't robust, but probably doesn't need to be... What's more, it doesn't appear in the mythical 2.09 version of the package.)

3.4 Abbreviations and logos

Font used for the METAFONT logo, etc.

```

154 \def\AllTeX{(\La\kern-.075em)\kern-.075emTeX}
155 \def\AMS{American Mathematical Society}
156 \def\AmS{$\mathcal{A}$\kern-.1667em\lower.5ex\hbox
157     {$\mathcal{M}$}\kern-.125em$\mathcal{S}$}
158 \def\AmSLaTeX{\AmS-\LaTeX}
159 \def\AmSTeX{\AmS-\TeX}
160 \def\ANSI{\acro{ANSI}}
161 \def\ASCII{\acro{ASCII}}
162 \def\aw{A\kern.1em-W}
163 \def\AW{Addison\kern.1em-\penalty\z@\hskip\z@skip Wesley}
164 %
165 % make \BibTeX work in slanted contexts too; it's common in titles, and
166 % especially burdensome to hack in .bib files.
167 \def\BibTeX{%
168     \ifdim \fontdimen1\font>0pt
169         B{\SMC\SMC IB}%
170     \else
171         \textsc{Bib}\kern-.08em
172     \fi
173     \TeX}
174 %
175 \def\CandT{\textsl{Computers \& Typesetting}}

```

We place our `\kern` after `\-` so that it disappears if the hyphenation is taken:

```

176 \newcommand\ConTeXt{C\kern-.0333em\on{-}\kern-.0667em\TeX\kern-.0333emt}
177 \newcommand\Cplusplus{C\plusplus}
178 \newcommand\plusplus{\raisebox{.7ex}{$_{++}$}}
179 \def\CSS{\acro{CSS}}
180 \def\CTAN{\acro{CTAN}}
181 \def\DTD{\acro{DTD}}
182 \def\DVD{\acro{DVD}}
183 \def\DVI{\acro{DVI}}
184 \def\DVIPDFMx{\acro{DVIPDFM}$x$}
185 \def\DVItOVDU{DVItO\kern-.12em VDU}
186 \DeclareRobustCommand\epsilon{\ensuremath{\varepsilon}-\kern-.125em\TeX}
187 \def\FAQ{\acro{FAQ}}
188 \def\FTP{\acro{FTP}}
189 \def\Ghostscript{Ghost\script}
190 \def\GNU{\acro{GNU}}

```

```

191 \def\GUI{\acro{GUI}}
192 \def\Hawaii{Hawai'i}
193 \def\HTML{\acro{HTML}}
194 \def\HTTP{\acro{HTP}}
195 \def\IEEE{\acro{IEEE}}
196 \def\ISBN{\acro{ISBN}}
197 \def\ISO{\acro{ISO}}
198 \def\ISSN{\acro{ISSN}}
199 \def\JPEG{\acro{JPEG}}
200 \def\JTeX{\leavevmode\hbox{\lower.5ex\hbox{J}\kern-.18em\TeX}}
201 \def\JoT{\textsl{The Joy of \TeX}}
202 \def\LAMSTeX{L\raise.42ex\hbox{\kern-.3em
203     $\m@th$\fontsize\sf@size\z@\selectfont
204     $\m@th\mathcal{A}$}%
205     \kern-.2em\lower.376ex\hbox{$\m@th\mathcal{M}$}\kern-.125em
206     {$\m@th\mathcal{S}$}-\TeX}
207 % This code
208 % is hacked from its definition of \cs{LaTeX}; it allows slants (for
209 % example) to propagate into the raised (small) 'A':
210 % \begin{macrocode}
211 \newcommand{\La}%
212     {\L\kern-.36em
213     {\setbox0\hbox{T}%
214     \vbox to\ht0{\hbox{$\m@th$%
215         \csname S@\f@size\endcsname
216         \fontsize\sf@size\z@
217         \math@fontsfalse\selectfont
218         A}%
219         \vss}%
220     }}

```

We started with the intention that we wouldn't redefine `\LaTeX` when we're running under it, so as not to trample on an existing definition. However, this proves less than satisfactory; a single logo may be OK for the run of documents, but for *TUGboat*, we find that something noticeably better is necessary; see section 3.11.

```

221 <!!latex>\def\LaTeX{\La\kern-.15em\TeX}
222 \def\MacOSX{Mac\,\acro{OS\,X}}
223 \def\MathML{Math\acro{ML}}
224 \def\Mc{\setbox\TestBox=\hbox{M}\vbox
225     to\ht\TestBox{\hbox{c}\vfil}} % for Robert McGaffey

```

If we're running under $\text{\LaTeX 2}_{\varepsilon}$, we're using (at least pro tem) Ulrik Vieth's `mflogo.sty` if it's present. Otherwise, we're using a short extract of Vieth's stuff. Either way, we don't need to specify `\MF` or `\MP`

```

226 \def\mf{\textsc{Metafont}}
227 \def\MFB{\textsl{The \MF book}}
228 \let\TB@\mp\mp
229 \DeclareRobustCommand\mp{\ifmmode\TB@\mp\else MetaPost\fi}
230 %

```

```

231 % In order that the \cs{OMEGA} command will switch to using the TS1
232 % variant of the capital Omega character if \texttt{textcomp.sty} is
233 % loaded, we define it in terms of the \cs{textohm} command. Note
234 % that this requires us to interpose a level of indirection, rather
235 % than to use \cs{let}\dots
236 %
237 % \begin{macrocode}
238 \DeclareTextSymbol{\textohm}{OT1}{'012}
239 \DeclareTextSymbolDefault{\textohm}{OT1}
240 \newcommand\OMEGA{\textohm}
241 \DeclareRobustCommand\OCP{\OMEGA\acro{CP}}
242 \DeclareRobustCommand\OTP{\OMEGA\acro{TP}}
243 \def\mtex{T\kern-.1667em\lower.424ex\hbox{\^E}\kern-.125emX\@}

Revised definition of \NTS based on that used by Phil Taylor.

244 \DeclareRobustCommand\NTS{\ensuremath{\mathcal{N}}\mkern-4mu
245 \raisebox{-0.5ex}{\mathcal{T}}\mkern-2mu \mathcal{S}}
246 \def\Pas{Pascal}
247 \def\pcMF{\leavevmode\raise.5ex\hbox{p\kern-.3\p@ c}MF\@}
248 \def\PCTeX{PC\thinspace\TeX}
249 \def\pcTeX{\leavevmode\raise.5ex\hbox{p\kern-.3\p@ c}\TeX}
250 \def\PDF{\acro{PDF}}
251 \def\PiC{P\kern-.12em\lower.5ex\hbox{I}\kern-.075emC\@}
252 \def\PiCTeX{\PiC\kern-.11em\TeX}
253 \def\PGF{\acro{PGF}}
254 \def\plain{\texttt{plain}}
255 \def\PNG{\acro{PNG}}
256 \def\POBox{P.\thinspace 0.\~Box }
257 \def\PS{{Post}\-Script}}
258 \def\PSTricks{\acro{PST}ricks}
259 \def\RTF{\acro{RTF}}
260 \def\SC{Steering Committee}
261 \def\SGML{\acro{SGML}}
262 \def\SliTeX{\textrm{S}\kern-.06em\textsc{l}\kern-.035em}%
263 \kern-.06em\TeX}
264 \def\slMF{\textsl{MF}} % should never be used
265 \def\stTeX{\textsc{st}\kern-0.13em\TeX}
266 \def\STIX{\acro{STIX}}
267 \def\SVG{\acro{SVG}}
268 \def\TANGLE{\texttt{TANGLE}\@}
269 \def\TB{\textsl{The \TeX book}}
270 \def\TIFF{\acro{TIFF}}
271 \def\TP{\textsl{\TeX}: \textsl{The Program}}
272 \DeclareRobustCommand\TeX{T\kern-.1667em\lower.424ex\hbox{E}\kern-.125emX\@}
273 \def\TeXhax{\TeX hax}
274 \def\TeXMaG{\TeX M\kern-.1667em\lower.5ex\hbox{A}}%
275 \kern-.2267emG\@}
276 \def\TeXtures{\textit{Textures}}
277 \let\Textures=\TeXtures
278 \def\TeXXeT{\TeX-}\XeT}

```

```

279 \def\TFM{\acro{TFM}}
280 \def\Thanh{H\`an~Th\`e\llap{\raise 0.5ex\hbox{\`{}}}\`Th\`anh}
281 \def\TikZ{Ti{\em k}Z}
282 \def\ttn{\textsl{TTN}\@}
283 \def\TTN{\textsl{\TeX} and TUG News}}
284 \let\texttub\textsl % redefined in other situations
285 \def\TUB{\texttub{TUGboat}}
286 \def\TUG{\TeX\ UG}
287 \def\tug{\acro{TUG}}
288 \def\UG{Users Group}
289 \def\UNIX{\acro{UNIX}}
290 \def\UTF{\acro{UTF}}
291 \def\VAX{V\kern-.12em A\kern-.1em X\@}
292 \def\VorTeX{V\kern-2.7\p@\lower.5ex\hbox{0\kern-1.4\p@ R}\kern-2.6\p@\TeX}
293 \def\XeT{X\kern-.125em\lower.424ex\hbox{E}\kern-.1667emT\@}
294 \def\XML{\acro{XML}}
295 \def\WEB{\texttt{WEB}\@}
296 \def\WEAVE{\texttt{WEAVE}\@}

```

XeTeX requires reflecting the first E, hence we complain if the graphics package is not present. (For plain documents, this can be loaded via Eplain.) Also, at Barbara's suggestion, if the current font is slanted, we rotate by 180 instead of reflecting so there is at least a chance to look ok. (The magic values here seem more or less ok for cmsl and cmti.)

```

297 \def\tubreflect#1{%
298   \@ifundefined{reflectbox}{%
299     \TBerror{A graphics package must be loaded for \string\XeTeX}%
300   }{%
301     \ifdim \fontdimen1\font>0pt
302       \raise 1.75ex \hbox{\kern.1em\rotatebox{180}{#1}}\kern-.1em
303     \else
304       \reflectbox{#1}%
305     \fi
306   }%
307 }
308 \def\tubhideheight#1{\setbox0=\hbox{#1}\ht0=0pt \dp0=0pt \box0 }
309 \def\Xe#1{\leavevmode
310   \tubhideheight{\hbox{X%
311     \setbox0=\hbox{\TeX}\setbox1=\hbox{E}%
312     \lower\dp0\hbox{\raise\dp1\hbox{\kern-.125em\tubreflect{E}}}%
313     \kern-.1667em #1}}}%
314 \def\XeTeX{\Xe\TeX}
315 \def\XeLaTeX{\Xe{\,}\LaTeX}}
316 %
317 \def\XHTML{\acro{XHTML}}
318 \def\XSLT{\acro{XSLT}}

```

3.5 General typesetting rules

```

319 \newlinechar='\^^J
320 \normallineskiplimit=\p@
321 \clubpenalty=10000
322 \widowpenalty=10000
323 \def\NoParIndent{\parindent=\z@}
324 \newdimen\normalparindent
325 \normalparindent=20\p@
326 \def\NormalParIndent{\global\parindent=\normalparindent}
327 \NormalParIndent
328 \def\BlackBoxes{\overfullrule=5\p@}
329 \def\NoBlackBoxes{\overfullrule=\z@}
330 \def\newline{\hskip\z@\@plus\pagewd\break}

```

Hyphen control: first, we save the hyphenpenalties in `\allowhyphens`. This allows us to permit hyphens temporarily in things like `\netaddresses`, which typically occur when `\raggedright` is set, but which need to be allowed to break at their artificial discretionaries.

```

331 \edef\allowhyphens{\noexpand\hyphenpenalty\the\hyphenpenalty\relax
332   \noexpand\exhyphenpenalty\the\exhyphenpenalty\relax}
333 \def\nohyphens{\hyphenpenalty\@M\exhyphenpenalty\@M}

```

3.6 Utility registers and definitions

We define a few scratch registers (and the like) for transient use; they're all paired: an internal one (`\T@st*`) and an external one (`\Test*`).

Comment: Exercise for an idle day: find whether all these are necessary, or whether we can use the L^AT_EX temporaries for some (or all) of the `\T@st*` ones.

Comment: (bb) All these registers are used in the plain version, `tugboat.sty`.

```

334 \newbox\T@stBox           \newbox\TestBox
335 \newcount\T@stCount       \newcount\TestCount
336 \newdimen\T@stDimen       \newdimen\TestDimen
337 \newif\ifT@stIf           \newif\ifTestIf

```

Control sequence existence test, stolen from T_EXbook exercise 7.7 (note that this provides functionality that in some sense duplicates something within L^AT_EX).

```

338 \def\ifundefined#1{\expandafter\ifx\csname#1\endcsname\relax }

```

L^AT_EX conventions which are also useful here.

```

339 <*\latex>
340   \let\@@input\input
341   \def\iinput#1{\@@input#1 }
342   \def\@inputcheck{\if\@nextchar\bgroup
343     \expandafter\iinput\else\expandafter\@@input\fi}
344   \def\input{\futurelet\@nextchar\@inputcheck}
345 <\/!\latex>

```

Smashes repeated from AMS- \TeX ; plain \TeX implements only full `\smash`.

```

346 \newif\iftop@           \newif\ifbot@
347 \def\topsmash{\top@true\bot@false\smash@}
348 \def\botsmash{\top@false\bot@true\smash@}
349 \def\smash{\top@true\bot@true\smash@}
350 \def\smash@{\relax\ifmmode\def\next{\mathpalette\mathsm@sh}%
351           \else\let\next\makesm@sh\fi \next }
352 \def\fin@msh{\iftop@ht\z@z@fi\ifbot@dp\z@z@fi\box\z@}

```

Vertical ‘laps’; cf. `\llap` and `\rlap`

```

353 \long\def\ulap#1{\vbox to \z@{\vss#1}}
354 \long\def\dlap#1{\vbox to \z@{#1\vss}}

```

And centered horizontal and vertical ‘laps’

```

355 \def\xlap#1{\hb@xt@\z@{\hss#1\hss}}
356 \long\def\ylap#1{\vbox to \z@{\vss#1\vss}}
357 \long\def\zlap#1{\ylap{\xlap{#1}}}

```

Avoid unwanted vertical glue when making up pages.

```

358 \def\basezero{\baselineskip\z@skip \lineskip\z@skip}

```

Empty rules for special occasions

```

359 \def\nullhrule{\hrule \@height\z@ \@depth\z@ \@width\z@ }
360 \def\nullvrule{\vrule \@height\z@ \@depth\z@ \@width\z@ }

```

Support ad-hoc strut construction.

```

361 \def\makestrut[#1;#2]{\vrule \@height#1 \@depth#2 \@width\z@ }

```

Construct box for figure pasteup, etc.; height = #1, width = #2, rule thickness = #3

```

362 \def\drawoutlinebox[#1;#2;#3]{\T@stDimen=#3
363   \vbox to#1{\hrule \@height\T@stDimen \@depth\z@
364     \vss\hb@xt@#2{\vrule \@width\T@stDimen
365       \hfil\makestrut[#1;\z@]%
366       \vrule \@width\T@stDimen}\vss
367     \hrule \@height\T@stDimen \@depth\z@}}

```

Today’s date, to be printed on drafts. Based on \TeX book, p.406.

```

368 <*\latex>
369 \def\today{\number\day\space \ifcase\month\or
370   Jan \or Feb \or Mar \or Apr \or May \or Jun \or
371   Jul \or Aug \or Sep \or Oct \or Nov \or Dec \fi
372   \number\year}
373 </!\latex>

```

Current time; this may be system dependent!

```

374 \newcount\hours
375 \newcount\minutes
376 \def\SetTime{\hours=\time
377   \global\divide\hours by 60
378   \minutes=\hours
379   \multiply\minutes by 60

```



```

380      \advance\minutes by-\time
381      \global\multiply\minutes by-1 }
382 \SetTime
383 \def\now{\number\hours:\ifnum\minutes<10 0\fi\number\minutes}
384 \def\Now{\today\ \now}
385 \newif\ifPrelimDraft
386 \def\midrttitle{\ifPrelimDraft {\textsl{preliminary draft, \Now}}\fi}

```

3.7 Ragged right and friends

`\raggedskip` Plain T_EX's definition of `\raggedright` doesn't permit any stretch, and results in too many overfull boxes. We also turn off hyphenation. This code lies somewhere between that of Plain T_EX and of L^AT_EX.

```

\raggedspaces 387 \newdimen\raggedskip \raggedskip=\z@
388 \newdimen\raggedstretch \raggedstretch=5em % ems of font set now (10pt)
389 \newskip\raggedparfill \raggedparfill=\z@\@plus 1fil
390 \def\raggedspaces{\spaceskip=.3333em \relax \xspaceskip=.5em \relax }

```

`\raggedright` Some applications may have to add stretch, in order to avoid all overfull boxes.
`\raggedleft` We define the following uses of the above skips, etc.

```

\raggedcenter 391 \def\raggedright{%
\normalspaces 392 \nohyphens
393 \rightskip=\raggedskip\@plus\raggedstretch \raggedspaces
394 \parfillskip=\raggedparfill
395 }
396 \def\raggedleft{%
397 \nohyphens
398 \leftskip=\raggedskip\@plus\raggedstretch \raggedspaces
399 \parfillskip=\z@skip
400 }
401 \def\raggedcenter{%
402 \nohyphens
403 \leftskip=\raggedskip\@plus\raggedstretch
404 \rightskip=\leftskip \raggedspaces
405 \parindent=\z@ \parfillskip=\z@skip
406 }
407 \def\normalspaces{\spaceskip\z@skip \xspaceskip\z@skip}

```

Miscellaneous useful stuff. Note that L^AT_EX 2_ε defines a robust `\,`, but that we provide a new definition of `~` by redefining its robust underpinnings¹ (based on the version in AMS-T_EX — the L^AT_EX 2_ε version has `\leavevmode` and doesn't care about surrounding space).

```

408 \DeclareRobustCommand{\nobreakspace}{%
409 \unskip\nobreak\ \ignorespaces}

```

Plain T_EX defines `\newbox` as `\outer`. We solemnly preserve the following, which removes the `\outer`ness; of course, we carefully exclude it from what we

¹`\DeclareRobustCommand` doesn't mind redefinition, fortunately

generate... (\outerness is a spawn of the devil, is it not? Barbara Beeton responded to the previous sentence “\outerness has its place: it avoids register buildup, hence running out of memory”. In another context, David Carlisle remarked that an error control mechanism that causes more confusing errors than it prevents is rather a poor one. This is perhaps not the place to conduct a serious debate...)

```

410 \def\boxcs#1{\box\csname#1\endcsname}
411 \def\setboxcs#1{\setbox\csname#1\endcsname}
412 \def\newboxcs#1{\expandafter\newbox\csname#1\endcsname}
413 \let\gobble@gobble
414 \def\vellipsis{%
415   \leavevmode\kern0.5em
416   \raise\p@\vbox{\baselineskip6\p@\vskip7\p@\hbox{.}\hbox{.}\hbox{.}}
417 }
418 \def\bull{\vrule \@height 1ex \@width .8ex \@depth -.2ex }
419 \def\cents{{\rm\raise.2ex\rlap{\kern.05em$\scriptstyle/$}c}}
420 \def\Dag{\raise .6ex\hbox{$\scriptstyle\dagger$}}
421 \def\careof{\leavevmode\hbox{\raise.75ex\hbox{c}\kern-.15em
422   /\kern-.125em\smash{\lower.3ex\hbox{o}}}\ignorespaces}
423 \DeclareRobustCommand\sfrac[1]{\@ifnextchar/{\@sfrac{#1}}%
424   {\@sfrac{#1}/}}
425 \def\@sfrac#1/#2{\leavevmode\kern.1em\raise.5ex
426   \hbox{$\m@th\mbox{\fontsize\sf@size\z@
427     \selectfont#1}$}\kern-.1em
428   /\kern-.15em\lower.25ex
429   \hbox{$\m@th\mbox{\fontsize\sf@size\z@
430     \selectfont#2}$}}
431 \DeclareRobustCommand\cs[1]{\texttt{\char'\#1}}
432 \DeclareRobustCommand\meta[1]{% don't stay bold in description items
433   \ensuremath{\langle}\mdseries\emph{#1}\ensuremath{\rangle}}
434 \DeclareRobustCommand\env[1]{%
435   \cs{begin}\texttt{\char'\#1\char'\}}
436 \def\thinskip{\hskip 0.16667em\relax}

```

We play a merry game with dashes, providing all conceivable options of breakability before and after.

```

437 \def\endash{--}
438 \def\emdash{\endash-}
439 \def\d@sh#1#2{\unskip#1\thinskip#2\thinskip\ignorespaces}
440 \def\dash{\d@sh\nobreak\endash}
441 \def\Dash{\d@sh\nobreak\emdash}
442 \def\ldash{\d@sh\empty{\hbox{\endash}\nobreak}}
443 \def\rdash{\d@sh\nobreak\endash}
444 \def\Ldash{\d@sh\empty{\hbox{\emdash}\nobreak}}
445 \def\Rdash{\d@sh\nobreak\emdash}

```

Hacks to permit automatic hyphenation after an actual hyphen, or after a slash.

```

446 \def\hyph{-\penalty\z@\hskip\z@skip }

```

```
447 \def\slash{/\penalty\z@\hskip\z@skip }
```

Adapted from `comp.text.tex` posting by Donald Arseneau, 26 May 93.
 $\text{\LaTeX 2}_{\epsilon}$ -isation added by Robin Fairbairns. Destroys both the `TestCounts`.

```
448 \def\nth#1{%
449   \def\reserved@a##1##2\@nil{\ifcat##1n%
450     0%
451     \let\reserved@b\ensuremath
452   \else##1##2%
453     \let\reserved@b\relax
454   \fi}%
455   \TestCount=\reserved@a#1\@nil\relax
456   \ifnum\TestCount <0 \multiply\TestCount by\m@ne \fi % subdue negatives
457   \T@stCount=\TestCount
458   \divide\T@stCount by 100 \multiply\T@stCount by 100
459   \advance\TestCount by-\T@stCount % n mod 100
460   \ifnum\TestCount >20 \T@stCount=\TestCount
461     \divide\T@stCount by 10 \multiply\T@stCount by 10
462     \advance\TestCount by-\T@stCount % n mod 10
463   \fi
464   \reserved@b{#1}%
465   \textsuperscript{\ifcase\TestCount th%      0th
466                     \or st%                  1st
467                     \or nd%                  2nd
468                     \or rd%                  3rd
469                     \else th%                nth
470                     \fi}%
471 }
```

3.8 Reviews

Format information on reviewed items for book review articles. For the $\text{\LaTeX 2}_{\epsilon}$ version, we follow Fairbairns' maxim, and define something that can even look like a \LaTeX macro...

```
472 \def\Review{\@ifnextchar:{\@Review}{\@Review:}}
473 \def\@Review:{\@ifnextchar[%]
474   {\@Rev}%
475   {\@Rev[Book review]}}
476 \def\@Rev[#1]#2{{\ignorespaces#1\unskip:\enspace\ignorespaces
477   \slshape\mdseries#2}}
478 \def\reviewitem{\addvspace{\BelowTitleSkip}%
479   \def\revauth##1{\def\therevauth{##1, }\ignorespaces}%
480   \def\revtitle##1{\def\therevtitle{\slshape##1. }\ignorespaces}%
481   \def\revpubinfo##1{\def\therevpubinfo{##1. }\ignorespaces}%
482 }
483 \def\endreviewitem{{\noindent\interlinepenalty=10000
484   \therevauth\therevtitle\therevpubinfo\endgraf}%
485   \vskip\medskipamount
486 }
```

```
487 \def\booktitle#1{{\slshape#1\}}
```

3.9 Dates, volume and issue numbers, etc.

Dates and other items which identify the volume and issue. `\issueseqno` is a sequential issue number starting from the first issue published; volume 15,4 has `\issueseqno=45`.

```
\vol 19, 1.
```

To use: `\issdate March 1998`.

```
\issueseqno=58
```

Starting with volume 23 (nominal 2002), we have `\issyear` instead of `\issdate`, because issues don't have months any more.

For production, these are set in a separate file, `tugboat.dates`, which is issue-specific.

Comment: I would like to make the code read a file `tugboat.dates` in the current directory or its parent. This is easy except under 'odd' operating systems (VMS is an example that springs to mind, RISCos may be even worse) whose syntax is out of the ordinary.

```
488 \newcount\issueseqno          \issueseqno=-1
489 \def\volx{\gdef\volx{Volume~\volno~(\volyr), No.~\issno}}
490 \def\volyr{}
491 \def\volno{}
492 \def\vol #1,#2.{\gdef\volno{#1\unskip}%
493     \gdef\issno{\ignorespaces#2\unskip}%
494     \setbox\TestBox=\hbox{\volyr}%
495     \ifdim \wd\TestBox > .2em \volx \fi }
496 \def\issyear #1.{\gdef\issdt{#1}\gdef\volyr{#1}%
497     \gdef\bigissdt{#1}%
498     \setbox\TestBox=\hbox{\volno}%
499     \ifdim \wd\TestBox > .2em \volx \fi }
500 \def\issdate #1#2 #3.{\gdef\issdt{#1#2 #3}\gdef\volyr{#3}%
501     \gdef\bigissdt{#1{\smc\uppercase{#2}} #3}%
502     \setbox\TestBox=\hbox{\volno}%
503     \ifdim \wd\TestBox > .2em \volx \fi }
504 \vol 0, 0.
505 \issdate Thermidor, 2060.
```

(The curious should know that *Thermidor* was one of the French revolutionary month names...)

For L^AT_EX use, define a version of the issue declaration that can take or leave the old plain syntax

```
506 \!latex\def\tubissue#1(#2)%
507 \*latex
508 \def\tubissue#1{\ifnextchar(%)
509     {\@tubissue@b{#1}}
510     {\@tubissue@a{#1}}}%
511 \def\@tubissue@b#1(#2){\@tubissue@a{#1}{#2}}
```

```

512 \def\tubissue@a#1#2%
513 </latex>
514 {\TUB~#1, no.~#2}

```

TUGboat conventions include the sequential issue number in the file name. Permit this to be incorporated into file names automatically. If issue number = 11, `\Input filnam` will read `tb11filnam.tex`

```

515 \def\infil@{\jobname}
516 \def\Input #1 {\ifnum\issueseqno<0
517   \def\infil@{#1}%
518   \else
519   \def\infil@{tb\number\issueseqno#1}
520   \fi
521   \edef\jobname{\infil@}\@readFLN
522   @@input \infil@relax
523   \if@RMKopen
524   \immediate\closeout\@TBremarkfile\@RMKopenfalse
525   \fi
526 }

```

`\TBremarks` are things that need to be drawn to the attention of the editors; the conscientious author will include such things in the article file. By default, remarks are suppressed, but their appearance may be enabled by the `\TEnableRemarks` command, which can be included in the configuration file `ltugboat.cfg` (or `ltugproc.cfg`, if that's what we're at).

```

527 \newif\if@RMKopen \@RMKopenfalse
528 \newwrite\@TBremarkfile
529 \def\@TBremark#1{%
530   \if@RMKopen
531   \else
532   \@RMKopenttrue\immediate\openout\@TBremarkfile=\infil@.rmk
533   \fi
534   \toks@={#1}%
535   \immediate\write\@TBremarkfile{^^J\the\toks@}%
536   \immediate\write16{^^JTremark:: \the\toks@^^J}%
537 }

```

We initialise `\TBremark` to ignore its argument (this used to involve a `\TBremarkOFF` which was cunningly defined exactly the same as `\gobble`)

```

538 \let\TBremark=\gobble

```

`\TEnableRemarks` simply involves setting `\TBremark` to use the functional `\@TBremark` defined above.

```

539 \def\TEnableRemarks{\let\TBremark\@TBremark}

```

For marking locations in articles that pertain to remarks in another file of editorial comments

```

540 \def\TUBedit#1{}

```

For using different filenames in the production process than those supplied by authors

```

541 \def\tubfilename#1#2{\expandafter\def\csname file@@#1\endcsname{#2}}
542 \newread\altfilenames
543 \def\@readFLN{\immediate\openin\altfilenames=\jobname.fln
544 \ifeof\altfilenames\let\@result\relax\else
545 \def\@result{\@input\jobname.fln }\fi
546 \immediate\closein\altfilenames
547 \@result}
548 \@readFLN
549 \everyjob=\expandafter{\the\everyjob\@readFLN}
550 \InputIfFileExists{\jobname.fln}%
551 {\TBInfo{Reading alternative file file \jobname.fln}}{}

```

The following needs to work entirely in T_EX's mouth

```

552 \def\@tubfilename#1{\expandafter\ifx\csname file@@#1\endcsname\relax
553 #1\else\csname file@@#1\endcsname\fi}
554 \def\fileinput#1{\@input\@tubfilename{#1} }

```

Write out (both to a file and to the log) the starting page number of an article, to be used for cross references and in contents. `\pagexref` is used for articles fully processed in the *TUGboat* run. `\PageXref` is used for 'extra' pages, where an item is submitted as camera copy, and only running heads (at most) are run.

```

555 <!\latex>
556 \def\pagexrefON#1{%
557     \write-1{\def\expandafter\noexpand\csname#1\endcsname{\number\pageno}}%
558     \write\ppoutfile{%
559         \def\expandafter\noexpand\csname#1\endcsname{\number\pageno}}%
560     }
561 \def\PageXrefON#1{%
562     \immediate\write-1{\def\expandafter
563         \noexpand\csname#1\endcsname{\number\pageno}}%
564     \immediate\write\ppoutfile{\def\expandafter
565         \noexpand\csname#1\endcsname{\number\pageno}}}
566 </!\latex>
567 <!\latex>
568 \def\pagexrefOFF#1{%
569     \write-1{\def\expandafter\noexpand\csname#1\endcsname{\number\c@page}}%
570     \write\ppoutfile{%
571         \def\expandafter\noexpand\csname#1\endcsname{\number\c@page}}%
572     }
573 \def\PageXrefOFF#1{%
574     \immediate\write-1{\def\expandafter
575         \noexpand\csname#1\endcsname{\number\c@page}}%
576     \immediate\write\ppoutfile{\def\expandafter
577         \noexpand\csname#1\endcsname{\number\c@page}}}
578 </\latex>
579 \def\pagexrefOFF#1{}
580 \let\pagexref=\pagexrefOFF
581 \def\PageXrefOFF#1{}

```

```

582 \let\PageXref=\PageXrefOFF
583 \def\xreftoON#1{%
584   \ifundefined{#1}%
585     ???\TBremark{Need cross reference for #1.}%
586   \else\csname#1\endcsname\fi}
587 \def\xreftoOFF#1{???}
588 \let\xrefto=\xreftoOFF

```

\TBdriver ‘marks code for use when articles are run together in a driver file’. Since we don’t yet have a definition of that arrangement, we don’t have a definition of \TBdriver. Its argument (which one presumes was intended as the code for this unusual state) is just gobbled.

```

589 \let\TBdriver\gobble

```

Some hyphenation exceptions:

```

590 \hyphenation{Del-a-ware Dijk-stra Duane Eijk-hout
591   Flor-i-da Free-BSD Ghost-script Ghost-view
592   Hara-lam-bous Jac-kow-ski Karls-ruhe
593   Mac-OS Math-Sci-Net
594   Net-BSD Open-BSD Open-Office
595   Pfa-Edit Post-Script Rich-ard Skoup South-all
596   VM-ware Win-Edt
597   acro-nym ap-pen-dix asyn-chro-nous
598   bit-map bit-mapped bit-maps buf-fer buf-fers bool-ean
599   col-umns com-put-able com-put-abil-ity cus-tom-iz-able
600   data-base data-bases
601   de-allo-cate de-allo-cates de-allo-cated de-allo-ca-tion
602   de-riv-a-tive de-riv-a-tives de-riv-a-ble der-i-va-tion
603   es-sence
604   fall-ing
605   half-way
606   in-fra-struc-ture
607   key-note
608   long-est
609   ma-gyar Ma-la-ya-lam man-u-script man-u-scripts mne-mon-ic mne-mon-ics
610   mono-space mono-spaced
611   name-space name-spaces
612   off-line over-view
613   pal-ettes par-a-digm par-a-dig-mat-ic par-a-digms
614   pipe-line pipe-lines
615   plug-in plug-ins pres-ent-ly pro-gram-mable
616   re-allo-cate re-allo-cates re-allo-cated
617   set-ups se-vere-ly spell-ing spell-ings stand-alone strong-est
618   sub-ex-pres-sion syn-chro-ni-city syn-chro-nous
619   time-stamp time-stamped
620   Vieth vis-ual vis-u-al-ly
621   which-ever white-space white-spaces wide-spread wrap-around
622 }
623 <!!latex>\restorecat\@
624 </common>

```

```

625 \*classtail
626 \PrelimDrafttrue

```

3.10 Page dimensions, glue, penalties etc

```

627 \textheight 54pc
628 \textwidth 39pc
629 \columnsep 1.5pc
630 \columnwidth 18.75pc
631 \parindent \normalparindent
632 \parskip \z@ % \@plus\p@
633 \leftmargini 2em
634 \leftmarginv .5em
635 \leftmarginvi .5em
636 \oddsidemargin \z@
637 \evensidemargin \z@
638 \topmargin -2.5pc
639 \headheight 12\p@
640 \headsep 20\p@
641 \marginparwidth 48\p@
642 \marginparsep 10\p@
643 \partopsep=\z@
644 \topsep=3\p@ \@plus\p@ \@minus\p@
645 \parsep=3\p@ \@plus\p@ \@minus\p@
646 \itemsep=\parsep
647 \twocolumn
648 \newdimen\pagewd \pagewd=39pc
649 \newdimen\trimwd \trimwd=\pagewd
650 \newdimen\trimlgt \trimlgt=11in
651 \newdimen\headmargin \headmargin=3.5pc

```

In L^AT_EX 2_ε, twoside option is forced on when `article.cls` is loaded.

3.11 Messing about with the L^AT_EX logo

Barbara Beeton’s pleas for L^AT_EX logos that look right in any font shape provoked me to generate the following stuff that is configurable.

Here’s the command for the user to define hir own new version. The arguments are font family, series and shape, and then the two kern values used in placing the raised ‘A’ of L^AT_EX.

```

652 \newcommand\DeclareLaTeXLogo[5]{\expandafter\def
653 \csname @LaTeX@#1/#2/#3\endcsname{{#4}{#5}}}

```

The default values are as used in the source of L^AT_EX itself:

```

654 \def\@LaTeX@default{{.36}{.15}}

```

More are defined in the initial version, for bold CM sans (which is used as `\SecTitleFont`), and CM italic medium and bold, and Bitstream Charter (which Nelson Beebe likes to use):

```

655 \DeclareLaTeXLogo{cmss}{bx}{n}{.3}{.15}

```



```

656 \DeclareLaTeXLogo{cmr}{m}{it}{.3}{.27}
657 \DeclareLaTeXLogo{cmr}{bx}{it}{.3}{.27}
658 \DeclareLaTeXLogo{bch}{m}{n}{.2}{.08}
659 \DeclareLaTeXLogo{bch}{m}{it}{.2}{.08}

```

Redefine `\LaTeX` to choose the parameters for the current font, or to use the default value otherwise:

```

660 \DeclareRobustCommand\LaTeX{\expandafter\let\expandafter\reserved@a
661   \csname @LaTeX@f@family/\f@series/\f@shape\endcsname
662   \ifx\reserved@a\relax\let\reserved@a@LaTeX@default\fi
663   \expandafter\@LaTeX\reserved@a}

```

Here's the body of what was originally `\LaTeX`, pulled out with its roots dripping onto the smoking ruin of original L^AT_EX, and then bits stuck in on the side.

`\@LaTeX@default` provides parameters as one finds in the original; other versions are added as needed.

```

664 \newcommand\@LaTeX[2]{L\kern-#1em
665   {\sbox\z@ T%
666     \vbox to\ht0{\hbox{$\m@th$%
667       \csname S@f@size\endcsname
668       \fontsize\sf@size\z@
669       \math@fontsfalse\selectfont
670       A}%
671       \vss}%
672   }%
673   \kern-#2em%
674   \TeX}

```

3.12 Authors, contributors, addresses, signatures

Each article may have several authors (of course), so we permit an `\author` command for each of them. The names are then stored in a set of `\csnames` called `\author1`, `\author2`, ... Similarly, there are several `\address<n>` and `\netaddress<n>` and `\PersonalURL<n>` commands set up for each article.

Comment: I would like to make provision for several authors at the same address, but (short of preempting the `*` marker, which it would be nice to retain so as to preserve compatibility with the `plain` style) I'm not sure how one would signal it.

```

675 \def\theauthor#1{\csname theauthor#1\endcsname}
676 \def\theaddress#1{\csname theaddress#1\endcsname}
677 \def\thenetaddress#1{\csname thenetaddress#1\endcsname}
678 \def\thePersonalURL#1{\csname thePersonalURL#1\endcsname}

```

The standard way of listing authors is to iterate from 1 to `\count@` and to pick the author names as we go.

```

679 <llatex>\newcount\@tempcnta

```

```

680 \def\@defaultauthorlist{%
681   \@getauthorlist\@firstofone
682 }

```

`\@getauthorlist` processes the author list, passing every bit of stuff that needs to be typeset to its argument.

```

683 \def\@getauthorlist#1{%
684   \count@\authornumber
685   \advance\count@ by -2
686   \@tempcnta0

```

Loop to output the first $n - 2$ of the n authors (the loop does nothing if there are two or fewer authors)

```

687   \loop
688     \ifnum\count@>0
689       \advance\@tempcnta by \@ne
690       #1{\ignorespaces\theauthor{\number\@tempcnta}\unskip, }%
691       \advance\count@ by \m@ne
692   \repeat
693   \count@\authornumber
694   \advance\count@ by -\@tempcnta
695   \ifnum\authornumber>0

```

If there are two or more authors, we output the penultimate author's name here, followed by 'and'

```

696     \ifnum\count@>1
697       \count@\authornumber
698       \advance\count@ by \m@ne
699       #1{\ignorespaces\theauthor{\number\count@}\unskip\ and }%
700     \fi

```

Finally (if there were any authors at all) output the last author's name:

```

701     #1{\ignorespaces\theauthor{\number\authornumber}\unskip}
702     \fi
703 }

```

Signature blocks. The author can (in principle) define a different sort of signature block using `\signature`, though this could well cause the editorial group to have collective kittens (unless it had been discussed in advance...)

```

704 \def\signature#1{\def\@signature{#1}}
705 \def\@signature{\@defaultsignature}

```

`\@defaultsignature` loops through all the authors, outputting the details we have about that author, or (if we're in a sub-article) outputs the contributor's name and closes the group opened by `\contributor`. It is (as its name implies) the default body for `\makesignature`

```

706 \def\@defaultsignature{%
707   \let\thanks\@gobble
708   \ifnum\authornumber<0

```

```

if \authornumber < 0, we are in a contributor's section
709     \medskip
710     \frenchspacing
711     \signaturemark
712     \theauthor{\number\authornumber}\\
713     \theaddress{\number\authornumber}\\
714     \allowhyphens
715     \thenetaddress{\number\authornumber}\\
716     \thePersonalURL{\number\authornumber}\\
717     \else
    \authornumber ≥ 0, so we are in the body of an ordinary article
718     \count@=0
719     \loop
720     \ifnum\count@<\authornumber
721         \medskip
722         \advance\count@ by \@ne
723         \signaturemark
724         \theauthor{\number\count@}\\
725         \theaddress{\number\count@}\\
726         {%
727             \allowhyphens
728             \thenetaddress{\number\count@}\\
729             \thePersonalURL{\number\count@}\\
730         }%
731     \repeat
732 \fi
733 }%
734 }
735 \newdimen\signaturewidth \signaturewidth=12pc

The optional argument to \makesignature is useful in some circumstances (e.g.,
multi-contributor articles)
736 \newcommand\makesignature[1][\medskipamount]{%
    check the value the user has put in \signaturewidth: it may be at most
    1.5pc short of \columnwidth
737 \@tempdima\signaturewidth
738 \advance\@tempdima 1.5pc
739 \ifdim \@tempdima>\columnwidth
740     \signaturewidth \columnwidth
741     \advance\signaturewidth -1.5pc
742 \fi
743 \par
744 \penalty9000
745 \vspace{#1}%
746 \rightline{%
747     \vbox{\hsize\signaturewidth \ninepoint \raggedright
748         \parindent \z@ \everypar={\hangindent 1pc }
749         \parskip \z@skip
750         \def\|{\unskip\hfil\break}%

```

```

751     \def\{\endgraf}%
752     \def\phone{\rm Phone: }
753     \rm\@signature}%
754 }%
755 \ifnum\authornumber<0 \endgroup\fi
756 }
757 \def\signaturemark{\leavevmode\llap{$\diamond$\enspace}}
    The code used to define the following:

    {\makeactive\@
     \gdef\signatureat{\makeactive\@\def@{\char"40\discretionary}{-}{-}}
     \makeactive\%
     \gdef\signaturepercent{\makeactive\%\def@{\char"25\discretionary}{-}{-}}
    }

```

However, they were never used within the class (or within `ltugproc.cls`). They have therefore been deleted; the identically defined `\netaddrat` and `\netaddrpercent` may be used in the unlikely event that they're needed elsewhere.

Now all the awful machinery of author definitions. `\authornumber` records the number of authors we have recorded to date.

```

758 \newcount\authornumber
759 \authornumber=0

```

`\author` ‘allocates’ another author name (by bumping `\authornumber`) and also sets up the address and netaddress for this author to produce a warning and to prevent oddities if they're invoked. This last assumes that invocation will be in the context of `\signature` (`ltugboat.cls`) or `\maketitle` (`ltugproc.cls`); in both cases, invocation is followed by a line break (tabular line break `\` in `ltugproc`, `\endgraf` in `\makesignature` in `ltugboat`).

```

760 \def\author{%
761   \global\advance\authornumber\@ne
762   \TB@author
763 }

```

`\contributor` is for a small part of a multiple-part article; it begins a group that will be ended in `\makesignature`

```

764 \def\contributor{%
765   \begingroup
766   \authornumber\m@ne
767   \TB@author
768 }

```

Both ‘types’ of author fall through here to set up the author name and to initialise author-related things. `\EDITORno*` commands allow the editor to record that there's good reason for an *address* or *netaddress* not to be there (the *personalURL* is optional anyway).

```

769 \def\TB@author#1{%
770   \expandafter\def\csname theauthor\number\authornumber\endcsname
771     {\ignorespaces#1\unskip}%
772   \expandafter\def\csname theaddress\number\authornumber\endcsname
773     {\TBWarningNL{Address for #1\space missing}\@gobble}%
774   \expandafter\def\csname thenetaddress\number\authornumber\endcsname
775     {\TBWarningNL{Net address for #1\space missing}\@gobble}%
776   \expandafter\let\csname thePersonalURL\number\authornumber\endcsname
777     \@gobble
778 }
779 \def\EDITORnoaddress{%
780   \expandafter\let\csname theaddress\number\authornumber\endcsname
781     \@gobble
782 }
783 \def\EDITORnonetaddress{%
784   \expandafter\let\csname thenetaddress\number\authornumber\endcsname
785     \@gobble
786 }

```

\address simply copies its argument into the \theaddress<n> for this author.

```

787 \def\address#1{%
788   \expandafter\def\csname theaddress\number\authornumber\endcsname
789     {\leavevmode\ignorespaces#1\unskip}}

```

\network is for use within the optional argument of \netaddress; it defines the *name* of the network the user is on.

Comment: I think this is a fantasy, since everyone (in practice, nowadays) quotes an internet address. In principle, there are people who will quote X.400 addresses (but they're few and far between) and I have (during 1995!) seen an address with an UUCP bang-path component on `comp.text.tex`, but *really*!

```

790 \def\network#1{\def\@network{#1: }}

```

\netaddress begins a group, executes an optional argument (which should not, presumably, contain global commands) and then relays to \@relay@netaddress with both @ and % made active (so that they can be discretionary points in the address). If we're using L^AT_EX 2_ε, we use the default-argument form of \newcommand; otherwise we write it out in all its horribleness.

```

791 \newcommand\netaddress[1][\relax]{%
792   \begingroup
793   \def\@network{}%

```

Unfortunately, because of the catcode hackery, we have still to do one stage of relaying within our own code, even if we're using L^AT_EX 2_ε.

```

794   #1\@sanitize\makespace\ \makeactive\@
795   \makeactive\.\makeactive%\@relay@netaddress}%

```

`\@relay@netaddress` finishes the job. It sets `\thenetaddress` for this author to contain the network name followed by the address. As a result of our kerfuffle above, `@` and `%` are active at the point we're entered. We ensure they're active when `\thenetaddress` gets expanded, too. (***WOT?!***)

```

796 \def\@relay@netaddress#1{%
797   \ProtectNetChars
798   \expandafter\protected@xdef
799     \csname thenetaddress\number\authornumber\endcsname
800     {\protect\leavevmode\textrm{\@network}%
801      {\protect\NetAddrChars\net
802       \ignorespaces#1\unskip}}}%
803 \endgroup
804 }

```

`\personalURL` is in essence the same as `\netaddress`, apart from (1) the lack of the eccentric optional argument, and (2) the activation of `'/'`.

We could imagine needing an `\URL` command in general. If so, we must remember that the code here would naturally permit a break between the last two characters of `http://`, and some sort of special action must be taken to ensure that it doesn't happen.

```

805 \def\personalURL{\begingroup
806   \@sanitize\makespace\ \makeactive\@
807   \makeactive\.\makeactive%\makeactive\/\@personalURL}%
808 \def\@personalURL#1{%
809   \ProtectNetChars
810   \expandafter\protected@xdef
811     \csname thePersonalURL\number\authornumber\endcsname{%
812     \protect\leavevmode
813     {%
814       \protect\URLchars\net
815       \ignorespaces#1\unskip
816     }%
817   }%
818 \endgroup
819 }

```

Define the activation mechanism for `'@'`, `'%'`, `'.'` and `'/'`, for use in the above. Note that, since the code has `'%'` active, we have `'*'` as a comment character, which has a tendency to make things look peculiar...

```

820 {%
821   \makecomment\*
822   \makeactive\@
823   \gdef\netaddrat{\makeactive\@*
824     \def@{\discretionary{\char"40}{\char"40}}
825   \makeactive\%
826   \gdef\netaddrpercent{\makeactive\%*
827     \def%{\discretionary{\char"25}{\char"25}}
828   \makeactive\
829   \gdef\netaddrdot{\makeactive\.*

```

```
830 \def.{\discretionary{\char"2E}{\char"2E}}
```

`\NetAddrChars` is what *we* use (we’re constrained to retain the old interface to this stuff, but it *is* clunky...). Since URLs are a new idea, we are at liberty not to define a separate `\netaddrslash` command, and we only have `\URLchars`.

```
831 \gdef\NetAddrChars{\netaddrat \netaddrpercent \netaddrdot}
832 \makeactive\
833 \gdef\URLchars{*
834   \NetAddrChars
835   \makeactive\/*
836   \def/{\discretionary{\char"2F}{\char"2F}}
```

`\ProtectNetChars` includes protecting ‘/’, since this does no harm in the case of net addresses (where it’s not going to be active) and we thereby gain by not having yet another csname.

```
837 \gdef\ProtectNetChars{*
838   \def@{\protect@}*
839   \def%{\protect%}*
840   \def.{\protect.}*
841   \def/{\protect/}*
842 }
843 }
```

L^AT_EX 2_ε (in its wisdom) suppresses `\DeclareOldFontCommand` when in compatibility mode, so that in that circumstance we need to use a declaration copied from `latex209.def` rather than the way we would normally do the thing (using the command L^AT_EX 2_ε defines for the job).

```
844 \if@compatibility
845   \DeclareRobustCommand\net{\normalfont\ttfamily\mathgroup\syntypewriter}
846 \else
847   \DeclareOldFontCommand{\net}{\ttfamily\upshape\mdseries}{\mathtt}
848 \fi
849 \def\authorlist#1{\def\@author{#1}}
850 \def\@author{\@defaultauthorlist}
```

```
\if@articletitle \maketitle takes an optional “*”; if present, the operation is not defining the
\maketitle title of a paper, merely that of a “business” section (such as the participants at
\@r@maketitle a meeting) that has no credited author or other title. In this case, the command
flushes out the latest \sectitle (or whatever) but does nothing else.
```

Provide machinery to skip extra space, even one or more full columns, above the top of an article to leave space to paste up a previous article that has finished on the same page. This is a fall back to accommodate the fact that multiple articles cannot yet be run together easily with L^AT_EX 2_ε.

```
851 \newif\if@articletitle
852 \def\maketitle{\@ifstar
853   {\@articletitlefalse\@r@maketitle}%
854   {\@articletitletrue\@r@maketitle}%
855 }
856 \def\@r@maketitle{\par
```

```

857 \ifdim\PreTitleDrop > \z@
858   \loop
859   \ifdim \PreTitleDrop > \textheight
860     \vbox{}\vfil\eject
861     \advance\PreTitleDrop by -\textheight
862   \repeat
863   \vbox to \PreTitleDrop{}
864   \global\PreTitleDrop=\z@
865 \fi
866 \begingroup
867 \setcounter{footnote}{0}
868 \def\thefootnote{\fnsymbol{footnote}}
869 \@maketitle
870 \@thanks
871 \endgroup
872 \setcounter{footnote}{0}
873 \gdef\@thanks{}
874 }

```

3.13 Section titles

The following macros are used to set the large *TUGboat* section heads (e.g. “General Delivery”, “Fonts”, etc.)

Define the distance between articles which are run together:

```

875 \def\secsep{\vskip 5\baselineskip}

```

Note that `\stbaselineskip` is used in the definition of `\sectitlefont`, in L^AT_EX 2_ε, so that it has (at least) to be defined before `\sectitlefont` is used (we do the whole job).

```

876 \newdimen\stbaselineskip      \stbaselineskip=18\p@
877 \newdimen\stfontheight
878 \settoheight{\stfontheight}{\sectitlefont 0}

```

Declaring section titles; the conditional `\ifSecTitle` records the occurrence of a `\sectitle` command. If (when) a subsequent `\maketitle` occurs, the section title box will get flushed out; as a result of this, one could in principle have a set of `\sectitle` commands in a semi-fixed steering file, and inclusions of files inserted only as and when papers have appeared. Only the last `\sectitle` will actually be executed.

```

879 \newif\ifSecTitle
880 \SecTitlefalse
881 \newif\ifWideSecTitle
882 \newcommand\sectitle{%
883   \SecTiteltrue
884   \@ifstar
885     {\WideSecTiteltrue\def\s@ctitle}%
886     {\WideSecTitlefalse\def\s@ctitle}%
887 }

```


`\PreTitleDrop` records the amount of column-space we need to eject before we start any given paper. It gets zeroed after that ejection has happened.

```
888 \newdimen\PreTitleDrop \PreTitleDrop=\z@
```

The other parameters used in `\@sectitle`; I don't think there's the slightest requirement for them to be registers (since they're constant values, AFAIK), but converting them to macros would remove the essentially useless functionality of being able to change them using assignment, which I'm not about to struggle with just now...

`\AboveTitleSkip` and `\BelowTitleSkip` are what you'd expect; `\strulethickness` is the value to use for `\fboxrule` when setting the title.

```
889 \newskip\AboveTitleSkip \AboveTitleSkip=12\p@
890 \newskip\BelowTitleSkip \BelowTitleSkip=8\p@
891 \newdimen\strulethickness \strulethickness=.6\p@
```

`\@sectitle` actually generates the section title (in a rather generous box). It gets called from `\maketitle` under conditional `\ifSecTitle`; by the time `\@sectitle` takes control, we already have `\SecTitlefalse`. This implementation uses L^AT_EX's `\framebox` command, on the grounds that one doesn't keep a dog and bark for oneself...

```
892 \def\@sectitle #1{%
893   \par
894   \penalty-1000
```

If we're setting a wide title, the stuff will be at the top of a page (let alone a column) but inside a box, so that the separator won't be discardable: so don't create the separator in this case.

```
895   \ifWideSecTitle\else\secsep\fi
896   {%
897     \fboxrule\strulethickness
898     \fboxsep\z@
899     \noindent\framebox[\hsize]{%
900       \vbox{%
901         \raggedcenter
902         \let\\ \@sectitle@newline
903         \sectitlefont
904         \makestrut[2\stfontheight;\z@]%
905         #1%
906         \makestrut[\z@;\stfontheight]\endgraf
907       }%
908     }%
909   }%
910   \nobreak
911   \vskip\baselineskip
912 }
```

`\@sectitle@newline` For use inside `\sectitle` as `\\`. Works similarly to `\\` in the “real world” — uses an optional argument

```

913 \newcommand{\@sectitle@newline}[1][\z@]{%
914   \ifdim#1>\z@
915     \makestrut[\z@;#1]%
916   \fi
917   \unskip\break
918 }

```

We need to trigger the making of a section title in some cases where we don't have a section title proper (for example, in material taken over from TTN).

```

919 \def\@makesectitle{\ifSecTitle
920   \global\SecTitlefalse
921   \ifWideSecTitle
922     \twocolumn[\@sectitle{\s@ctitle}]%
923   \global\WideSecTitlefalse
924   \else
925     \@sectitle{\s@ctitle}%
926   \fi
927 \else
928   \vskip\AboveTitleSkip
929   \kern\topskip
930   \hrule \@height\z@ \@depth\z@ \@width 10\p@
931   \kern-\topskip
932   \kern-\strulethickness
933   \hrule \@height\strulethickness \@depth\z@
934   \kern\medskipamount
935   \nobreak
936 \fi
937 }

```

`\@maketitle` Finally, the body of `\maketitle` itself.

```

938 \def\@maketitle{%
939   \@makesectitle
940   \if@articletitle{%
941     \nohyphens \interlinepenalty\@M
942     \setbox0=\hbox{%
943       \let\thanks\@gobble
944       \let\=\quad
945       \let\and=\quad
946       \ignorespaces\@author}%
947     {%
948       \noindent\bf\raggedright\ignorespaces\@title\endgraf
949     }%
950     \ifdim \wd0 < 5\p@ % omit if author is null
951     \else

```

Since we have $\text{\BelowTitleSkip} + 4\text{pt} = \text{\baselineskip}$, we say:

```

952   \nobreak \vskip 4\p@
953   {%
954     \leftskip=\normalparindent
955     \raggedright

```

```

956         \def\and{\unskip\\}%
957         \noindent\@author\endgraf
958     }%
959     \fi
960     \nobreak
961     \vskip\BelowTitleSkip
962 } \fi%
963 \global\@afterindentfalse
964 \aftergroup\@afterheading
965 }

```

Dedications are ragged right, in italics.

```

966 \newenvironment{dedication}%
967 { \raggedright\noindent\itshape\ignorespaces}%
968 { \endgraf\medskip}

```

The abstract and longabstract environments both use `\section*`.

```

969 \renewenvironment{abstract}%
970 {%
971     \begin{SafeSection}%
972     \section*{Abstract}%
973 }%
974 {\end{SafeSection}}
975 \newenvironment{longabstract}%
976 {%
977     \begin{SafeSection}%
978     \section*{Abstract}%
979     \bgroup\small
980 }%
981 {%
982     \endgraf\egroup
983     \end{SafeSection}%
984 \vspace{.25\baselineskip}
985 \begin{center}
986     {$--*--$}
987 \end{center}
988 \vspace{.5\baselineskip}}

```

3.14 Headings

Redefine style of section headings to match plain *TUGboat*. Negative before skip suppresses following parindent. (So negate the stretch and shrink too).

These macros are called `*head` in the plain styles.

Relaying via `\TB@startsection` detects inappropriate use of `\section*`. Of course, if (when) *we* use it, we need to avoid that relaying; this can be done by `\letting \TB@startsection to \TB@safe@startsection`, within a group.

First the version for use in the default case, when class option `NUMBERSEC` is in effect.

```

989 \if@numbersec
990   \def\section{\TB@startsection{section}%
991     1%
992     \z@
993     {-8\p@}%
994     {4\p@}%
995     {\normalsize\bf\raggedright\hyphenpenalty=\@M}}
996   \def\subsection{\TB@startsection{subsection}%
997     2%
998     \z@
999     {-8\p@}%
1000    {4\p@}%
1001    {\normalsize\bf\raggedright\hyphenpenalty=\@M}}
1002   \def\subsubsection{\TB@startsection{subsubsection}%
1003     3%
1004     \z@
1005     {-8\p@}%
1006     {4\p@}%
1007     {\normalsize\bf\raggedright\hyphenpenalty=\@M}}
1008   \def\paragraph{\TB@startsection{paragraph}%
1009     4%
1010     \z@
1011     {2.5ex\@plus 1ex}%
1012     {-1em}%
1013     {\normalsize\bf}}

```

Now the version if class option NONUMBER is in effect, i.e., if \if@numbersec is false.

```

1014 \else
1015   \setcounter{secnumdepth}{0}
1016   \def\section{\TB@nolimlabel
1017     \TB@startsection{section}%
1018     1%
1019     \z@
1020     {-8\p@}%
1021     {4\p@}%
1022     {\normalsize\bf\raggedright\hyphenpenalty=\@M}}
1023   \def\subsection{\TB@nolimlabel
1024     \TB@startsection{subsection}%
1025     2%
1026     \z@
1027     {-8\p@}%
1028     {-0.5em\@plus-\fontdimen3\font}%
1029     {\normalsize\bf\raggedright\hyphenpenalty=\@M}}
1030   \def\subsubsection{\TB@nolimlabel
1031     \TB@startsection{subsubsection}%
1032     3%
1033     \parindent
1034     {-8\p@}%
1035     {-0.5em\@plus-\fontdimen3\font}%

```

```

1036          {\normalsize\bf\raggedright\hyphenpenalty=\@M}}
1037 \fi

```

`\TB@startsection` traps * versions of sectioning commands, if numbering isn't in effect. Its argument is the complete set of `\@startsection` arguments.

```

1038 \if@numbersec
1039   \def\TB@startsection#1{\@startsection#1}%
1040 \else
1041   \def\TB@startsection#1{%
1042     \ifstar
1043       {\TBWarning{* - form of \expandafter\string\csname\@firstofsix#1%
1044         \endcsname\space
1045         \MessageBreak
1046         conflicts with nonumber class option}%
1047       \@startsection#1}%
1048     {\@startsection#1}%
1049   }
1050 \fi
1051 \def\@firstofsix#1#2#3#4#5#6{#1}

```

`\TB@safe@startsection` is to be used where `\section*` (etc.) appear in places where the request is OK (because it's built in to some macro we don't fiddle with).

```

1052 \def\TB@safe@startsection#1{\@startsection#1}

```

The `SafeSection` environment allows use of *-forms of sectioning environments. It's not documented for the general public: it's intended as an editor's facility.

```

1053 \newenvironment{SafeSection}%
1054   {\let\TB@startsection\TB@safe@startsection}%
1055   {}

```

And now for the exciting sectioning commands that L^AT_EX defines but we don't have a definition for (whatever else, we don't want Lamport's originals, which come out 'like the blare of a bugle in a lullaby'²).

The three inappropriate ones are subparagraph (indistinguishable from paragraph), and chapter and part. The last seemed almost to be defined in an early version of these macros, since there was a definition of `\l@part`. I've not got down to where that came from (or why). If class option `NONUMBER` is in effect, we also suppress `\paragraph`, since it has no parallel in the plain style.

```

1056 \if@numbersec
1057   \def\subparagraph{\TB@nosection\subparagraph\paragraph}
1058 \else
1059   \def\paragraph{\TB@nosection\paragraph\subsubsection}
1060   \def\subparagraph{\TB@nosection\subparagraph\subsubsection}
1061 \fi
1062 \def\chapter{\TB@nosection\chapter\section}

```

²Thurber, *The Wonderful O*

```

1063 \def\part{\TB@nosection\part\section}
1064 \def\TB@nosection#1#2{\TBWarning{class does not support \string#1,
1065   \string#2\space used instead}\#2}

    \l@<sectioning-name> is for table of contents (of an article).
    We define new macros to allow easily changing the font used for toc entries
    (for TUGboat, we usually want roman, not bold), and the space between entries.
    Nelson Beebe's articles are almost the only ones that ever have toc's.

1066 \def\TBtocsectionfont{\normalfont}
1067 \newskip\TBtocsectionspace \TBtocsectionspace=1.0em\@plus\p@

    Don't ask me (RF) why \l@part is there; I commented it out because I
    couldn't understand why it had been left there for me. To be finally deleted in a
    future release of these macros...

1068 %\def\l@part#1#2{\addpenalty{\@secpenalty}%
1069 % \addvspace{2.25em\@plus\p@}%
1070 % \begingroup
1071 %   \@tempdima 3em \parindent\z@ \rightskip\z@ \parfillskip\z@
1072 %   {\large \bf \leavevmode #1\hfil \hbox to\@pnumwidth{\hss #2}}\par
1073 %   \nobreak
1074 % \endgroup}
1075 %
1076 \def\l@section#1#2{\addpenalty{\@secpenalty}%
1077 \addvspace{\TBtocsectionspace}%
1078 \@tempdima 1.5em
1079 \begingroup
1080   \parindent\z@ \rightskip\z@ % article style makes \rightskip > 0
1081   \parfillskip\z@
1082   \TBtocsectionfont
1083   \leavevmode\advance\leftskip\@tempdima\hskip-\leftskip#1\nobreak\hfil
1084   \nobreak\hb@xt@\@pnumwidth{\hss #2}\par
1085 \endgroup}

```

3.15 Appendices

Appendices (which are really just another sort of section heading) raise a problem: if the sections are unnumbered, we plainly need to restore the section numbering, which in turn allows labelling of section numbers again (`\TBnolimelabel` happens before the `\refstepcounter`, so its effects get lost ... what a clever piece of design that was). So here we go:

```

1086 \renewcommand\appendix{\par
1087 \renewcommand\thesection{\@Alph@c@section}%
1088 \setcounter{section}{0}%
1089 \if@numbersec
1090 \else
1091 \setcounter{secnumdepth}{1}%
1092 \fi

```

Now: is this the start of an appendix environment? This can be detected by looking at `\@currenvir`; if we are, we need to relay to `\@appendix@env` to pick up the optional argument.

```

1093 \def\@tempa{appendix}
1094 \ifx\@tempa\@currenvir
1095   \expandafter\@appendix@env
1096 \fi
1097 }

```

Here we deal with `\begin{appendix}[\langle app-name \rangle]`

```

1098 \newcommand\app@prefix@section{}
1099 \newcommand\@appendix@env[1][Appendix]{%
1100   \renewcommand\@secntformat[1]{\csname app@prefix@##1\endcsname
1101     \csname the##1\endcsname\quad}%
1102   \renewcommand\app@prefix@section{#1 }%
1103 }

```

Ending an appendix environment is pretty trivial...

```

1104 \let\endappendix\relax

```

3.16 References

If the sections aren't numbered, the natural tendency of the author to cross-reference (which, after all, is one of the things \LaTeX is for ever being advertised as being good at) can cause headaches for the editor. (Yes it can; believe me ... there's always one.)

The following command is used by each of the sectioning commands to make a following `\ref` command bloop at the author. Even if the author then ignores the complaint, the poor old editor may find the offending `\label` rather more easily.

(Note that macro name is to be read as “*noli me label*” (I don't know the mediæval Latin for ‘label’).

Comment To come (perhaps): detection of the act of labelling, and an analogue of `\ifG@refundefined` for this sort of label

```

1105 \def\TB@nolimelabel{%
1106   \def\@currentlabel{%
1107     \protect\TBWarning{%
1108       Invalid reference to numbered label on page \thepage
1109       \MessageBreak made%
1110     }%
1111     \textbf{?!?}%
1112   }%
1113 }

```

3.17 Title references

This is a first cut at a mechanism for referencing by the title of a section; it employs the delightfully simple idea Sebastian Rahtz has in the `nameref` package (which is part of `hyperref`). As it stands, it lacks some of the bells and whistles of the original, but they could be added; this is merely proof-of-concept.

The name label comes from the moveable bit of the section argument; we subvert the `\@sect` and `\@ssect` commands (the latter deals with starred section commands) to grab the relevant argument.

```

1114 \let\TB@@sect\@sect
1115 \let\TB@@ssect\@ssect
1116 \def\@sect#1#2#3#4#5#6[#7]#8{%
1117   \def\@currentlabelname{#7}%
1118   \TB@@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{#8}%
1119 }
1120 \def\@ssect#1#2#3#4#5{%
1121   \def\@currentlabelname{#5}%
1122   \TB@@ssect{#1}{#2}{#3}{#4}{#5}%
1123 }
```

The `\newlabel` command that gets written to the `.aux` file needs to be redefined to have three components to its argument:

```

1124 \def\label#1{%
1125   \bsphack
1126   \let\label\@gobble
1127   \let\index\@gobble
1128   \if@filesw
1129     \protected@write\@auxout{%
1130       {\string\newlabel{#1}{%
1131         {\@currentlabel}{\thepage}{\@currentlabelname}}}%
1132       }%
1133   \fi
1134   \esphack
1135 }%
1136 }
```

Of course, in the case of a sufficiently mad author, there will be no sectioning commands, so we need to

```

1137 \let\@currentlabelname\empty
```

References are pretty straightforward, but need three extra utility commands (analogous to the `\@firstof...`, etc., defined in the kernel).

```

1138 \DeclareRobustCommand\ref[1]{\expandafter\@setref
1139   \csname r@#1\endcsname\@firstofthree{#1}}
1140 \DeclareRobustCommand\pageref[1]{\expandafter\@setref
1141   \csname r@#1\endcsname\@secondofthree{#1}}
1142 \DeclareRobustCommand\nameref[1]{\expandafter\@setref
1143   \csname r@#1\endcsname\@thirdofthree{#1}}
1144 \long\def\@firstofthree#1#2#3{#1}
1145 \long\def\@secondofthree#1#2#3{#2}
```



```
1146 \long\def\@thirdofthree#1#2#3{#3}
```

3.18 Float captions

By analogy with what we've just done to section titles and the like, we now do our best to discourage hyphenation within captions. We also typeset them in `\small`.

```
1147 \long\def\@makecaption#1#2{%
1148   \vskip\abovcaptionskip
1149   \sbox\@tempboxa{\small #1: #2}%
1150   \ifdim \wd\@tempboxa >\hsize
1151     \raggedright\hyphenpenalty=\@M \parindent=1em
1152     {\small \noindent #1: #2\par}%
1153   \else
1154     \global \@minipagefalse
1155     \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
1156   \fi
1157   \vskip\belowcaptionskip}
```

Also use `\small` for the caption labels, and put the label itself (Figure xx) in bold.

```
1158 \def\fnun@figure{\small \bf \figurename\nobreakspace\thefigure}}
1159 \def\fnun@table{\small \bf \tablename\nobreakspace\thetable}}
```

3.19 Size changing commands

Apart from their 'normal' effects, these commands change the glue around displays.

```
1160 \renewcommand\normalsize{%
1161   \@setfontsize\normalsize\@xpt\@xipt
1162   \abovedisplayskip=3\p@\@plus 3\p@\@minus\p@
1163   \belowdisplayskip=\abovedisplayskip
1164   \abovedisplayshortskip=\z@\@plus 3\p@
1165   \belowdisplayshortskip=\p@\@plus 3\p@\@minus\p@
1166 }
1167
1168 \renewcommand\small{%
1169   \@setfontsize\small\@ixpt{11}%
1170   \abovedisplayskip=2.5\p@\@plus 2.5\p@\@minus\p@
1171   \belowdisplayskip=\abovedisplayskip
1172   \abovedisplayshortskip=\z@\@plus 2\p@
1173   \belowdisplayshortskip=\p@\@plus 2\p@\@minus\p@
1174 }
1175 \renewcommand\footnotesize{%
1176   \@setfontsize\footnotesize\@viipt{9.5}%
1177   \abovedisplayskip=3\p@\@plus 3\p@\@minus\p@
1178   \belowdisplayskip=\abovedisplayskip
1179   \abovedisplayshortskip=\z@\@plus 3\p@
1180   \belowdisplayshortskip=\p@\@plus 3\p@\@minus\p@
1181 }
```

3.20 Lists and other text inclusions

```

1182 \def\@listi{%
1183   \leftmargin\leftmargini\parsep=\p@\@plus\p@\@minus\p@
1184   \itemsep=\parsep
1185   \listparindent=1em
1186 }
1187
1188 \def\@listii{%
1189   \leftmargin\leftmarginii
1190   \labelwidth=\leftmarginii \advance\labelwidth-\labelsep
1191   \topsep=2\p@\@plus\p@\@minus\p@
1192   \parsep=\p@\@plus\p@\@minus\p@
1193   \itemsep=\parsep
1194   \listparindent=1em
1195 }
1196
1197 \def\@listiii{%
1198   \leftmargin=\leftmarginiii
1199   \labelwidth=\leftmarginiii \advance\labelwidth-\labelsep
1200   \topsep=\p@\@plus\p@\@minus\p@
1201   \parsep=\z@
1202   \itemsep=\topsep
1203   \listparindent=1em
1204 }
1205 \def\quote{\list{}{\rightmargin.5\leftmargin}\item[]}
```

From Dominik Wujastyk's font article. First paragraph of a quotation will not be indented, and right margin is decreased for narrow columns.

```

1206 \renewcommand{\quotation}{\list{}{\listparindent 1.5em
1207   \rightmargin.5\leftmargin\parsep \z@\@plus\p@}\item[]}
```

3.21 Some fun with verbatim

The plain *TUGboat* style allows [optional] arguments to its `\verbatim` command. This will allow the author (or editor) to specify a range of exciting features; we would definitely like the numbered verbatim style for code (that facility is reserved for a future version of this package), and the present little bit of code imposes the `\ruled` option on the built-in `verbatim` environment. (Note that we don't yet deal with `verbatim*`, which is in itself an option to the plain original.)

We start by saving various bits and bobs whose operation we're going to subvert.

```

1208 %\let\@TB@verbatim\@verbatim
1209 \let\@TBverbatim\verbatim
1210 \let\@TBendverbatim@endverbatim
```

Impose an optional argument on the environment.

We start the macro with `\par` to avoid a common error: if the optional argument is `\small`, and the document has no blank line before the verbatim block, we don't want that preceding paragraph to be set with `\small`'s line spacing.

(\obeylines added to prevent the \futurelet from propagating into the body of the verbatim, thus causing lines that start with odd characters (like # or even \) to behave peculiarly.)

```
1211 \def\verbatim{\par\obeylines
1212 \futurelet\reserved@a\@switch@sqbverbatim}
1213 \def\@switch@sqbverbatim{\ifx\reserved@a[%]
1214 \expandafter\@sqbverbatim\else
1215 \def\reserved@b{\@sqbverbatim[]}\expandafter\reserved@b\fi}
1216 \def\@sqbverbatim[#1]{%
```

The optional argument consists entirely of functions that modify the appearance of the environment. Following the `plain` style, we define the functions we can execute in the optional argument here.

The command `\ruled` tells us that there should be rules above and below the verbatim block.

```
1217 \def\ruled{\let\if@ruled\iftrue}%
```

Then we just execute the ones we've got, and relay to a (hacked) copy of the built-in environment.

```
1218 #1\@TBverbatim}
```

The built-in environment itself relays to `\@verbatim`, which we've subverted to impose our views on appearance.

```
1219 \def\@verbatim{%
```

First, we deal with `\ruled`:

```
1220 \if@ruled\trivlist\item\hrule\kern5\p@\nobreak\fi
```

Now, the code out of the original verbatim environment:

```
1221 \trivlist \item\relax
1222 \if@minipage\else\vskip\parskip\fi
1223 \leftskip\@totalleftmargin\rightskip\z@skip
1224 \parindent\z@\parfillskip\@flushglue\parskip\z@skip
1225 @@par
1226 \@tempswafalse
1227 \def\par{%
1228 \if@tempswa
1229 \leavevmode \null @@par\penalty\interlinepenalty
1230 \else
1231 \@tempwattrue
1232 \ifhmode\@par\penalty\interlinepenalty\fi
1233 \fi}%
1234 \obeylines \verbatim@font \@noligs
1235 \let\do\@makeoother \dospecials
1236 \everypar \expandafter{\the\everypar \unpenalty}%
1237 }%
```

To end the environment, we do everything in reverse order: relay via the copy we made of `\endverbatim`, and then finish off the option changes (again `\ruled` only, so far).

```

1238 \def\endverbatim{\@TBendverbatim
1239 \if@ruled\kern5\p@\hrule\endtrivlist\fi}

\enablemetacode simply typesets3 something that looks (verbatim) like:
    <meta-text>

as:
    <meta-text>

1240 {\makeactive<
1241 \gdef<#1>{\reset@font\ensuremath{\langle}%
1242 \textit{#1}%
1243 \ensuremath{\rangle}}}
1244 }

Finally, we define the \if used by the \ruled option
1245 \let\if@ruled\iffalse

```

3.22 Bibliography

This is more or less copied verbatim from Glenn Paulley's *chicago.sty* (gnpaulle@bluebox.uwaterloo.ca). It produces an author-year citation style bibliography, using output from the BIBTEX style file based on that by Patrick Daly. It needs extra macros beyond those in standard L^AT_EX to function properly. The form of the bibitem entries is:

```

\bibitem[\protect\citeauthoryear{Jones, Baker, and Smith}
{Jones et al.}{1990}{key}...

```

The available citation commands are:

```

\cite{key}      → (Jones, Baker, and Smith 1990)
\citeA{key}     → (Jones, Baker, and Smith)
\citeNP{key}    → Jones, Baker, and Smith 1990
\citeANP{key}   → Jones, Baker, and Smith
\citeN{key}     → Jones, Baker, and Smith (1990)
\shortcite      → (Jones et al. 1990)
\citeyear       → (1990)
\citeyearNP     → 1990

```

First of all (after checking that we're to use Harvard citation at all), make a copy of L^AT_EX's default citation mechanism.

```

1246 \if@Harvardcite
1247 \let\@internalcite\cite

```

Normal forms.

```

1248 \def\cite{\def\@citesep{-1000}%
1249 \def\@cite##1##2{(\@1\if@tempwa , ##2\fi)}%
1250 \def\citeauthoryear##1##2##3{##1, ##3\@internalcite}
1251 \def\citeNP{\def\@citesep{-1000}%

```

³Or will simply typeset, when we get around to implementation proper

```

1252 \def\cite##1##2{##1\if@tempswa , ##2\fi}%
1253 \def\citeauthoryear##1##2##3{##1, ##3}\@internalcite}
1254 \def\citeN{\def\@citesep{-1000}%
1255 \def\cite##1##2{##1\if@tempswa , ##2\else{}}\fi}%
1256 \def\citeauthoryear##1##2##3{##1 (##3)\@citedata}
1257 \def\citeA{\def\@citesep{-1000}%
1258 \def\cite##1##2{##1\if@tempswa , ##2\fi}}%
1259 \def\citeauthoryear##1##2##3{##1}\@internalcite}
1260 \def\citeANP{\def\@citesep{-1000}%
1261 \def\cite##1##2{##1\if@tempswa , ##2\fi}%
1262 \def\citeauthoryear##1##2##3{##1}\@internalcite}

```

Abbreviated forms (using *et al.*)

```

1263 \def\shortcite{\def\@citesep{-1000}%
1264 \def\cite##1##2{##1\if@tempswa , ##2\fi}}%
1265 \def\citeauthoryear##1##2##3{##2, ##3}\@internalcite}
1266 \def\shortciteNP{\def\@citesep{-1000}%
1267 \def\cite##1##2{##1\if@tempswa , ##2\fi}%
1268 \def\citeauthoryear##1##2##3{##2, ##3}\@internalcite}
1269 \def\shortciteN{\def\@citesep{-1000}%
1270 \def\cite##1##2{##1\if@tempswa , ##2\else{}}\fi}%
1271 \def\citeauthoryear##1##2##3{##2 (##3)\@citedata}
1272 \def\shortciteA{\def\@citesep{-1000}%
1273 \def\cite##1##2{##1\if@tempswa , ##2\fi}}%
1274 \def\citeauthoryear##1##2##3{##2}\@internalcite}
1275 \def\shortciteANP{\def\@citesep{-1000}%
1276 \def\cite##1##2{##1\if@tempswa , ##2\fi}%
1277 \def\citeauthoryear##1##2##3{##2}\@internalcite}

```

When just the year is needed:

```

1278 \def\citeyear{\def\@citesep{-1000}%
1279 \def\cite##1##2{##1\if@tempswa , ##2\fi}}%
1280 \def\citeauthoryear##1##2##3{##3}\@citedata}
1281 \def\citeyearNP{\def\@citesep{-1000}%
1282 \def\cite##1##2{##1\if@tempswa , ##2\fi}%
1283 \def\citeauthoryear##1##2##3{##3}\@citedata}

```

Place commas in-between citations in the same `\citeyear`, `\citeyearNP`, `\citeN`, or `\shortciteN` command. Use something like `\citeN{ref1,ref2,ref3}` and `\citeN{ref4}` for a list.

```

1284 \def\@citedata{%
1285 \ifnextchar [{\@tempswatrue\@citedatax}%
1286 {\@tempswafalse\@citedatax[]}%
1287 }
1288
1289 \def\@citedatax[#1]#2{%
1290 \if@filesw\immediate\write\auxout{\string\citation{#2}}\fi%
1291 \def\@citea{}\@cite{\for\@citeb:=#2\do%
1292 {\@citea\def\@citea{, }\@ifundefined% by Young
1293 {b@\@citeb}{\bf ?}%
1294 \@warning{Citation ‘\@citeb’ on page \thepage \space undefined}}%

```

1295 {\csname b@%citeb\endcsname}}{#1}}%

Don't box citations, separate with ; and a space; Make the penalty between citations negative: a good place to break.

1296 \def\@citex[#1]#2{%

1297 \if@files\immediate\write\@auxout{\string\citation{#2}}\fi%

1298 \def\@citea{}\@cite{\@for\@citeb:=#2\do%

1299 {\@citea\def\@citea{; }\@ifundefined% by Young

1300 {b@%citeb}{\bf ?}}%

1301 \@warning{Citation '%citeb' on page \thepage \space undefined}}%

1302 {\csname b@%citeb\endcsname}}{#1}}%

No labels in the bibliography.

1303 \def\@biblabel#1{}

Set length of hanging indentation for bibliography entries.

1304 \newlength{\bibhang}

1305 \setlength{\bibhang}{2em}

Indent second and subsequent lines of bibliographic entries. Stolen from openbib.sty: \newblock is set to {}.

1306 \newdimen\bibindent

1307 \bibindent=1.5em

1308 \@ifundefined{refname}%

1309 {\newcommand{\refname}{References}}%

1310 {}%

For safety's sake, suppress the \TB@startsection warnings here...

1311 \def\thebibliography#1{%

1312 \let\TB@startsection\TB@safe@startsection

1313 \section*{\refname

1314 \@mkboth{\uppercase{\refname}}{\uppercase{\refname}}}%

1315 \list{[\arabic{enumi}]}{%

1316 \labelwidth\z@ \labelsep\z@

1317 \leftmargin\bibindent

1318 \itemindent -\bibindent

1319 \listparindent \itemindent

1320 \parsep \z@

1321 \usecounter{enumi}}%

1322 \def\newblock{}

1323 \BibJustification

1324 \sfcode'\.=1000\relax

1325 }

etal Other bibliography odds and ends.

\bibentry 1326 \def\etal{et\,al.\@}

1327 \def\bibentry{%

1328 \smallskip

1329 \hangindent=\parindent

1330 \hangafter=1

1331 \noindent

```

1332 \sloppy
1333 \clubpenalty500 \widowpenalty500
1334 \frenchspacing
1335 }

```

`\bibliography` Changes made to accommodate TUB file naming conventions

```

\bibliographystyle 1336 \def\bibliography#1{%
1337   \if@filesw
1338     \immediate\write\@auxout{\string\bibdata{\@tubfilename{#1}}}%
1339   \fi
1340   \input{\jobname.bbl}%
1341 }
1342 \def\bibliographystyle#1{%
1343   \if@filesw
1344     \immediate\write\@auxout{\string\bibstyle{\@tubfilename{#1}}}%
1345   \fi
1346 }

```

`\thebibliography` If the user's asked to use L^AT_EX's default citation mechanism (using the `rawcite` option), we still need to play with `\TB@startsection`: this is a boring fact of life...

We also patch `\sloppy` in case there's a need for alternative justification of the body of the bibliography.

```

1347 \else
1348 \let\TB@thebibliography\thebibliography
1349 \def\thebibliography{%
1350   \let\TB@startsection\TB@safe@startsection
1351   \let\sloppy\BibJustification
1352   \TB@thebibliography}
1353 \fi

```

`\BibJustification` `\BibJustification` defines how the bibliography is to be justified. The Lamport default is simply “`\sloppy`”, but we regularly find some sort of ragged right setting is appropriate. (`\BibJustification` is nevertheless reset to its default value at the start of a paper.)

```

1354 \let\TB@sloppy\sloppy
1355 \let\BibJustification\TB@sloppy
1356 \newcommand{\SetBibJustification}[1]{%
1357   \renewcommand{\BibJustification}{#1}%
1358 }
1359 \ResetCommands\expandafter{\the\ResetCommands
1360   \let\BibJustification\TB@sloppy
1361 }

```

3.23 Registration marks

```

1362 \def\HorzR@gisterRule{\vrule \@height 0.2\p@ \@depth\z@ \@width 0.5in }
1363 \def\DownShortR@gisterRule{\vrule \@height 0.2\p@ \@depth 1pc \@width 0.2\p@ }
1364 \def\UpShortR@gisterRule{\vrule \@height 1pc \@depth\z@ \@width 0.2\p@ }

```

“T” marks centered on top and bottom edges of paper

```

1365 \def\ttopregister{\dlap{%
1366     \hb@xt@\trimwd{\HorzR@gisterRule \hfil \HorzR@gisterRule
1367         \HorzR@gisterRule \hfil \HorzR@gisterRule}%
1368     \hb@xt@\trimwd{\hfil \DownShortR@gisterRule \hfil}}}
1369 \def\tbotregister{\ulap{%
1370     \hb@xt@\trimwd{\hfil \UpShortR@gisterRule \hfil}%
1371     \hb@xt@\trimwd{\HorzR@gisterRule \hfil \HorzR@gisterRule
1372         \HorzR@gisterRule \hfil \HorzR@gisterRule}}}
1373 \def\topregister{\ttopregister}
1374 \def\botregister{\tbotregister}

```

3.24 Running heads

```

1375 \def \rtitlex{\def\texttub##1{{\normalsize\textrm{##1}}}\TUB, \volx }
1376 \def\PrelimDraftfooter{%
1377     \dlap{\kern\textheight\kern3pc
1378         \rlap{\hb@xt@\pagewd{\midrttitle\hfil\midrttitle}}
1379     }}
1380

```

registration marks; these are temporarily inserted in the running head

```

1381 \def\MakeRegistrationMarks{}
1382 \def\UseTrimMarks{%
1383     \def\MakeRegistrationMarks{%
1384         \ulap{\rlap{%
1385             \vbox{\dlap{\vbox to\trimlgt{\vfil\botregister}}}%
1386             \topregister\vskip \headmargin \vskip 10\p@}}}%
1387     }
1388
1389 \def\@oddhead{\MakeRegistrationMarks\PrelimDraftfooter
1390     \normalsize\csname normalshape\endcsname\rm
1391     \rtitlex\quad\midrttitle \hfil \thepage}
1392 \def\@evenhead{\MakeRegistrationMarks\PrelimDraftfooter
1393     \normalsize\csname normalshape\endcsname\rm
1394     \thepage\hfil\midrttitle\quad\rtitlex}
1395 \def\@oddfoot{}
1396 \def\@evenfoot{}
1397 \def\ps@headings{}
1398 \pagestyle{headings}

```

3.25 Output routine

Modified to alter \brokenpenalty across columns

Comment We’re playing with fire here: for example, \@outputdblcol has changed in L^AT_EX 2_ε for 1995/06/01 (with the use of \hb@xt@). *This* time there’s no semantic change, but...

```

1399 \def\@outputdblcol{\if@firstcolumn \global\@firstcolumnfalse
1400     \global\setbox\@leftcolumn\box\@outputbox
1401     \global\brokenpenalty10000

```



```

1402 \else \global\@firstcolumntrue
1403 \global\brokenpenalty100
1404 \setbox\@outputbox\vbox{\hb@xt@\textwidth{\hb@xt@\columnwidth
1405 {\box\@leftcolumn \hss}\hfil \vrule \width\columnseprule\hfil
1406 \hb@xt@\columnwidth{\box\@outputbox \hss}}}\@combinedblfloats
1407 \outputpage \begingroup \@dblfloatplacement \@startdblcolumn
1408 \whiles\if@fcolmade \fi{\@outputpage\@startdblcolumn}\endgroup
1409 \fi}

```

3.26 Font-related definitions and machinery

These are mostly for compatibility with plain `tugboat.sty`

```

1410 \newif\ifFirstPar \FirstParfalse
1411 \def\smc{\sc}
1412 \def\ninepoint{\small}
1413 \</classtail>

```

`\SMC` *isn't* small caps — Barbara Beeton says she thinks of it as “big small caps”. She says (modulo capitalisation of things...):

For the things it's used for, regular small caps are not appropriate — they're too small. Real small caps are appropriate for author names (and are so used in continental bibliographies), section headings, running heads, and, on occasion, words to which some emphasis is to be given. `\SMC` was designed to be used for acronyms and all-caps abbreviations, which look terrible in small caps, but nearly as bad in all caps in the regular text size. The principle of using “one size smaller” than the text size is similar to the design of caps in German — where they are smaller relative to lowercase than are caps in fonts intended for English, to improve the appearance of regular text in which caps are used at the heads of all nouns, not just at the beginnings of sentences.

We define this in terms of the memory of the size currently selected that's maintained in `\@currsize`: if the user does something silly re. selecting fonts, we'll get the wrong results. The following code is adapted from an old version of `resize.sty` by Donald Arseneau and Matt Swift. (Note that the order of examination of `\@currsize` is to get the commonest cases out of the way first.)

```

1414 \<*common>
1415 \DeclareRobustCommand\SMC{%
1416 \ifx\@currsize\normalsize\small\else
1417 \ifx\@currsize\small\footnotesize\else
1418 \ifx\@currsize\footnotesize\scriptsize\else
1419 \ifx\@currsize\large\normalsize\else
1420 \ifx\@currsize\Large\large\else
1421 \ifx\@currsize\LARGE\Large\else
1422 \ifx\@currsize\scriptsize\tiny\else
1423 \ifx\@currsize\tiny\tiny\else
1424 \ifx\@currsize\huge\LARGE\else
1425 \ifx\@currsize\Huge\huge\else

```

```

1426          \small\SMC@unknown@warning
1427 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
1428 }
1429 \newcommand\SMC@unknown@warning{\TBWarning{\string\SMC: nonstandard
1430   text font size command -- using \string\small}}
1431 \newcommand\textSMC[1]{\SMC #1}

```

The `\acro` command uses `\SMC` as it was originally intended. Note that, since most of these things are uppercase-only names, it fiddles with the spacefactor after inserting its text.

```

1432 \newcommand\acro[1]{\textSMC{#1}\@}
1433 \common

```

3.27 Miscellaneous definitions

`\EdNote` allows the editor to enter notes in the text of a paper. If the command is given something that appears like an optional argument, the entire text of the note is placed in square brackets. (Yes, it really is!)

```

1434 \*classtail
1435 \def\xEdNote{\EdNoteFont Editor's note:\enspace }
1436 \def \EdNote{\@ifnextchar [%]
1437   {%
1438     \ifvmode
1439       \smallskip\noindent\let\@EdNote@\@EdNote@
1440     \else
1441       \unskip\quad\def\@EdNote@{\unskip\quad}%
1442       \fi
1443       \@EdNote
1444     }%
1445     \xEdNote
1446 }
1447 \long\def\@EdNote[#1]{%
1448   [\thinspace\xEdNote\ignorespaces
1449     #1%
1450     \unskip\thinspace]%
1451   \@EdNote@
1452 }
1453 \def\@EdNote@v{\par\smallskip}

```

Macros for Mittelbach's self-documenting style

```

1454 \def\SelfDocumenting{%
1455   \setlength\textwidth{31pc}
1456   \onecolumn
1457   \parindent \z@
1458   \parskip 2\p@\@plus\p@\@minus\p@
1459   \oddsidemargin 8pc
1460   \evensidemargin 8pc
1461   \marginparwidth 8pc
1462   \toks@\expandafter{\@oddhead}%

```

```

1463 \xdef\@oddhead{\hss\hb@xt@\pagewd{\the\toks@}}%
1464 \toks@\expandafter{\@evenhead}%
1465 \xdef\@evenhead{\hss\hb@xt@\pagewd{\the\toks@}}%
1466 \def\ps@titlepage{}%
1467 }
1468 \def\ps@titlepage{}
1469
1470 \long\def\@makefnmark#1{\parindent 1em\noindent\hb@xt@2em{}%
1471 \llap{\@makefnmark}\null$\mskip5mu$#1}
1472
1473 %% \long\def\@makefnmark#1{\parindent 1em
1474 %% \noindent
1475 %% \hb@xt@2em{\hss\@makefnmark}%
1476 %% \hskip0.27778\fontdimen6\textfont\z@\relax
1477 %% #1%
1478 %% }

```

`\creditfootnote` Sometimes we want the label “Editor’s Note:”, sometimes not.

```

\supportfootnote 1479 \def\creditfootnote{\nomarkfootnote\xEdNote}
1480 \def\supportfootnote{\nomarkfootnote\relax}

```

General macro `\nomarkfootnote` to make a footnote without a reference mark, etc. `#1` is an extra command to insert, `#2` the user’s text.

```

1481 \gdef\nomarkfootnote#1#2{\begingroup
1482 \def\thefootnote{}%
1483 % no period, please, also no fnmark.
1484 \def\@makefnmark##1{##1}%
1485 \footnotetext{\noindent #1#2}%
1486 \endgroup
1487 }

```

3.28 Initialization

If we’re going to use Harvard-style bibliographies, we set up the bibliography style: the user doesn’t get any choice.

```

1488 \if@Harvardcite
1489 \AtBeginDocument{%
1490 \bibliographystyle{ltugbib}%
1491 }
1492 \fi
1493 \authornumber\z@
1494 \let\@signature\@defaultsignature
1495 \InputIfFileExists{ltugboat.cfg}{\TBInfo{Loading ltugboat
1496 configuration information}}{}
1497 </classtail>

```

4 L^AT_EX 2_ε Proceedings class

`\@tugclass` Make the code of `ltugboat.cls` (when we load it) say it's really us:

```
1498 <*ltugproccls>
1499 \def\@tugclass{ltugproc}
```

`\if@proctw@column` For the case where we're preparing the preprints, we may not have been able to prepare submissions for typesetting in two columns. In this case, therefore, we may need the option `onecolumn`, that will suppress the use of `twocolumn` setting within the article.

```
1500 \newif\if@proctw@column \@proctw@columntrue
1501 \DeclareOption{onecolumn}{\@proctw@columnfalse}
```

`\if@proc@sober` TUG'96 proceedings switched to more sober headings still; so the `tug95` option establishes the original state. In the absence of any other guidance, we use the '96 for TUG'97 proceedings, but also allow numbering of sections.

```
1502 \newif\if@proc@sober
1503 \newif\if@proc@numerable
1504 \DeclareOption{tug95}{%
1505   \@proc@soberfalse
1506   \@proc@numerablefalse
1507 }
1508 \DeclareOption{tug96}{%
1509   \@proc@sobertrue
1510   \@proc@numerablefalse
1511 }
1512 \DeclareOption{tug97}{%
1513   \@proc@sobertrue
1514   \@proc@numerabletrue
1515 }
1516 \DeclareOption{tug2002}{%
1517   \@proc@sobertrue
1518   \@proc@numerabletrue
1519   \let\if@proc@numbersec\iftrue
1520   \PassOptionsToClass{numbersec}{ltugboat}%
1521 }
```

`\if@proc@numbersec` If we're in a class that allows section numbering (the actual check occurs after `\ProcessOptions`, we can have the following:

```
1522 \DeclareOption{numbersec}{\let\if@proc@numbersec\iftrue
1523   \PassOptionsToClass{numbersec}{ltugboat}%
1524 }
1525 \DeclareOption{nonumber}{\let\if@proc@numbersec\iffalse
1526   \PassOptionsToClass{nonumber}{ltugboat}%
1527 }
```

`\ifTB@title` If we have a paper for which we want to create a detached title, with an editor's note, and then set the paper separately, we use option `notitle`.

```

1528 \newif\ifTB@title
1529 \DeclareOption{title}{\TB@titletrue}
1530 \DeclareOption{notitle}{\TB@titlefalse}
1531 \AtBeginDocument{\stepcounter{page}}

```

There are these people who seem to think `tugproc` is an option as well as a class...

```

1532 \DeclareOption{tugproc}{%
1533   \ClassWarning{\@tugclass}{Option \CurrentOption\space ignored}%
1534 }

```

All other options are simply passed to `ltugboat`...

```

1535 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{ltugboat}}

```

If there's a `tugproc` defaults file, input it now: it may tell us which year we're to perform for... (Note: this code *is* millenium-proof. It's not terribly classy for years beyond 2069, but then I'm not going to be around then—this will be an interesting task for a future `TeX`ie...)

```

1536 \InputIfFileExists{\@tugclass.cfg}{\ClassInfo{ltugproc}%
1537   {Loading ltugproc configuration information}}{}
1538 \@ifundefined{TUGprocExtraOptions}%
1539   {\let\TUGprocExtraOptions\@empty}%
1540   {\edef\TUGprocExtraOptions{\TUGprocExtraOptions}}

```

`\tugProcYear` Now work out what year it is

```

1541 \@tempcnta\year
1542 \ifnum\@tempcnta<2000
1543   \divide\@tempcnta by100
1544   \multiply\@tempcnta by100
1545   \advance\@tempcnta-\year
1546   \@tempcnta-\@tempcnta
1547 \fi

```

And use that for calculating a year for us to use.

```

1548 \edef\@tempa{\noexpand\providecommand\noexpand\tugProcYear
1549   {\ifnum10>\@tempcnta0\fi\the\@tempcnta}}
1550 \@tempa
1551 \ClassInfo{ltugproc}{Class believes year is
1552   \expandafter\ifnum\tugProcYear<2000 19\fi\tugProcYear
1553   \@gobble}

```

Check that this is a “sensible year” (one for which we have a class option defined). If not, make it a ‘suitable’ year, in particular, one that allows numbering sections.

```

1554 \expandafter\ifx\csname ds@tug\tugProcYear\endcsname\relax
1555   \def\tugProcYear{2002}\fi

```

Now execute the default ‘year’ option and get on with processing. Note that this command gets ignored if the configuration file specifies a silly year.

```

1556 \ExecuteOptions{tug\tugProcYear,title\TUGprocExtraOptions}
1557 \ProcessOptions
1558 \if@proc@numbersec
1559   \if@proc@numerable
1560   \else
1561     \ClassWarning{\@tugclass}{This year's proceedings may not have
1562       numbered sections}%
1563   \fi
1564 \fi

```

Call `\tugboat`, adding whichever section numbering option is appropriate

```

1565 \LoadClass[\if@proc@numbersec numbersec\else nonumber\fi]{tugboat}

```

4.1 Proceedings titles

`\maketitle` There's no provision for 'section titles' in proceedings issues, as there are in *TUGboat* proper. Note the tedious L^AT_EX bug-avoidance in the `\@TB@test@document` macro.

```

1566 \def\maketitle{%
1567   \begingroup

      first, a bit of flim-flam to generate an initial value for \rhAuthor (unless the
      user's already given one with a \shortAuthor command).

1568   \ifshortAuthor\else
1569     \global\let\rhAuthor\@empty
1570     \def\g@addto@rhAuthor##1{%
1571       \begingroup
1572       \toks@\expandafter{\rhAuthor}%
1573       \let\thanks\@gobble
1574       \protected@xdef\rhAuthor{\the\toks@##1}%
1575     \endgroup
1576   }%
1577   \@getauthorlist\g@addto@rhAuthor
1578 \fi

      now, the real business of setting the title

1579   \ifTB@title
1580     \setcounter{footnote}{0}%
1581     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1582     \if@proctw@column
1583       \twocolumn[\@maketitle]%
1584     \else
1585       \onecolumn
1586       \global\@topnum\z@
1587       \@maketitle
1588     \fi
1589     \@thanks
1590     \thispagestyle{TBproctitle}
1591   \fi
1592 \endgroup

```

```

1593 \TB@madetitletrue
1594 }
1595 \newif\ifTB@madetitle \TB@madetitlefalse

\TB@test@document \TB@test@document checks to see, at entry to \maketitle, if we've had
\begin{document}. See LATEX bug report latex/2212, submitted by Robin Fair-
bairns, for details.

1596 \def\@TB@test@document{%
1597 \edef\@tempa{\the\everypar}
1598 \def \@tempb{\@nodocument}
1599 \ifx \@tempa\@tempb
1600 \@nodocument
1601 \fi
1602 }

\AUTHORfont Define the fonts for titles and things
\TITLEfont 1603 \def\AUTHORfont {\large\rmfamily\mdseries\upshape}
\addressfont 1604 \def\TITLEfont {\Large\rmfamily\mdseries\upshape}
\netaddrfont 1605 \def\addressfont{\small\rmfamily\mdseries\upshape}
1606 \def\netaddrfont{\small\ttfamily\mdseries\upshape}

\aboveauthorskip Some stretchable stuff to permit variability in page layout.
\belowauthorskip 1607 \newskip\aboveauthorskip \aboveauthorskip=18\p@ \@plus4\p@
\belowabstractskip 1608 \newskip\belowauthorskip \belowauthorskip=\aboveauthorskip
1609 \newskip\belowabstractskip \belowabstractskip=14\p@ \@plus3\p@ \@minus2\p@

\@maketitle The body of \maketitle
1610 \def\@maketitle{%
1611 {\parskip\z@
1612 \frenchspacing
1613 \TITLEfont\raggedright\noindent\@title\par
1614 \count@=0
1615 \loop
1616 \ifnum\count@<\authornumber
1617 \vskip\aboveauthorskip
1618 \advance\count@\@ne
1619 {\AUTHORfont\theauthor{\number\count@}\endgraf}%
1620 \addressfont\theaddress{\number\count@}\endgraf
1621 }%
1622 \allowhyphens
1623 \hangindent1.5pc
1624 \netaddrfont\thenetaddress{\number\count@}\endgraf
1625 \hangindent1.5pc
1626 \thePersonalURL{\number\count@}\endgraf
1627 }%
1628 \repeat
1629 \vskip\belowauthorskip}%
1630 \if@abstract
1631 \centerline{\bfseries Abstract}%

```

```

1632     \vskip.5\baselineskip\rmfamily
1633     \list{}\{\listparindent20\p@
1634         \itemindent\z@ \leftmargin4.875pc
1635         \rightmargin\leftmargin \parsep \z@\item[]\ignorespaces
1636         \the\abstract@toks
1637     \endlist\global\@ignoretrue
1638     \fi
1639     \vskip\belowabstractskip
1640     \global\@afterindentfalse\aftergroup\@afterheading
1641 }

```

Comment This is all very weird...why we (of all people) don't allow `\thanks` currently escapes me.

This restriction simply removed 1998/01/09

```

1642 %\def\thanks#1{\@bsphack\TBWarning{\string\thanks\space
1643 %             is not supported}\@esphack}

```

`abstract` Save the contents of the abstract environment in the token register `\abstract@toks`.
`\if@abstract` We need to do this, as otherwise it may get 'typeset' (previously, it got put in a
`\abstract@toks` box) before `\begin{document}`, and experiments prove that this means our shiny new `\SMC` doesn't work in this situation.

If you need to understand the ins and outs of this code, look at the place I lifted it from: `tabularx.dtx` (in the tools bundle). The whole thing pivots on having stored the name of the 'abstract' environment in `\@abstract@`

```

1644 \newtoks\abstract@toks \abstract@toks{}
1645 \let\if@abstract\iffalse
1646 \def\abstract{%
    we now warn unsuspecting users who provide an abstract environment after
    the \maketitle that would typeset it...
1647     \ifTB@madetitle
1648         \TBWarning{abstract environment after \string\maketitle}
1649     \fi
1650     \def\@abstract@{abstract}%
1651     \ifx\@currenvir\@abstract@
1652     \else
1653         \TBEError{\string\abstract\space is illegal:%
1654             \MessageBreak
1655             use \string\begin{\@abstract@} instead}%
1656         {\@abstract@\space may only be used as an environment}
1657     \fi
1658     \global\let\if@abstract\iftrue
1659     {\ifnum0='}\fi
1660     \@abstract@getbody}
1661 \let\endabstract\relax

```

`\@abstract@getbody` gets chunks of the body (up to the next occurrence of `\end`) and appends them to `\abstract@toks`. It then uses `\@abstract@findend` to detect whether this `\end` is followed by `{abstract}`


```

1662 \long\def\@abstract@getbody#1\end{%
1663   \global\abstract@toks\expandafter{\the\abstract@toks#1}%
1664   \@abstract@findend}

```

Here we've got to `\end` in the body of the abstract. `\@abstract@findend` takes the 'argument' of the `\end` do its argument.

```

1665 \def\@abstract@findend#1{%
1666   \def\@tempa{#1}%

```

If we've found an 'end' to match the 'begin' that we started with, we're done with gathering the abstract up; otherwise we stuff the end itself into the token register and carry on.

```

1667   \ifx\@tempa\@abstract@
1668     \expandafter\@abstract@end
1669   \else

```

It's not `\end{abstract}` — check that it's not `\end{document}` either (which signifies that the author's forgotten about ending the abstract)

```

1670     \def\@tempb{document}%
1671     \ifx\@tempa\@tempb
1672       \TBError{\string\begin{\@abstract@}
1673         ended by \string\end{\@tempb}}%
1674       {You've forgotten \string\end{\@abstract@}}
1675     \else
1676       \global\abstract@toks\expandafter{\the\abstract@toks\end{#1}}%
1677       \expandafter\expandafter\expandafter\@abstract@getbody
1678     \fi
1679   \fi}

```

In our case, the action at the 'proper' `\end` is a lot simpler than what appears in `tabularx.dtx` ... don't be surprised!

```

1680 \def\@abstract@end{\ifnum0='{ \fi}%
1681   \expandafter\end\expandafter{\@abstract@}}

```

`\makesignature` `\makesignature` is improper in proceedings, so we replace it with a warning (and a no-op otherwise)

```

1682 \renewcommand{\makesignature}{\TBWarning
1683   {\string\makesignature\space is invalid in proceedings issues}}

```

`\title` We redefine the `\title` command, so as to set the `\rhTitle` command at the same time. While we're at it, we redefine it to have optional arguments for use as 'short' versions, thus obviating the need for users to use the `\shortTitle` command.

```

1684 \renewcommand\title{\@dblarg\TB@title}
1685 \def\TB@title[#1]#2{\gdef\@title{#2}%
1686   \bgroup
1687     \let\thanks\@gobble
1688     \let\\\ %
1689     \protected@xdef\rhTitle{#1}%
1690   \egroup
1691 }

```

```

\shortTitle The \rh* commands are versions to be used in the running head of the article.
\ifshortAuthor Normally, they are the same things as the author and title of the article, but in the
\shortAuthor case that there are confusions therein, the text should provide substitutes, using
the \short* commands.

1692 \def\shortTitle #1{\def\rhTitle{#1}}
1693 \newif\ifshortAuthor
1694 \def\shortAuthor #1{\def\rhAuthor{#1}\shortAuthortrue}

\ps@TBproctitle Now we define the running heads in terms of the \rh* commands.
\ps@TBproc 1695 \def\ps@TBproctitle{\let\@oddhead\MakeRegistrationMarks
\dopagecommands 1696 \let\@evenhead\MakeRegistrationMarks
\setpagecommands 1697 \TB@definefeet
\TB@definefeet 1698 }
\pfoottext 1699 \def\ps@TBproc{%
\rfoottext 1700 \def\@oddhead{\MakeRegistrationMarks
1701 {%
1702 \hfil
1703 \def\{\unskip\ \ignorespaces}%
1704 \rmfamily\rhTitle
1705 }%
1706 }%
1707 \def\@evenhead{\MakeRegistrationMarks
1708 {%
1709 \def\{\unskip\ \ignorespaces}%
1710 \rmfamily\rhAuthor
1711 \hfil
1712 }%
1713 }%
1714 \TB@definefeet
1715 }
1716
1717 \advance\footskip8\p@ % for deeper running feet
1718
1719 \def\dopagecommands{\csname @@pagecommands\number\c@page\endcsname}
1720 \def\setpagecommands#1#2{\expandafter\def\csname @@pagecommands#1\endcsname
1721 {#2}}
1722 \def\TB@definefeet{%
1723 \def\@oddfoot{\ifpreprint\pfoottext\hfil\Now\hfil\thepage
1724 \else\rfoottext\hfil\thepage\fi\dopagecommands}%
1725 \def\@evenfoot{\ifpreprint\thepage\hfil\Now\hfil\pfoottext
1726 \else\thepage\hfil\rfoottext\fi\dopagecommands}%
1727 }
1728
1729 \def\pfoottext{\smc Preprint}: Proceedings of the \volyr{} Annual Meeting}
1730 \def\rfoottext{\normalfont\TUB, \volx\Dash
1731 {Proceedings of the \volyr{} Annual Meeting}}
1732
1733 \pagestyle{TBproc}

```

4.2 Section divisions

Neither sections nor subsections are numbered by default in the proceedings style: note that this puts a degree of stress on authors' natural tendency to reference sections, which is a matter that needs attention. The class option `NUMBERSEC` once again numbers the sections (and noticeably changes the layout).

```
1734 \if@proc@numbersec
1735 \else
1736   \setcounter{secnumdepth}{0}
1737 \fi
```

Otherwise, the `\section` command is pretty straightforward. However, the `\subsection` and `\subsubsection` are run-in, and we have to remember to have negative stretch (and shrink if we should in future choose to have one) on the `<afterskip>` parameter of `\@startsection`, since the whole skip is going to end up getting negated. We use `TB@startsection` to detect inappropriate forms.

```
1738 \if@proc@numbersec
1739 \else
1740   \if@proc@sober
1741     \def\section
1742       {\TB@nolimelabel
1743        \TB@startsection{{section}%
1744                          1%
1745                          \z@%
1746                          {-8\p@\@plus-2\p@\@minus-2\p@}%
1747                          {6\p@}%
1748                          {\normalsize\bfseries\raggedright}}}
1749   \else
1750     \def\section
1751       {\TB@nolimelabel
1752        \TB@startsection{{section}%
1753                          1%
1754                          \z@%
1755                          {-8\p@\@plus-2\p@\@minus-2\p@}%
1756                          {6\p@}%
1757                          {\large\bfseries\raggedright}}}
1758   \fi
1759   \def\subsection
1760     {\TB@nolimelabel
1761      \TB@startsection{{subsection}%
1762                        2%
1763                        \z@%
1764                        {6\p@\@plus 2\p@\@minus2\p@}%
1765                        {-5\p@\@plus -\fontdimen3\the\font}%
1766                        {\normalsize\bfseries}}}
1767   \def\subsubsection
1768     {\TB@nolimelabel
1769      \TB@startsection{{subsubsection}%
1770                        3%
```

```

1771 \parindent%
1772 \z@%
1773 {-5\p@\@plus -\fontdimen3\the\font}%
1774 {\normalsize\bfseries}}
1775 \fi
1776 </ltugproccls>

```

5 Plain T_EX styles

```

1777 <*tugboatsty>
1778 % err...
1779 </tugboatsty>
1780 <*tugprocsty>
1781 % err...
1782 </tugprocsty>

```

6 The L^AT_EX 2_ε compatibility-mode style files

```

1783 <*tugboatsty>
1784 \@obsoletedefile{ltugboat.cls}{ltugboat.sty}
1785 \LoadClass{ltugboat}
1786 </ltugboatsty>
1787 <*ltugprocsty>
1788 \@obsoletedefile{ltugproc.cls}{ltugproc.sty}
1789 \LoadClass{ltugproc}
1790 </ltugprocsty>

```