

L^AT_EX-cursus Week 1

T_EXniCie

26 september 2022

Log in op
[overleaf.com](https://www.overleaf.com)

(Maak een account aan als je er nog geen hebt)

Agenda

- ▶ Introductie tot LaTeX en Overleaf
- ▶ LaTeX documentstructuur
- ▶ Tekst
- ▶ Wiskunde
- ▶ Tot slot / vervolgcursus

Overleaf

Overleaf

New Project

All Projects

Your Projects

Shared with you

Archived Projects

Trashed Projects

TAGS/FOLDERS

+ New Folder

Jaar 1 (1)

Jaar 2 (5)

METEC (2)

Uncategorized (6)

Search projects...

You're on the free plan [Upgrade](#)


Title	Owner	Last Modified	Actions
<input type="checkbox"/> hw2 datastructuren Tim & Manuel	You	2 months ago by You	Share Like Comment Delete
<input type="checkbox"/> hw1 datastructuren	You	4 months ago by You	Share Like Comment Delete
<input type="checkbox"/> lina_groepsopdracht_1	You	a year ago by You	Share Like Comment Delete
<input type="checkbox"/> or_project_literatuur_tim_jio	You	a year ago by You	Share Like Comment Delete
<input type="checkbox"/> presentatie_gr_ri_1	You	a year ago by You	Share Like Comment Delete
<input type="checkbox"/> antwoorden_dictaat_getaltheorie	You	2 years ago by You	Share Like Comment Delete
<input type="checkbox"/> Enqueteverantwoording METEC Jaar 2 METEC	You	2 years ago by You	Share Like Comment Delete
<input type="checkbox"/> ISTAT Eindopdracht verslag Jaar 2	You	2 years ago by jioni_dboy	Share Like Comment Delete
<input type="checkbox"/> Eindrapport METEC Jaar 2 METEC	You	2 years ago by You	Share Like Comment Delete
<input type="checkbox"/> Verwerkingsopdrachten week 1 tm 4 Jaar 2	You	2 years ago by You	Share Like Comment Delete

© 2022 Overleaf

[English](#) | [Privacy and Terms](#) [Security](#) [Contact Us](#) [About](#) [Blog](#)

[Twitter](#) [Facebook](#)

Overleaf



New Project

×

GSNS workshop|

Cancel

Create

Een eenvoudig document in L^AT_EX

```
1 \documentclass{article}
2
3
4 \begin{document}
5
6
7
8
9
10
11
12
13 \end{document}
```

}

preamble: document settings go here

}

body: content (text and images) goes here

Een eenvoudig document in L^AT_EX

```
1 \documentclass{article}
```

```
4 \begin{document}
```

```
6 The Differential and Integral  
7 Calculus, or, as it was formerly  
8 called in this country,  
9 the Doctrine of Fluxions, has always  
10 been supposed to present remarkable  
11 obstacles to the beginner.
```

```
13 \end{document}
```



body: inhoud (tekst, plaatjes, tabellen) hier

Example text: "Elementary Illustrations of the Differential and Integral Calculus" by Augustus De Morgan

Een eenvoudig document in L^AT_EX

```
1 \documentclass[a4paper,11pt]{article}
2
3
4 \begin{document}
5
6 The Differential and Integral
7 Calculus, or, as it was formerly
8 called in this country,
9 the Doctrine of Fluxions, has always
10 been supposed to present remarkable
11 obstacles to the beginner.
12
13 \end{document}
```



preamble: instellingen hier

Example text: "Elementary Illustrations of the Differential and Integral Calculus" by Augustus De Morgan

LaTeX commands

LaTeX commando's beginnen met een backslash `\`, gevolgd door letters of een speciaal teken: `,` `#`, `%`, `....`

Commando's kunnen **argumenten** en **optionele argumenten** hebben.

```
\commando
```

of

```
\commando{argument}
```

or

```
\commando[optioneel argument]{argument}
```


LaTeX commands

Sommige commando's staan in de **body** van het document

- ▶ Het commando `\LaTeX` print het \LaTeX logo. Dit commando staat in de **body** van het document.
- ▶ `\newpage` begint een nieuwe pagina en staat ook in de **body** van het document.
- ▶ `\textbf{text}` is een commando voor **vetgedrukte** tekst. Dit commando heeft 1 argument.
- ▶ `\sqrt[3]{y}` het wortelargument heeft 1 argument en 1 optioneel argument.

LaTeX commands

Andere commando's staan in de **preamble** van het document

- ▶ Met `\title` geef je het document een titel.
- ▶ `\usepackage{PACKAGE-NAAM}` laadt LaTeX code van anderen in je document. Deze code definieert vaak nieuwe commando's of past bestaande commando's aan. Soms verandert de opmaak van je pagina ook door het laden van een package.
- ▶ `\usepackage[paper=a5paper, margin=2cm, landscape=true]{geometry}` laadt het geometry package met 3 optionele argumenten.

Oefeningen



Whitespace

- `a_ _ _ _ _ b`

`a b`

Whitespace

- `a_ _ _ _ _b`

- `a\ _ \ _ \ _ \ _b`

`a b`

`a b`

Whitespace

- `a_ _ _ _ _ b`
- `a\ _ \ _ \ _ \ _ b`
- `a\quad_ b`

`a b`
`a b`
`a b`

Whitespace

- `a_ _ _ _ _ b`
- `a\ _ \ _ \ _ \ _ b`
- `a\quad _ b`
- `a\hspace_{2cm} b`

a b

a b

a b

a b

Whitespace

- `a_____b`
- `a_____\b`
- `a\quad_\b`
- `a\hspace_{2cm}b`
- `\LaTeX_is_cool!`

a b

a b

a b

a b

LaTeX is cool!

Whitespace

- `a_____b`
- `a_____b`
- `a\quad_b`
- `a\hspace_{2cm}b`
- `\LaTeX_is_cool!`
- `\LaTeX_{ }_is_cool!`

`a b`
`a b`
`a b`
`a b`
`\LaTeX is cool!`
`\LaTeX is cool!`

Paragrafen

Een paragraaf bestaat uit enkele regels tekst. Paragrafen worden van elkaar gescheiden door **witregels**.

```
\documentclass[a4paper, 10pt]{article}
\begin{document}
```

The agitation for the Universal Colour Bill continued for three years; and up to the last moment of that period it seemed as though Anarchy were destined to triumph.

A whole army of Polygons, who turned out to fight as private soldiers, was utterly annihilated by a superior force of Isosceles Triangles --- the Squares and Pentagons meanwhile remaining neutral.

```
\end{document}
```

The agitation for the Universal Colour Bill continued for three years; and up to the last moment of that period it seemed as though Anarchy were destined to triumph.

A whole army of Polygons, who turned out to fight as private soldiers, was utterly annihilated by a superior force of Isosceles Triangles — the Squares and Pentagons meanwhile remaining neutral.

Paragraphs

Standaard worden paragrafen ingesprongen. De paragrafen scheiden met een witregel in plaats van inspringing kan door het commando `\usepackage{parskip}` aan de preamble toe te voegen.

```
\documentclass[a4paper, 10pt]{article}
\usepackage{parskip}
\begin{document}
```

The agitation for the Universal Colour Bill continued for three years; and up to the last moment of that period it seemed as though Anarchy were destined to triumph.

A whole army of Polygons, who turned out to fight as private soldiers, was utterly annihilated by a superior force of Isosceles Triangles --- the Squares and Pentagons meanwhile remaining neutral.

```
\end{document}
```

The agitation for the Universal Colour Bill continued for three years; and up to the last moment of that period it seemed as though Anarchy were destined to triumph.

A whole army of Polygons, who turned out to fight as private soldiers, was utterly annihilated by a superior force of Isosceles Triangles — the Squares and Pentagons meanwhile remaining neutral.

Sections

Het commando `\section{SECTIONNAME}` maakt een heading (titel, kop, tussenkopje). Deze headings worden automatisch genummerd. Andere headings zijn:

- `\subsection{}` , `\subsubsection{}` and `\paragraph{}`

```
1 \documentclass[a4paper]{article}
2 \begin{document}
3 \section{How I tried to teach the Theory of Three Dimensions to my
4 Grandson, and with what success}
5 I awoke rejoicing, and began to reflect on the glorious career before me.
6 I would go forth, methought, at once, and evangelize the whole of Flatland.
7 Even to Women and Soldiers should the Gospel of Three Dimensions
8 be proclaimed. I would begin with my Wife.
9 \end{document}
```

Example text: "Flatland" by Edwin A. Abbott

Title, author and date

We geven het artikel nu een titel. We gebruiken drie commando's om een **title**, **author** en **date** in te stellen. Deze commando's staan in de **preamble**.

Het commando `\maketitle` staat in de **body** van het document en bepaalt de positie van de titel.

```
1 \documentclass[a4paper, 12pt]{article}
2 \title{Elementary Illustrations of the Differential and Integral Calculus}
3 \author{Augustus De Morgan}
4 \date{November 11}
5 \begin{document}
6 \maketitle
7 The Differential and Integral Calculus, or, as it was formerly
8 called in this country, the Doctrine of Fluxions, has always
9 been supposed to present remarkable obstacles to the beginner.
10 \end{document}
```

Speciale tekens

Code	Resultaat
<code>\{</code>	{
<code>\}</code>	}
<code>\%</code>	%
<code>_</code>	—
<code>\textasciicircum</code>	^
<code>\\$</code>	\$
<code>\textbackslash</code>	\
<code>\&</code>	&
<code>\#</code>	#
<code>\textgreater</code>	>
<code>\textless</code>	<

Code	Resultaat,
<code>{</code>	Begin groep,
<code>}</code>	Eindig groep,
<code>%</code>	Comment
<code>_</code>	Betekenis voor wiskunde,
<code>^</code>	Betekenis voor wiskunde,
<code>\$</code>	Wiskundemodus,
<code>\</code>	Commando,
<code>&</code>	Kolomscheiding,
<code>#</code>	Parameter
<code>></code>	>
<code><</code>	<

Speciale tekens

Code	Resultaat
$\backslash\{$	$\{$
$\backslash\}$	$\}$
$\%$	$\%$
$_$	$_$
\textasciicircum	\wedge
$\$$	$\$$
\textbackslash	\backslash
$\&$	$\&$
$\#$	$\#$
\textgreater	$\>$
\textless	$\<$

Code	Resultaat,
$\{$	Begin groep,
$\}$	Eindig groep,
$\%$	Comment
$_$	Betekenis voor wiskunde,
\wedge	Betekenis voor wiskunde,
$\$$	Wiskundemodus,
\backslash	Commando,
$\&$	Kolomscheiding,
$\#$	Parameter
$\>$	$\>$
$\<$	$\<$

Formatting text

Resultaat,	Code	Resultaat,	Code
Text		Text	
<i>Text</i>		Text	
TEXT		Text	
<u>Text</u>		Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	
<i>Text</i>		Text	
TEXT		Text	
<u>Text</u>		Text	
bf = boldface it = italics sc = smallcaps tt = teletype (a.k.a. monospace)			

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	
<i>Text</i>	<code>\textit{Text}</code>	Text	
TEXT		Text	
<u>Text</u>		Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	
<i>Text</i>	<code>\textit{Text}</code>	Text	
TEXT	<code>\textsc{Text}</code>	Text	
<u>Text</u>		Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	
<i>Text</i>	<code>\textit{Text}</code>	Text	
TEXT	<code>\textsc{Text}</code>	Text	
<u>Text</u>	<code>\underline{Text}</code>	Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	<code>\texttt{Text}</code>
<i>Text</i>	<code>\textit{Text}</code>	Text	
TEXT	<code>\textsc{Text}</code>	Text	
<u>Text</u>	<code>\underline{Text}</code>	Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	<code>\texttt{Text}</code>
<i>Text</i>	<code>\textit{Text}</code>	Text	<code>{\tiny Text}</code>
TEXT	<code>\textsc{Text}</code>	Text	
<u>Text</u>	<code>\underline{Text}</code>	Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	<code>\texttt{Text}</code>
<i>Text</i>	<code>\textit{Text}</code>	Text	<code>{\tiny Text}</code>
TEXT	<code>\textsc{Text}</code>	Text	<code>{\LARGE Text}</code>
<u>Text</u>	<code>\underline{Text}</code>	Text	

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	<code>\texttt{Text}</code>
<i>Text</i>	<code>\textit{Text}</code>	Text	<code>{\tiny Text}</code>
TEXT	<code>\textsc{Text}</code>	Text	<code>{\LARGE Text}</code>
<u>Text</u>	<code>\underline{Text}</code>	Text	

Huge, huge, LARGE, Large, large, normalsize, small, footnotesize, scriptsize, tiny

Formatting text

Resultaat,	Code	Resultaat,	Code
Text	<code>\textbf{Text}</code>	Text	<code>\texttt{Text}</code>
<i>Text</i>	<code>\textit{Text}</code>	Text	<code>{\tiny Text}</code>
TEXT	<code>\textsc{Text}</code>	Text	<code>{\LARGE Text}</code>
<u>Text</u>	<code>\underline{Text}</code>	Text	<code>\textcolor{red}{Text}</code> ¹

Huge, huge, LARGE, Large, large, normalsize, small, footnotesize, scriptsize, tiny

¹`\usepackage{xcolor}`

Logische opmaak

Het is vaak beter om niet teveel van de vorige commando's gebruik te maken om de *logische opmaak* filosofie van L^AT_EX te volgen.

	niet logisch	logisch	resultaat
vector	<code>\stackrel{\rightarrow}{w}</code>	<code>\vec{w}</code>	\vec{w}
nadruk	<code>\textit{text}</code>	<code>\emph{text}</code>	<i>text</i>
kop	<code>\Large</code> My Heading	<code>\subsection{My Heading}</code>	My Heading
lemma	<code>\textsc{LEMMA 3.2}</code>	<code>\begin{mylemma}...\end{mylemma}</code>	LEMMA 3.

Wiskunde

Er zijn twee manieren om wiskunde te zetten:

inline mode

The trigonometric identity is given by $\sin^2(\theta) + \cos^2(\theta) = 1$ for all θ .

display mode

The Pythagorean trigonometric identity is given by

$$\sin^2(\theta) + \cos^2(\theta) = 1. \tag{1}$$

The identity

$$1 + \tan^2(\theta) = \frac{1}{\cos^2\theta} \tag{2}$$

is also called the Pythagorean trigonometric identity.

Inline wiskunde

Tekst en symbolen tussen \$ en \$ worden gezien als **wiskundige symbolen**.

```
1 \documentclass[a5paper]{article}
2 \begin{document}
3 The trigonometric identity is
4 given by $ \sin^2(\theta) + \cos^2(\theta) = 1 $. This identity is also
5 called the Pythagorean trigonometric identity.
6 \end{document}
```

The trigonometric identity is given by $\sin^2(\theta) + \cos^2(\theta) = 1$. This identity is also called the Pythagorean trigonometric identity.

Wiskundepackages

De onderstaande drie packages zijn handig om wiskunde te zetten:

```
1 \documentclass[a4paper, 10pt]{article}
2 \usepackage{amsmath}
3 \usepackage{amssymb}
4 \usepackage{amsthm}
5 \begin{document}
6 \[
7     ax^2 + bx + c = 0 \quad \text{\texttt{\textbackslash quad}}
8     \text{\texttt{\textbackslash text}}{De algemene vorm van de kwadratische vergelijking}
9 \]
10 \end{document}
```

Met deze packages kun je tekst toevoegen aan formules, extra symbolen gebruiken zoals \boxplus , \rightsquigarrow en \mathbb{R} betere environments voor stellingen en bewijzen gebruiken.

Wiskunde - basis

Formule	Code		Formule	Code
$\sqrt{2}$	$\$$	$\$$	$\sqrt[3]{8}$	$\$$ $\$$
$\frac{2}{3}$	$\$$	$\$$	x_1	$\$$ $\$$
$6 \geq 3$	$\$$	$\$$	x_1^2	$\$$ $\$$
$a^2 + b^2$	$\$$	$\$$	a^{2+b^2}	$\$$ $\$$

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	$\$ \backslash\text{sqrt}\{2\} \$$	$\sqrt[3]{8}$	$\$ \quad \$$
$\frac{2}{3}$	$\$ \quad \$$	x_1	$\$ \quad \$$
$6 \geq 3$	$\$ \quad \$$	x_1^2	$\$ \quad \$$
$a^2 + b^2$	$\$ \quad \$$	a^{2+b^2}	$\$ \quad \$$

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2+b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2+b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2+b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2+b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2+b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2+b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2 + b^2} \$</code>

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2 + b^2} \$</code>
<code>\$ x^{22} \$</code> : x^{22}			

Wiskunde - basis

Formule	Code	Formule	Code
$\sqrt{2}$	<code>\$ \sqrt{2} \$</code>	$\sqrt[3]{8}$	<code>\$ \sqrt[3]{8} \$</code>
$\frac{2}{3}$	<code>\$ \frac{2}{3} \$</code>	x_1	<code>\$ x_1 \$</code>
$6 \geq 3$	<code>\$ 6 \geq 3 \$</code>	x_1^2	<code>\$ x_1^2 \$</code>
$a^2 + b^2$	<code>\$ a^2 + b^2 \$</code>	a^{2+b^2}	<code>\$ a^{2 + b^2} \$</code>
<code>\$ x^{22} \$</code> : x^2 <code>\$ x^{22} \$</code> : x^{22}			

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	$\$$ $\$$	$\bigcup_{i \in I} U_i$	$\$$ $\$$
$A \cup B$	$\$$ $\$$	\emptyset	$\$$ $\$$
$A \cap B$	$\$$ $\$$	\forall	$\$$ $\$$
$A \subseteq B$	$\$$ $\$$	\exists	$\$$ $\$$
$x \in A \implies x \in B$	$\$$	\neg	$\$$ $\$$

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	$\$ \backslash \text{sum_i } x_i \$$	$\bigcup_{i \in I} U_i$	$\$ \qquad \qquad \qquad \$$
$A \cup B$	$\$ \qquad \qquad \$$	\emptyset	$\$ \qquad \qquad \$$
$A \cap B$	$\$ \qquad \qquad \$$	\forall	$\$ \qquad \qquad \$$
$A \subseteq B$	$\$ \qquad \qquad \$$	\exists	$\$ \qquad \qquad \$$
$x \in A \implies x \in B$	$\$ \qquad \qquad \qquad$	\neg	$\$ \qquad \qquad \$$

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	$\$ \backslash \text{sum_i } x_i \$$	$\bigcup_{i \in I} U_i$	$\$ \quad \quad \quad \$$
$A \cup B$	$\$ A \backslash \text{cup } B \$$	\emptyset	$\$ \quad \quad \$$
$A \cap B$	$\$ \quad \quad \$$	\forall	$\$ \quad \quad \$$
$A \subseteq B$	$\$ \quad \quad \$$	\exists	$\$ \quad \quad \$$
$x \in A \implies x \in B$	$\$$	\neg	$\$ \quad \$$

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \forall \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \exists \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \neg \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \$ \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \$ \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \$ \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \$ \$</code>
$x \in A \implies x \in B$	<code>\$ \$ \$</code>	\neg	<code>\$ \$ \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \forall \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \exists \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \neg \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \forall \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \exists \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \neg \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \forall \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \exists \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \neg \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \forall \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \exists \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \neg \$</code>

Wiskunde - Bewijzen in de Wiskunde

Formule	Code	Formule	Code
$\sum_i x_i$	<code>\$ \sum_i x_i \$</code>	$\bigcup_{i \in I} U_i$	<code>\$ \bigcup_{i \in I} U_i \$</code>
$A \cup B$	<code>\$ A \cup B \$</code>	\emptyset	<code>\$ \emptyset \$</code>
$A \cap B$	<code>\$ A \cap B \$</code>	\forall	<code>\$ \forall \$</code>
$A \subseteq B$	<code>\$ A \subseteq B \$</code>	\exists	<code>\$ \exists \$</code>
$x \in A \implies x \in B$	<code>\$ x \in A \implies x \in B \$</code>	\neg	<code>\$ \neg \$</code>

Display mode

Er bestaan vele environmets voor wiskunde in Display mode. Vandaag bekijken we de **align** environment.

The double angle formula can now be rewritten as

```
\begin{align}
\cos(2\theta) &= \cos^2\theta - \sin^2\theta \\
&= 2\cos^2\theta - 1
\end{align}
```

The double angle formula can now be rewritten as

$$\cos(2\theta) = \cos^2 \theta - \sin^2 \theta \quad (3)$$

$$= 2 \cos^2 \theta - 1 \quad (4)$$

Eigen commando's

```
\newcommand{\Mod}[1]{\ (\mathrm{mod}\ #1)}
```

Because x is even we have

```
\begin{align*}
```

```
  x &= 0\ (\mathrm{mod}\ #1)\\
```

```
  x &= 0\Mod{2}
```

```
\end{align*}
```

Because x is even we have


$$x = 0 \pmod{2}$$

$$x = 0 \pmod{2}$$

Closing remarks

Het beste boek om meer te leren is **LaTeX Beginner's Guide** door **Stefan Kottwitz**.
De eerste editie is verkrijgbaar als eBook via de uu bibliotheek.

1



Access Online

[LaTeX beginner's guide](#)

Authors: [Stefan Kottwitz](#)

 eBook ©2011

Birmingham, UK : Packt, ©2011.

Summary: Annotation LaTeX is high-quality Open Source typesetting software that produces professional prints and PDF files. However, as LaTeX is a powerful and complex tool, getting started can be intimidating. There is no official support and certain aspects such as layout modifications can seem rather complicated. It may

[Show More](#) ▼

✓ Available

Utrecht University Library

 Cite

 Share

 Save

Closing remarks

De volgende cursusavond is op maandag 3 oktober van 17:15 tot 19:00.
Locatie komt op de website te staan en in de mail.

texnicie.nl

Contributors

Copyright (c) 2022 Tim Weijers

Copyright (c) 2021-2022 Vincent Kuhlmann

Copyright (c) 2022 Hanneke Schroten

Copyright (c) 2022 Thomas van Maaren

De T_EXniCie licenseert deze PDF aan het publiek onder

Creative Commons CC BY-NC-ND 4.0

Als je slide-inhoud in een andere presentatie wil gebruiken, moet je de T_EXniCie eerst om een andere licentie vragen.