Neovim keybindings — sorted and grouped (v2)

Leader is `<Space>`. Modes: `n` normal · `x` visual · `o` operator-pending · `s` select · `i` insert · `c` command-line · `v` = `x` + `s`. Sections 1–10 are your own mappings (set in `init.lua`). Sections 11–13 are Neovim 0.12 defaults and plugin built-ins.

Total binds

Source	Entries	Unique Keys
This config	201	163
Neovim 0.12	59	53
Plugin built-ins	15	7
Internal `<Plug>` targets	16	16
Total	275	220

Leader map at a glance

`<Space>` +	Group	Plugin
`b...`	Buffers	bufferline / bufdelete
`cc`	Colour picker	ccc
`d...`	Debug	nvim-dap
`e`	Focus file tree	Neo-tree
`f...`	Pickers (`ff fg fb fh fl* fv*...`) and `fz` = fzf files	Telescope / fzf-lua
`g...`	Git pickers (`gb gd gs`)	fzf-lua
`h...`	Hunks (`hs hr hS hR hu hP hb hd hD`)	Gitsigns
`j...`	Jujutsu (`jj` status picker, `jd*` describe/diff, `jg*` pickers, `jb*`, `jt*`, `jp*`)	jj.nvim
`k`	Toggle hover docs	LSP
`l...`	LSP lists (`ld lr lwd`), `lo` otter	Trouble / otter
`m...`	SSH mounts	sshfs.nvim
`n...`	New buffer (`nn`), tree toggle (`nt`)	Neo-tree
`r...`	Rustlings	rustlings.nvim
`s...`	Leap (`ss sS sx sX`), `sj` JJ squash	Leap
`t...`	Toggles (`tt tb td`), todo lists (`tdt tds tdq`)	misc / Gitsigns / todo-comments
`u`	Undo history	fzf-lua
`x...`	Diagnostics/lists (`xx xX xs xl xL xq xQ`)	Trouble
`/ ;`	Live grep, resume last picker	fzf-lua

What changed since the previous file

Moved or renamed

- JJ describe: `<Space>jd` → `<Space>jdd`.
- JJ diff / hdiff current buffer: `<Space>df` / `dF` → `<Space>jdf` / `jdF`.
- JJ status picker: `<Space>gj` → `<Space>jj`.
- `<Tab>` is now next buffer and `<S-Tab>` previous (they were the other way round).
- Arrow-key versions of mini.move added (`<M-Up>` `<M-Down>` `<M-Left>` `<M-Right>`), alongside `<M-h/j/k/l>`.
- Most mappings now have descriptions.

Present before, gone now (check these were removed on purpose)

- lazygit: `<Space>gg`.
- Harpoon: `<Space>a`, `<C-E>`, `<C-J>`, `<C-K>`, `<C-L>`, `<C-;>`.
- Git-conflict: `<Space>co` `ct` `cb` `c0`, `[x`, `]x`.
- `<Space>cs` (colour schemes), `<Space>d` (diagnostic float).
- `K` (toggle LSP hover), `f<Space>` (format), visual `J` / `K` (move lines).
- `<C-Q>` and `<C-X>` in modes other than normal.
- `<C-L>` is back to the Neovim default (clear highlight and redraw).

---

1. Core editing, files and quitting

Mode	Key	Action
n	`<Esc>`	Clear highlights
n x o s i c	`<C-S>`	Save
n x o s i c	`<M-q>`	Save, then force-quit (`:write` + `:q!`)
n	`<C-Q>`	Force-quit, discards changes (`:q!`)
n	`<C-X>`	Force-delete buffer (`:bdelete!`)
n	`<M-w>`	Delete buffer (`:bdelete`)
n	`<Tab>`	Next buffer
n	`<S-Tab>`	`:previous` (arglist command, labelled "previous buffer")
n	`<M-Left>`	Go to end of previous word (`ge`)
n	`-`	Open Oil file explorer
n	`<C-T>`	Toggle terminal (toggleterm)
n	`jj`	Open jujutsu (`:J`)
n	`j`	Disabled (`<Nop>`)
n	`x`	Disabled (`<Nop>`)
n x o s i c	`<F1>`	Disabled (`<Nop>`)
i	`<M-t>`	Insert a literal Tab

Move lines and selections (mini.move)

Mode	Key	Action
n	`<M-h> <M-j> <M-k> <M-l>`	Move line left / down / up / right
n	`<M-Up> <M-Down> <M-Right>`	Move line up / down / right
x	`<M-h> <M-j> <M-k> <M-l>`	Move selection left / down / up / right
v	`<M-Up> <M-Down> <M-Left> <M-Right>`	Move selection up / down / left / right

Comments

Mode	Key	Action
n	`gcc`	Toggle current line comment
n	`gc`	Toggle line comment (operator)
x	`gc`	Toggle selected comment
o	`gc`	Comment text object
n	`gb`	Toggle block comment (operator)
n	`gbc`	Toggle current block comment
x	`gb`	Toggle selected block

---

2. Buffers

Mode	Key	Action
n	`<Tab>`	Next buffer
n	`<Space>bn`	Next buffer (bufferline)
n	`<Space>bp`	Previous buffer (bufferline)
n	`<Space>bc`	Pick buffer
n	`<Space>bx`	Close buffer (bufdelete)
n	`<M-w>`	Close buffer (`:bdelete`)
n	`<C-X>`	Force close buffer
n	`<Space>bmn`	Move buffer next
n	`<Space>bmp`	Move buffer previous
n	`<Space>bsd`	Sort by directory
n	`<Space>bse`	Sort by extension
n	`<Space>bsi`	Sort by ID
n	`<Space>nn`	New empty buffer (`:enew`)

---

3. Navigation

File tree and explorers

Mode	Key	Action
n	`-`	Oil
n	`<Space>e`	Neo-tree: focus
n	`<Space>nt`	Neo-tree: toggle
n	`gO`	Toggle aerial (symbol outline)

Leap

Mode	Key	Action
n x o	`<Space>ss`	Leap forward
n x o	`<Space>sS`	Leap backward
n x o	`<Space>sx`	Leap forward till
n x o	`<Space>sX`	Leap backward till
n x o	`gs`	Leap from window

---

4. Search and pickers

fzf-lua

Mode	Key	Action
n	`<Space>fz`	Files
n	`<Space>fz/`	Live grep
n	`<Space>fz;`	Resume last picker
n	`<Space>u`	Undo history
n	`<Space>gb`	Git branches
n	`<Space>gd`	Git diff
n	`<Space>gs`	Git status

Telescope: general

Mode	Key	Action
n	`<Space>ff`	Find files
n	`<Space>fg`	Live grep
n	`<Space>fb`	Buffers
n	`<Space>fh`	Help tags

Mode	Key	Action
n	`<Space>ft`	Open Telescope
n	`<Space>fr`	Resume previous search
n	`<Space>fp`	Projects
n	`<Space>fs`	Treesitter

Telescope: git (`<Space>fv...`)

Mode	Key	Action
n	`<Space>fvf`	Git files
n	`<Space>fvs`	Git status
n	`<Space>fvb`	Git branches
n	`<Space>fvcw`	Git commits
n	`<Space>fvcb`	Git buffer commits
n	`<Space>fvx`	Git stash

Telescope: LSP (`<Space>fl...`)

Mode	Key	Action
n	`<Space>fld`	Diagnostics
n	`<Space>flD`	Definitions
n	`<Space>flt`	Type definitions
n	`<Space>fli`	Implementations
n	`<Space>flr`	References
n	`<Space>flsb`	Document symbols
n	`<Space>flsw`	Workspace symbols

SSH remote search (`<Space>m...`)

Mode	Key	Action
n	`<Space>mf`	Find files
n	`<Space>mg`	Grep files
n	`<Space>mF`	Live find (remote)
n	`<Space>mG`	Live grep (remote)

---

5. LSP, diagnostics and todo lists

Your mappings

Mode	Key	Action
n	`<Space>k`	Toggle hover docs
n	`<Space>lo`	Activate LSP at cursor (otter)

Trouble

Mode	Key	Action
n	`<Space>xx`	Diagnostics (all)
n	`<Space>xX`	Diagnostics (current buffer)
n	`<Space>xs`	Symbols
n	`<Space>xq`	Quickfix
n	`<Space>xQ`	Quickfix (`Trouble qflist toggle`)
n	`<Space>xl`	Location list
n	`<Space>xL`	Location list (`Trouble loclist toggle`)
n	`<Space>ld`	Document diagnostics
n	`<Space>lwd`	Workspace diagnostics
n	`<Space>lr`	LSP references

Todo comments

Mode	Key	Action
n	`<Space>tdt`	Todos in Trouble
n	`<Space>tds`	Todos in Telescope
n	`<Space>tdq`	Todos in quickfix

---

6. Git (Gitsigns and fzf-lua)

Gitsigns

Mode	Key	Action
n	`]c` / `[c`	Next / previous hunk
n v	`<Space>hs`	Stage hunk
n v	`<Space>hr`	Reset hunk
n	`<Space>hS`	Stage buffer
n	`<Space>hR`	Reset buffer
n	`<Space>hu`	Undo stage hunk
n	`<Space>hP`	Preview hunk
n	`<Space>hb`	Blame line
n	`<Space>hd`	Diff this

Mode	Key	Action
n	`<Space>hD`	Diff project
n	`<Space>tb`	Toggle blame
n	`<Space>td`	Toggle deleted

Pickers

Mode	Key	Action
n	`<Space>gb`	fzf-lua: git branches
n	`<Space>gd`	fzf-lua: git diff
n	`<Space>gs`	fzf-lua: git status
n	`<Space>fv...`	Telescope git pickers (section 4)

---

7. Jujutsu (`<Space>j...`)

Mode	Key	Action
n	`jj`	Open jujutsu (`:J`)
n	`<Space>js`	Status
n	`<Space>jy`	Picker: status
n	`<Space>jl`	Log
n	`<Space>jL`	Log all
n	`<Space>jdd`	Describe
n	`<Space>je`	Edit
n	`<Space>jn`	New
n	`<Space>jq`	Squash
n	`<Space>jr`	Rebase
n	`<Space>ja`	Abandon
n	`<Space>ju`	Undo
n	`<Space>jy`	Redo
n	`<Space>jf`	Fetch
n	`<Space>jtt`	Tug

Diff

Mode	Key	Action
n	`<Space>jdf`	Diff current buffer
n	`<Space>jdF`	hdiff current buffer

Push and PRs

Mode	Key	Action
n	`<Space>jpp`	Push
n	`<Space>jpa`	Push all to origin
n	`<Space>jpr`	Open PR from bookmark in current revision or parent
n	`<Space>jpl`	Open PR listing available bookmarks

Bookmarks and tags

Mode	Key	Action
n	`<Space>jbc`	Bookmark create
n	`<Space>jbm`	Bookmark move
n	`<Space>jbd`	Bookmark delete
n	`<Space>jba`	Bookmark advance
n	`<Space>jts`	Tag set
n	`<Space>jtd`	Tag delete
n	`<Space>jtp`	Tag push

Pickers

Mode	Key	Action
n	`<Space>jj`	Picker: status
n	`<Space>jgh`	Picker: history
n	`<Space>jgc`	Picker: conflicts
n	`<Space>jgs`	Picker: conflict sections

---

8. Debugging (nvim-dap, `<Space>d...`)

Mode	Key	Action
n	`<Space>db`	Toggle breakpoint
n	`<Space>dc`	Continue
n	`<Space>dgc`	Continue to cursor
n	`<Space>dgj`	Next step
n	`<Space>dgi`	Step into
n	`<Space>dgo`	Step out
n	`<Space>dgk`	Step back
n	`<Space>dvo`	Go up stacktrace

Mode	Key	Action
n	`<Space>dvi`	Go down stacktrace
n	`<Space>dh`	Hover
n	`<Space>dr`	Toggle REPL
n	`<Space>d.`	Re-run last session
n	`<Space>dR`	Restart
n	`<Space>dq`	Terminate

---

9. SSH mounts (sshfs.nvim, `<Space>m...`)

`<Space>m` itself is a `<Nop>` used as the "mount" group label.

Mode	Key	Action
n	`<Space>mm`	Mount a server
n	`<Space>mu`	Unmount a server
n	`<Space>mU`	Unmount all servers
n	`<Space>me`	Explore mount
n	`<Space>md`	Change dir to mount
n	`<Space>mo`	Run command on mount
n	`<Space>mt`	Open SSH terminal
n	`<Space>mc`	Edit SSH config
n	`<Space>mr`	Reload SSH config
n	`<Space>mf` `mg` `mF` `mG`	Remote find / grep (see section 4)

---

10. Misc

Mode	Key	Action
n	`<Space>cc`	Colour picker (ccc)
n	`<Space>tt`	Toggle transparency and regenerate matugen theme
n	`<Space>rn`	Rustlings: next exercise
n i	`<MouseMove>`	Bufferline hover

---

11. Insert, select and command-line mode

Mode	Key	Action
i	`<C-S>` `<M-q>` `<F1>`	Same as section 1
i	`<M-t>`	Insert a literal Tab
c	`<C-S>` `<M-q>` `<F1>`	Same as section 1
s	`<C-S>` `<M-q>` `<F1>`	Same as section 1
s i	`<Tab>` / `<S-Tab>`	Jump in active snippet, otherwise normal key (default)
i	`<C-W>` / `<C-U>`	Delete word / line, with undo break (default)
c	`<C-R><C-G>`	Insert fugitive object path (fugitive)

---

12. Neovim 0.12 defaults

LSP

Mode	Key	Action
n	`grn`	Rename
n x	`gra`	Code action
n	`grr`	References
n	`gri`	Implementation
n	`grt`	Type definition
n	`grx`	Run codelens

Diagnostics

Mode	Key	Action
n	`[d` / `]d`	Previous / next diagnostic
n	`[D` / `]D`	First / last diagnostic
n	`<C-W>d` / `<C-W><C-D>`	Show diagnostics under cursor

Bracket pairs (previous / next)

Mode	Key	Action
n	`[b` / `]b`	`:bprevious` / `:bnext`
n	`[B` / `]B`	`:brewind` / `:blast`
n	`[l` / `]l`	`:lprevious` / `:lnext`
n	`[L` / `]L`	`:lrewind` / `:llast`
n	`[<C-L>` / `]<C-L>`	`:lpfile` / `:lnfile`
n	`[a` / `]a`	`:previous` / `:next` (arglist)
n	`[A` / `]A`	`:rewind` / `:last`

Mode	Key	Action
n	`[t` / `]t`	`:tprevious` / `:tnext`
n	`[T` / `]T`	`:trewind` / `:tlast`
n	`[<C-T>` / `]<C-T>`	`:ptprevious` / `:ptnext`
n	`[<Space>` / `]<Space>`	Add empty line above / below

The quickfix pairs `[q` `]q` `[Q` `]Q` `[<C-Q>` `]<C-Q>` do not appear in this export.

Treesitter selection

Mode	Key	Action
x	`[n` / `]n`	Select previous / next node
x	`[N` / `]N`	Select previous / next sibling node
x o	`an`	Select parent (outer) node
x o	`in`	Select child (inner) node

Other

Mode	Key	Action
n	`<C-L>`	Clear highlight, update diff, redraw
n x	`gx`	Open path or URI under cursor with system handler
n	`&`	Repeat last `:s` (`:&&`)
n	`Y`	Yank to end of line (`y$`)
x	`*` / `#`	Search selection forward / backward
x	`@`	Run macro on each selected line (linewise)
x	`Q`	Replay last recorded macro on each selected line

---

13. Plugin built-ins

Plugin	Mode	Key	Action
matchit	n x o	`%`	Jump to matching pair (forward)
matchit	n x o	`g%`	Jump to matching pair (backward)
matchit	n x o	`[%` / `]%`	Previous / next unmatched group
matchit	x	`a%`	Select matching-pair text object
fugitive	n	`y<C-G>`	Yank fugitive object path
fugitive	c	`<C-R><C-G>`	Insert fugitive object path
plenary	n	`<Plug>PlenaryTestFile`	Run current file as a test

---

14. Cleanup flags

Likely bugs

- `<S-Tab>` runs `:previous` (argument list), not `:bprevious`. Its description says "previous buffer", so this probably should be `:bprevious`.
- `<M-Left>` in normal mode is `ge`, which overrides mini.move's "move line left". `<M-h>` still moves the line left, so only the arrow version is affected.

Prefix clashes (the shorter key waits for `timeoutlen` before firing)

- `<Space>f` (fzf files) vs every `<Space>f...` Telescope map.
- `<Space>td` (toggle deleted) vs `<Space>tdt` / `tds` / `tdq`.

The old `<Space>d` clash is gone now that the diagnostic float is removed.

Overlapping functionality

- Two pickers: fzf-lua and Telescope both cover files, grep, resume, git status and git branches.
- Trouble duplicates: `xl` / `xL` (loclist) and `xq` / `xQ` (quickfix).
- Diagnostics lists: `xX`, `ld` and `fld`.
- Git status: `<Space>gs` (fzf), `fvs` (Telescope), `js` / `jj` (JJ).
- Close buffer: `<Space>bx`, `<M-w>` and `<C-X>`.
- Next buffer: `<Tab>`, `<Space>bn` and `]b`.
- Mini.move: arrow keys and `<M-hjkl>` do the same thing.

Mnemonic outliers

- `<Space>rn` is Rustlings, but rename is `grn`.
- `<Space>t` mixes transparency, Gitsigns toggles and todo lists.
- `<Space>g` now holds only fzf git pickers, while the `fv...` Telescope git pickers live under `f`.

Risky keys

- `<C-Q>` (`:q!`) and `<C-X>` (`:bdelete!`) discard unsaved changes without a prompt.
- `<M-q>` writes first but works in insert and command-line mode too, so a stray press closes Neovim.
- `<F1>` is disabled in every mode, `j` and `x` in normal mode (intentional per their descriptions).

Shadowed built-ins

- `<Tab>` = `<C-I>` (jumplist forward).
- `<C-T>` (tag stack pop).
- `<C-Q>` (alternate visual-block key).
- `<C-X>` is no longer shadowed in insert mode.