



技术规格书

Block Bottomer

方底阀口制袋机

青岛利国兴精密机械有限公司

技术附件

Technical Attachment

一、设备主要技术参数

Forming	Hot air
粘合成型方式	热风

二、

适用面料	PP 覆膜布
Feasible material	Laminated PP Tubular

设计最高速度 120pcs/min

Max Speed

- 生产速度根据袋长、底宽而不同

Production speed based on bag length and bottom width

底宽 8-9cm 时 速度 speed≤100pcs/min

Bottom width 8-9cm

底宽 10-11cm 时 速度 speed≤110pcs/min

Bottom width 10-11cm

底宽 12-13cm 时 速度 speed≤90pcs/min

Bottom width 12-13cm

底宽 14-16cm 时 速度 speed≤70pcs/min

Bottom width 14-16cm

基布面料要求 Ground fabric quality requirement:

- 透明度>65%的材料无法加工

Material Transparent >65% can not be processed

- 复膜剥离强度≥2.7N/CM

Lamination strength≥2.7N/CM

- 基布膜边宽度≤5mm

Lamination trimming edge width≤5mm

袋宽 350-600mm

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本





更加卓越，不负所托

Sack width 350-600mm

成品袋长 450-910mm

Finished Sack length 450-910

底宽 (阀口袋) 80-160mm

Bottom Width (Valve Type)

成品袋型 敞口袋和方底阀口袋

Finished Bag Valve or Open Mouth

基布要求 55-80g/m²

Basic Fabric

覆膜要求 18-20g/m²

Lamination

功率 120kw

Power

设备尺寸 15x8.5x2.3m

Machine Size

三、用户自备 User Supply

电源 电压 380V，三相交流电，配零线和接地保护，如电压波动过大，建议配稳压器

Gas Source Voltage 380V 3Phase AC with Zero and Ground Line. If voltage fluctuate so much. Suggestion for voltage regulator.

气源 0.7Mpa, 120 M³/h

Gas Source

水源 0.4Mpa, 1 M³/h, < 20°

Water Source

我们所有的努力就是为了给用户高品质产品和服务 | 技术文本



四、设备组成 *Machine Unit*

放送部 *Unwinding Unit*

- 自动张力调节

Tension auto adjustment

- 放送配气胀轴，布卷卷芯尺寸：8 英寸和 3 英寸均可

unwind station with Air Expansion Shaft. The roll core diameter: available for both 8 and 3 inches.

- 自动上布，布卷直径 1000-1400mm

Auto loading. Unwinding diameter 1000-1400mm

- 自动纠偏

Auto EPC

微孔处理 *Micro Perforation Unit*

- 灌装物品时达到更好透气性

Micro perforation for better air permeability

- 双面微孔处理，密度 64 针/cm²

Micro perforation for both sides. The density is 64needles per cm²

输送装置 *Convey Unit*

- 伺服输送

Convey driven by servo motor

- 色标检测

Sensor mark tracking

冲孔 *Punching Holes*

- 冲孔位置可调

The position of punching can be adjustment

- 气动方式

Pneumatic Driven

- 废片吸取

Punching hole fabric sucking

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



切断 Cutting Unit

- 色标或预设长度切断

Cutting length control by sensor tracking or pre-setting

- 伺服驱动

Cutting driven by servo motor

- 切断辅助装置

Cutting assistant device

- 吹气装置

Blowing device

转向装置 Turning Device

- 机械爪输送转向

Gripper catch the bags for run direction change

- 机械爪间距可调

Gripper distance can be adjusted

- 永磁体钢带输送袋片

Bags convey driven by magnetic steel belt

- 钢带涨力可调

Tension of steel belt can be adjustment

- 钢带、机械爪输送为同一驱动动力

The power of steel belt and grippers driven by same motor

袋底打开 End Open

- 袋底打开装置由吸盘装置、仰角撑开器等组成，

End open is comprised by suckers. Spreaders and so on

- 根据袋宽选择吸嘴数量

Suckers chosen depend on bag width

- 撑开器精确开底

Spreader for ends open precision

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



- 撑开器长度可调

The spreader length can be adjustment

- 伺服驱动

Driven by servo

阀口成型 Valve Forming

- 放送配气涨轴，布卷卷芯尺寸 8 英寸和 3 英寸均可

unwind station with air shaft. Roll core diameter available for 8 and 3 inches.

- 光电纠偏

Auto edge guiding system

- 伺服输送阀口

Valve patch convey driven by servo

- 预热装置

Pre-heating for better welding

- 热风焊接系统

Hot Welding System

- 在线调节阀口位置

Adjustment of valve patch position during operation is possible

- 切刀调整方便，带有特殊设计的尺寸标尺。

Easy adjustment of knives with a specially designed gauge

- 焊接进退装置防止设备停机时烫伤袋片

Welding moving system for avoiding burn bags when machine stop

- 橡胶压辊间隙可调，气动自动调节

Gap adjustment of rubber roller driven by pneumatic

- 阀口装置单独驱动动力

Valve own driven power

阀口切断长度

80-200mm

Valve Cutting Length

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



袋底折边 Bottom Folding

- 底宽变化，手轮调整折边器之间的间距

Manual adjustment folding gap based on bottom width

袋底成型 Bottom Forming

- 放送配气涨轴，布卷卷芯尺寸 8 英寸和 3 英寸均可

unwind station with air shaft. Roll core diameter available for 8 and 3 inches.

- 光电纠偏

Auto edge guiding system

- 伺服输送底贴

Bottom patch convey driven by servo

- 预热装置

Pre-heating for better welding

- 热风焊接系统

Hot Welding System

- 在线调节底贴位置

Bottom Patch position can be on line adjustment

- 切刀调整方便，带有特殊设计的尺寸标尺

Easy adjustment of knives with a specially designed gauge

- 焊接进退装置防止设备停机时烫伤袋片

Welding moving system for avoiding burn bags when machine stop

- 橡胶压辊间隙可调，气动自动调节

Gap adjustment of rubber roller driven by pneumatic

- 底贴装置单独驱动动力

Its own driven power

- 光纤检测底贴，底贴缠绕保护自动停机

Photo-cell detect bottom patch. Auto machine stop once bottom patch jammed

底贴切断长度

230-500mm

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



Bottom Patch Cutting Length

底贴宽度

75-175mm

Bottom Patch Width

计数出袋 Accounting

- 光电自动计数

Photo-cell control accounting

- 拍袋装置使得堆集效果更好

Pat system for good stacking

剔废装置 Wastes Ejecting

- 剔废装置

Ejecting Device

- 废品自动检测剔除

Wastes auto detected for ejecting

- 剔废输送装置

Wastes convey

- 气动驱动

Triggering by pneumatic

预热处理 Preheating

- 预热刀辊、预热辊等，使得焊接更加牢固。

For tempering cutting cylinder and preheating cylinders for better welding

整机分离装置 Separation

- 整机操作侧和传动侧可自动分离

Auto separation between machine operation and driven side

- 电机驱动

Driven by motor

中央控制系统 Central control system

- 先进的检测、控制、驱动系统。

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



Adopts advanced detection .control and driven system

- 带有文字说明的流程图，控制方便，图示直观。

Self-explaining process images for intuitive and comfortable control

- 高分辨率、高灵敏度的压力、电感式、光电传感器精确采集现场数据

Pressure sensors. inductive sensors and photo sensors with high resolution definition and sensitivity collect the on-the-spot data accurately

- 采用可编程计算机控制、分散安装的可带电插拔模块化 I/O 系统，可更新和增加模块；配有再生扼流圈、线型滤波器和逆变器的完美自动化伺服驱动系统，通信、控制循环周期极短，可高效精确地完成定位任务；

It adopts PLC and dispersed installed hot plug module I/O system. which can update and increase modules. The perfect auto servo driving system equipped with regenerative chokes. linear filters and inverters ensures precise location task within a very short period of communication and control

- 高清晰度的触摸屏集控制与显示为一体，实现设置、监控、诊断等功能，节能高效，可直观、舒适地操作

Touched screen with high resolution definition is integrated with control and display. Which can achieve functions of setting. Monitoring and diagnosing. The controlling system is easy and comfortable to operate with high efficiency and less energy.

四. 电气仪表清单 *Electric brand*

序号 No	部件名称 Name	品牌 Brand
1	风门控制电磁阀 Magnetic Valve For Hot Air Gun Mouth	SMC
2	打落气缸 Dropping Cylinder	SMC
3	风门气缸	SMC

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



	Air Cylinder For Hot Air Gun Mouth	
4	接近开关 Approaching switch	易福门 IFM. Germany
5	光电开关 Photo-cell switch	易福门 IFM. Germany
6	压力传感器 Pressure feeler	易福门 IFM. Germany
7	运动控制器 Motion Controller	贝加莱 B&R Austria
8	伺服驱动器 Servo Controller	贝加莱 B&R Austria
9	滤波器 Filter	贝加莱 B&R Austria
10	扼流圈 Enchoke	贝加莱 B&R Austria
11	模拟量输入 Simulation Input	贝加莱 B&R Austria
12	模拟量输出 Simulation output	贝加莱 B&R Austria
13	数字量输入、输出 Digital input & Output	贝加莱 B&R Austria
14	温度模块 Temperature Module	贝加莱 B&R Austria
15	接触器 Contact	施耐德 Schneider
16	继电器	日本和泉

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



	Relay	IDEC. Japan
17	热风头 Hot Air Gun	利国兴 Li Guo Xing

五. 随机配件 Spare parts

序号 No	名称 Part Name	图号或型号 Design No	数量 Quantity
1	膨胀螺栓 Expansion Bolts	M16 M8	40Units+20Units
2	吸盘 Suckers		500Pcs
3	羊角胶帽 Header for spreader		20Pcs
4	羊角校正模具 Regulator For Spreader	BVM120-LJ-07-01 到 07-06	1Unit
5	羊角加长杆 Prolonged Rod for spreader	4 个规格	1Unit 32Pcs
6	片基带 Belt	1250*15*1	1P
7	片基带 Belt	1010*15*1	2Pcs
8	片基带 Belt	985*15*1	2Pcs
9	片基带 Belt	2005*30*3	1P
10	同步带 Timing Belt	T5*15*1500	4Pcs
11	规尺块 Scale Plate	BVM120-LJ-01-01	2Pcs
12	规尺 Scale Ruler	BVM120-LJ-01-02	2Pcs
13	阀口刀对正杆 Regulator Rod For Valve Blade	BVM120-LJ-02-01	2Pcs
14	底帖刀模 Blade Module For Bottom	BVM120-LJ-06	1P

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



15	耐热润滑脂 Lubricated Oil		1Tube
16	磁铁 Magnetic steel		50Pcs
17	加热芯 Heating Core	18KW	1P
18	热电偶 Thermocouple		1P
19	吸盘堵头 Blocking Head For suckers		20Pcs
20	吸盘杆 Sucking Rod		6Pcs
21	胶水 Glue		2Bottles
22	四氟板 Teflon Plate	30	1M
23	斜板胶条 Rubber Plate	30	1M
24	气路接头 Gas Jointer		1Unit
25	PU 管 Tube	8. 10	2+10M
26	橡胶条 Rubber Plate	10*10*1000	1P
27	橡胶棒 Rubber Rod	5	1M
28	推抓弹簧 Gripper Spring	BVM120-C-02-43	4Pcs
29	推抓扭簧 Gripper Torque Spring	BVM120-C-02-39	4Pcs
30	扭簧 Torque Spring	BVM120-C-04CZ-01-42	2Pcs
31	切断吹气铜嘴 Blowing Nozzle		4Pcs
32	紧定螺丝 Fasten Screw	M5*6	20Pcs
33	叉子 Spread Fork	#2	各 1 套 Each Unit
34	电磁阀 Magnetic Valve		1P

我们所有的努力就是为了给用户提供高品质的产品和服务 | 技术文本



35	电磁阀 Magnetic Valve		1P
36	热风咀导流板 BVM-120-C-06-084 Blocking Plate For Hot gun	75	6Pcs
		85	6Pcs
		95	6Pcs
		105	6Pcs
		115	6Pcs
		125	6Pcs
		135	6Pcs
		145	6Pcs
		155	6Pcs
		165	6Pcs
		175	6Pcs
37	密封圈 Seal Ring	44*3	2Pcs
		58*3	2Pcs
		102*3	2Pcs
		90*5	4Pcs
38	链扣 Chain Holder		5Pcs
39	羊角归零器 Zero Adjust for Spreader	BVM120-LJ-13-1	1 件
40	羊角归零箭头 Zero Pointer for spreader	BVM120-LJ-13-2	1 件
41	随机工具 Working Tools		1Unit

