







SYCL (traditional)

Developed by : Benson Muite, benson_muite@emailplus.org Work supported by NSF grant OAC-1829644

GPGPU programming

(General-Purpose Graphics Processing Unit)


- Graphics processing requires many similar operations in "graphics pipeline"
 - Triangles going through rotation and scaling, shading, and texturing
- Graphics Processing Units (GPUs) develop to meet this need and then get converted for general purpose programs

- SYCL is an XPU (GPU, CPU and FPGA) design and extension of C++ to support Heterogeneous programming developed by the Khronos group
 - Alternatives for GPUs include OpenCL, CUDA, ROCm

Programming model: Memory

 Program mainly runs on "Host" (= CPU), but can call functions on "Devices" (= GPU, FPGA, CPU)

- Host and Device can have separate address spaces (at least historically)
 - Memory may need to be explicitly transferred
 - SYCL can automate some of the transfers



Programming model: Processing

- XPU can run many threads simultaneously, but not independently
 - Performance benefits obtained from SIMD = Single Instruction, Multiple Data
 - SYCL abstracts away SIMD parallelism to enable the same code to run on different compute devices
- Programmer writes function to run on device (kernel)
- All the threads run the function

"Hello World" for SYCL

Overview of a SYCL program

- In host code:
 - Setup problem call kernel
- In device code:
 - Allocate memory on device
 - Copy data from host
 - Kernel call
 - Copy results to host (can be done implicitly on expiry of scope)
 - Free device memory (can be done implicitly on expiry of scope)
 - q.submit([&](cl::sycl::handler& cgh)
 - determine thread ID
 - bounds check

Adding vectors and Hello World using SYCL

(Not actually fast...)

Recall: Calling a SYCL kernel


Recall: Calling a SYCL kernel

- Why use more than a single block?
- Why not use N blocks?


Recall: Calling a SYCL kernel

- Why use more than a single block?
 - Limited number of threads per processing element (depends on card being used)
- Why not use N blocks?
 - Threads in a processing unit share variables and have synchronization barriers
 - So, technically limited


- Memory is typically mapped to 1D arrays
- Need to represent 2D array:



- Memory is typically mapped to 1D arrays
- need to represent 2D array:



- Memory is typically mapped to1D arrays
- need to represent 2D array:




Consider cell with 1D coordinate i:

What is the coordinate of the cell below it?

What expression tests if it is on the right edge?

- Memory is typically mapped to1D arrays
- Need to represent 2D array:



Consider cell with 1D coordinate i:

What is the coordinate of the cell below it? What expression tests if it is on the right edge?

```
i + row_length
i % row_length == row_length - 1
```