# Softmax Inundation and Generational Context in Long-Horizon Agent Systems

## Analytical Attention Dilution Bounds and the Generational Memory Architecture

**Shaurya Sanyal** • Team Auralis • Autonomous Systems Research Group
Preprint Ref: ACI-MATH-2026-FT-REV2 • October 2026

***Abstract.*** *Autonomous AI agent architectures routinely treat the transformer context window as an unbounded, append-only linear interaction transcript. We analyze the theoretical and empirical consequences of this paradigm. We formalize the* ***Softmax Inundation Bound****, an analytical upper bound showing that under bounded projection energy, the maximum aggregate self-attention probability mass allocated to a fixed set of invariant constraint tokens decays asymptotically as O(L_u / |S_noise|) when unpruned execution observations accumulate. This attention dilution creates a systemic vulnerability: as noisy tracebacks dominate context length, attention heads dilute focus from foundational system invariants toward high-entropy symptom tokens. To resolve this failure mode, we specify* ***Generational Context****, an operating-system-inspired memory architecture that separates memory into* ***Gen-0 Ephemeral*** *(tool outputs distilled to 3-line signatures and evicted in 1 turn),* ***Gen-1 Evaporative*** *(working memory paged via the Attention-Weighted Eviction algorithm), and* ***Gen-2 Tenured*** *(permanently pinned invariants). We prove that Generational Context maintains a non-zero lower bound on invariant attention uniformly for all interaction turns t ∈ N, eliminating unbounded softmax dilution and stabilizing long-horizon autonomy.*

## 1. Introduction

Despite expansions in foundation model context windows, practical autonomy in multi-turn software engineering loops remains fragile. Agents frequently lose adherence to system constraints, repeat failed tool invocations, and apply superficial micro-patches around symptoms rather than addressing root causes.

In typical agent sessions, over 90% of active tokens consist of raw tool outputs (compiler stderr, test dumps, DOM trees). We analyze this pathology via **Payload Inundation** (attention dilution), **Error Gravitation** (semantic bias toward error tracebacks), and **Generational Context** (multi-tiered memory management).

## 2. The Softmax Inundation Bound

Let context tokens be partitioned into Invariant Subspace S_inv (|S_inv| = L_u) and Observation Subspace S_noise. Under bounded query and key energies ||q_i||_2 ≤ M_Q and ||k_j||_2 ≤ M_K, let κ = exp(2 M_Q M_K / sqrt(d_k)).

***Theorem 1 (Softmax Inundation Upper Bound).***
*For any query position i, the aggregate attention probability mass allocated to the invariant subspace S_inv is upper-bounded by:*

$$A_{i,inv} \le \kappa \frac{L_u}{L_u + |S_{noise}|} = O\left(\frac{L_u}{|S_{noise}|}\right)$$

*Proof Sketch: By Cauchy-Schwarz, -M_Q M_K ≤ q_i^T k_j ≤ M_Q M_K. The numerator is bounded above by L_u exp(M_Q M_K / sqrt(d_k)) and the denominator is bounded below by (L_u + |S_noise|) exp(-M_Q M_K / sqrt(d_k)). Dividing numerator by denominator yields the result directly.*

## 3. Generational Context & Retention Guarantee

Generational Context stratifies memory into three lifecycle tiers: **Gen-0 Ephemeral** (tool outputs distilled to 3 lines and purged in 1 turn), **Gen-1 Evaporative** (working memory paged via AWE), and **Gen-2 Tenured** (permanently pinned invariants).

***Theorem 2 (Generational Retention Guarantee).***
*Under Generational Context with bounded distillation $||\sigma_distill(G_0)|| \le K_0$, working capacity $||G_1|| \le C_1$, and bounded framing overhead C_overhead (delimiters, role tags, headers), the active non-invariant tokens satisfy $|S_non\text{-}inv^(t)| \le C_1 + K_0 + C_overhead = C_bound$ for all turns t. Under uniform bounded projection energy:*

$$A_{i, inv} = 1 / (1 + R_t) \ge L_u / (L_u + \kappa C_{bound}) > 0$$

*where $R_t \le (\kappa C_bound) / L_u$. Invariant attention remains strictly bounded away from zero uniformly for all interaction turns $t \in N$.*

**Numerical Sensitivity Analysis & Comparative Bound Analysis (L_u = 100, C_bound = 150)**

| Regime | Logit Gap (Δs) | Contrast (κ) | GenContext Min Attn | Flat Context (N=5k) | Bound Ratio R(5k) |
|---|---|---|---|---|---|
| Illustrative Low Contrast | 1.0 | 2.72 | 19.70% | 0.73% | 27.0x |
| Illustrative Intermediate | 2.0 | 7.39 | 8.28% | 0.27% | 30.7x |
| Illustrative Moderate | 3.0 | 20.09 | 3.21% | 0.10% | 32.3x |
| Illustrative High Contrast | 4.0 | 54.60 | 1.21% | 0.037% | 32.9x |
| Illustrative Extreme Gap | 6.0 | 403.4 | 0.165% | 0.0049% | 33.3x |

*Comparative Bound Analysis: Flat context values represent theoretical lower bounds under identical uniform score assumptions, not empirical observations. The theoretical bound ratio $R(\kappa, N) = (L_u + \kappa N) / (L_u + \kappa C_bound)$ approaches $N / C_bound$ as $\kappa \to \infty$ (33.3x at N = 5,000; 333.3x at N = 50,000). For finite κ, R ranges from 27.0x to 33.3x (at N = 5k) and 268.1x to 332.8x (at N = 50k). This compares theoretical bound expressions, not measured attention distributions in a neural model.*

## 4. The Attention-Weighted Eviction (AWE) Algorithm

```
Algorithm 1: AWE with Hard Capacity Invariant
  1: Input: Capacity C, incoming chunk E, boundary parameter p
  2: if E.tokens > C then Truncate E.content to C tokens; E.tokens ← C
  3: Compute IDS(E) = AttentionWeight(E) × 100 / (Entropy(E) + 10^-4) [or tier prior if unmeasured]
  4: if E.key ∈ T1 ∪ T2 then Update and promote to T2
  5: else if E.key ∈ B1 then Adapt p ← min(C, p + |B2|/|B1| × E.tokens); Evict lowest IDS victim
  6: else if E.key ∈ B2 then Adapt p ← max(0, p - |B1|/|B2| × E.tokens); Evict lowest IDS victim
  7: else Evict lowest IDS chunk; Insert E into T1; assert total_tokens() ≤ C
```

## 5. Empirical Token Compaction & Attention Simulation

*Methodological Scope Notice: Attention metrics represent a deterministic 128-dimensional subword hash-projection surrogate modeling softmax dilution mechanics, distinct from neural transformer forward passes. Controlled empirical evaluations with live neural models (e.g., Claude 3.5 Sonnet, GPT-4o, Llama-3-70B) across SWE-bench Verified are **planned future work** (Phase 2); no live model reasoning claims are made prior to Phase 2 completion.*

| Architecture Arm | Mean Active Tokens | Context Signal Ratio (CSR) | Simulated Attn(Inv) (Proxy) | Token Reduc |
|---|---|---|---|---|
| Arm A: Flat Append-Only | 5,099 | 0.0059 | 0.0425 | Baseline |
| Arm B: Auto-Compaction | 3,340 | 0.0077 | 0.0553 | -34.5% |
| Arm C: Generational Context | 129 | 0.2000 | 0.0757 | **-97.5% (33.9x CSR)** |

## 6. Related Work & Conclusion

Our work connects with Liu et al. (2023) on context retrieval degradation, Xiao et al. (2023) on attention sinks, Packer et al. (2023) on MemGPT tiered memory, and Megiddo & Modha (2003) on ARC. By formalizing the Softmax Inundation Bound and providing the Generational Context architecture, we offer a deterministic, verifiable memory framework that preserves foundational constraints across arbitrary interaction horizons.

[1] A. Vaswani et al., 'Attention is all you need,' in NeurIPS, 2017.
[2] N. Megiddo and D. S. Modha, 'ARC: A self-tuning, low overhead replacement cache,' in USENIX FAST, 2003.
[3] N. F. Liu et al., 'Lost in the middle: How language models use long contexts,' TACL, 2024.

[4] G. Xiao et al., 'Efficient streaming language models with attention sinks,' in ICLR, 2024.
[5] C. Packer et al., 'MemGPT: Towards LLMs as operating systems,' arXiv:2310.08560, 2023.