Documentation steps for deployment via Akamai:

1. Navigate to cloud.linode.com, login, and click "Create Linode"
2. Use a "Nanode", or the cheapest option after selecting a region.
3. Use Ubuntu Linux (any version) when creating Nanode
4. Install Docker using Step 1 of this guide:
   a. https://www.digitalocean.com/community/tutorials/how-to-install-and-use-docker-on-ubuntu-22-04
5. Once docker is installed, use "git clone" to clone the production branch of project. For example:
   a. git clone https://github.com/Team-Aytche/Team_Aytche_BucStop.git
6. Create docker volume with command:
   a. docker volume create bucstop_json_data
7. Change directory into Project directory with:
   a. cd Team_Aytche_BucStop
8. Change directory into webapp directory with:
   a. cd BucStop_Webapp
9. To deploy container, run:
   a. docker compose up
10. Navigate to public IP of linode and port 8080 to view webapp.
11. To view submission Json data:
    a. docker run --rm -it -v bucstop_json_data:/data alpine cat /data/game_submissions.json
12. Weekly Rebuild:
    a. To rebuild weekly with the newest build, but not lose data in Docker Volume, navigate to directory with docker-compose.yml in terminal, and run "docker compose up -d –build"
13. If needed for rollback or other reasons, below are the commands to manually build the image and launch the container inside of Docker:
    a. For BucStop: i. docker build -f .\BucStop\Dockerfile --force-rm - t bucstop .
14. Create a Docker Volume to store game submission files in:
    a. docker volume create bucstop_json_data
15. Run a Docker container with the newly built image. You can run the command below:
    a. docker run -d -p 8080:80 --name bucstopLocal -v bucstop_json_data:/app/data bucstop

Miscellaneous Items:

1. Akamai information:
    a. Akamai aka Linode, region US ATLANTA.
    b. 194.195.208.108 (public ip)
    c. 194.195.208.108:8080 (bucstop URL)
2. To show running containers:
    a. docker ps
3. To create the docker volume:
    a. docker volume create bucstop_data_json