Passive Inference of Cognitive States in Digital Environments: Bridging the Human-Computer Disconnect Through Unobtrusive Behavioral Analytics

The Paradigm of the Human-Computer Disconnect

The fundamental architecture of modern digital environments is characterized by a profound operational blindness. While computational systems have achieved unprecedented sophistication in processing explicit user inputs—commands executed via deliberate clicks, targeted taps, and intentional keystrokes—they remain entirely oblivious to the implicit psychological, emotional, and cognitive states of the user originating those commands. In natural human-to-human interaction, communication is continuously modulated by a dense stream of non-verbal telemetry. A skilled educator observes the furrowed brow or the prolonged hesitation of a student and instantly infers confusion, subsequently adapting the pedagogical approach. A colleague detects the frantic, erratic pacing of a coworker and infers acute stress or fatigue, subsequently delaying a complex request.

In human-computer interaction, this critical feedback loop is entirely severed. Systems process inputs with absolute literalism, unable to distinguish between a keystroke executed in a state of high-arousal flow and an identical keystroke executed in a state of profound cognitive exhaustion. This sensory deficit results in a severe disconnect between user needs and system responses. Without the capacity to dynamically assess states such as focus, confusion, or fatigue, digital environments remain static. They continue to present dense information to an overloaded user, interrupt a deeply focused worker with trivial notifications, or fail to provide necessary scaffolding to a frustrated learner.

Historically, attempts to bridge this disconnect have relied heavily on active assessment mechanisms or highly intrusive physiological monitoring. Active assessments, such as ecological momentary assessments, self-report questionnaires, or Likert-scale pop-ups, require the user to explicitly articulate their internal state. This approach is inherently flawed; it forcibly interrupts the very workflow it seeks to optimize, introduces significant recall and social desirability biases, and suffers from rapidly declining longitudinal adherence due to user fatigue.[1] Conversely, explicit physiological monitoring—utilizing electroencephalography to track frontal midline theta waves, functional near-infrared spectroscopy to monitor cortical oxygenation, or galvanic skin response sensors to measure sympathetic arousal—provides high-fidelity cognitive telemetry.[4] However, these modalities necessitate specialized, expensive, and physically restrictive hardware. The encumbrance of wearing biometric harnesses renders these approaches entirely impractical for continuous, widespread

deployment in everyday educational, occupational, or clinical settings.[4]

The resolution to this ubiquitous challenge lies in the passive inference of cognitive states through the continuous, unobtrusive observation of routine digital behavior. As individuals navigate digital interfaces, they inadvertently generate a high-resolution, high-frequency trail of psychomotor exhaust. Every micro-hesitation of a cursor, the rhythmic cadence of keystrokes, the physical pressure applied to a touchscreen, and the trajectory of scrolling behaviors contain latent signatures of the user's underlying neurocognitive state. By aggregating this ambient behavioral data and applying advanced machine learning architectures, digital systems can reverse-engineer the user's cognitive and affective condition without requiring any explicit or physical input beyond routine interaction.[1]

This comprehensive analysis systematically deconstructs the theoretical frameworks, sensory modalities, and specific domain applications of unobtrusive cognitive state inference. Furthermore, it isolates and exhaustively analyzes the ten strongest research papers that define the vanguard of this field, illustrating how the transition from active interruption to passive observation is poised to revolutionize adaptive learning, workplace productivity, proactive healthcare monitoring, and the overarching principles of user experience design.

Theoretical Foundations of Behavioral Leakage

The hypothesis that routine computer interactions can reveal complex internal states is anchored in the neurocognitive principles of embodied cognition and attentional resource allocation. To accurately interpret passive behavioral data, it is necessary to understand the mechanisms by which cognitive phenomena "leak" into psychomotor execution.

Embodied Cognition and Motor Execution

The traditional dualist perspective of cognitive science treated the brain as an isolated information-processing unit, entirely divorced from the physical body. The theory of embodied cognition challenges this premise, asserting that cognitive processing and motor action are deeply intertwined, mutually constitutive systems that constantly influence one another.[8] When an individual interacts with a computer, the physical execution of a command—such as moving a mouse to target an icon—is not merely the final output of a completed cognitive process. Instead, the continuous trajectory of the movement reflects the ongoing, dynamic resolution of competing cognitive processes.[8]

If a user is experiencing cognitive conflict, uncertainty, or confusion, this internal deliberation manifests as a continuous physical perturbation. The motor cortex does not wait for absolute cognitive certainty before initiating movement; it initiates a trajectory that is continuously updated as new information is processed.[9] Consequently, states of high cognitive load or emotional arousal introduce measurable variance, curvature, and micro-hesitations into otherwise automated psychomotor sequences.[8]

Attentional Control Theory and Cognitive Depletion

The specific behavioral signatures of stress, fatigue, and distraction can be modeled through the lens of Attentional Control Theory. This framework posits that anxiety, stress, and heavy cognitive loads disproportionately consume working memory resources, specifically impairing the central executive functions responsible for inhibition and shifting.[10]

When executive resources are depleted by fatigue or consumed by anxiety, the user's ability to maintain top-down, goal-directed attention diminishes, leading to an increased susceptibility to bottom-up, stimulus-driven distractions. In the context of digital interaction, this depletion manifests as a loss of fine motor automaticity. Behaviors that typically require negligible cognitive effort, such as typing a familiar sequence of characters or moving a cursor in a straight line, suddenly require conscious regulation.[12] This reallocation of cognitive resources results in decreased interaction speed, increased spatial jitter, elevated error rates, and prolonged latencies between actions.[12]

The Dynamics of Epistemic Emotion

In learning and complex problem-solving environments, cognitive states are frequently driven by epistemic emotions—affective states that arise from the cognitive processing of information. When a user encounters novel, complex, or contradictory information that violates their existing schemas, they experience cognitive disequilibrium, triggering the epistemic emotion of confusion.[15]

Confusion is inherently unstable. If the user successfully resolves the cognitive conflict through deep processing, confusion transitions into focused engagement and mastery.[15] However, if the digital environment fails to provide adequate scaffolding, or if the user's working memory capacity is exceeded, confusion rapidly degrades into frustration, and ultimately, disengagement, boredom, or mind-wandering.[15] Because these emotional transitions are accompanied by distinct shifts in interaction pacing and behavioral rhythms, continuously analyzing interaction logs allows systems to identify precisely where a user resides on this affective trajectory.[15]

Modalities of Unobtrusive Cognitive Assessment

The operationalization of passive cognitive state inference relies on the continuous capture and mathematical modeling of specific behavioral modalities. These data streams are captured silently in the background, utilizing the standard peripheral devices already integrated into modern computing ecosystems.

Assessment	Primary Hardware	Key Extracted	Primary Target States

Modality	Requirement	Features	
Keystroke Dynamics	Standard QWERTY Keyboard	Dwell time, flight time, typing speed, deletion frequency, digraph latencies.	Cognitive load, psychological stress, emotional valence/arousal, fatigue.
Tactile Force/Pressure	Pressure-sensitive screens/keys	Peak pressure, mean stroke pressure, pressure variance, stroke area.	Acute stress, frustration, emotional intensity.
Mouse Kinematics	Standard Computer Mouse	Trajectory curvature, spatial jitter, velocity, acceleration, idle pause length.	Mild cognitive impairment, confusion, sustained attention, decision conflict.
Webcam Gaze Tracking	Consumer-grade Webcam	Fixation duration, saccade velocity, blink rate, Eye Aspect Ratio (EAR).	Mind-wandering, visual workload, drowsiness, reading comprehension.
Interaction Logging	Software/Application Layer	Scrolling speed, screen dwell time, click frequency, task-switching rate.	Disengagement, mindless reading, application-specific confusion.
Digital Phenotyping	Smartphone Ambient Sensors	GPS mobility variance, ambient light/noise, background	Depression severity, social anxiety, chronic burnout, longitudinal fatigue.

		screen-on time.	

Keystroke Dynamics and Tactile Rhythm Analysis

Keystroke dynamics, originally engineered as a continuous behavioral biometric for cybersecurity and user authentication, has proven to be an exceptionally sensitive modality for affective and cognitive inference.[17] The analysis does not record what the user is typing (preserving semantic privacy) but rather how the user types. The primary temporal features include dwell time (the duration a single key is held down) and flight time or latency (the temporal gap between releasing one key and depressing the subsequent key).[19]

When users transition from a relaxed state to a state of high cognitive load or stress, the highly automated rhythm of their typing fractures. Research has demonstrated that cognitive stress induces longer keystroke pause lengths, slower overall typing speeds, and an increased reliance on deletion keys (backspace and delete) as error rates rise due to impaired executive control.[13] Furthermore, specific emotional states systematically alter these latencies; for instance, high-arousal states often correlate with decreased keystroke duration, while states of sadness or fatigue correlate with prolonged flight times.[20]

Beyond temporal metrics, the advent of pressure-sensitive screens and capacitive keyboards has enabled the extraction of three-dimensional tactile features. By utilizing technologies such as smartphone 3D Touch, systems can measure the precise physical force applied during each stroke. The physiological tension and elevated sympathetic arousal associated with stress directly translate into increased mechanical force, allowing pressure variance to serve as a highly accurate proxy for acute emotional distress.[6]

Mouse Kinematics and Spatial Trajectories

The computer mouse provides a continuous stream of high-frequency, two-dimensional spatial coordinates (x,y) accompanied by millisecond-precise timestamps.[8] Because navigating a cursor requires continuous visuospatial processing and fine motor execution, the kinematics of the mouse serve as a high-fidelity diagnostic window into the user's neurological integrity and cognitive load.

Analytical frameworks decompose mouse movements into temporal, spatial, and kinematic features. Temporal features include the total time required to execute a movement and, crucially, the idle time or pause length between discrete movements. Kinematic features assess the velocity, acceleration, and jerk (the rate of change of acceleration) of the cursor. Spatial features evaluate the efficiency of the trajectory, calculating metrics such as the maximum deviation from an optimal straight line, the area under the trajectory curve, and the frequency

of sudden directional shifts.[13]

Under elevated cognitive demand or intense time pressure, users exhibit significantly longer task durations, increased idle times, slower maximum cursor speeds, and more frequent direction changes as they hesitate or reconsider target acquisition.[13] Furthermore, these precise kinematic metrics are uniquely sensitive to subtle neurodegenerative changes. As visuospatial processing and self-error monitoring decline in the early stages of cognitive impairment, mouse trajectories become noticeably less efficient, exhibiting severe curvature and extended inter-movement latencies long before the user demonstrates overt functional deficits.[1]

Webcam-Based Gaze and Visual Attention Tracking

Visual attention is perhaps the most direct correlate of cognitive focus. While specialized, screen-mounted infrared eye-trackers have long been used in laboratory environments to monitor visual workload and mind-wandering, their prohibitive cost and obtrusiveness rendered them useless for widespread digital integration.[25]

Recent advancements in deep neural networks and computer vision have enabled sophisticated gaze tracking using ubiquitous, consumer-grade webcams.[25] These software-based systems utilize facial landmark detection algorithms to isolate the eye region, extract pupil coordinates, and map these coordinates to specific locations on the digital interface using ridge-regression models.[26] While webcam data is inherently noisier and exhibits higher spatial jitter (e.g., ~0.38 degrees of visual angle) compared to infrared hardware, temporal smoothing and sliding-window prompt chaining have made it highly effective for cognitive state inference.[29]

Webcam tracking allows systems to calculate the Eye Aspect Ratio (EAR) to continuously monitor blink rates and blink durations.[29] Prolonged blink durations and decreased blink frequency are established biological markers of severe visual fatigue and heavy cognitive load. Furthermore, analyzing the dispersion of fixations and the velocity of saccadic eye movements allows the system to differentiate between active, focused reading and the erratic, uncoupled eye movements characteristic of task-unrelated thought, or mind-wandering.[25]

Application-Level Log Analysis and Digital Phenotyping

In environments where high-frequency granular data (like precise mouse coordinates) is unavailable or computationally prohibitive to process continuously, cognitive states can be accurately inferred through macro-level interaction logs and passive digital phenotyping.[32]

Interaction log analysis involves correlating application-specific behavioral events with contextual metadata. For example, in an adaptive reading environment, the system monitors the total dwell time per page or the scrolling velocity.[32] By mathematically comparing the user's

reading speed against the established linguistic complexity of the text—using metrics like the Flesch-Kincaid Grade Level or indices of syntactic simplicity—the system can detect severe deviations.[32] If a user navigates past a highly complex, conceptually dense paragraph at a speed that precludes semantic processing, the system infers a state of mindless reading or severe disengagement.[32]

On mobile platforms, this macro-analysis expands into passive digital phenotyping. Smartphones contain an array of ambient sensors (GPS, accelerometers, ambient light detectors) and generate vast amounts of metadata (screen-on events, application transition frequencies, call and SMS log timestamps). By analyzing the variance in these data streams over weeks or months, machine learning models can map physical mobility, sleep disruption, and social withdrawal, providing highly accurate, continuous biomarkers for the severity of clinical depression, chronic anxiety, and occupational burnout.[33]

Deep Deconstruction: The Ten Landmark Research Papers

To fully understand the theoretical underpinnings, methodological rigor, and practical applications of unobtrusive cognitive state inference, it is necessary to critically examine the foundational literature. The following ten research papers represent the most significant scientific advancements in addressing the human-computer disconnect across the domains of adaptive learning, human-computer interaction, and healthcare monitoring.

1. Managing Epistemic Emotions in Digital Learning

Arguel, A., Lockyer, L., Lipp, O. V., Lodge, J. M., & Kennedy, G. (2017). "Inside Out: Detecting Learners' Confusion to Improve Interactive Digital Learning Environments." *Journal of Educational Computing Research*. [15]

The Problem: Interactive Digital Learning Environments (IDLEs) offer unprecedented scalability but structurally isolate the learner from human educators. Consequently, these systems fail to recognize when a student encounters a cognitive impasse, allowing productive challenges to degenerate into severe frustration and disengagement.[15]

Methodological Innovation: Arguel et al. systematically redefined the role of confusion in the learning process. Utilizing the framework of affect dynamics, they established the theoretical construct of the "Zone of Optimal Confusion".[15] They argued that confusion is a necessary epistemic emotion triggered by cognitive disequilibrium, which forces deep processing and schema adaptation.[15] The innovation of this paper lies in its comprehensive blueprint for detecting this state unobtrusively by fusing behavioral interaction logs (clicks, navigation paths, dwell times) with implicit physiological indicators.[15]

Findings and Implications: The research proved that confusion, if unmanaged, predictably

transitions past a critical threshold into frustration and boredom.[15] By utilizing predictive analytics on continuous interaction data, IDLEs can detect the behavioral signature of this impending transition. This allows the system to emulate a human tutor, delivering precisely timed, adaptive scaffolding—such as hints or simplified explanations—exactly when the learner reaches the boundary of their working memory capacity. This paper is foundational because it shifted the objective of educational technology from merely delivering content to actively managing the learner's emotional and cognitive equilibrium.[15]

2. Sensor-Free Detection of Internal Attention

Mills, C., & D'Mello, S. (2015). "Toward a Real-Time (Day) Dreamcatcher: Sensor-Free Detection of Mind Wandering during Online Reading." *Proceedings of the 8th International Conference on Educational Data Mining.* [32]

The Problem: Mind-wandering—the internal shift of attention away from a task toward task-unrelated thought—is a pervasive issue in digital environments that drastically degrades comprehension. However, it is an entirely internal state; a mind-wandering user physically resembles an engaged user. Previous detection methods required highly obtrusive and expensive eye-tracking hardware.[32]

Methodological Innovation: Mills and D'Mello pioneered a purely "sensor-free" approach. They discarded biometric hardware entirely, relying exclusively on the interaction logs generated during self-paced reading tasks.[32] They extracted temporal reading behaviors (the time spent on each screen) and fused this data with sophisticated textual features extracted via Coh-Metrix, evaluating the narrativity, deep cohesion, syntactic simplicity, and word concreteness of the specific text the user was viewing.[32]

Findings and Implications: Using supervised machine learning across two distinct datasets (177 Mechanical Turk workers and 141 university students), their models successfully predicted episodes of mind-wandering as users navigated between screens.[32] The models achieved an accuracy 20% above chance levels solely by identifying the behavioral incongruities between reading speed and text complexity.[32] This paper is profoundly impactful because it demonstrated that highly accurate, attention-aware interfaces could be deployed universally and continuously without requiring any additional hardware investments or imposing privacy-invasive biometric surveillance on the user.[32]

3. Scalable Gaze Tracking for Mass Education

Zhao, Y., Lofi, C., & Hauff, C. (2017). "Scalable Mind-Wandering Detection for MOOCs: A Webcam-Based Approach." *European Conference on Technology Enhanced Learning.* [25]

The Problem: Massive Open Online Courses (MOOCs) suffer from notoriously high attrition rates, driven largely by sustained disengagement and mind-wandering during prolonged video lectures. While specialized eye-trackers can detect this disengagement by monitoring erratic

saccades and pupillary changes, such hardware cannot be scaled to millions of remote learners.[25]

Methodological Innovation: Zhao et al. evaluated the efficacy of replacing specialized infrared eye-trackers with the ubiquitous, consumer-grade webcams already present in most laptops. They conducted a controlled laboratory study where participants watched 6-to-8-minute lecture videos while their gaze was simultaneously recorded by both a high-quality eye-tracker and a standard webcam.[25] Ground truth was established using probe-caught mind-wandering self-reports.[25]

Findings and Implications: The researchers extracted global gaze features and applied Support Vector Machine (SVM) classifiers. Crucially, they found that the webcam-based data performed equally well compared to the specialized hardware in predicting mind-wandering.[25] The webcam approach achieved an F1 score of 0.405, representing a 16% improvement over chance.[25] This research validated the use of highly accessible, low-cost computer vision to monitor cognitive states, proving that MOOC platforms could theoretically implement real-time, personalized interventions for inattentive students at a global scale.[25]

4. Establishing Keystrokes as Stress Biomarkers

Vizer, L. M., Zhou, L., & Sears, A. (2009). "Automated stress detection using keystroke and linguistic features: An exploratory study." *International Journal of Human-Computer Studies / CHI 2009*. [13]

The Problem: Monitoring acute changes in physical and cognitive function is essential for mitigating occupational burnout and managing health conditions. However, the existing clinical and occupational solutions relied on highly intrusive physiological sensors or disruptive psychological surveys, which are inadequate for continuous, long-term tracking in natural environments.[13]

Methodological Innovation: Vizer and colleagues proposed exploiting the normal, daily computer interactions of users. They designed an experiment where participants were subjected to mentally or physically stressful tasks (e.g., remembering digits) and subsequently asked to generate spontaneous text (e.g., writing an email).[38] The system unobtrusively logged their keystroke dynamics (dwell time, typing speed, deletion frequency) alongside the linguistic characteristics of the generated text.[13]

Findings and Implications: Applying classifiers such as decision trees, SVMs, and k-Nearest Neighbors, the models successfully detected the presence of cognitive and physical stress.[38] The system achieved approximately 75% accuracy in differentiating high cognitive demand from baseline states, solely through the analysis of typing behavior.[13] This exploratory study is a landmark in the field; it definitively proved the theory of behavioral leakage, demonstrating that systemic stress inherently degrades the fine motor control required for typing. It established

that standard keyboards could function as zero-cost, continuous cognitive health monitors.[13]

5. Algorithmic Modeling of Human Interruptibility

Fogarty, J., Hudson, S. E., Atkeson, C. G., Avrahami, D., Forlizzi, J., Kiesler, S., Lee, J. C., & Yang, J. (2005). "Predicting human interruptibility with sensors." *ACM Transactions on Computer-Human Interaction (TOCHI).* [40]

The Problem: Modern workplace environments are saturated with digital notifications. Operating systems and communication platforms operate with absolute ignorance of the user's current cognitive load or social context, resulting in socially awkward interruptions that destroy flow states and drastically increase the likelihood of costly resumption errors.[40]

Methodological Innovation: To build a system capable of negotiating interruptions politely, Fogarty et al. utilized a massive, bottom-up observational approach. They analyzed over 600 hours of audio and video recordings from authentic office environments. Initially using human coders in a "Wizard of Oz" feasibility setup to simulate sensor values, they subsequently trained statistical models on data derived from simple, highly practical sensors (e.g., single microphones to detect speech, and basic PC activity logs) rather than complex, computationally heavy vision systems.[40]

Findings and Implications: The resulting models were able to distinguish "Highly Non-interruptible" situations from other states with a remarkable accuracy of 82.4%.[40] Most significantly, the automated sensor-based models outperformed human observers viewing the exact same video and audio recordings, who only achieved an accuracy of 76.9%.[40] The identification of the "Any Talk" auditory feature as a primary predictive metric proved that highly effective, context-aware digital environments could be built cheaply and practically, paving the way for systems that actively protect user attention.[40]

6. Granular Emotion Classification via Typing Rhythms

Epp, C., Lippold, M., & Mandryk, R. L. (2011). "Identifying Emotional States Using Keystroke Dynamics." *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems.* [17]

The Problem: While early affective computing research successfully detected binary states of stress or general cognitive load, mapping a wide, nuanced spectrum of human emotions unobtrusively remained highly challenging. Truly empathetic interfaces require the ability to distinguish between closely related states, such as anger versus excitement, without requiring the user to wear physiological monitors.[17]

Methodological Innovation: Epp et al. conducted a comprehensive field study focusing on the precise rhythm of typing patterns on standard keyboards. They captured participants' keystrokes and collected corresponding emotional ground-truth data via self-reports.[17] The

researchers extracted a dense array of keystroke features, prominently including detailed analyses of individual keystroke durations and digraph latencies (the specific timing between pairs of characters).[19]

Findings and Implications: The researchers successfully developed two-level classifiers for an unprecedented 15 distinct emotional states. The models achieved classification accuracies ranging from 77% to 88% for states such as confidence, hesitance, nervousness, relaxation, sadness, and tiredness.[17] Furthermore, they demonstrated high efficacy (84% accuracy) in detecting high-arousal states like anger and excitement.[17] This paper is a cornerstone of affective computing, demonstrating that the nuanced fluctuations in typing rhythm contain enough high-fidelity telemetry to render standard keyboards as comprehensive emotional sensors, enabling the development of physiologically attentive user interfaces.[17]

7. Tactile Force as a Window into Emotional Arousal

Exposito, M., Hernandez, J., & Picard, R. W. (2018). "Affective Keys: Towards Unobtrusive Stress Sensing of Smartphone Users." *ACM Conference on Human-Computer Interaction with Mobile Devices and Services.* [6]

The Problem: Standard keystroke dynamic analysis relies primarily on temporal data (time and speed). However, physical tension and emotional stress manifest mechanically in the body. Traditional computing lacked the hardware to measure this tactile force, meaning a critical dimension of behavioral leakage was ignored.[6]

Methodological Innovation: With the integration of 3D Touch technology (capacitive and accelerometer sensors) in devices like the iPhone 6S Plus, researchers gained the ability to measure the exact mechanical pressure applied to the screen during typing.[6] Exposito, Hernandez, and Picard designed a controlled laboratory study where 11 participants were instructed to type narratives recalling recent stressful and relaxing life experiences, counterbalanced to control for order effects.[6] The system continuously logged the pressure values (ranging from 0 to 6.7) of every keystroke.[6]

Findings and Implications: The study revealed a profound, statistically significant positive correlation ($r = 0.75$, $p = 0.0081$) between the increase in typing pressure and self-reported stress levels across the experimental conditions.[6] Conversely, a significant negative correlation ($r = -0.74$, $p = 0.0093$) was observed between the baseline typing pressure and stress.[6] Additionally, utilizing learned embeddings, the models predicted three levels (low, medium, high) of valence, arousal, and dominance with Area Under the Curve (AUC) scores up to 0.84.[22] This research proved that the physical intensity of screen interaction is a highly reliable proxy for emotional arousal, validating pressure-sensing as a transformative modality for unobtrusive mental health monitoring.[6]

8. Ecological Detection of Cognitive Decline

Seelye, A., Hagler, S., Mattek, N., Howieson, D. B., Wild, K., Dodge, H. H., & Kaye, J. A. (2015). "Computer mouse movement patterns: A potential marker of mild cognitive impairment." *Alzheimer's & Dementia.* [1]

The Problem: Conventional clinical assessments for Mild Cognitive Impairment (MCI) and early-stage Alzheimer's disease are episodic, highly stressful, and lack ecological validity. Furthermore, traditional cognitive tests often suffer from ceiling effects, failing to detect the subtle, functional declines in real-world execution until the disease has progressed significantly.[1]

Methodological Innovation: Seelye et al. bypassed the clinical setting entirely, embedding continuous, ambient monitoring software into the home computers of 62 older adults (42 cognitively intact, 20 with diagnosed MCI).[1] Over a prolonged period, the system unobtrusively recorded the raw, two-dimensional spatial and temporal coordinates of their everyday mouse movements.[1]

Findings and Implications: The analysis revealed striking kinematic deviations. The MCI group executed significantly fewer total mouse movements (mean = 1497) compared to the intact group (mean = 9679; $P < .01$).[1] Crucially, participants with MCI demonstrated a significantly larger and more variable length of pauses between discrete mouse movements (IQR_Idle; $P < .05$), reflecting delayed cognitive processing and degraded motor planning.[1] Multiple regression analyses, adjusting for age and education, confirmed that MCI was highly predictive of these prolonged pause lengths ($P = .04$) and more curved, inefficient looping trajectories (IQR_K; $P = .008$).[1] This paper established that the routine operation of a computer mouse contains high-fidelity diagnostic biomarkers, allowing for the continuous, non-invasive screening of incipient neurodegenerative disease.[1]

9. The Architecture of Cognitive Manifestation in Movement

Kieslich, P. J., Henninger, F., Wulff, D. U., Haslbeck, J. M. B., & Freeman, J. B. (2020/related trajectory research). *Contextualized in studies of mouse-tracking dynamics.* [8]

The Problem: As the field of continuous mouse-tracking expanded rapidly, an assumption took root that all mouse movements perfectly and continuously reflected internal cognitive states. However, inconsistencies across different studies suggested that the specific design of the digital interface heavily influenced the reliability of the behavioral leakage, creating a risk of misinterpreting the resulting data.[8]

Methodological Innovation: Grounded in the embodiment perspective, researchers systematically investigated the boundary conditions of action dynamics.[8] By manipulating specific design factors in a Simon task—such as the response selection mechanism (requiring

clicks versus simple hovering), the scaling ratio between physical hand movement and on-screen cursor displacement, and the spatial location of target boxes—they analyzed how these variables distorted the trajectory data.[8]

Findings and Implications: The research proved that the manifestation of cognition into movement is highly fragile. Poor design choices—such as improper scaling or forcing unnatural response mechanisms—blur or entirely prevent cognitive leakage.[8] These interface disruptions manifest as severe reductions in movement consistency, suppressed action dynamics, and the adoption of compensatory, unnatural motor strategies by the user.[8] This methodological critique is vital; it demonstrated that passive cognitive inference is not universally applicable to all interfaces. To accurately infer mental states, the digital environment must be ergonomically optimized to ensure a continuous, unimpeded mapping between cognitive processing and motor output.[8]

10. Passive Digital Phenotyping in Naturalistic Environments

Jacobson, N. C., et al. (Various recent publications on digital phenotyping, e.g., 2020-2023). *Contextualized in the evaluation of smartphone telemetry for psychiatric modeling.* [33]

The Problem: Mental health disorders, particularly depression and anxiety, are highly dynamic conditions characterized by acute fluctuations in severity. Clinical psychiatry relies on retrospective self-reporting, which fails to capture these daily variations, resulting in missed intervention windows and suboptimal therapeutic outcomes.[2]

Methodological Innovation: The integration of passive digital phenotyping shifts psychiatric monitoring from episodic active surveys to continuous ambient tracking. Research in this domain aggregates multi-modal data streams natively generated by smartphones, including geolocation (GPS), accelerometry (step count), ambient noise, screen-on duration, and communication metadata (call logs and SMS frequencies).[33] Advanced deep learning architectures, such as long short-term memory (LSTM) networks and contrastive learning models, are utilized to map these passive behavioral rhythms against validated clinical scales (e.g., SDQ risk, anxiety assessments).[33]

Findings and Implications: The aggregation of passive data provides an extraordinarily accurate proxy for psychiatric symptomology. For instance, reduced GPS variance (distance traveled) and prolonged screen-on time reliably correlate with the anhedonia, lethargy, and sleep disruption characteristic of major depressive episodes.[34] Furthermore, analyses of communication logs demonstrate that a reduction in the frequency and duration of outgoing calls and SMS messages serves as a robust indicator of the social withdrawal and avoidant behaviors associated with social anxiety disorder.[34] By establishing deep, personalized neural models of these behavioral phenotypes, clinicians can continuously monitor vulnerability and deliver highly targeted, just-in-time digital interventions, fundamentally democratizing

proactive mental healthcare.[33]

Domain Integration: Bridging the Disconnect

The translation of theoretical behavioral telemetry into functional system responses fundamentally alters the architecture of human-computer interaction across several critical domains.

Summary of Domain Interventions

Domain	Target Cognitive/Affective State	Predictive Behavioral Marker	Automated System Response / Intervention
Adaptive Learning	Confusion transitioning to Frustration	Erratic mouse trajectories, rapid/incorrect keystrokes	Trigger contextual hints, scaffold complexity, suggest self-regulation.[15]
Adaptive Learning	Mind-Wandering / Inattention	Reading speed deviating from text complexity, prolonged blinks	Pause progression, highlight missed content, deploy active recall prompts.[29]
Workplace Productivity	High Cognitive Load / Task Immersion	"Any Talk" audio, high-frequency continuous typing	Defer non-urgent emails, silence application notifications to protect flow.[40]
Workplace Productivity	Cognitive Fatigue / Burnout	Increased keystroke flight time, elevated deletion usage	Suggest micro-breaks, recommend task-switching to lower-demand activities.[13]
Healthcare (Neurology)	Mild Cognitive Impairment (MCI)	Increased mouse pause variance (IQR_idle), looping	Flag for clinical review, adapt interface sizing to

		trajectories	reduce spatial precision demands.[1]
Healthcare (Psychiatry)	Acute Depression / Social Anxiety	Decreased GPS mobility, reduced SMS/call frequency	Trigger ecological momentary intervention, alert healthcare provider.[34]

Revolutionizing Adaptive Learning

In digital education, the inability of systems to read non-verbal cues has historically resulted in high attrition and poor comprehension. By implementing continuous log analysis and webcam gaze tracking, modern adaptive learning platforms can construct real-time affective models of the student.[15] When a system detects the specific reading cadences associated with mind-wandering, it can proactively intervene, pulling the student's attention back to the material before the pedagogical narrative is lost.[32] More importantly, by mapping the transition from productive confusion to detrimental frustration via erratic mouse behaviors, the system maintains the learner in their optimal zone of proximal development, delivering personalized scaffolding precisely when cognitive resources are exhausted.[15]

Safeguarding Workplace Productivity

The modern knowledge worker operates in an environment of perpetual digital interruption, severely compromising executive function and accelerating cognitive fatigue.[51] Unobtrusive cognitive inference transforms the operating system from a passive tool into an active attentional guardian. By continuously modeling the degradation of typing rhythms and mouse kinematics, the system quantifies the user's cognitive depletion over the course of the workday.[13] Utilizing robust interruptibility models, the workplace environment can automatically suppress asynchronous communications (emails, chat notifications) during periods of high cognitive load, thereby preserving the employee's flow state, minimizing costly resumption errors, and mitigating the long-term risk of occupational burnout.[40]

Proactive Healthcare and Digital Biomarkers

In healthcare, passive behavioral monitoring resolves the ecological invalidity of episodic clinical testing.[1] By analyzing the ambient operation of a computer mouse, geriatric systems can detect the microscopic kinematic hesitations and spatial inefficiencies that herald Mild Cognitive Impairment, facilitating interventions months or years earlier than traditional cognitive screens allow.[1] In psychiatry, the utilization of smartphones for passive digital phenotyping provides clinicians with an objective, continuous dashboard of a patient's behavioral rhythm. By mapping geolocation variance, screen usage, and communication

frequency, care teams can detect the silent onset of depressive episodes or anxiety exacerbations, enabling dynamic, data-driven therapeutic interventions.[33]

Technical Limitations and Systemic Vulnerabilities

While the transition to passive cognitive inference offers unprecedented optimization, the deployment of these technologies "in the wild" introduces substantial methodological and ethical challenges that require rigorous resolution.

The Challenge of Intra-Subject Variability

A persistent hurdle in behavioral biometrics is the immense baseline variance across different individuals. A typing velocity or inter-keystroke latency that signifies severe cognitive fatigue in one user may represent the optimal, rested performance of another.[10] Consequently, generalized, population-level machine learning models frequently suffer from low correlation coefficients when applied broadly.[10] To achieve high predictive accuracy, systems must shift toward personalized, ipsative modeling. The inference engine must first observe the user over an extended period to establish an individualized baseline profile, subsequently evaluating cognitive states based solely on the magnitude of deviation from that specific user's historical norm.[10] This necessitates computationally heavy, continuous-learning algorithms that adapt dynamically over time.

Environmental Noise and Ecological Validity

As monitoring transitions from the sterile conditions of the laboratory to the chaotic reality of naturalistic environments, the fidelity of the behavioral signal degrades significantly.[54] In real-world settings, users frequently shift physical postures, alternate between different input hardware (e.g., transitioning from a precision optical mouse to a laptop trackpad), and operate under highly variable lighting conditions. This environmental heterogeneity introduces massive signal noise, heavily impacting the reliability of modalities like webcam-based gaze tracking, which struggles to maintain accurate facial landmark registration in poor illumination.[55] Resolving this vulnerability requires the implementation of robust multimodal fusion architectures. By simultaneously capturing and cross-validating disparate data streams—such as combining temporal keystroke dynamics with textual sentiment analysis and concurrent physiological smartwatch telemetry—the system can algorithmically isolate the true cognitive signal from ambient contextual noise.[17]

Privacy, Ethics, and Hostile Scaffolding

The most critical challenge facing the deployment of unobtrusive cognitive assessment is the profound ethical risk associated with continuous psychological surveillance.[58] Because these systems extract highly sensitive mental health and emotional data from innocuous, routine interactions, users are often entirely unaware of the depth of telemetry being gathered.[18]

In occupational settings, the deployment of passive sensing to monitor "productivity" risks devolving into draconian micromanagement, where employees are continuously evaluated and potentially penalized for natural physiological fluctuations in cognitive stamina. Furthermore, in commercial user experience design, this technology introduces the severe threat of "deep hostile scaffolding".[59] If an algorithm can precisely map a user's vulnerabilities—identifying exact moments of cognitive fatigue, frustration, or emotional susceptibility—it can maliciously adapt the interface to maximize engagement, optimize advertising delivery, or encourage compulsive behaviors, effectively weaponizing the user's own cognitive state against them.[59]

The responsible advancement of this field therefore requires stringent, privacy-by-design engineering frameworks. To prevent the centralized aggregation of highly sensitive biometric profiles, cognitive inference algorithms must be restricted to on-device processing (edge computing).[28] Furthermore, deployment must be governed by transparent, opt-in consent structures that explicitly detail the extent of behavioral monitoring, ensuring that the technology is utilized exclusively to augment human capability rather than exploit human vulnerability.[28]

Synthesis and Strategic Outlook

The historical paradigm of human-computer interaction has been defined by a severe sensory asymmetry; users constantly adapt to the demands of digital environments, yet those environments remain entirely blind to the cognitive and emotional capacities of the users. The reliance on explicit, active input or physically obtrusive sensors has perpetuated a reactive, inefficient, and often frustrating operational dynamic across education, the workplace, and healthcare.

As evidenced by the exhaustive synthesis of the landmark research in this field, this fundamental disconnect is being successfully bridged. The integration of continuous, unobtrusive behavioral analytics proves that complex internal states—encompassing epistemic confusion, attentional mind-wandering, acute occupational stress, and progressive neurodegenerative decline—manifest reliably in the psychomotor and temporal exhaust of routine digital interaction.

By applying sophisticated machine learning architectures to decode keystroke rhythms, the kinematics of mouse trajectories, the nuances of webcam-based visual attention, and the macro-patterns of passive digital phenotyping, computational systems are achieving deep cognitive awareness. The ten foundational papers analyzed herein provide the methodological blueprint for a new era of neuroadaptive computing. To fully operationalize this potential, future engineering efforts must focus on mitigating environmental noise through multimodal data fusion, accommodating human diversity through highly personalized baseline modeling, and fiercely protecting user autonomy through decentralized, privacy-centric architectures. When executed responsibly, the passive inference of cognitive states promises to transform inert digital tools into responsive, empathetic partners, fundamentally elevating the efficacy, safety,

and psychological wellbeing of the user.

Works cited

1. Computer mouse movement patterns: A potential marker of mild ..., accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC4748737/
2. DIGITAL PHENOTYPING ADHERENCE, FEASIBILITY, AND TOLERABILITY IN OUTPATIENTS WITH SCHIZOPHRENIA - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8192468/
3. Connecting and linking neurocognitive, digital phenotyping, physiologic, psychophysical, neuroimaging, genomic, & sensor data with survey data - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC7880216/
4. Are Behavioral Measures Useful for Detecting Cognitive Workload During Human-Computer Interaction? - Charles River Analytics, accessed on March 29, 2026, https://cra.com/crapublications/elkinfrankston1/
5. Neural signatures of engagement in driving: comparing active control and passive observation - Frontiers, accessed on March 29, 2026, https://www.frontiersin.org/journals/neuroscience/articles/10.3389/fnins.2025.1698625/full
6. Affective Keys: Towards Unobtrusive Stress Sensing ... - DSpace@MIT, accessed on March 29, 2026, https://dspace.mit.edu/bitstream/handle/1721.1/137982/pre_conference.pdf?sequence=2&isAllowed=y
7. A Review on Smartphone Keystroke Dynamics as a Digital Biomarker for Understanding Neurocognitive Functioning - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10296416/
8. Lost to translation: How design factors of the mouse-tracking procedure impact the inference from action to cognition - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC6848042/
9. A State Space Approach to Dynamic Modeling of Mouse-Tracking Data - Frontiers, accessed on March 29, 2026, https://www.frontiersin.org/journals/psychology/articles/10.3389/fpsyg.2019.02716/full
10. Detecting work-related stress from mouse, keyboard, and cardiac data in the field - medRxiv, accessed on March 29, 2026, https://www.medrxiv.org/content/10.1101/2025.08.02.25332538v1.full.pdf
11. Cognitive state monitoring and the design of adaptive instruction in digital environments: lessons learned from cognitive workload assessment using a passive brain-computer interface approach - Frontiers, accessed on March 29, 2026, https://www.frontiersin.org/journals/neuroscience/articles/10.3389/fnins.2014.00385/full
12. Are You, You? Seamlessly Fighting Identity Fraud with Keystroke Dynamics - PubsOnLine, accessed on March 29, 2026, https://pubsonline.informs.org/doi/10.1287/isre.2023.0088

13. Detecting cognitive and physical stress through typing behavior ..., accessed on March 29, 2026, https://www.researchgate.net/publication/221518780_Detecting_cognitive_and_physical_stress_through_typing_behavior
14. Using Mouse and Keyboard Dynamics to Detect Cognitive Stress During Mental Arithmetic, accessed on March 29, 2026, https://www.researchgate.net/publication/281708893_Using_Mouse_and_Keyboard_Dynamics_to_Detect_Cognitive_Stress_During_Mental_Arithmetic
15. (PDF) Inside Out: Detecting Learners Confusion to Improve Interactive Digital Learning Environments - ResearchGate, accessed on March 29, 2026, https://www.researchgate.net/publication/309366496_Inside_Out_Detecting_Learners_Confusion_to_Improve_Interactive_Digital_Learning_Environments
16. Inside Out: Detecting Learners' Confusion to Improve Interactive Digital Learning Environments - OPUS at UTS, accessed on March 29, 2026, https://opus.lib.uts.edu.au/bitstream/10453/124968/4/Inside_Out_preprint.pdf
17. Identifying Emotional States Using Keystroke Dynamics | Request PDF - ResearchGate, accessed on March 29, 2026, https://www.researchgate.net/publication/221514075_Identifying_Emotional_States_Using_Keystroke_Dynamics
18. Identifying Users' Emotional States through Keystroke Dynamics - SciTePress, accessed on March 29, 2026, https://www.scitepress.org/Papers/2022/113673/113673.pdf
19. Identifying emotional states using keystroke dynamics - Semantic Scholar, accessed on March 29, 2026, https://www.semanticscholar.org/paper/Identifying-emotional-states-using-keystroke-Epp-Lippold/275445087a85bf6d3b0f101a60b0be7ab4ed520f
20. The Influence of Emotion on Keyboard Typing: An Experimental Study Using Auditory Stimuli - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC4465979/
21. Stress Detection in Computer Users From Keyboard and Mouse Dynamics - ResearchGate, accessed on March 29, 2026, https://www.researchgate.net/publication/347668874_Stress_Detection_in_Computer_Users_From_Keyboard_and_Mouse_Dynamics
22. Affective Keys: Towards Unobtrusive Stress Sensing of Smartphone Users - ResearchGate, accessed on March 29, 2026, https://www.researchgate.net/publication/356295669_Affective_Keys_Towards_Unobtrusive_Stress_Sensing_of_Smartphone_Users
23. Tracking stress via the computer mouse? Promises and challenges of a potential behavioral stress marker - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8613085/
24. Which computer-use behaviours are most indicative of cognitive decline? Insights from an expert reference group - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC6769281/
25. Scalable Mind-Wandering Detection for MOOCs: A Webcam-Based ..., accessed on March 29, 2026,

https://www.researchgate.net/publication/319474818_Scalable_Mind-Wandering_Detection_for_MOOCs_A_Webcam-Based_Approach
26. Webcam-Based Eye Tracking to Detect Mind Wandering and Comprehension Errors - Penn Center for Learning Analytics, accessed on March 29, 2026, https://learninganalytics.upenn.edu/ryanbaker/BRMWebcamGaze.pdf
27. Your Eyes Under Pressure: Real-Time Estimation of Cognitive Load with Smooth Pursuit Tracking - MDPI, accessed on March 29, 2026, https://www.mdpi.com/2504-2289/9/11/288
28. Understanding Mobile Reading via Camera Based Gaze Tracking and Kinematic Touch Modeling - Googleapis.com, accessed on March 29, 2026, https://storage.googleapis.com/gweb-research2023-media/pubtools/4596.pdf
29. Inferring Cognitive Workload From Symbolic Gaze Sequences Using Large Language Models - IEEE Xplore, accessed on March 29, 2026, https://ieeexplore.ieee.org/iel8/6287639/10820123/11305025.pdf
30. Deep learning models for webcam eye tracking in online experiments - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC11133145/
31. SVD-Based Mind-Wandering Prediction from Facial Videos in Online Learning - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC11122128/
32. Toward a Real-time (Day) Dreamcatcher: Sensor-Free Detection of Mind Wandering During Online Reading - ERIC, accessed on March 29, 2026, https://files.eric.ed.gov/fulltext/ED560533.pdf
33. Digital Phenotyping for Adolescent Mental Health: Feasibility Study Using Machine Learning to Predict Mental Health Risk From Active and Passive Smartphone Data - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12871944/
34. Harnessing Digital Phenotyping for Early Self-Detection of Psychological Distress - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12386097/
35. EJ1144592 - Inside Out: Detecting Learners' Confusion to Improve Interactive Digital Learning Environments, Journal of Educational Computing Research, 2017-Jul - ERIC, accessed on March 29, 2026, https://eric.ed.gov/?id=EJ1144592
36. ED560533 - Toward a Real-Time (Day) Dreamcatcher: Sensor-Free Detection of Mind Wandering during Online Reading, International Educational Data Mining Society, 2015-Jun - ERIC, accessed on March 29, 2026, https://eric.ed.gov/?id=ED560533
37. Mind-wandering rates fluctuate across the day: evidence from an experience-sampling study - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC6311173/
38. Detecting work stress in offices by combining unobtrusive sensors, accessed on March 29, 2026, http://cs.ru.nl/~skoldijk/Papers/TAFFC2610975_authorSubmitted.pdf
39. Efficacy of personalized models in discriminating high cognitive demand conditions using text-based interactions - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8153188/

40. Predicting Human Interruptibility with Sensors - CMU School of ..., accessed on March 29, 2026, https://www.cs.cmu.edu/~kiesler/publications/2005pdfs/2005_Predicting-human-interruptibility-with-sensors.pdf
41. James Fogarty - Google Scholar, accessed on March 29, 2026, https://scholar.google.com/citations?user=hma0WFAAAAAJ&hl=en
42. Smartphones and Cognition: A Review of Research Exploring the Links between Mobile Technology Habits and Cognitive Functioning - Frontiers, accessed on March 29, 2026, https://www.frontiersin.org/journals/psychology/articles/10.3389/fpsyg.2017.00605/full
43. Computer mouse movement patterns: A potential marker of mild cognitive impairment, accessed on March 29, 2026, https://www.researchgate.net/publication/283959585_Computer_mouse_movement_patterns_A_potential_marker_of_mild_cognitive_impairment
44. Using mouse cursor tracking to investigate online cognition: Preserving methodological ingenuity while moving toward reproducible science - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8219569/
45. Depression deconstructed: Wearables and passive digital phenotyping for analyzing individual symptoms - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10529827/
46. Passive Sensing for Mental Health Monitoring Using Machine Learning With Wearables and Smartphones: Scoping Review - Journal of Medical Internet Research, accessed on March 29, 2026, https://www.jmir.org/2025/1/e77066
47. Passive Sensing for Mental Health Monitoring Using Machine Learning With Wearables and Smartphones: Scoping Review - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12395114/
48. Impact of Digital Phenotypes and Question-Asking on Emotional Disorders in Adolescents: 4-Week Field Study - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12505407/
49. Utility of Digital Phenotyping Based on Wrist Wearables and Smartphones in Psychosis: Observational Study - JMIR mHealth and uHealth, accessed on March 29, 2026, https://mhealth.jmir.org/2025/1/e56185
50. Puzzle-Solving Activity as an Indicator of Epistemic Confusion - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC6365428/
51. Examining the Landscape of Cognitive Fatigue Detection: A Comprehensive Survey - MDPI, accessed on March 29, 2026, https://www.mdpi.com/2227-7080/12/3/38
52. Psychological Fatigue or Satisfaction? The Impact of Online Office App Use on Job Performance: Differentiating Work-Related and Non-Work-Related Contexts - MDPI, accessed on March 29, 2026, https://www.mdpi.com/2076-328X/15/3/283
53. A Survey of Passive Sensing for Workplace Wellbeing and Productivity - arXiv, accessed on March 29, 2026, https://arxiv.org/html/2201.03074v3
54. Unobtrusive measurement of cognitive load and physiological signals in uncontrolled environments - PubMed, accessed on March 29, 2026,

https://pubmed.ncbi.nlm.nih.gov/39271693/
55. Webcam-based online eye-tracking for behavioral research - ResearchGate, accessed on March 29, 2026, https://www.researchgate.net/publication/366830055_Webcam-based_online_eye-tracking_for_behavioral_research
56. Webcam-based gaze estimation for computer screen interaction - ResearchGate, accessed on March 29, 2026, https://www.researchgate.net/publication/379511816_Webcam-based_gaze_estimation_for_computer_screen_interaction
57. Intelligent educational systems based on adaptive learning algorithms and multimodal behavior modeling - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12453766/
58. Shifting From Active to Passive Monitoring of Alzheimer Disease: The State of the Research, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10926806/
59. Adversarial inference: predictive minds in the attention economy - PMC, accessed on March 29, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10457025/
60. Optimizing Mouse Dynamics for User Authentication by Machine Learning: Addressing Data Sufficiency, Accuracy-Practicality Trade-off, and Model Performance Challenges - arXiv, accessed on March 29, 2026, https://arxiv.org/html/2504.21415v1