Date: 26/03/2026

Software Requirement Specification (SRS)

PSB Hackathon 2026

Version 1.0

Project Name: Rakshak
Team Name: Gabrus
Institute Name: Indian Institute of Technology, Kharagpur

Revision History

Version No	Date	Prepared by/Modified by	Significant Changes
Draft V1.0	13/03/26	Sheersh Nigam, Akshat Jiwrajka, Arunangshu Karmakar, Simarpreet Singh	First Draft
V1.0	26/03/26	Sheersh Nigam, Akshat Jiwrajka, Arunangshu Karmakar, Simarpreet Singh	Audit corrections against deployed prototype: corrected PQC label taxonomy (Partially Quantum-Safe replaces Quantum-Safe); corrected FR-11 label definitions and decision tree to match Platform Guide; added FR-11a Weakest-Link Downgrade Rule; added FR-26a User Management page; updated FR-25 to activity-based idle timeout; updated FR-26 to tamper-evident audit log hashing; updated FR-27/FR-29 sidebar and global search; expanded §3.2.3 REST API table from 21 to 42 endpoints; removed unimplemented features (Slack delivery, NTP integration, Dynamic Scan Throttling NFR, Plugin Architecture NFR); corrected operating environment to SQLite on AWS EC2; updated §4.1 to include all 4 export formats (JSON, XML, CSV, PDF); added new features (Platform Guide, User Management, Dark/Light Theme, Smart CBOM Routing, §4.4 deployment section).

Declaration

The purpose of this Software Requirements Specification (SRS) document is to identify and document the user requirements for our platform **Rakshak**. The end deliverable software that will be supplied by our team **Gabrus** will comprise of all the requirements documented in the current document and will be operated in the manner specified in the document. The Source code will be developed subsequently based on these requirements and will formally go through code review during testing process.

Team Member Details:

Member 1	**Member 2**	**Member 3**	**Member 4**
Team Lead	Developer	Analyst	Tester
Sheersh Nigam	Akshat Jiwrajka	Arunangshu Karmakar	Simarpreet Singh
IIT Kharagpur	IIT Kharagpur	IIT Kharagpur	IIT Kharagpur
 26/03/26	Akshat Jiwrajka 26/03/26	Arunangshu Karmakar 26/03/26	 26/03/26

Table of Content

1. Introduction
    - 1.1 Purpose
    - 1.2 Scope
    - 1.3 Intended Audience
2. Overall Description
    - 2.1 Product Perspective
    - 2.2 Product Functions
    - 2.3 User Classes and Characteristics
    - 2.4 Operating Environment
    - 2.5 Design and Implementation Constraints
    - 2.6 Assumptions and Dependencies
3. Specific Requirements
    - 3.1 Functional Requirements
    - 3.2 External Interface Requirements
        - 3.2.1 User Interfaces
        - 3.2.2 Hardware Interfaces
        - 3.2.3 Software / Communication Interfaces
    - 3.3 System Features
    - 3.4 Non-functional Requirements
        - 3.4.1 Performance Requirements
        - 3.4.2 Software Quality Attributes
        - 3.4.3 Other Non-functional Requirements
4. Technological Requirements
    - 4.1 Technologies used in development of the web application
    - 4.2 I.D.E. (Integrated Development Environment)
    - 4.3 Database Management Software
    - 4.4 Deployment Environment
5. Security Requirements
    - Annexure-A (CERT-IN CBOM elements)

---

1. Introduction

1.1 Purpose

To develop a quantum-proof cryptographic scanner that
discovers, inventories, and validates the cryptographic posture of public-facing banking applications against NIST PQC standards.

1.2 Scope

This document is prepared with the following objectives:

- To provide behaviour of the system.
- To provide Process Flow charts.
- Discover cryptographic inventory (TLS certificates, VPN endpoints, APIs).
- Identify cryptographic controls (cipher suites, key exchange mechanisms, TLS versions).
- Validate whether deployed algorithms are quantum-safe.
- Generate actionable recommendations for non-PQC ready assets.
- Issue digital labels: Not Quantum-Safe, Partially Quantum-Safe, PQC-Ready, or Fully Quantum Safe.
- Enterprise-wide console for central management: A GUI console to display status of scanned systems (public facing applications) covering details mentioned in Annexure-A (CERT-IN CBOM Elements).
- As per the variation of score (like High, Medium, Low rating etc) for any public applications, dashboard should display that change as well.

System Process Flow



1.3 Intended Audience

The intended audience of this document is business and technical users from Punjab National Bank (PNB) and IIT Kanpur evaluators.

---

2. Overall Description

2.1 Product Perspective

Rakshak is a new, standalone quantum-proof cryptographic scanner introduced into Punjab National Bank's cybersecurity ecosystem. It does not replace any existing system; rather, it adds a new capability — the ability to discover, inventory, and validate the cryptographic posture of all public-facing applications (Web Servers, APIs, and Systems including TLS-based VPNs) against NIST Post-Quantum Cryptography (PQC) standards (FIPS 203/204/205).

Why it is needed: With the rapid digitalization of banking, PNB's critical applications are publicly accessible 24×7. While secured by classical cryptographic algorithms (RSA, ECC) today, these are vulnerable to the emerging quantum computing threat. Adversaries can execute **"Harvest Now, Decrypt Later" (HNDL)** attacks — intercepting encrypted data now for decryption once quantum computers mature. Rakshak provides proactive defense by identifying vulnerable assets and guiding PNB's transition to quantum-safe cryptography.

System positioning: Rakshak is deployed within PNB's intranet with outbound access to public-facing endpoints on port 443 for scanning. It performs **passive, non-intrusive** TLS handshakes only — no write operations on target systems and no disruption to live banking services. It exposes a REST API layer (HTTPS/JSON) enabling future integration with existing SIEM platforms or security dashboards, and supports Webhook notifications for pushing alerts to external systems.

Data flow: Targets are scanned → cryptographic details extracted (TLS versions, cipher suites, certificates, key exchange mechanisms) → evaluated against NIST PQC standards → a **Cryptographic Bill of Materials (CBOM)** is generated per CERT-IN Annexure-A → quantum-safety labels are assigned → actionable remediation recommendations are produced — all presented through an enterprise-wide web console with dashboards, risk ratings, and exportable reports.

Users: Two roles — **Admin** (cybersecurity teams, IT administrators — full access) and **Checker** (compliance auditors, risk managers — read-only access).

External dependencies: SMTP server (email notifications and password recovery).

2.2 Product Functions

1. **Target input** (URLs, IPs, TLS-based VPN endpoints, APIs) with input validation and bulk CSV/JSON import
2. **TLS scanning** — perform TLS handshakes, extract protocol version, and enumerate all supported cipher suites using a dual-engine approach (sslyze + OQS Docker probe)
3. **TLS-based VPN endpoint scanning** — assess cryptographic posture of VPN services
4. **API endpoint scanning** — discover and validate TLS configurations of REST and SOAP-based APIs
5. **Certificate analysis** — extract and parse certificate details (issuer, subject, signature algorithm, public key, validity, chain) including X.509 OID-based PQC detection
6. **Real-time scan monitoring** — WebSocket-based live progress updates with per-target status and ETA
7. **PQC classification** — classify the quantum-safety status of each cryptographic component based on NIST PQC standards (FIPS 203/204/205), using a cert-chain OID walk as the primary detection signal
8. **Weakest-Link Downgrade Rule** — automatically forces a "Critical / Not Quantum-Safe" rating if any legacy protocol (TLS 1.0/1.1, SSL 2.0/3.0) or broken cipher (RC4, 3DES, NULL) is detected on the asset
9. **CBOM generation** — produce Cryptographic Bill of Materials per CERT-IN Annexure-A (Algorithms, Keys, Protocols, Certificates)
10. **CBOM snapshot comparison** — compare two CBOM snapshots to track cryptographic posture changes over time
11. **Certificate chain visualization** — per-certificate OID-level quantum-safety status shown inline in the CBOM drill-down view
12. **Labeling** — assign labels: Not Quantum-Safe, Partially Quantum-Safe, PQC Ready, or Fully Quantum Safe
13. **Actionable recommendations** — generate specific algorithm migration steps for non-PQC ready assets
14. **Automated PQC migration playbooks** — step-by-step migration guides tailored per asset
15. **Quantum risk timeline** — projected vulnerability timeline based on quantum computing advancement estimates
16. **Authentication & access control** — login, password recovery, Role-Based Access Control (Admin / Checker), session management with 30-minute idle timeout, and audit logging
17. **Home overview dashboard** — high-level summaries of asset counts, PQC adoption %, CBOM vulnerabilities, and cyber rating

18. **Dashboard navigation** — persistent sidebar, global search with smart CBOM routing, and time period filters
19. **Asset inventory management** — maintain, search, sort, and manage all public-facing assets with risk levels and certificate details
20. **Asset discovery** — discover assets across domains, SSL certificates, IP/subnets, and software with network topology visualization
21. **PQC posture module** — compliance dashboard (Elite-PQC Ready, Standard, Legacy, Critical) with risk overview and improvement recommendations
22. **Cyber rating** — consolidated enterprise-level score (out of 1000) with compliance matrix (Tier 1–4)
23. **Enterprise reporting & export** — scheduled and on-demand reports in PDF, CSV formats with report history
24. **Webhook / API notifications** — push real-time alerts on scan completion, critical findings, or certificate expiration to external systems
25. **Platform Guide** — built-in reference page explaining PQC posture definitions, label criteria (FR-11), and risk level descriptions
26. **User Management** — Admin-only panel to view all users, add new Admin/Checker accounts, and review tamper-evident audit logs with cryptographic hash per entry
27. **Dark / Light Theme** — persistent theme toggle accessible from the top navigation bar

2.3 User Classes and Characteristics

- **Primary Users:** Bank cybersecurity teams, IT administrators.
- **Secondary Users:** Compliance auditors, risk managers.
- Users are expected to have technical knowledge of cryptography and networking.

User at	User Type	Menus for User
PNB / IIT Kanpur officials	Admin User	Full Access: Home, Asset Inventory, Asset Discovery, CBOM, Posture of PQC, Cyber Rating, Reporting, User Management.
PNB	Checker	Read-Only Access: Home, Asset Inventory, Asset Discovery, CBOM, Posture of PQC, Cyber Rating, Export Reports.

2.4 Operating Environment

The operating environment for **Rakshak** is as listed below.

- **Server system:** Containerized environment (Docker) deployed on an AWS EC2 Virtual Server (production) or any Virtual Machine capable of running Python 3.11+ applications.
- **Operating system:** Linux (Ubuntu 22.04 LTS or higher) is required for the production server; Linux or Windows can be used for local development.
- **Database:** SQLite (both local development and current production deployment). The schema is designed for forward-compatibility with PostgreSQL for future enterprise scaling.
- **Platform:** Web-based application built on the FastAPI (async) framework, serving Jinja2 HTML templates and a REST API.
- **Technology:** Python 3.11+ (core engine), `sslyze` (TLS scanning), `openquantumsafe/curl` Docker image (PQC detection via liboqs), and the Python `cryptography` library (X.509 certificate parsing).
- **API:** RESTful API architecture facilitating communication between the scanning engine, the database, and the frontend dashboard. WebSocket endpoint for real-time scan progress.
- **Deployment (Production):** AWS EC2 Virtual Server — live at https://rakshak.live. The Docker socket is mounted in the container to allow the OQS probe to spawn child containers.

2.5 Design and Implementation Constraints

1. Technical Constraints (Deployment):

- **Network Configuration:** The application requires outbound network access strictly over port 443 (HTTPS/TLS) to successfully reach and scan public-facing target endpoints. The application must be deployed within a private intranet, requiring appropriate firewall rules to allow outbound scanning while restricting unauthorized inbound access.
- **Hosting Environment:** The system must be hosted on an internal, secure intranet server so that the centralized management dashboard is never directly exposed to the public internet.

2. Security Constraints

- **Access Control:** Implementation of Role-Based Access Control (RBAC) is mandatory. The system must enforce separation of duties, supporting at least two distinct roles: 'Admin' (full access to schedule scans and manage targets) and 'Checker' (read-only access to view reports and verify compliance)
- **Data Encryption:** All data transmitted between the user's web browser and the internal

dashboard must be encrypted using HTTPS (TLS 1.2 or higher).

- **Passive Scanning Protocol:** The scanner must operate in a strictly read-only, passive mode. It must not disrupt live banking services, execute intrusive payloads, or attempt to write/modify target configurations.

3. Performance Constraints

- **Concurrency and Throughput:** The backend scanning engine must be highly concurrent, capable of handling 50+ target endpoints simultaneously without causing severe degradation in the dashboard's responsiveness.
- **Failover Mechanisms:** The scanning engine should be designed statelessly. In the event of a failure, the application must be able to restart, recover safely, and retrieve its last known state from the database backups.

4. User Interface Constraints

- **User Experience Consistency:** The web dashboard must be fully responsive and maintain intuitive, consistent design elements. It must clearly present complex cryptographic data (e.g., CBOM tables, PQC status badges) so that no specialized training is required for basic operations.

5. Domain-Specific Constraints

- The logic analyzer must strictly comply with NIST Post-Quantum Cryptography (PQC) standards (FIPS 203, 204, 205) and adhere to CERT-In guidelines for Cryptographic Bill of Materials (CBOM) generation.
- The scanner is restricted to operating exclusively on public-facing applications (Web Servers, APIs, TLS-based VPNs).
- The system must not disrupt live banking services.
- The system must be able to export its scan results and CBOM inventories in machine-readable formats (JSON, XML, CSV, and PDF) to allow integration with other banking compliance tools.

2.6 Assumptions and Dependencies

Assumptions:

- **Standard Browser Support-** It is assumed that bank officials and end-users will access the application dashboard using modern, HTML5-compliant web browsers such as Google Chrome (version 90+).
- **Protocol Uniformity-** It is assumed that TLS-based communication is actively implemented across all targeted public-facing applications (HTTP over TLS, TLS-VPNs).
- **Network Connectivity-** The underlying server hosting the scanner is assumed to have

stable, continuous internet connectivity to successfully probe external endpoints.

Dependencies:

- **Core Software Stack-** The application is heavily dependent on Python 3.11+ and specialized third-party libraries (`sslyze` for protocol enumeration and `cryptography` for certificate parsing). Any deprecation or breaking changes in these libraries will require immediate system updates.
- **Database System-** The application relies on SQLite for persistent data storage in the current prototype deployment (on AWS EC2). Any maintenance, downtime, or performance bottlenecks within the database will directly impact the application's ability to generate reports or retrieve scan histories. PostgreSQL is planned for future enterprise-scale deployment.
- **Cryptographic Standard Finalization-** The analyzer's rule engine depends on the finalized NIST PQC algorithms (e.g., ML-KEM, ML-DSA, SLH-DSA) acting as the definitive source of truth for quantum-safe validation.

---

3. Specific Requirements

3.1 Functional Requirements

Core Scanning & Analysis

ID	Requirement
FR-01	The system shall accept target inputs including URLs, IP addresses, TLS-based VPN endpoints, and API endpoints for scanning.
FR-02	The system shall perform a TLS handshake with each target and extract the negotiated protocol version (TLS 1.0, 1.1, 1.2, 1.3).
FR-03	The system shall enumerate all cipher suites supported by each target, including key exchange, authentication, encryption, and hashing algorithms.
FR-04	The system shall extract and parse certificate details including issuer name, subject name, signature algorithm, public key algorithm, key length, validity period (Not Valid Before / Not Valid After), and certificate chain.
FR-05	The system shall discover and scan TLS-based VPN endpoints to assess their cryptographic posture.
FR-06	The system shall discover and validate API endpoint TLS configurations, including REST and SOAP-based services.

ID	Requirement
FR-07	The system shall classify each cryptographic component's quantum-safety posture and assign exactly one of four labels: **Not Quantum-Safe**, **Partially Quantum-Safe**, **PQC-Ready**, or **Fully Quantum Safe** — based on NIST PQC standards (FIPS 203/204/205) and the cert-chain OID walk described in FR-11.
FR-08	The system shall provide **Real-Time Scan Monitoring** via WebSocket-based live progress updates, showing per-target scan status, current phase (handshake, cipher enumeration, cert parsing), and ETA.
FR-09	The system shall perform **Input Validation** on all target inputs (URL format, IP address format, CIDR notation, port ranges) before initiating scans, rejecting malformed entries with descriptive error messages.

CBOM & Labeling

ID	Requirement
FR-10	The system shall generate a Cryptographic Bill of Materials (CBOM) per CERT-IN Annexure-A format, covering all four asset categories: Algorithms, Keys, Protocols, and Certificates with their mandatory fields.
FR-11	The system shall evaluate each scanned asset's cryptographic posture and assign exactly one of the following labels (listed from least to most quantum-ready):
FR-12	The system shall generate actionable remediation recommendations for each asset classified as "Not Quantum-Safe" or "Partially Quantum-Safe", including specific algorithm migration steps (e.g., "Upgrade key exchange from ECDHE to ML-KEM-768 (FIPS 203)").
FR-13	The system shall support **CBOM Snapshot Comparison** — allowing users to compare two CBOM snapshots taken at different times to track cryptographic posture changes, newly added/removed assets, and migration progress.
FR-14	The system shall provide **Certificate Chain Visualization** — an interactive tree/graph view showing the full certificate chain from leaf to root CA, with quantum-safety status color-coded at each level.

FR-11 — Label Definitions:

> ***Weakest-Link Rule (FR-11a):*** *If a scanned asset supports any legacy protocol (SSL 2.0, SSL 3.0, TLS 1.0, TLS 1.1) or broken cipher (RC4, 3DES, DES, NULL, MD5), the asset shall be automatically downgraded to* ***Not Quantum-Safe / Critical*** *regardless of any PQC primitives also detected. This prevents false-positive safe ratings on downgrade-vulnerable endpoints.*

Label	Criteria	Real-World Example
🔴 **Not Quantum-Safe**	**No PQC detected anywhere** — neither in the negotiated TLS cipher suite (key exchange) nor in any X.509 certificate chain OID. The connection relies entirely on classical cryptography vulnerable to Shor's algorithm. Also applied by the Weakest-Link Rule when any legacy protocol or broken cipher is present.	ECDHE key exchange + RSA/ECDSA certificate + AES-256-GCM. Scan targets: `google.com`, `badssl.com`.
🟡 **Partially Quantum-Safe**	**PQC detected in one layer only.** At least one PQC algorithm has been detected — either in the negotiated cipher suite (ML-KEM key exchange) *or* from the server's leaf certificate signature OID (ML-DSA, SLH-DSA) — but not across both layers simultaneously. Data may be protected against HNDL, but identity authentication or KEX remains classical.	ML-KEM-768 key exchange with a classical RSA identity certificate. Scan target: `kms.us-east-1.amazonaws.com`.
🔵 **PQC-Ready**	**PQC in both KEX and leaf certificate auth.** Both the key exchange and the leaf certificate's authentication use PQC algorithms (verified via real X.509 OID parsing). However, at least one Intermediate or Root CA in the trust chain still uses a classical signature, preventing end-to-end quantum resilience.	ML-DSA-65 leaf certificate (OID: 2.16.840.1.101.3.4.3.18) + ML-KEM key exchange, but a Root CA signed with RSA-2048. Scan target: `scans.rakshak.live:4433`.

Label	Criteria	Real-World Example
● **Fully Quantum-Safe**	**End-to-end PQC.** Every certificate in the trust chain (Leaf → Intermediate → Root CA) uses a NIST-standardized PQC signature OID (ML-DSA, SLH-DSA, or FN-DSA). No classical asymmetric cryptography remains in any layer of the connection.	ML-DSA-65 leaf + ML-DSA-87 Intermediate + ML-DSA-87 Root CA — entire chain verified via NIST OID inspection. Scan target: `test.openquantumsafe.org:6182`.

> ***Note on X25519:*** *X25519 (Curve25519) is classified as a classical/vulnerable key exchange algorithm — it is not quantum-safe and does not qualify for any PQC label. Only NIST-standardized PQC algorithms (ML-KEM per FIPS 203, ML-DSA per FIPS 204, SLH-DSA per FIPS 205, Falcon/FN-DSA) qualify.*

Reporting & Export

ID	Requirement
FR-15	The system shall export scan reports in JSON, XML, and CSV formats.
FR-16	The system shall provide an enterprise-wide console displaying the status of all scanned systems with High/Medium/Low risk ratings (mapped to the Cyber Rating tiers defined in FR-47 through FR-49) per Annexure-A.
FR-17	The system shall support both **Scheduled Reporting** (recurring reports at configurable frequency — daily, weekly, monthly) and **On-Demand Reporting** (immediate generation).
FR-18	The system shall allow users to configure report contents by selecting which modules to include (Asset Discovery, Asset Inventory, CBOM, PQC Posture, Cyber Rating).
FR-19	The system shall support multiple report delivery channels: **email** (SMTP delivery with attachment) and **local** (file saved to server directory).
FR-20	The system shall support PDF report generation with optional password protection and chart/graph inclusion.

ID	Requirement
FR-21	The system shall implement **Webhook / API Notifications** allowing external systems to receive real-time alerts on scan completion, critical findings, or certificate expiration warnings.

Authentication & Access Control

ID	Requirement
FR-22	The system shall provide a login screen requiring email/username and password for authentication.
FR-23	The system shall implement a "Forgot Password" recovery mechanism via email (password reset link sent to registered email).
FR-24	The system shall enforce Role-Based Access Control (RBAC) with at least two roles: **Admin** (full access — configure targets, schedule scans, manage users, view audit logs) and **Checker** (read-only — view reports, verify compliance).
FR-25	The system shall enforce **Session Management** policies including: activity-based idle timeout (30 minutes of inactivity), automatic logout after idle period, and token-based session verification on every page load.
FR-26	The system shall maintain **Tamper-Evident Audit Logs** recording all significant events including: user login/logout, scan initiation/completion, report generation, asset additions/modifications, and configuration changes — each with user ID, username, timestamp, IP address, event type, event details, and a cryptographic hash to ensure immutability.
FR-26a	The system shall provide a **User Management** page (Admin-only) displaying all registered users with their ID, username, email, role (Admin/Checker), active status, and last login timestamp, with the ability to add new users and view audit logs.

Dashboard & Navigation

ID	Requirement
FR-27	The system shall provide a persistent sidebar navigation menu with links to: Home, Asset Inventory, Asset Discovery, CBOM, Posture of PQC, Cyber Rating, Reporting, Platform Guide (reference documentation), and Users (Admin-only User Management).

ID	Requirement
FR-28	The system shall provide a **Home Overview Dashboard** displaying high-level summaries including: total asset discovery counts, PQC adoption percentage, CBOM vulnerability count, Cyber Rating score, and a PQC Posture Distribution donut chart.
FR-29	The system shall provide a **Global Search** bar enabling users to search across domains, URLs, IP addresses, contacts, Indicators of Compromise (IoCs), and other assets. When a user selects an asset from search results, the system shall navigate directly to the latest CBOM snapshot for that asset (Smart Asset-to-CBOM Routing).
FR-30	The system shall provide a **Time Period Filter** allowing users to specify start and end dates to filter all displayed dashboard data.

Asset Inventory Module

ID	Requirement
FR-31	The system shall maintain an **Asset Inventory** displaying top-level metrics for Public Web Apps, APIs, Servers, and Total Assets.
FR-32	The system shall display visual distribution charts for: Asset Risk levels, Expiring Certificates timeline, IP Version Breakdown (IPv4 vs IPv6), and Asset Type Distribution (Critical, High, Medium, Low).
FR-33	The system shall provide a searchable, sortable data table listing all inventoried assets with columns: Asset Name, URL, IPv4/IPv6 Address, Type, Owner, Risk Level, Certificate Status, Key Length, and Last Scan Timestamp.
FR-34	The system shall display Nameserver Records including Domain, Hostname, IP Address, Record Type, IPv6 Address, Asset association, TTL, Key Length, Cipher Suite (TLS), and Certificate Authority.
FR-35	The system shall allow users to manually **Add Assets** and trigger a **Scan All** action across all inventoried assets.
FR-36	The system shall support **Bulk Target Import** via CSV or JSON file upload, enabling administrators to onboard large numbers of targets at once.

Asset Discovery Module

ID	Requirement
FR-37	The system shall provide an **Asset Discovery** module with categorized tabs for Domains, SSL Certificates, IP Address/Subnets, and Software.
FR-38	The system shall support status filtering of discovered assets: New, False Positive/Ignore, Confirmed, and All.
FR-39	The system shall display detailed discovery tracking tables for each category: Registration Date and Registrar for Domains; Fingerprint and Certificate Authority for SSL; Location, Subnet, ASN, and Netname for IPs.
FR-40	The system shall render a **Visual Network Topology Graph** mapping connections between IPs, SSL certificates, Web servers, Domains, and scanning tags.

PQC Posture Module

ID	Requirement
FR-41	The system shall provide a **PQC Compliance Dashboard** categorizing assets into: Elite-PQC Ready, Standard, Legacy, and Critical.
FR-42	The system shall display Risk Overview charts and Application Status tracking within the PQC module.
FR-43	The system shall display actionable **Improvement Recommendations** within the PQC Posture module UI, surfacing the remediation steps generated by FR-12 in a categorized panel (e.g., upgrading to TLS 1.3 with PQC cipher suites, implementing ML-KEM for key exchange, updating cryptographic libraries, developing a PQC Migration Plan).
FR-44	The system shall display detailed individual app profiles showing PQC Support status, Ownership, Exposure level, TLS type, and an assigned Score/Status.
FR-45	The system shall generate a **Quantum Risk Timeline** — a projected timeline visualization showing when each asset's current cryptographic algorithms are expected to become vulnerable based on quantum computing advancement projections (NIST/CISA estimates), highlighting exposure to **Harvest Now, Decrypt Later (HNDL)** attacks where adversaries intercept encrypted data today for future quantum decryption.
FR-46	The system shall provide **Automated PQC Migration Playbooks** — auto-generated step-by-step migration guides per asset, tailored to its current cipher suite and target PQC algorithms, with estimated effort and risk assessment.

Cyber Rating Module

ID	Requirement
FR-47	The system shall compute and display a **Consolidated Enterprise-Level Cyber-Rating Score** as a numerical metric (out of 1000) with a visual dial/gauge indicator.
FR-48	The system shall maintain a classification table mapping asset status (Legacy, Standard, Elite-PQC) to specific numerical score ranges.
FR-49	The system shall implement a **Compliance Matrix** defining tiers: Tier 1 (Elite), Tier 2 (Standard), Tier 3 (Needs Improvement), Tier 4 (Critical) — each with defined Security Level, Compliance Criteria (TLS version, cipher strength), and Priority/Action.
FR-50	The system shall provide a **Historical Trend Analysis** dashboard tracking the organization's overall quantum-readiness score over time with trend lines, showing improvement or regression.

3.2 External Interface Requirements

3.2.1 User Interfaces

The application shall provide a **responsive web-based user interface** accessible via modern web browsers (Google Chrome 90+, Mozilla Firefox, Microsoft Edge). The UI shall consist of the following components:

Global Layout:

- A **persistent sidebar navigation** menu providing access to all modules: Home, Asset Inventory, Asset Discovery, CBOM, Posture of PQC, Cyber Rating, Reporting, Platform Guide, and Users (Admin-only).
- A **top navigation bar** containing: global search bar, time period filter (date range selector), user profile dropdown, and notification bell icon.
- A **login page** with email/username and password fields, "Forgot Password" link, and "Sign In" button.

Home Overview Dashboard:

- Summary cards displaying key metrics: total assets discovered (domains, IPs, subdomains, cloud assets), PQC adoption percentage (circular progress indicator), CBOM vulnerability count, and Asset Inventory summary (SSL certificates, software, public-facing services).
- A Cyber Rating breakdown widget showing tier distribution (Excellent, Good,

Satisfactory, Needs Improvement).

Asset Inventory View:

- Metric cards for Public Web Apps, APIs, Servers, and Total Assets counts.
- Interactive charts: Asset Risk distribution (pie/donut), Expiring Certificates timeline (bar), IP Version Breakdown (pie), Asset Type Distribution by severity (stacked bar).
- A searchable, sortable, paginated data table with columns: Asset Name, URL, IPv4/IPv6, Type, Owner, Risk, Cert Status, Key Length, Last Scan.
- A Nameserver Records sub-section table.
- "Add Asset" button (opens modal form) and "Scan All" action button.

Asset Discovery View:

- Tabbed interface for Domains, SSL, IP Address/Subnets, and Software categories.
- Status filter bar: New, False Positive/Ignore, Confirmed, All.
- Detailed tracking tables per category with category-specific columns.
- A **Network Topology Graph** (interactive, zoomable, drag-enabled) showing relationships between discovered assets.

CBOM View:

- Summary metric cards: Total Applications, Sites Surveyed, Active Certificates, Weak Cryptography count, Certificate Issues count.
- Analytical charts: Cipher Usage distribution, Top Certificate Authorities, Key Length Distribution, Encryption Protocols breakdown.
- A granular mapping table showing per-application Key Length, Cipher, and Certificate Authority.
- Drill-down capability to view full Annexure-A CBOM detail per asset (all 4 categories: Algorithms, Keys, Protocols, Certificates).

PQC Posture View:

- PQC Compliance Dashboard with category cards: Elite-PQC Ready, Standard, Legacy, Critical.
- Risk Overview charts and Application Status tracking.
- Improvement Recommendations panel with actionable items.
- Individual app profile cards showing: PQC Support status, Ownership, Exposure level, TLS type, Score/Status badge.
- Quantum Risk Timeline visualization showing projected vulnerability timelines per asset.

Cyber Rating View:

- A large visual dial/gauge indicator showing the Consolidated Enterprise-Level Cyber-Rating Score (out of 1000).
- Classification table mapping asset status to score ranges.
- Compliance Matrix grid defining Tier 1–4 with Security Level, Compliance Criteria, and Priority/Action.
- Historical trend chart showing score changes over time.

Reporting View:

- Toggle between Scheduled Reporting and On-Demand Reporting modes.
- Configuration form: Report Type, Frequency (Weekly/Daily/Monthly), Target Asset selection.
- Module inclusion checkboxes: Discovery, Inventory, CBOM, PQC Posture, Cyber Rating.
- Scheduling tools: Date picker, Time picker, Time Zone selector.
- Delivery settings: Email routing or local directory path.
- Output settings: File Format (PDF/JSON/XML/CSV), Password Protection toggle, Include Charts checkbox.

Label Badges:

- Color-coded badges displayed on assets across all views:
  - 🟢 **Fully Quantum Safe** — green badge
  - 🔵 **PQC Ready** — blue badge
  - 🟡 **Partially Quantum-Safe** — amber/yellow badge
  - 🔴 **Not Quantum-Safe** — red badge
  - ⚪ **Unknown** — grey badge (target unreachable or scan failed)

Theme Toggle:

- A sun/moon icon in the top navigation bar allows users to switch between Light and Dark UI themes, persisted for the session.

Platform Guide View:

- A dedicated reference page accessible from the sidebar explaining PQC label definitions, compliance tier criteria, and risk level descriptions for non-expert users.

3.2.2 Hardware Interfaces

- The system requires a **standard server** (physical or virtual) with network access to the public internet on port **443 (HTTPS/TLS)**.
- No specialized hardware is required. The system operates entirely in software.
- The server must have a **network interface** capable of establishing outbound TCP connections to target endpoints for TLS handshakes.
- For TLS-based VPN endpoint scanning, the server must be able to reach port **443** (HTTPS/TLS). Note: Ports 500 (IKE) and 4500 (NAT-T) are UDP-based and outside the scope of TLS-based scanning.
- Minimum recommended hardware: **4-core CPU, 8 GB RAM, 50 GB disk** (scales with number of targets and historical data retention).

3.2.3 Software / Communication Interfaces

REST API Endpoints:

The system shall expose the following REST API endpoints, communicating over **HTTPS** using **JSON** as the data interchange format:

Method	Endpoint	Description
`POST`	`/api/auth/login`	Authenticate user and return JWT token
`POST`	`/api/auth/forgot-password`	Initiate password recovery via email
`POST`	`/api/auth/reset-password`	Submit new password using the reset token from email
`POST`	`/api/auth/logout`	Invalidate the current session token
`POST`	`/api/auth/register`	Register a new user account (Admin-only)
`POST`	`/api/scan`	Submit a new scan request with target list
`POST`	`/api/scan/bulk-import`	Upload CSV/JSON file for bulk target import

Method	Endpoint	Description
GET	/api/scan	List all scans (paginated)
GET	/api/scan/{id}/status	Get real-time status of a running scan
GET	/api/scan/{id}/results	Retrieve scan results for a specific scan
DELETE	/api/scan/{id}	Cancel or remove a scan
GET	/api/assets	List all inventoried assets (paginated, filterable by risk)
POST	/api/assets	Add a new asset manually
DELETE	/api/assets/{asset_id}	Remove an asset from inventory
POST	/api/assets/discover	Trigger asset discovery (DNS, IP, subnet, software enumeration)
GET	/api/assets/metrics	Get asset inventory metric cards (web apps, APIs, servers, total)
GET	/api/assets/discovery	List discovered assets with status (New / Confirmed / False Positive)
PATCH	/api/assets/discovery/{disc_id}/status	Update discovered asset triage status
GET	/api/assets/nameservers	Retrieve nameserver records for inventoried assets
GET	/api/cbom	List all CBOM snapshots (paginated)
GET	/api/cbom/metrics	Get CBOM summary metrics (applications, certs, weak crypto, cert issues)

Method	Endpoint	Description
GET	/api/cbom/compare	Compare two CBOM snapshots and return diff
GET	/api/cbom/{snap_id}	Retrieve full CBOM detail for a specific snapshot
GET	/api/cbom/cert-chain/{snap_id}	Retrieve the parsed X.509 certificate chain for a snapshot
GET	/api/pqc/posture	Get PQC posture summary categorised by tier
GET	/api/pqc/recommendations/{asset_id}	Get PQC migration playbook for a specific asset
GET	/api/pqc/risk-timeline/{asset_id}	Get projected quantum risk timeline for a specific asset
GET	/api/rating	Get enterprise cyber rating score with tier and breakdown
GET	/api/rating/history	Get historical rating trend data over time
POST	/api/reports/generate	Generate an on-demand report immediately
POST	/api/reports/schedule	Create a scheduled recurring report
GET	/api/reports	List all generated reports with status and download links
GET	/api/reports/export/{report_id}	Download an export of a specific generated report
DELETE	/api/reports/{report_id}	Delete a generated report
GET	/api/reports/scheduled	List all scheduled report configurations

Method	Endpoint	Description
`POST`	`/api/webhooks`	Register a new webhook for event notifications
`GET`	`/api/webhooks`	List all registered webhooks
`DELETE`	`/api/webhooks/{webhook_id}`	Remove a registered webhook
`GET`	`/api/users`	List all system users with roles and status (Admin-only)
`GET`	`/api/audit-logs`	Retrieve tamper-evident audit log entries (paginated)
`GET`	`/api/home/summary`	Get home dashboard summary (assets, PQC %, CBOM count, rating)
`WebSocket`	`/ws/scan/{scan_id}`	Real-time scan progress stream

External Service Integrations:

- **SMTP Server** — For email-based report delivery and password recovery.

Data Formats:

- All API request/response bodies use **JSON** (`application/json`).
- Report exports support **JSON**, **XML**, **CSV**, and **PDF** formats.
- CBOM output conforms to **CERT-IN Annexure-A** schema.

3.3 System Features

SF-01: Authentication & Access Control

Description: Provides secure login, password recovery, and role-based access control to ensure only authorized users can access the system with appropriate privilege levels.

Stimulus/Response Sequences:

Stimulus	Response
User navigates to the application URL	System displays login page with email/password fields
User enters valid credentials and clicks "Sign In"	System authenticates user, issues JWT token, redirects to Home Dashboard
User enters invalid credentials	System displays error message: "Invalid email or password"
User clicks "Forgot Password" and enters email	System sends password reset link to registered email
Admin navigates to user management	System displays user list with role assignments (Admin/Checker)
Checker user attempts to access Admin-only feature	System denies access and displays "Insufficient permissions" message

Functional Requirements: FR-22, FR-23, FR-24, FR-25, FR-26

SF-02: Home Overview Dashboard

Description: Provides a centralized, at-a-glance view of the organization's entire cryptographic posture, aggregating key metrics from all modules into a single summary page.

Stimulus/Response Sequences:

Stimulus	Response
Authenticated user lands on Home page	System displays summary cards for Asset Discovery counts, PQC adoption %, CBOM vulnerability count, Cyber Rating, and Asset Inventory
User applies a time period filter	System refreshes all dashboard widgets to reflect data within the selected date range
User enters a search query in the global search bar	System displays matching results across domains, URLs, IPs, IoCs, and assets

Functional Requirements: FR-27, FR-28, FR-29, FR-30

SF-03: Asset Inventory Management

Description: Maintains a comprehensive inventory of all known public-facing assets (web apps, APIs, servers), their risk levels, certificate details, and scan history. Enables both manual asset addition and bulk operations.

Stimulus/Response Sequences:

Stimulus	Response
User navigates to Asset Inventory	System displays metric cards (Web Apps, APIs, Servers, Total) and visual distribution charts
User scrolls to the data table	System renders paginated, searchable table of all assets with risk, cert status, key length
User clicks "Add Asset"	System opens a modal form to input asset details (URL, IP, type, owner)
User fills and submits the Add Asset form	System validates input, adds asset to inventory, and queues it for scanning
User clicks "Scan All"	System initiates a scan across all inventoried assets and shows progress indicators
User clicks on an asset row	System navigates to a detail view with full cert chain, cipher suite, and CBOM data

Functional Requirements: FR-31, FR-32, FR-33, FR-34, FR-35, FR-36

SF-04: Asset Discovery Engine

Description: Automatically discovers public-facing cryptographic assets across multiple categories (domains, SSL certificates, IP subnets, software) and maps their interconnections through a visual network topology.

Stimulus/Response Sequences:

Stimulus	Response
User navigates to Asset Discovery	System displays tabbed view (Domains, SSL, IP/Subnets, Software) with status filters

Stimulus	Response
User selects a category tab (e.g., Domains)	System displays tracking table with Registration Date, Registrar, and other category-specific fields
User applies status filter (e.g., "New")	System filters the table to show only newly discovered assets
User marks an asset as "False Positive / Ignore"	System updates asset status and excludes it from future scan reports
User marks an asset as "Confirmed"	System moves asset to confirmed inventory for active monitoring
User clicks "Network Topology"	System renders an interactive graph showing relationships between IPs, SSLs, servers, and domains

Functional Requirements: FR-37, FR-38, FR-39, FR-40

SF-05: TLS & VPN & API Scanner Engine

Description: Core scanning engine that performs TLS handshakes, enumerates cipher suites, extracts certificate details, and scans VPN and API endpoints for their cryptographic posture.

Stimulus/Response Sequences:

Stimulus	Response
Admin submits a scan request with a list of targets	System queues targets, initiates TLS handshakes, and begins cipher enumeration per target
Scan engine connects to a web server target	System extracts TLS version, all supported cipher suites, full certificate chain, key exchange algorithm, and authentication method
Scan engine connects to a TLS-based VPN endpoint	System extracts VPN-specific TLS parameters and cipher suite configuration
Scan engine discovers an API endpoint	System validates TLS configuration of the API including protocol version and cipher strength
A scan is in progress	System sends real-time progress updates via WebSocket (current phase, target, ETA)

Stimulus	Response
Scan completes for a target	System stores results in database and triggers post-scan analysis (PQC classification)
Scan fails for a target (unreachable / timeout)	System logs the failure, marks target as "Scan Failed," and continues with remaining targets

Functional Requirements: FR-01, FR-02, FR-03, FR-04, FR-05, FR-06, FR-08, FR-09

SF-06: PQC Analysis & Classification Engine

Description: Analyzes scanned cryptographic data against NIST PQC standards (FIPS 203/204/205), classifies each component's quantum safety, assigns labels, and generates tailored remediation recommendations and migration playbooks.

Stimulus/Response Sequences:

Stimulus	Response
Scan results are available for a target	System evaluates each cryptographic component (key exchange, auth, encryption, hashing) against NIST PQC criteria
Component uses AES-256/SHA-384 (symmetric/hash only)	System notes these are classically safe against Grover's but the KEX/auth layer determines the PQC label
Component uses ML-KEM for key exchange but RSA certificate authentication	System classifies as "Partially Quantum-Safe" (PQC in one layer only)
Both KEX and leaf certificate use PQC, but classical Root CA in chain	System classifies as "PQC-Ready"
All components and full cert chain use PQC	System classifies as "Fully Quantum Safe"
Asset is classified as Not Quantum-Safe or Partially Quantum-Safe	System generates remediation recommendations with specific algorithm migration steps
User requests a migration playbook for an asset	System generates a step-by-step PQC Migration Playbook tailored to the asset's current cipher suite

Stimulus	Response
User views the Quantum Risk Timeline	System displays projected vulnerability timeline based on quantum computing advancement estimates

Functional Requirements: FR-07, FR-11, FR-12, FR-41, FR-42, FR-43, FR-44, FR-45, FR-46

SF-07: CBOM Generator

Description: Generates a complete Cryptographic Bill of Materials conforming to CERT-IN Annexure-A specifications, covering Algorithms, Keys, Protocols, and Certificates with all mandatory fields. Supports snapshot comparison for tracking changes over time.

Stimulus/Response Sequences:

Stimulus	Response
Scan and classification complete for a target	System auto-generates CBOM with all four Annexure-A categories and mandatory fields
User navigates to CBOM module	System displays summary metrics: Total Applications, Sites Surveyed, Active Certificates, Weak Cryptography, Certificate Issues
User views analytical charts	System renders Cipher Usage distribution, Top CAs, Key Length Distribution, Encryption Protocol breakdown
User clicks on a specific application in the CBOM table	System displays granular CBOM detail: Key Length, Cipher, CA, plus full Annexure-A breakdown
User selects "Compare Snapshots" and picks two dates	System generates a diff view highlighting added/removed/changed cryptographic assets between snapshots
User views certificate chain for an asset	System renders interactive tree view of the full cert chain with quantum-safety color coding per level

Functional Requirements: FR-10, FR-13, FR-14

SF-08: Cyber Rating System

Description: Computes a consolidated enterprise-level cybersecurity score based on the cryptographic posture of all scanned assets, categorizes assets into compliance tiers, and tracks score progression over time.

Stimulus/Response Sequences:

Stimulus	Response
User navigates to Cyber Rating module	System displays the enterprise score dial (out of 1000) with current rating
System recalculates score after new scan	System updates the score based on weighted evaluation of all asset classifications (Elite-PQC → Legacy → Critical)
User views classification table	System shows asset status mapped to numerical score ranges
User views Compliance Matrix	System displays Tier 1–4 definitions with Security Level, Compliance Criteria (TLS version, cipher strength), and Priority/Action
User views historical trend chart	System displays a time-series graph of the enterprise score over weeks/months, showing improvement or regression

Functional Requirements: FR-47, FR-48, FR-49, FR-50

SF-09: Enterprise Reporting & Export

Description: Comprehensive reporting system supporting both scheduled (recurring) and on-demand report generation, with configurable content, multiple delivery channels, and diverse export formats.

Stimulus/Response Sequences:

Stimulus	Response
User navigates to Reporting module	System displays Scheduled and On-Demand reporting options
User selects "On-Demand Report" and configures options	System generates report immediately with selected modules, format, and delivers to chosen channel

Stimulus	Response
Admin configures a Scheduled Report (weekly, email)	System saves schedule, generates report at configured time, and sends via email
User selects modules to include (e.g., CBOM + PQC Posture)	System includes only selected module data in the generated report
User selects PDF format with password protection	System generates an encrypted PDF with charts and tables included
User exports raw data as CSV	System generates downloadable CSV file of scan results
External system is registered for webhook notifications	System sends POST request to webhook URL on scan completion or critical findings

Functional Requirements: FR-15, FR-16, FR-17, FR-18, FR-19, FR-20, FR-21

3.4 Non-functional Requirements

3.4.1 Performance Requirements

- **Scan Execution Time:** The scanning engine must be highly optimized, capable of completing a full cryptographic scan of a single target endpoint in under 30 seconds.
- **UI Responsiveness:** The web dashboard and all related UI components must render and load in under 3 seconds to ensure a fluid user experience.
- **Concurrency:** The backend system must be capable of processing and supporting 50+ concurrent scan targets simultaneously without performance degradation.
- **Report Generation:** The system must compile and generate complex exportable reports (JSON, PDF, CSV) in under 5 seconds upon user request.

3.4.2 Software Quality Attributes

- **Reliability:** The central dashboard and API must maintain an uptime of 99.9% to ensure continuous visibility into the organization's cryptographic posture.
- **Usability:** The system must feature an intuitive user interface, requiring absolutely no specialized training for users to perform basic scans and interpret PQC readiness.
- **Maintainability:** The backend must be built using a highly modular codebase, allowing developers to easily add or update new NIST PQC algorithms as standards evolve.
- **Portability:** The application environment must be capable of running smoothly on both Linux and Windows for development, with Linux required for production.

- **Scalability:** The architecture must allow for horizontal scaling, enabling administrators to easily add more scan workers to the system as the target inventory grows.

3.4.3 Other Non-functional Requirements

- **Logging:** The system must enforce comprehensive logging, ensuring all scan events and system actions are recorded with a precise timestamp.
- **Compliance:** The core evaluation logic must strictly align with NIST PQC standards (FIPS 203, 204, 205) and adhere precisely to CERT-IN CBOM formatting guidelines.
- **Localization:** The primary language for the user interface, documentation, and all generated reports shall be English.

---

4. Technological Requirements

4.1 Technologies used in development of the web application

- **Core Programming Language:** Python 3.11+, selected for its robust ecosystem and extensive support for network protocol analysis and cryptographic operations.
- **Backend Web Framework:** FastAPI (async), utilized for building a high-performance, asynchronous REST API to serve the web dashboard, manage scan routing, and handle concurrent target evaluations efficiently. SQLAlchemy (async) is used as the ORM layer.
- **Scanning Engine & Analysis Libraries:** The backend uses a dual-engine scanning architecture: `sslyze` for classical TLS handshakes and cipher suite enumeration, and the `openquantumsafe/curl` Docker image (liboqs + oqs-provider) for PQC-enabled handshake detection. The Python `cryptography` library is used for X.509 certificate parsing and OID-level PQC classification.
- **PQC Classification Engine:** A custom rule engine (`pqc_classifier.py`) implementing NIST FIPS 203/204/205 algorithm tables. Applies a cert-chain OID walk as primary signal and a Weakest-Link downgrade rule for legacy protocol/cipher detection.
- **Frontend & Reporting Layer:** The web dashboard is built using HTML5, Bootstrap 5, Vanilla JS, and Chart.js. Jinja2 templating dynamically renders scan results and compliance badges (Not Quantum-Safe / Partially Quantum-Safe / PQC Ready / Fully Quantum Safe). Reports are generated in **JSON, XML, CSV, and PDF** formats; PDF reports support optional password encryption via `pypdf`.

4.2 I.D.E. (Integrated Development Environment)

- **Primary Development Environment:** VS Code (Visual Studio Code) and Google Antigravity AI coding assistant, chosen for their cutting-edge Python tooling, live debugging capabilities, integrated terminals for testing scanner scripts, and seamless Git integration for agile team collaboration.

4.3 Database Management Software

- **Development / Testing:** SQLite, utilized as a lightweight, serverless database for rapid local prototyping and testing of the cryptographic mappings and schema designs.
- **Current Production Deployment:** SQLite (persisted via AWS EC2 volume mount) — provides a pragmatic, zero-configuration relational store for the prototype deployment.
- **Target Production Environment:** PostgreSQL is planned for enterprise-scale deployment to provide a high-concurrency, robust relational database capable of storing extensive historical scan data, user audit trails, and complex CBOM inventories across the bank's public-facing infrastructure.

4.4 Deployment Environment

- **Platform:** AWS EC2 Virtual Server (https://rakshak.live) — containerized deployment via Docker with the Docker socket mounted to enable the OQS probe subprocess.
- **Domain & TLS:** Custom domain `rakshak.live` with HTTPS enforced. WebSocket connections use `wss://` over the same domain to avoid mixed-content browser restrictions.

---

5. Security Requirements

The following points shall be considered at a minimum while preparing the security requirements for the system or system application:

- **Compatibility of the proposed system with current IT set up:** The system is engineered to operate as a standalone scanning tool; it is completely passive and will have no structural or performance impact on existing live banking systems.
- **Tamper-Evident Audit Trails:** All scans and system events must be logged meticulously with user ID, timestamp, IP address, and event details. Audit logs will be cryptographically hashed upon creation to ensure tamper-evident immutability and securely stored in the database.
- **Control Access to Information:** Implementation of strict Role-Based Access Control (RBAC) is mandatory, ensuring only 'Admin' users can schedule scans and manage the application, while 'Checkers' are restricted to read-only access for viewing reports.
- **Recoverability of Application in case of Failure:** The scanning engine is designed to be fully stateless and can instantly restart upon failure, relying on secure, scheduled database backups for total data recoverability.
- **Compliance with any legal, statutory and contractual obligations:** The system's analysis engine strictly complies with NIST FIPS 203, 204, and 205 for Post-Quantum Cryptography, as well as the CERT-IN mandate for CBOM generation.
- **Security vulnerabilities involved when connecting with other systems:** The scanner

performs strictly passive, read-only scanning operations; it requires and utilizes absolutely no write access to target systems, eliminating the risk of payload injection or configuration alteration during audits.

- **Operating environment security:** All internal and external communications, including dashboard access and REST API calls, must be heavily encrypted over TLS 1.2 or higher.
- **Cost of providing security to the system over its life cycle:** The system leverages a robust open-source technology stack (e.g., Python, sslyze), resulting in minimal infrastructure and licensing costs to maintain its security posture.

Annexure-A (CERT-IN CBOM elements)

Table 9: Minimum Elements pertaining to Cryptographic Asset

Cryptographic Asset Type	Element	Description
Algorithms	Name	The name of the cryptographic algorithm or asset. For example, "AES-128-GCM" refers to the AES algorithm with a 128-bit key in Galois/Counter Mode (GCM).
	Asset Type	Specifies the type of cryptographic asset. For algorithms, the asset type is "algorithm".
	Primitive	Describes the cryptographic primitive. For "SHA512withRSA", the primitive is "signature" as it's used for digital signing.
	Mode	The operational mode used by the algorithm. For example, "gcm" refers to the Galois/Counter Mode used with AES encryption.
	Crypto Functions	The cryptographic functions supported by the asset. For example, the functions in the case of "AES-128-GCM" are key generation, encryption, decryption, and authentication tag generation.
	Classical security level	The classical security level represents the strength of the cryptographic asset in terms of its resistance to attacks using classical (non-quantum) methods. For AES-128, it's 128 bits.

Cryptographic Asset Type	Element	Description
	OID	The Object Identifier (OID) is a globally unique identifier used to refer to the algorithm. It helps in distinguishing algorithms across different systems. For example, "2.16.840.1.101.3.4.1.6" for AES-128-GCM, "1.2.840.113549.1.1.13" for SHA512withRSA
	List	Lists the cryptographic algorithms employed by the quantum device or system, allowing for an assessment of its security capabilities, especially in the context of post-quantum encryption standards.
Keys	Name	The name of the key, which is a unique identifier for the key used in cryptographic operations.
	Asset Type	Defines the type of cryptographic asset. For keys, the asset type is typically "key".
	id	A unique identifier for the key, such as a key ID or reference number.
	state	The state of the key, such as whether it is active, revoked, or expired.
	size	The size of the key, typically measured in bits. For example, a 128-bit key or a 2048-bit RSA key.
	Creation Date	The date when the key was created.
	Activation Date	The date when the key became operational or was first used.
Protocols	Name	The name of the cryptographic protocol, such as TLS, IPsec, or SSH
	Asset Type	Defines the type of cryptographic asset. In this case, it would be a "protocol"
	Version	The version of the protocol used, such as TLS 1.2 or TLS 1.3.
	Cipher Suites	The set of cryptographic algorithms and parameters supported by the protocol for tasks like encryption, key exchange, and integrity checking.

Cryptographic Asset Type	Element	Description
	OID	The Object Identifier (OID) associated with the protocol, identifying its unique specifications.
Certificates	Name	The name of the certificate, typically referring to its subject or the entity it represents (e.g., a website).
	Asset Type	Defines the type of cryptographic asset. For certificates, the asset type is "certificate".
	Subject Name	This refers to the Distinguished Name (DN) of the entity that the certificate represents. It typically contains information about the organization, domain name
	Issuer Name	The issuer is the Certificate Authority (CA) that issued and signed the certificate. This field contains the DN of the CA that verified and issued the certificate.
	Not Valid Before	This specifies the date and time from which the certificate is valid.
	Not Valid After	This specifies the expiration date and time of the certificate. The certificate becomes invalid after this timestamp.
	Signature Algorithm Reference	This refers to the cryptographic algorithm used to sign the certificate. It provides a reference to the algorithm and its OID (Object Identifier).
	Subject Public Key Reference	This points to the public key used by the subject (the entity being identified in the certificate). It provides a reference to the key's details, including the algorithm.
	Certificate Format	Specifies the format of the certificate. Common formats include X.509, which is the most widely used format for certificates.
	Certificate Extension	This refers to the file extension associated with the certificate. It is commonly .crt for certificates in the X.509 format.