🚀 Bullet-OS: Master Architectural Blueprint

Bullet-OS is an open-source, performance-engineered mobile operating system based on the **Linux Kernel** and the **Android Open Source Project (AOSP)**, developed exclusively for **Team BULLET IT Solutions**.

🏛️ System Architecture

📦 What Was Built and Committed

All source code has been structured and pushed to Team-of-BULLET-IT-Solutions/Bullet-OS:

Component	Path	Description
Repo Manifests		AOSP 14.0.0_r50 base tracking & Bullet-OS repo trees
Product & Versioning		OS version tags, `common.mk`, `version.mk`, `branding.mk`
SystemUI & Overlays		Cyber-Kinetic styling (`#00F0FF`, `#0B0E14`), 120Hz refresh, gesture nav
BulletLauncher		Sleek, zero-bloat launcher with responsive app grid and widgets
Bullet Lab		Performance governor switch, battery protect, and sensor shield
BulletTerminal		Developer shell providing root access to Linux commands (`toybox`, `top`, `ps`)
Core Daemon (`bulletd`)		High-performance C++ daemon with `/dev/socket/bulletd` IPC control
Boot Animation		High-tech animated splash screen generated for 1080x2400 displays
Device Trees		Generic System Image (GSI) tree for ARM64 smartphones
PC Emulator Tree		QEMU / PC Emulator target with hardware virtualization
Build Tools & Docker		Automated build scripts, Dockerfile, fastboot flasher, QEMU runner
Web Simulator		Interactive browser-based phone simulator with functional apps & shell
CI/CD Automation		Linting, bootanimation verification, and automatic GitHub Pages deployment

⚡ How to Test and Run Right Now

1. Interactive Web Simulator (Instant Preview)

Open in your browser:

- Pull down the top status bar to open the **Quick Settings** shade.
- Click **Terminal** and run commands like `neofetch`, `uname -a`, `top`, `ps`, and `bulletd`.
- Open **Bullet Lab** to test hardware performance boost and security toggles.

2. Flashing onto an Android Phone (Project Treble GSI)

```
bash
# Windows:
build\tools\flash-gsi.bat

# Linux / Mac:
bash build/tools/flash-gsi.sh
```

3. Compiling from Source with Docker

```
bash
docker build -t bullet-os-builder build/docker/
docker run -it -v $(pwd):/home/bullet/bullet_os bullet-os-builder
source build/envsetup.sh
lunch bullet_arm64-userdebug
make_bullet
```