HINO

200

SPECIFICATIONS

Made For The City

HINO 200 SERIES SPECIFICATIONS

Category Type	Description	Hino 200 310
Dimensions (mm)	SMC	FH2
	BBC - Rear Structure	1515
	OL - Overall Length	4590
	WB - Wheel Base Std	2545
	WB - Wheel Base (min.-max.)	2545 - 3700
	CA - Cab to Axle	1990
	OVH - Overall Vehicle Height	1985
	HF - Frame Height Front Axle	630
	HR - Frame Height Rear Axle	700
	MGC - Minimum Ground Clearance	155
	CW - Cab Width (excl. mirrors)	1695
	WARW - Width Across Rear Wheels	1915
	FW - Frame Width (Outside)	800
	FOH - Front Overhang	960
	ROH - Rear Overhang	1085
	FT - Front Track	1440
	RT - Rear Track	1500
	Max. homologated body width (min.-max.)	1920 - 2100
	Max. body length	3500
	Suggested body length	2950
Engine	Model	TOYOTA 5L
	4-stroke compression ignition	Yes
	Aspiration	Naturally aspirated
	Bore x Stroke (mm)	99.5 x 96
	Piston displacement (cc)	2986
	Compression ratio	22.2 : 1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 2
	Firing order	1 - 3 - 4 - 2
	Max Eng. Speed (rpm)	4900
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	66 @ 4000
	Torque (Nm@rpm)	192 @ 2400
	Type of cylinders	Dry liners
	Valve configuration	Single overhead camshaft
Mass Data (kg)	A - Front	1800
	A - Rear	2550
	Approx. body + payload allowance	1880
	D/T	5700
	GA - Front	1800
	GA - Rear	2550
	GCM	5700
	GVM	3500
	Tare - Front	1070
	Tare - Rear	550
	Tare - Total (incl. spare wheel)	1620
	V - rating	3500
Front Axle	Type	Independent Type

Category Type	Description	Hino 200 310
Rear Axle	Housing Type	Full-floating
	Inter-Axle Diff lock	N/A
	Ratio (:1)	3,727
	Type	Single Reduction Hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Disc
	Brake system: Rear	Drum
	Dual Circuit Hydraulic	Yes
	LSP Valve on Rear Axle	Yes
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	No
Parking Brake	Type	Mechanical
Steering	Type	Telescopic & tilt steering column, power steering
	Turning radius between kerbs (mm)	4900
	Turning radius between walls (mm)	5500
Transmission	Synchromesh or Automatic	Synchromesh
	Gear Ratio (1st - top gear)	5.147 - 0.830
	Gearshift operation	Mechanical
	Model	R452
	Number of forward gears	5
	Reverse ratio	5,036
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Chassis rear
	Tyre construction	Tubeless
	Tyre size	195/70R15C
	Load/speed rating	104/102 S
	Wheel size	15 x 5J
	Wheel type	Steel
Fuel Tank	Capacity (L)	80
Safety & Security	Airbags	No
	Seatbelt pre-tensioner	Driver and passenger
	Transponder key immobiliser	No
	Daytime running lights	No
	Side impact beams	Std
	Microdot vehicle identification	Std
	Reverse buzzer	Std
Comfort & Convenience	Air-conditioner	No
	Key activated central locking	No
	Electric windows	No
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service intervals (on-road application)	TBC
	Warranty	24 Months, Unlimited kms
	Powertrain	24 Months, Unlimited kms
	Cab corrosion	36 Months, Unlimited kms
	Chassis frame	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.21.83.1

* Please refer to Hino Care Disclaimer

HINO VALUE ADDED SERVICES

HOW HINO GOES THE DISTANCE FOR ITS CUSTOMERS

24-HOUR ROADSIDE ASSISTANCE

- Hino dealer service and parts assistance
- Hino's Dealer Network is more than 66 strong in Southern Africa
- 24-hour call centre 0800 878 257 (0800 TRUCKS)
- Technically-trained staff for breakdown assistance
- Roadside security – In the event that your vehicle breaks down in an unsafe area*
- Medical assistance

HINO-CONNECT

- HINO-CONNECT is a telematics fleet management system equipped as standard on all new Hino trucks in South Africa
- It provides vehicle tracking and recovery

SERVICE AND MAINTENANCE PLANS

- These can be tailor-made to your requirements
- Speak to your Hino dealer for more information

HINO CARE

EXTENDED WARRANTY PERIOD

- Hino Superior Extended Warranty: 24-36 Months
- Hino Basic Extended Warranty: 36 Months

TOWING ASSISTANCE

- Recovery towing services to the nearest Hino dealer for repairs or to a safe location**

SERVICE INTERVALS

- 200 Series – 10 000km

  Dependent on application and operating conditions

  Speak to your Hino dealer for more information

SERVICE AND MAINTENANCE PLANS

Your Hino 200's service and maintenance plans can be tailor-made to your requirements. For complete convenience, current plans can be up or downgraded to provide more or less cover, depending on each owner's requirements.

* Can be arranged with the call centre - costs to be paid by customer.
** At customer's cost.

Certain vehicle details and specifications contained in this leaflet may differ from the available models. Hino Motors Limited and Hino South Africa reserve the right to alter any details of specifications and equipment without notice. For the most current information on prices and specifications, as well as comprehensive information about products offered by Hino, contact your dealer or Hino South Africa. Call 0800 139 111 or visit www.hino.co.za