HINO

300

SPECIFICATIONS

Your Reliable Partner

HINO 300 SERIES SPECIFICATIONS

Hino 300 614 SWB MT

Hino 300 614 SWB AT

Hino 300 614 LWB MT

Hino 300 714 SWB MT

Hino 300 714 SWB AT

Hino 300 714 LWB MT

Hino 300 714 LWB CC AT

Hino 300 816 SWB MT

Hino 300 816 SWB AT

Hino 300 816 LWB CC AT

Hino 300 916 LWB MT

Hino 300 916 LWB AT

Hino 300 916 LWB CC AT

Keep on Truckin'

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 614 SWB MT
Dimensions (mm)	Short Model Code	EU3
	Katashiki	XZU600R-WKMMKN3
	BBC - Rear Structure	1549
	OL - Overall Length	4715
	WB - Wheel Base Std	2525
	WB - Wheel Base (min. - max.)	2525 - 3800
	CA - Cab to Axle	1920
	OVH - Overall Vehicle Height	2110
	HF - Frame Height Front Axle	635
	HR - Frame Height Rear Axle	705
	MGC - Minimum Ground Clearance	195
	CW - Cab Width (excl. mirrors)	1695
	WARW - Width Across Rear Wheels	1870
	FW - Frame Width (Outside)	300
	FOH - Front Overhang	990
	ROH - Rear Overhang	1230
	FT - Front Track	1400
	RT - Rear Track	1435
	Max. homologated body width (min. - max.)	1870 - 2100
	Max. body length	3400
	Suggested body length	3200
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbocharged & Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	2300
	A - Rear	4360
	Approx. body + payload allowance	3365
	D/T	7300
	GA - Front	2600
	GA - Rear	4400
	GCM	7300
	GVM	5500
	Tare - Front	1380
	Tare - Rear	755
	Tare - Total (incl. spare wheel)	2135
	V - rating	5500
Performance (sea level)	Gradeability tanθ (%)	44,9
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 614 SWB MT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	4,333
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Disc
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	22.6 : 1
	Steering column	Tilt & Telescopic
	Turning radius between kerbs (mm)	5500
	Turning radius between walls (mm)	6100
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Synchromesh
	Gear ratio (1st - top gear)	5.342 - 0.712
	Gearshift operation	Mechanical
	Make	Hino
	Model	RE50
	Number of forward gears	5
	Reverse ratio	4,970
Wheels & Tyres	Attachment	5-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	205/75R16C
	Load/speed rating	113/111
	Wheel size	16 x 5.50
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	80
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 614 SWB AT
Dimensions (mm)	Short Model Code	EV3
	Katashiki	XZU600R-WKTMKN3
	BBC - Rear Structure	1549
	OL - Overall Length	4715
	WB - Wheel Base Std	2525
	WB - Wheel Base (min. - max.)	2525 - 3800
	CA - Cab to Axle	1920
	OVH - Overall Vehicle Height	2110
	HF - Frame Height Front Axle	630
	HR - Frame Height Rear Axle	700
	MGC - Minimum Ground Clearance	195
	CW - Cab Width (excl. mirrors)	1695
	WARW - Width Across Rear Wheels	1870
	FW - Frame Width (Outside)	700
	FOH - Front Overhang	990
	ROH - Rear Overhang	1230
	FT - Front Track	1400
	RT - Rear Track	1435
	Max. homologated body width (min. - max.)	1870 - 2100
	Max. body length	3400
	Suggested body length	3200
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbocharged & Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	2300
	A - Rear	4360
	Approx. body + payload allowance	3325
	D/T	7300
	GA - Front	2600
	GA - Rear	4400
	GCM	7300
	GVM	5500
	Tare - Front	1400
	Tare - Rear	775
	Tare - Total (incl. spare wheel)	2175
	V - rating	5500
Performance (sea level)	Gradeability tanθ (%)	60
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 614 SWB AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,125
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Disc
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	22.6 : 1
	Steering column	Tilt & Telescopic
	Turning radius between kerbs (mm)	5500
	Turning radius between walls (mm)	6100
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	5-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	205/75R16C
	Load/speed rating	113/111
	Wheel size	16 x 5.50
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	80
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 614 LWB MT
Dimensions (mm)	Short Model Code	EW3
	Katashiki	XZU650R-WKMMKN3
	BBC - Rear Structure	1576
	OL - Overall Length	5965
	WB - Wheel Base Std	3375
	WB - Wheel Base (min. - max.)	2525 - 3800
	CA - Cab to Axle	2770
	OVH - Overall Vehicle Height	2105
	HF - Frame Height Front Axle	630
	HR - Frame Height Rear Axle	700
	MGC - Minimum Ground Clearance	195
	CW - Cab Width (excl. mirrors)	1695
	WARW - Width Across Rear Wheels	1870
	FW - Frame Width (Outside)	700
	FOH - Front Overhang	985
	ROH - Rear Overhang	1605
	FT - Front Track	1400
	RT - Rear Track	1435
	Max. homologated body width (min. - max.)	1870 - 2100
	Max. body length	4800
	Suggested body length	4200
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbocharged & Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	2300
	A - Rear	4360
	Approx. body + payload allowance	3295
	D/T	7300
	GA - Front	2600
	GA - Rear	4400
	GCM	7300
	GVM	5500
	Tare - Front	1430
	Tare - Rear	755
	Tare - Total (incl. spare wheel)	2205
	V - rating	5500
Performance (sea level)	Gradeability tanθ (%)	44,9
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 614 LWB MT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	4,333
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Disc
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	22.6 : 1
	Steering column	Tilt & Telescopic
	Turning radius between kerbs (mm)	7100
	Turning radius between walls (mm)	7700
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Synchromesh
	Gear ratio (1st - top gear)	5.342 - 0.712
	Gearshift operation	Mechanical
	Make	Hino
	Model	RE50
	Number of forward gears	5
	Reverse ratio	4,970
Wheels & Tyres	Attachment	5-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	205/75R16C
	Load/speed rating	113/111
	Wheel size	16 x 5.50
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 714 SWB MT
Dimensions (mm)	Short Model Code	EX3
	Katashiki	XZU710R-WKFQKN3
	BBC - Rear Structure	1658
	OL - Overall Length	6120
	WB - Wheel Base Std	3430
	WB - Wheel Base (min. - max.)	3430 - 4600
	CA - Cab to Axle	2860
	OVH - Overall Vehicle Height	2220
	HF - Frame Height Front Axle	710
	HR - Frame Height Rear Axle	780
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1575
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	4800
	Suggested body length	4200
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5100
	Approx. body + payload allowance	4030
	D/T	8300
	GA - Front	3100
	GA - Rear	5100
	GCM	8300
	GVM	6500
	Tare - Front	1590
	Tare - Rear	880
	Tare - Total (incl. spare wheel)	2470
	V - rating	6500
Performance (sea level)	Gradeability tanθ (%)	47,6
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 714 SWB MT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	4,625
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	6200
	Turning radius between walls (mm)	6900
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Synchromesh
	Gear ratio (1st - top gear)	6.370 - 0.703
	Gearshift operation	Mechanical
	Make	Hino
	Model	RE61
	Number of forward gears	6
	Reverse ratio	5,926
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 714 SWB AT
Dimensions (mm)	Short Model Code	EY3
	Katashiki	XZU710R-WKTQKN3
	BBC - Rear Structure	1658
	OL - Overall Length	6120
	WB - Wheel Base Std	3430
	WB - Wheel Base (min. - max.)	3430 - 4600
	CA - Cab to Axle	2860
	OVH - Overall Vehicle Height	2220
	HF - Frame Height Front Axle	710
	HR - Frame Height Rear Axle	780
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1575
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	4800
	Suggested body length	4200
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5100
	Approx. body + payload allowance	3990
	D/T	8300
	GA - Front	3100
	GA - Rear	5100
	GCM	8300
	GVM	6500
	Tare - Front	1620
	Tare - Rear	890
	Tare - Total (incl. spare wheel)	2510
	V - rating	6500
Performance (sea level)	Gradeability tanθ (%)	60
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 714 SWB AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,125
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	6200
	Turning radius between walls (mm)	6900
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 714 LWB MT
Dimensions (mm)	Short Model Code	EZ3
	Katashiki	XZU720R-WKFQKN3
	BBC - Rear Structure	1670
	OL - Overall Length	6740
	WB - Wheel Base Std	3870
	WB - Wheel Base (min. - max.)	3430 - 4600
	CA - Cab to Axle	3300
	OVH - Overall Vehicle Height	2220
	HF - Frame Height Front Axle	710
	HR - Frame Height Rear Axle	780
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1755
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	5600
	Suggested body length	5200
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5100
	Approx. body + payload allowance	4010
	D/T	8300
	GA - Front	3100
	GA - Rear	5100
	GCM	8300
	GVM	6500
	Tare - Front	1610
	Tare - Rear	880
	Tare - Total (incl. spare wheel)	2490
	V - rating	6500
Performance (sea level)	Gradeability tanθ (%)	47,6
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 714 LWB MT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	4,625
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	6900
	Turning radius between walls (mm)	7600
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Synchromesh
	Gear ratio (1st - top gear)	6.370 - 0.703
	Gearshift operation	Mechanical
	Make	Hino
	Model	RE61
	Number of forward gears	6
	Reverse ratio	5,926
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 714 LWB CC AT
Dimensions (mm)	Short Model Code	FC3
	Katashiki	XZU720R-ZKTQKN3
	BBC - Rear Structure	1670
	OL - Overall Length	6740
	WB - Wheel Base Std	3870
	WB - Wheel Base (min. - max.)	3430 - 4600
	CA - Cab to Axle	2195
	OVH - Overall Vehicle Height	2235
	HF - Frame Height Front Axle	700
	HR - Frame Height Rear Axle	780
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1755
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	4500
	Suggested body length	4000
Engine	Model	N04C - WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line cylinder
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	100 @ 2500
	Torque (Nm@rpm)	392 @ 1600
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5100
	Approx. body + payload allowance	3760
	D/T	8300
	GA - Front	3100
	GA - Rear	5100
	GCM	8300
	GVM	6500
	Tare - Front	1760
	Tare - Rear	980
	Tare - Total (incl. spare wheel)	2740
	V - rating	6500
Performance (sea level)	Gradeability tanθ (%)	60
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 714 LWB CC AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,125
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	6900
	Turning radius between walls (mm)	7600
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 816 SWB MT
Dimensions (mm)	Short Model Code	FA3
	Katashiki	XZU720R-WKFRLN3
	BBC - Rear Structure	1658
	OL - Overall Length	6740
	WB - Wheel Base Std	3870
	WB - Wheel Base (min. - max.)	3430 - 5200
	CA - Cab to Axle	3300
	OVH - Overall Vehicle Height	2220
	HF - Frame Height Front Axle	705
	HR - Frame Height Rear Axle	795
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1755
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	5600
	Suggested body length	5200
Engine	Model	N04C - WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	110 @ 2800
	Torque (Nm@rpm)	420 @ 1400
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5500
	Approx. body + payload allowance	4980
	D/T	9300
	GA - Front	3100
	GA - Rear	5500
	GCM	9300
	GVM	7500
	Tare - Front	1620
	Tare - Rear	900
	Tare - Total (incl. spare wheel)	2520
	V - rating	7500
Performance (sea level)	Gradeability tanθ (%)	46,4
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 816 SWB MT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	4,875
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	6900
	Turning radius between walls (mm)	7600
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Synchromesh
	Gear ratio (1st - top gear)	6.370 - 0.703
	Gearshift operation	Mechanical
	Make	Hino
	Model	RE61
	Number of forward gears	6
	Reverse ratio	5,926
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 816 SWB AT
Dimensions (mm)	Short Model Code	FB3
	Katashiki	XZU720R-WKTRLN3
	BBC - Rear Structure	1658
	OL - Overall Length	6740
	WB - Wheel Base Std	3870
	WB - Wheel Base (min. - max.)	3430 - 5200
	CA - Cab to Axle	3300
	OVH - Overall Vehicle Height	2215
	HF - Frame Height Front Axle	705
	HR - Frame Height Rear Axle	795
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1755
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	5600
	Suggested body length	5200
Engine	Model	N04C - WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	110 @ 2800
	Torque (Nm@rpm)	420 @ 1400
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5500
	Approx. body + payload allowance	4950
	D/T	9300
	GA - Front	3100
	GA - Rear	5500
	GCM	9300
	GVM	7500
	Tare - Front	1645
	Tare - Rear	905
	Tare - Total (incl. spare wheel)	2550
	V - rating	7500
Performance (sea level)	Gradeability tanθ (%)	60,0
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 816 SWB AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,571
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	6900
	Turning radius between walls (mm)	7600
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 816 LWB CC AT
Dimensions (mm)	Short Model Code	FF3
	Katashiki	XZU730R-ZKTRLN3
	BBC - Rear Structure	1658
	OL - Overall Length	7250
	WB - Wheel Base Std	4200
	WB - Wheel Base (min. - max.)	4200 - 5200
	CA - Cab to Axle	2525
	OVH - Overall Vehicle Height	2235
	HF - Frame Height Front Axle	700
	HR - Frame Height Rear Axle	795
	MGC - Minimum Ground Clearance	210
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	1985
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1970
	FT - Front Track	1655
	RT - Rear Track	1520
	Max. homologated body width (min. - max.)	1995 - 2500
	Max. body length	5000
	Suggested body length	4200
Engine	Model	N04C - WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	110 @ 2800
	Torque (Nm@rpm)	420 @ 1400
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	5500
	Approx. body + payload allowance	4715
	D/T	9300
	GA - Front	3100
	GA - Rear	5500
	GCM	9300
	GVM	7500
	Tare - Front	1790
	Tare - Rear	995
	Tare - Total (incl. spare wheel)	2785
	V - rating	7500
Performance (sea level)	Gradeability tanθ (%)	60
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 816 LWB CC AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,571
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	7400
	Turning radius between walls (mm)	8100
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 916 LWB MT
Dimensions (mm)	Short Model Code	FD3
	Katashiki	XZU730R-WKFTLN3
	BBC - Rear Structure	1658
	OL - Overall Length	7250
	WB - Wheel Base Std	4200
	WB - Wheel Base (min. - max.)	3430 - 5200
	CA - Cab to Axle	3630
	OVH - Overall Vehicle Height	2235
	HF - Frame Height Front Axle	725
	HR - Frame Height Rear Axle	805
	MGC - Minimum Ground Clearance	195
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	2055
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1970
	FT - Front Track	1655
	RT - Rear Track	1590
	Max. homologated body width (min. - max.)	2055 - 2500
	Max. body length	6000
	Suggested body length	5500
Engine	Model	N04C - WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	110 @ 2800
	Torque (Nm@rpm)	420 @ 1400
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	6200
	Approx. body + payload allowance	5915
	D/T	10300
	GA - Front	3100
	GA - Rear	6200
	GCM	10300
	GVM	8500
	Tare - Front	1645
	Tare - Rear	940
	Tare - Total (incl. spare wheel)	2585
	V - rating	8500
Performance (sea level)	Gradeability tanθ (%)	42,5
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 916 LWB MT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,142
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	7400
	Turning radius between walls (mm)	8100
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Synchromesh
	Gear ratio (1st - top gear)	6.370 - 0.703
	Gearshift operation	Mechanical
	Make	Hino
	Model	RE61
	Number of forward gears	6
	Reverse ratio	5,926
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	150
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 916 LWB AT
Dimensions (mm)	Short Model Code	FE3
	Katashiki	XZU730R-WKTTLN3
	BBC - Rear Structure	1658
	OL - Overall Length	7250
	WB - Wheel Base Std	4200
	WB - Wheel Base (min. - max.)	3430 - 5200
	CA - Cab to Axle	3630
	OVH - Overall Vehicle Height	2230
	HF - Frame Height Front Axle	725
	HR - Frame Height Rear Axle	805
	MGC - Minimum Ground Clearance	195
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	2055
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1970
	FT - Front Track	1655
	RT - Rear Track	1590
	Max. homologated body width (min. - max.)	2055 - 2500
	Max. body length	6000
	Suggested body length	5500
Engine	Model	N04C - WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	110 @ 2800
	Torque (Nm@rpm)	420 @ 1400
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	6200
	Approx. body + payload allowance	5885
	D/T	10300
	GA - Front	3100
	GA - Rear	6200
	GCM	10300
	GVM	8500
	Tare - Front	1670
	Tare - Rear	945
	Tare - Total (incl. spare wheel)	2615
	V - rating	8500
Performance (sea level)	Gradeability tanθ (%)	59,8
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 916 LWB AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,857
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	7400
	Turning radius between walls (mm)	8100
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	150
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO 300 SERIES SPECIFICATIONS

Category Type	Model Description	Hino 300 916 LWB CC AT
Dimensions (mm)	Short Model Code	FG3
	Katashiki	XZU730R-ZKTTLN3
	BBC - Rear Structure	1658
	OL - Overall Length	7250
	WB - Wheel Base Std	4200
	WB - Wheel Base (min. - max.)	4200 - 5200
	CA - Cab to Axle	2525
	OVH - Overall Vehicle Height	2250
	HF - Frame Height Front Axle	720
	HR - Frame Height Rear Axle	800
	MGC - Minimum Ground Clearance	195
	CW - Cab Width (excl. mirrors)	1995
	WARW - Width Across Rear Wheels	2055
	FW - Frame Width (Outside)	750
	FOH - Front Overhang	1115
	ROH - Rear Overhang	1970
	FT - Front Track	1655
	RT - Rear Track	1590
	Max. homologated body width (min. - max.)	2055 - 2500
	Max. body length	5050
	Suggested body length	4400
Engine	Model	N04C - WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo Intercooled
	Bore x Stroke (mm)	104 X 118
	Piston displacement (cc)	4009
	Compression ratio	18:1
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	Euro 3
	Firing order	1 - 3 - 4 - 2
	Max eng. speed (rpm)	3100
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kw@rpm)	110 @ 2800
	Torque (Nm@rpm)	420 @ 1400
	Type of cylinders	Dry liners
	Valve configuration	Overhead
Mass Data (kg)	A - Front	3100
	A - Rear	6200
	Approx. body + payload allowance	5665
	D/T	10300
	GA - Front	3100
	GA - Rear	6200
	GCM	10300
	GVM	8500
	Tare - Front	1805
	Tare - Rear	1030
	Tare - Total (incl. spare wheel)	2835
	V - rating	8500
Performance (sea level)	Gradeability tanθ (%)	59,8
	Geared speed-km/h (speed limited)	100

Category Type	Model Description	Hino 300 916 LWB CC AT
Front Axle	Type	Reversed Elliot, "I" Beam
Rear Axle	Housing type	Full-floating
	Inter-axle diff lock	N/A
	Make	Hino
	Ratio (:1)	5,857
	Type	Single reduction hypoid
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit hydraulic	Yes
	LSP valve on rear axle	Not fitted
	Type	Vacuum Servo
	HINO ES (Easy & Smooth) Start System	Yes
Parking Brake	Type	Mechanical
Steering	Ratio	20.9 : 1
	Steering column	Tilt and Telescopic
	Turning radius between kerbs (mm)	7400
	Turning radius between walls (mm)	8100
	Type	Recirculating ball
Transmission	Synchromesh or Automatic	Automatic
	Gear ratio (1st - top gear)	3.742 - 0.634
	Gearshift operation	Automatic
	Make	Hino
	Model	A860E
	Number of forward gears	6
	Reverse ratio	3,539
Wheels & Tyres	Attachment	6-stud disc wheel
	Number of wheels (incl. spare wheel)	7
	Spare wheel carrier location	Rear chassis
	Tyre construction	Tubeless
	Tyre size	215/75R17.5
	Load/speed rating	126/124
	Wheel size	17.5 x 6.00
	Wheel type	Single piece steel
Fuel Tank	Capacity (L)	100
Safety & Security	Airbags	Driver and passenger
	Seatbelt	Driver and passenger
	Transponder key immobiliser	Std
	Daytime running lights	Std
	Side impact beams	Std
	Microdot vehicle identification	Std
Comfort & Convenience	Air-conditioner	Std
	Key-activated central locking	Std
	Electric windows	Driver and passenger
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval*	10 000 km
	Entire vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months, Unlimited kms
	Cab corrosion warranty	36 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms
Advalorem Tariff Headings		8704.22.90(0)

*Period may vary based on application.

HINO VALUE ADDED SERVICES

HOW HINO GOES THE DISTANCE FOR ITS CUSTOMERS

24-HOUR ROADSIDE ASSISTANCE

- Hino dealer service and parts assistance
- Hino's Dealer Network is more than 66 strong in Southern Africa
- 24-hour call centre 0800 878 257 (0800 TRUCKS)
- Technically-trained staff for breakdown assistance
- Roadside security – In the event that your vehicle breaks down in an unsafe area*
- Medical assistance

HINO-CONNECT

- HINO-CONNECT is a telematics fleet management system equipped as standard on all new Hino trucks in South Africa
- It provides vehicle tracking and recovery
- Fuel consumption, oil and water temperatures, as well as fault reporting.

SERVICE AND MAINTENANCE PLANS

- These can be tailor-made to your requirements
- Speak to your Hino dealer for more information

HINO CARE

EXTENDED WARRANTY PERIOD

- Hino Superior Extended Warranty: 24-36 Months
- Hino Basic Extended Warranty: 36 Months

TOWING ASSISTANCE

- Recovery towing services to the nearest Hino dealer for repairs or to a safe location**

SERVICE INTERVALS

- 300 Series – 10 000km

  Dependent on application and operating conditions

  Speak to your Hino dealer for more information

SERVICE AND MAINTENANCE PLANS

Your Hino 300's service and maintenance plans can be tailor-made to your requirements. For complete convenience, current plans can be up or downgraded to provide more or less cover, depending on each owner's requirements.

* Can be arranged with the call centre - costs to be paid by customer.
** At customer's cost.

Certain vehicle details and specifications contained in this leaflet may differ from the available models. Hino Motors Limited and Hino South Africa reserve the right to alter any details of specifications and equipment without notice. For the most current information on prices and specifications, as well as comprehensive information about products offered by Hino, contact your dealer or Hino South Africa. Call 0800 139 111 or visit www.hino.co.za