HINO

500

SPECIFICATIONS

Driven To Perfection

HINO 500 SERIES SPECIFICATIONS

Hino 500 1018 FC

Hino 500 1326 Tipper

Hino 500 1326 FC

Hino 500 1322 4X4 FC SWA / DWA

Hino 500 1627 FC LWB

Hino 500 1627 FC LWB AT

Hino 500 1627 FC SLWB / Crew Cab

Hino 500 1627 FC SLWB AT / Crew Cab

Hino 500 1627 Tipper

Hino 500 2829 FC LWB

Hino 500 2829 FC LWB AT

Hino 500 2829 FC SLWB

Hino 500 2829 FC SLWB AT

Hino 500 2836 FC

Hino 500 2836 Mixer

Hino 500 2836 Tipper

HINO 500 SERIES SPECIFICATIONS

Hino 500 Below 16 000kg GVM

Category Type	Model Description	Hino 500 1018 FC
Dimensions (mm)	Short Model Code	5EP
	Katashiki	FC9JLKA-NRQ
	CA - Cab to Axle	4365
	CH - Cab Height	2490
	CW - Cab Width (excl. mirrors)	2190
	FH - Frame Height Rear Axle	885
	FOH - Front Overhang	1145
	FT - Front Track	1800
	FW - Frame Width (Front)	820
	FW - Frame Width (Rear)	N/A
	Max. homologated body width	2400
	Maximum body length	7200
	Suggested body length	6500
	MGC - Minimum Ground Clearance	225
	OL - Overall Length	8540
	OVH - Overall Vehicle Height	2475
	ROH - Rear Overhang	2260
	RT - Rear Track	1660
	WB - Wheel Base	4990
Engine	Make and model	Hino JO5E - TC
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112 x 130
	Capacity (cc)	5123
	Compression ratio (:1)	18
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-3-4-2
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2900
	Number of main bearings	5
	Number of cylinders	4
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	129 @ 2500
	Torque Nm	500 @ 1500
	Type of cylinders (liners; wet or dry)	Dry liners
	Valve configuration	Overhead cam
Mass Data (kg)	A - Front	3600
	A - Rear	6520
	Approx. body + payload allowance	7380
	D/T	15000
	GA - Front	3600
	GA - Rear	7000
	GCM	15000
	GVM	10400
	Tare - Front	1920
	Tare - Rear	1070
	Tare - Total (incl. spare wheel)	2990
	V - rating	10400
Performance (sea level)	First gear grade (at max. gvm)	34,7
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Banjo full floating
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 13
	Ratio (:1)	4,100
	Ring gear size (inches)	13”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1018 FC
Front Axle	Make	Hino LF366
	Type	Reverse Elliot “I” Section Beam
	Shock absorbers	Yes
Parking Brake	Type	Rear of Transmission
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	No
	Type	Air over hydraulics
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	7840
	Turning radius between walls (mm)	8500
	Type	Power assisted; re-circulating ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	8.190 - 1.0
	Gearshift operation	Cable
	Make	HINO
	Model	LX 06 S
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	7,619
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	6-stud JIS fixing
	Load/Speed index - dual wheel	126L
	Load/Speed index - single wheel	128L
	Number of wheels including spare	7
	Spare wheel carrier location	Rear of chassis
	Tyre construction	Radial tubed
	Tyre size - Front	8.25R16
	Tyre size - Rear	8.25R16
	Wheel size - Front	6.00 X 16
	Wheel size - Rear	6.00 X 16
	Wheel type	Multi-piece steel
Fuel Tank	Capacity (cc)	100
Safety	Airbag	N/A
	Seatbelt pre-tensioner	N/A
	Immobiliser	N/A
	Side impact beams	
	Microdot vehicle identification	Yes
Comfort	Power windows	Yes
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	N/A
	Retractable cup holders	N/A
	Radio/Speakers - CD	Yes
	Air suspension seat	N/A
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	N/A
	Belly plate under radiator	N/A
	Insect protection screen in front of radiator	N/A

HINO 500 SERIES SPECIFICATIONS

Hino 500 Below 16 000kg GVM

Category Type	Model Description	Hino 500 1326 Tipper
Dimensions (mm)	Short Model Code	5AU
	Katashiki	FG8JGKD-QEQ
	CA - Cab to Axle	2955
	CH - Cab Height	2635
	CW - Cab Width (excl. mirrors)	2355
	FH - Frame Height Rear Axle	1035
	FOH - Front Overhang	1235
	FT - Front Track	1920
	FW - Frame Width (Front)	870
	FW - Frame Width (Rear)	N/A
	Max. homologated body width	2600
	Maximum body length	5100
	Suggested body length	3900
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	6445
	OVH - Overall Vehicle Height	2635
	ROH - Rear Overhang	1285
	RT - Rear Track	1825
	WB - Wheel Base	3780
Engine	Make and model	Hino JO8E - UD
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130
	Capacity (cc)	7684
	Compression ratio (:1)	18
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2900
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	184 @ 2500
	Torque Nm	739 @ 1500
	Type of cylinders (liners; wet or dry)	Dry liners
	Valve configuration	Overhead cam
Mass Data (kg)	A - Front	5500
	A - Rear	9000
	Approx. body + payload allowance	9300
	D/T	17000
	GA - Front	5500
	GA - Rear	10000
	GCM	17000
	GVM	13500
	Tare - Front	2565
	Tare - Rear	1635
	Tare - Total (incl. spare wheel)	4200
	V - rating	13500
Performance (sea level)	First gear grade (at max. gvm)	49
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Banjo full floating
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	6,142
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1326 Tipper
Front Axle	Make	Hino LF571
	Type	Reverse Elliot “I” Section Beam
	Shock absorbers	Yes
Parking Brake	Type	Spring brake on rear wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	No
	Type	Full Air Wedge Type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	7170
	Turning radius between walls (mm)	7940
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.746 - 0.823
	Gearshift operation	Cable/Air assist
	Make	HINO
	Model	LJ 06 S
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6,453
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	10-stud ISO fixing
	Load/Speed index - dual wheel	144L
	Load/Speed index - single wheel	148L
	Number of wheels including spare	7
	Spare wheel carrier location	Strapped on chassis
	Tyre construction	Radial tubeless
	Tyre size - Front	11 R 22.5
	Tyre size - Rear	11 R 22.5
	Wheel size - Front	8.25 x 22.5
	Wheel size - Rear	8.25 x 22.5
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	200
Safety	Airbag	N/A
	Seatbelt pre-tensioner	N/A
	Immobiliser	N/A
	Side impact beams	
	Microdot vehicle identification	Yes
Comfort	Power windows	Yes
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	N/A
	Retractable cup holders	N/A
	Radio/Speakers - CD	Yes
	Air suspension seat	N/A
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	N/A
	Belly plate under radiator	N/A
	Insect protection screen in front of radiator	N/A

HINO 500 SERIES SPECIFICATIONS

Hino 500 Below 16 000kg GVM

Category Type	Model Description	Hino 500 1326 FC
Dimensions (mm)	Short Model Code	5BD
	Katashiki	FG8JPKA-QEQ
	CA - Cab to Axle	4705
	CH - Cab Height	2635
	CW - Cab Width (excl. mirrors)	2355
	FH - Frame Height Rear Axle	1035
	FOH - Front Overhang	1235
	FT - Front Track	1920
	FW - Frame Width (Front)	870
	FW - Frame Width (Rear)	N/A
	Max. homologated body width	2600
	Maximum body length	7900
	Suggested body length	6500
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	9460
	OVH - Overall Vehicle Height	2635
	ROH - Rear Overhang	2550
	RT - Rear Track	1825
	WB - Wheel Base	5530
Engine	Make and model	Hino JO8E - UD
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130
	Capacity (cc)	7684
	Compression ratio (:1)	18
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2900
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	184 @ 2500
	Torque Nm	739 @ 1500
	Type of cylinders (liners; wet or dry)	Dry liners
	Valve configuration	Overhead cam
Mass Data (kg)	A - Front	5500
	A - Rear	9000
	Approx. body + payload allowance	9125
	D/T	17000
	GA - Front	5500
	GA - Rear	10000
	GCM	17000
	GVM	13500
	Tare - Front	2670
	Tare - Rear	1705
	Tare - Total (incl. spare wheel)	4375
	V - rating	13500
Performance (sea level)	First gear grade (at max. gvm)	39,3
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Banjo full floating
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	5,428
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1326 FC
Front Axle	Make	Hino LF571
	Type	Reverse Elliot “I” Section Beam
	Shock absorbers	Yes
Parking Brake	Type	Spring brake on rear wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	No
	Type	Full Air Wedge Type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10120
	Turning radius between walls (mm)	10770
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.746 - 0.823
	Gearshift operation	Cable/Air assist
	Make	HINO
	Model	LJ 06 S
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6,453
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	10-stud ISO fixing
	Load/Speed index - dual wheel	144L
	Load/Speed index - single wheel	148L
	Number of wheels including spare	7
	Spare wheel carrier location	Rear of chassis
	Tyre construction	Radial tubeless
	Tyre size - Front	11 R 22.5
	Tyre size - Rear	11 R 22.5
	Wheel size - Front	8.25x22.5
	Wheel size - Rear	8.25x22.5
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	200
Safety	Airbag	N/A
	Seatbelt pre-tensioner	N/A
	Immobiliser	N/A
	Side impact beams	
	Microdot vehicle identification	Yes
Comfort	Power windows	Yes
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	N/A
	Retractable cup holders	N/A
	Radio/Speakers - CD	Yes
	Air suspension seat	N/A
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	N/A
	Belly plate under radiator	N/A
	Insect protection screen in front of radiator	N/A

HINO 500 SERIES SPECIFICATIONS

Hino 500 Below 16 000kg GVM

Category Type	Model Description	Hino 500 1322 4X4 FC SWA / DWA
Dimensions (mm)	Short Model Code	5DE / 5DF
	Katashiki	GT8JKKA-HEQ / GT8JKKA-1EQ
	CA - Cab to Axle	3825
	CH - Cab Height	2865/2800
	CW - Cab Width (excl. mirrors)	2355
	FH - Frame Height Rear Axle	1275/1210
	FOH - Front Overhang	1235
	FT - Front Track	1970/1925
	FW - Frame Width (Front)	870
	FW - Frame Width (Rear)	N/A
	Max. homologated body width	2600
	Maximum body length	6500
	Suggested body length	5800
	MGC - Minimum Ground Clearance	300 (rear axle)/225
	OL - Overall Length	7960
	OVH - Overall Vehicle Height	2800
	ROH - Rear Overhang	1930
	RT - Rear Track	1970/1820
	WB - Wheel Base	4650
Engine	Make and model	Hino JO8C - UL
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130
	Capacity (cc)	7684
	Compression ratio (:1)	18
	Configuration	In-line
	Engine oil cooler	Yes
	Euro Emission Status	2
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Zexel
	Max eng. speed (rpm)	2900
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	152 @ 2500
	Torque Nm	603 @ 1500
	Type of cylinders (liners; wet or dry)	Dry liners
	Valve configuration	Overhead cam
Mass Data (kg)	A - Front	4500
	A - Rear	7800/9000
	Approx. body + payload allowance	7340/8145
	D/T	21000
	GA - Front	4500
	GA - Rear	9200
	GCM	21000
	GVM	12300/13000
	Tare - Front	3065/2985
	Tare - Rear	1895/1870
	Tare - Total (incl. spare wheel)	4960/4855
	V - rating	12300/13000
Performance (sea level)	First gear grade (at max. gvm)	30,2
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Banjo full floating
	Inter-axle diff lock	Non-spin diff
	Make	Hino
	Model	SH 16
	Ratio (:1)	5,428
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1322 4X4 FC SWA / DWA
Front Axle	Make	Hino SS15
	Type	Reverse Elliot “I” Section Beam
	Shock absorbers	Yes
Parking Brake	Type	Spring brake on rear
Service Brakes	ABS	No
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	Yes
	Type	Air over hydraulics
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10500/10350
	Turning radius between walls (mm)	11200/10880
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.515 - 1.0
	Gearshift operation	Cable
	Make	HINO
	Model	LX 06 S
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6,06
	Transfer box ratio	2.224 Low / 1.000 High
Wheels & Tyres	Attachment	10-stud (SAE type)/8-stud JIS fixing
	Load/Speed index - dual wheel	142L
	Load/Speed index - single wheel	146L
	Number of wheels including spare	5/7
	Spare wheel carrier location	Rear of chassis
	Tyre construction	Radial tubed
	Tyre size - Front	10 R 20
	Tyre size - Rear	12 R 20 / 10 R 20
	Wheel size - Front	7.00 X 20
	Wheel size - Rear	8.50x20 / 7.00 X 20
	Wheel type	Multi-piece steel
Fuel Tank	Capacity (cc)	200
Safety	Airbag	N/A
	Seatbelt pre-tensioner	N/A
	Immobiliser	N/A
	Side impact beams	
	Microdot vehicle identification	Yes
Comfort	Power windows	Yes
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	N/A
	Retractable cup holders	N/A
	Radio/Speakers - CD	Yes
	Air suspension seat	N/A
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	N/A
	Belly plate under radiator	N/A
	Insect protection screen in front of radiator	N/A

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 1627 FC LWB
Dimensions (mm)	Short Model Code	EJ5
	Katashiki	FG8JP1A-PGQ
	CA - Cab to Axle	4700
	CH - Cab Height	2775
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1080
	FOH - Front Overhang	1280
	FT - Front Track	2050
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	7918
	Suggested body length	7175
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	9450
	OVH - Overall Vehicle Height	2775
	ROH - Rear Overhang	2640
	RT - Rear Track	1835
	WB - Wheel Base	5530
Engine	Make and model	J08E-WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	195 kW {265 PS} at 2500 r/min (JIS GROSS) 191 kW {260 PS} at 2500 r/min (ISO NET)
	Torque Nm	804 Nm {82 kgfm} at 1500 r/min (JIS GROSS) 794 Nm {81 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7380
	A - Rear	9000
	Approx. body + payload allowance	10817
	D/T	32000
	GA - Front	7500
	GA - Rear	11500
	GCM	32 000
	GVM	16 000
	Tare - Front	3121
	Tare - Rear	2062
	Tare - Total (incl. spare wheel)	5183
	V - rating	16000
Performance (sea level)	First gear grade (at max. gvm)	35.3
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	5.857
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1627 FC LWB
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	9400
	Turning radius between walls (mm)	10200
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.515 - 0.702
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	MX06
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6.991
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148L
	Load/Speed index - single wheel	152
	Number of wheels including spare	7
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	12R22.5
	Tyre size - Rear	12R22.5
	Wheel size - Front	22.5 x 8.25
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 1627 FC LWB AT
Dimensions (mm)	Short Model Code	EK5
	Katashiki	FG8JP1A-RGQ
	CA - Cab to Axle	4700
	CH - Cab Height	2770
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1080
	FOH - Front Overhang	1280
	FT - Front Track	2050
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	7918
	Suggested body length	7175
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	9450
	OVH - Overall Vehicle Height	2770
	ROH - Rear Overhang	2640
	RT - Rear Track	1835
	WB - Wheel Base	5530
Engine	Make and model	J08E-WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	195 kW {265 PS} at 2500 r/min (JIS GROSS) 191 kW {260 PS} at 2500 r/min (ISO NET)
	Torque Nm	804 Nm {82 kgfm} at 1500 r/min (JIS GROSS) 794 Nm {81 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7380
	A - Rear	9000
	Approx. body + payload allowance	10771
	D/T	32000
	GA - Front	7500
	GA - Rear	11500
	GCM	32000
	GVM	16000
	Tare - Front	3155
	Tare - Rear	2074
	Tare - Total (incl. spare wheel)	5229
	V - rating	16000
Performance (sea level)	First gear grade (at max. gvm)	52.4
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	6.428
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1627 FC LWB AT
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	9400
	Turning radius between walls (mm)	10200
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	N/A
	Gear ratio (1:)	3.487 - 0.653
	Gearshift operation	N/A
	Make	Allison
	Model	3000
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	5.027
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148L
	Load/Speed index - single wheel	152
	Number of wheels including spare	7
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	12R22.5
	Tyre size - Rear	12R22.5
	Wheel size - Front	22.5 x 8.25
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 1627 FC SLWB / Crew Cab
Dimensions (mm)	Short Model Code	EL5 / CM5
	Katashiki	FG8JT1A-PGQ / FG8JT1A-PUQ
	CA - Cab to Axle	5600/4850
	CH - Cab Height	2770/2865
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1020
	FOH - Front Overhang	1280
	FT - Front Track	2050
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	9358
	Suggested body length	8625
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	10900/10835
	OVH - Overall Vehicle Height	2770/2865
	ROH - Rear Overhang	3190
	RT - Rear Track	1835
	WB - Wheel Base	6430
Engine	Make and model	J08E-WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	195 kW {265 PS} at 2500 r/min (JIS GROSS) 191 kW {260 PS} at 2500 r/min (ISO NET)
	Torque Nm	804 Nm {82 kgfm} at 1500 r/min (JIS GROSS) 794 Nm {81 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7380
	A - Rear	9000
	Approx. body + payload allowance	10717
	D/T	32000
	GA - Front	7500
	GA - Rear	11500
	GCM	32000
	GVM	16000
	Tare - Front	3166/3535
	Tare - Rear	2117/2535
	Tare - Total (incl. spare wheel)	5283/5830
	V - rating	16000
Performance (sea level)	First gear grade (at max. gvm)	35.3
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	5.857
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1627 FC SLWB / Crew Cab
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10800
	Turning radius between walls (mm)	11600
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.515 - 0.702
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	MX06
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6.991
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148L
	Load/Speed index - single wheel	152
	Number of wheels including spare	7
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	12R22.5
	Tyre size - Rear	12R22.5
	Wheel size - Front	22.5 x 8.25
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3/7
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 1627 FC SLWB AT / Crew Cab
Dimensions (mm)	Short Model Code	EM5 / CC5
	Katashiki	FG8JT1A-RGQ / FG8JT1A-RUQ
	CA - Cab to Axle	5600/4850
	CH - Cab Height	2770/2860
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1075
	FOH - Front Overhang	1280
	FT - Front Track	2050/2055
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	9358
	Suggested body length	8625
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	10900/10835
	OVH - Overall Vehicle Height	2770/2860
	ROH - Rear Overhang	3190
	RT - Rear Track	1835
	WB - Wheel Base	6430
Engine	Make and model	J08E-WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	195 kW {265 PS} at 2500 r/min (JIS GROSS) 191 kW {260 PS} at 2500 r/min (ISO NET)
	Torque Nm	804 Nm {82 kgfm} at 1500 r/min (JIS GROSS) 794 Nm {81 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7380
	A - Rear	9000
	Approx. body + payload allowance	10671
	D/T	32000
	GA - Front	7500
	GA - Rear	11500
	GCM	32000
	GVM	16000
	Tare - Front	3205/3695
	Tare - Rear	2124/2315
	Tare - Total (incl. spare wheel)	5329/6010
	V - rating	16000
Performance (sea level)	First gear grade (at max. gvm)	52.4
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	6.428
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1627 FC SLWB AT / Crew Cab
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10800
	Turning radius between walls (mm)	11600
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	N/A
	Gear ratio (1:)	3.487 - 0.653
	Gearshift operation	N/A
	Make	Allison
	Model	3000
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	5.027
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148L
	Load/Speed index - single wheel	152
	Number of wheels including spare	7
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	12R22.5
	Tyre size - Rear	12R22.5
	Wheel size - Front	22.5 x 8.25
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3/7
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 1627 Tipper
Dimensions (mm)	Short Model Code	DH5
	Katashiki	FG8JF1D-PGQ
	CA - Cab to Axle	2900
	CH - Cab Height	2775
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1080
	FOH - Front Overhang	1280
	FT - Front Track	2050
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	4225
	Suggested body length	4225
	MGC - Minimum Ground Clearance	230
	OL - Overall Length	6500
	OVH - Overall Vehicle Height	2775
	ROH - Rear Overhang	1490
	RT - Rear Track	2460
	WB - Wheel Base	3730
Engine	Make and model	J08E-WH
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	195 kW {265 PS} at 2500 r/min (JIS GROSS) 191 kW {260 PS} at 2500 r/min (ISO NET)
	Torque Nm	804 Nm {82 kgfm} at 1500 r/min (JIS GROSS) 794 Nm {81 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7380
	A - Rear	9000
	Approx. body + payload allowance	11117
	D/T	32000
	GA - Front	7500
	GA - Rear	11500
	GCM	32000
	GVM	16000
	Tare - Front	2856
	Tare - Rear	2027
	Tare - Total (incl. spare wheel)	4883
	V - rating	16000
Performance (sea level)	First gear grade (at max. gvm)	35.3
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 16
	Ratio (:1)	5.857
	Ring gear size (inches)	16”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 1627 Tipper
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	6600
	Turning radius between walls (mm)	7400
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.515 - 0.702
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	MX06
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6.991
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148L
	Load/Speed index - single wheel	152
	Number of wheels including spare	7
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	12R22.5
	Tyre size - Rear	12R22.5
	Wheel size - Front	22.5 x 8.25
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	200
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2829 FC LWB
Dimensions (mm)	Short Model Code	DN5
	Katashiki	FL8JT1A-UGQ
	CA - Cab to Axle	4775
	CH - Cab Height	2770
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1060
	FOH - Front Overhang	1280
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	8713
	Suggested body length	7725
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	10000
	OVH - Overall Vehicle Height	2770
	ROH - Rear Overhang	2440
	RT - Rear Track	1855
	WB - Wheel Base	4930 + 1350
Engine	Make and model	J08E-WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	210 kW {285 PS} at 2500 r/min (JIS GROSS) 206 kW {280 PS} at 2500 r/min (ISO NET)
	Torque Nm	892 Nm {91 kgfm} at 1500 r/min (JIS GROSS) 883 Nm {90 kgfm} at 2750 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	18692
	D/T	32000
	GA - Front	7500
	GA - Rear	21800
	GCM	32 000
	GVM	27 500
	Tare - Front	3046
	Tare - Rear	3762
	Tare - Total (incl. spare wheel)	6808
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	26.7
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 17
	Ratio (:1)	6.833
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2829 FC LWB
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10300
	Turning radius between walls (mm)	11000
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	6.515 - 0.702
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	MX06
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	6.991
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2829 FC LWB AT
Dimensions (mm)	Short Model Code	DP5
	Katashiki	FL8JT1A-WGQ
	CA - Cab to Axle	4775
	CH - Cab Height	2770
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1060
	FOH - Front Overhang	1280
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	8713
	Suggested body length	7725
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	10000
	OVH - Overall Vehicle Height	2770
	ROH - Rear Overhang	2440
	RT - Rear Track	1855
	WB - Wheel Base	4930 + 1350
Engine	Make and model	J08E-WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:2
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	211 kW {285 PS} at 2500 r/min (JIS GROSS) 206 kW {280 PS} at 2500 r/min (ISO NET)
	Torque Nm	893 Nm {91 kgfm} at 1500 r/min (JIS GROSS) 883 Nm {90 kgfm} at 2750 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	18641
	D/T	38000
	GA - Front	7500
	GA - Rear	21800
	GCM	38 000
	GVM	27 500
	Tare - Front	3085
	Tare - Rear	3774
	Tare - Total (incl. spare wheel)	6859
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	44.7
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 17
	Ratio (:1)	6.428
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2829 FC LWB AT
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10300
	Turning radius between walls (mm)	11000
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	N/A
	Gear ratio (1:)	4.593 - 0.651
	Gearshift operation	N/A
	Make	Allison
	Model	3500
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	4.999
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2829 FC SLWB
Dimensions (mm)	Short Model Code	DR5
	Katashiki	FL8JW1G-XHQ
	CA - Cab to Axle	5685
	CH - Cab Height	2765
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1040
	FOH - Front Overhang	1280
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	10164
	Suggested body length	9075
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	11350
	OVH - Overall Vehicle Height	2765
	ROH - Rear Overhang	2885
	RT - Rear Track	1840
	WB - Wheel Base	5845 + 1340
Engine	Make and model	J08E-WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:3
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	212 kW {285 PS} at 2500 r/min (JIS GROSS) 206 kW {280 PS} at 2500 r/min (ISO NET)
	Torque Nm	894 Nm {91 kgfm} at 1500 r/min (JIS GROSS) 883 Nm {90 kgfm} at 2750 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	18814
	D/T	38000
	GA - Front	7500
	GA - Rear	21800
	GCM	38 000
	GVM	27 500
	Tare - Front	3333
	Tare - Rear	3353
	Tare - Total (incl. spare wheel)	6686
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	37.8
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 17
	Ratio (:1)	4.300
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2829 FC SLWB
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	11800
	Turning radius between walls (mm)	12600
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	2 ~ 6 Only
	Gear ratio (1:)	14.056 - 1.000
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	M009DD
	Number of forward gears	9
	PTO & control	Not standard
	Reverse Ratio (:1)	13.636
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Air
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2829 FC SLWB AT
Dimensions (mm)	Short Model Code	DQ5
	Katashiki	FL8JW1G-WHQ
	CA - Cab to Axle	5685
	CH - Cab Height	2770
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1040
	FOH - Front Overhang	1280
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	10164
	Suggested body length	9075
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	11350
	OVH - Overall Vehicle Height	2770
	ROH - Rear Overhang	2885
	RT - Rear Track	1840
	WB - Wheel Base	5845 + 1340
Engine	Make and model	J08E-WG
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	112x130mm
	Capacity (cc)	7.684 L
	Compression ratio (:1)	18.0:3
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2750
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	212 kW {285 PS} at 2500 r/min (JIS GROSS) 206 kW {280 PS} at 2500 r/min (ISO NET)
	Torque Nm	894 Nm {91 kgfm} at 1500 r/min (JIS GROSS) 883 Nm {90 kgfm} at 2750 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHC
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	18898
	D/T	38000
	GA - Front	7500
	GA - Rear	21800
	GCM	38 000
	GVM	27 500
	Tare - Front	3265
	Tare - Rear	3337
	Tare - Total (incl. spare wheel)	6602
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	44.7
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	N/A
	Make	Hino
	Model	SH 17
	Ratio (:1)	6.428
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2829 FC SLWB AT
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	11800
	Turning radius between walls (mm)	12600
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	N/A
	Gear ratio (1:)	4.593 - 0.651
	Gearshift operation	N/A
	Make	Allison
	Model	3500
	Number of forward gears	6
	PTO & control	Not standard
	Reverse Ratio (:1)	4.999
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	N/A
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Air
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2836 FC
Dimensions (mm)	Short Model Code	DU5
	Katashiki	FM2PT1A-SHQ
	CA - Cab to Axle	4925
	CH - Cab Height	2910
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1060
	FOH - Front Overhang	1380
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	8893
	Suggested body length	7975
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	10250
	OVH - Overall Vehicle Height	2910
	ROH - Rear Overhang	1340
	RT - Rear Track	1855
	WB - Wheel Base	4980 + 1350
Engine	Make and model	P11C-VT
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	122x150 mm
	Capacity (cc)	10.520 L
	Compression ratio (:1)	16.0:1
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2300
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	265 kW {360 PS} at 2100 r/min (JIS GROSS) 257 kW {250 PS} at 2100 r/min (ISO NET)
	Torque Nm	1314 Nm {134 kgfm} at 1500 r/min (JIS GROSS) 1275 Nm {130 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHV
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	17581
	D/T	45000
	GA - Front	7500
	GA - Rear	21800
	GCM	45 000
	GVM	27 500
	Tare - Front	3781
	Tare - Rear	4138
	Tare - Total (incl. spare wheel)	7919
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	51.1
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	Diif lock with Cross Lock
	Make	Hino
	Model	THD 17
	Ratio (:1)	5.250
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2836 FC
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	10000
	Turning radius between walls (mm)	10900
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	1 ~ 9 Only
	Gear ratio (1:)	10.178 - 0.724
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	M009OD
	Number of forward gears	9
	PTO & control	Not standard
	Reverse Ratio (:1)	9,874
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	390
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2836 Mixer
Dimensions (mm)	Short Model Code	DT5
	Katashiki	FM2PN1M-SHQ
	CA - Cab to Axle	3875
	CH - Cab Height	2915
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1060
	FOH - Front Overhang	1380
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	5521
	Suggested body length	5521
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	8000
	OVH - Overall Vehicle Height	2915
	ROH - Rear Overhang	1340
	RT - Rear Track	1855
	WB - Wheel Base	3930 + 1.350
Engine	Make and model	P11C-VT
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	122x150 mm
	Capacity (cc)	10.520 L
	Compression ratio (:1)	16.0:2
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2300
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	265 kW {360 PS} at 2100 r/min (JIS GROSS) 257 kW {250 PS} at 2100 r/min (ISO NET)
	Torque Nm	1314 Nm {134 kgfm} at 1500 r/min (JIS GROSS) 1275 Nm {130 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHV
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	17796
	D/T	45000
	GA - Front	7500
	GA - Rear	21800
	GCM	45 000
	GVM	27 500
	Tare - Front	3691
	Tare - Rear	4013
	Tare - Total (incl. spare wheel)	7704
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	51.1
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	Diif lock with Cross Lock
	Make	Hino
	Model	THD 17
	Ratio (:1)	5.250
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2836 Mixer
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	8400
	Turning radius between walls (mm)	9300
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	1 ~ 9 Only
	Gear ratio (1:)	10.178 - 0.724
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	M009OD
	Number of forward gears	9
	PTO & control	Engine driven
	Reverse Ratio (:1)	9,874
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	Rear
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	200
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO 500 SERIES SPECIFICATIONS

Hino 500 Wide Cab

Category Type	Model Description	Hino 500 2836 Tipper
Dimensions (mm)	Short Model Code	DS5
	Katashiki	FM2PL1D-SHQ
	CA - Cab to Axle	3425
	CH - Cab Height	2915
	CW - Cab Width (excl. mirrors)	2490
	FH - Frame Height Rear Axle	1060
	FOH - Front Overhang	1380
	FT - Front Track	2030
	FW - Frame Width (Front)	950
	FW - Frame Width (Rear)	840
	Max. homologated body width	2600
	Maximum body length	5225
	Suggested body length	5225
	MGC - Minimum Ground Clearance	220
	OL - Overall Length	7500
	OVH - Overall Vehicle Height	2915
	ROH - Rear Overhang	1290
	RT - Rear Track	1855
	WB - Wheel Base	3.480 + 1.350
Engine	Make and model	P11C-VT
	4-stroke compression ignition	Yes
	Aspiration	Turbo-intercooled
	Bore X Stroke	122x150 mm
	Capacity (cc)	10.520 L
	Compression ratio (:1)	16.0:3
	Configuration	Six Cylinder In-Line
	Engine oil cooler	Yes
	Euro Emission Status	3
	Firing order	1-4-2-6-3-5
	Governor: All speed/RLD	Yes
	Governor: Electric	Yes
	Injector pump	Common rail
	Max eng. speed (rpm)	2300
	Number of main bearings	7
	Number of cylinders	6
	Number of valves per cylinders	4
	Power (EEC/ISO NET) Kw	265 kW {360 PS} at 2100 r/min (JIS GROSS) 257 kW {250 PS} at 2100 r/min (ISO NET)
	Torque Nm	1314 Nm {134 kgfm} at 1500 r/min (JIS GROSS) 1275 Nm {130 kgfm} at 1500 r/min (ISO NET)
	Type of cylinders (liners; wet or dry)	Dry
	Valve configuration	OHV
Mass Data (kg)	A - Front	7500
	A - Rear	9000
	Approx. body + payload allowance	17881
	D/T	45000
	GA - Front	7500
	GA - Rear	21800
	GCM	45 000
	GVM	27 500
	Tare - Front	3531
	Tare - Rear	4088
	Tare - Total (incl. spare wheel)	7619
	V - rating	25500
Performance (sea level)	First gear grade (at max. gvm)	51.1
	Geared speed-km/h (S/L regulation)	80
Rear Axle	Housing type	Full floating - hypoid gearing
	Inter-axle diff lock	Diif lock with Cross Lock
	Make	Hino
	Model	THD 17
	Ratio (:1)	5.250
	Ring gear size (inches)	17”
	Type	Single reduction - hypoid

Category Type	Model Description	Hino 500 2836 Tipper
Front Axle	Make	MF78IR
	Type	Reverse “I” Bean Elliot
	Shock absorbers	Yes
Parking Brake	Type	Spring Break on Rear Wheels
Service Brakes	ABS	Yes
	Brake system: Front	Drum
	Brake system: Rear	Drum
	Dual circuit	Yes
	LSP valve on rear axle	N/A
	Type	Full air S-Cam type
Steering	Steering column	Tilt & Telescopic
	Turning radius on tyre (mm)	7.700
	Turning radius between walls (mm)	8.600
	Type	Power Assisted; Re-Circulating Ball
Transmission	Full synchromesh	1 ~ 9 Only
	Gear ratio (1:)	10.178 - 0.724
	Gearshift operation	Cable/Air assist
	Make	Hino
	Model	M009OD
	Number of forward gears	9
	PTO & control	Not standard
	Reverse Ratio (:1)	9,874
	Transfer box ratio	N/A
Wheels & Tyres	Attachment	ISO - 10 studs
	Load/Speed index - dual wheel	148M
	Load/Speed index - single wheel	154
	Number of wheels including spare	11
	Spare wheel carrier location	
	Tyre construction	Radial tubeless
	Tyre size - Front	315/80R22.5
	Tyre size - Rear	295/80R22.5
	Wheel size - Front	22.5 x 9.00
	Wheel size - Rear	22.5 x 8.25
	Wheel type	Single piece steel
Fuel Tank	Capacity (cc)	320
Safety	Airbag	Driver only
	Seatbelt pre-tensioner	Driver only
	Immobiliser	Yes
	Side impact beams	Yes
	Microdot vehicle identification	Yes
Comfort	Power windows	Driver & Passenger
	Central locking	Yes
	Air conditioner	Yes
	Easy start	Yes
	Cruise control	Yes
	Retractable cup holders	Yes
	Radio/Speakers - CD	Yes
	Air suspension seat	Driver only
Aftersales	Service interval	20 000 km
	Entire vehicle warranty	24 Months
	Powertrain warranty	24 Months
	Cab corrosion	36 Months
	Chassis frame warranty	36 Months
Seating Capacity	Number of seats	3
Suspension	Front	Leaf
	Rear	Steel
QDR	Dust prevent	Yes
	Belly plate under radiator	Yes
	Insect protection screen in front of radiator	Yes

HINO VALUE ADDED SERVICES

HOW HINO GOES THE DISTANCE FOR ITS CUSTOMERS

24-HOUR ROADSIDE ASSISTANCE

- Hino dealer service and parts assistance
- Hino's Dealer Network is more than 66 strong in Southern Africa
- 24-hour call centre 0800 878 257 (0800 TRUCKS)
- Technically-trained staff for breakdown assistance
- Roadside security – In the event that your vehicle breaks down in an unsafe area*
- Medical assistance

HINO-CONNECT

- HINO-CONNECT is a telematics fleet management system equipped as standard on all new Hino trucks in South Africa
- It provides vehicle tracking and recovery
- Fuel consumption, oil and water temperatures, as well as fault reporting

SERVICE AND MAINTENANCE PLANS

- These can be tailor-made to your requirements
- Speak to your Hino dealer for more information

HINO CARE

EXTENDED WARRANTY PERIOD

- Hino Superior Extended Warranty: 24-36 Months
- Hino Basic Extended Warranty: 36 Months

TOWING ASSISTANCE

- Recovery towing services to the nearest Hino dealer for repairs or to a safe location**

SERVICE INTERVALS

- 500 Series – 20 000km

  Dependent on application and operating conditions

  Speak to your Hino dealer for more information

SERVICE AND MAINTENANCE PLANS

Your Hino 500's service and maintenance plans can be tailor-made to your requirements. For complete convenience, current plans can be up or downgraded to provide more or less cover, depending on each owner's requirements.

* Can be arranged with the call centre - costs to be paid by customer.
** At customer's cost.

Certain vehicle details and specifications contained in this leaflet may differ from the available models. Hino Motors Limited and Hino South Africa reserve the right to alter any details of specifications and equipment without notice. For the most current information on prices and specifications, as well as comprehensive information about products offered by Hino, contact your dealer or Hino South Africa. Call 0800 139 111 or visit www.hino.co.za