HINO

700

SPECIFICATIONS

We're All Business

HINO 700 SERIES 2845 TT SPECIFICATIONS

Category type	Model Description	2845 TT
Dimensions (mm)	BBC - Rear Structure	2035
	OL -Overall Length	6845
	WB - Wheel Base Std	3150 + 1350
	WB - Wheel Base (Min - Max)	No chassis modification allowed*
	CA - Cab to Axle Center	3190
	OVH - Overall Vehicle Height	3025
	HF - Frame Height Front Axle	1015
	HR - Frame Height Rear Axle	1090
	MGC - Minimum Ground Clearance	255
	CW - Cab Width (Excl. mirrors)	2490
	WARW - Width Across Rear Wheels	2485
	FW - Frame Width (Outside)	840
	FOH - Front Overhang	1400
	ROH - Rear Overhang	945
	FT - Front Track	2030
	RT - Rear Track	1825
	Max. Homologated Body Width	2600
	Max. Body Length	N/A
Engine	Make	HINO
	Model	HINO E13C-BF
	4 Stroke compression ignition	Yes
	Aspiration	Turbocharged and Intercooled
	Bore x Stroke (mm)	137 x 146
	Piston displacement (cc)	12913
	Compression ratio (~:1)	17
	Configuration	In-line 6 Cylinder
	Engine oil cooler	Yes
	Euro emission status	Euro 2
	Firing order	1-4-2-6-3-5
	Max engine speed (rpm)	2300
	No of main bearings	7
	Number of cylinders	6
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kW@rpm)	331 @ 1500 - 1800
	Torque (Nm@rpm)	2157 @ 1050 - 1400
	Type of cylinders	Dry Liners
	Valve configuration	Overhead Camshaft
	Hino Stop & Start System	Yes
Clutch	Model	DSF-430
	Facing material	Mold Type (non-asbestos)
	Control	ZF ConAct Pneumatic System
	Clutch automatic gap adjuster	Yes
Transmission	Make	ZF
	Model	ZF16 TX2440TO
	Synchromesh or Automatic	AMT
	No of forward gears	16
	Gearshift operation	Mechanical Auto
	Gear Ratio (1st - Top Gear)	14.682 - 0.821
	Reverse ratio (~:1)	14.138 / 11.602
Mass Data (kg)	A - Front	7500
	A - Rear	21800
	Approx. body + payload allowance	15895
	D/T	65000
	GA - Front	7500
	GA - Rear	21800
	GCM	65000
	GVM	28300
	Tare - Front	5010
	Tare - Rear	4595
	Tare - Total (Incl. spare wheel)	9605
	V - rating	25500
Performance (sea level)	Gradeability tanθ (%)	32
	Geared Speed-km/h (Speed limited)	80

Category type	Model Description	2845 TT
Front Axle	Model	MF78IR
	Type	I-beam, Reverse Elliot
Rear Axle	Model	THD17
	Type	Full-floating
		Single Reduction
		Single Speed by Hypoid Gearings
	Ratio (~:1)	3,9
Service Brake	Type	Full Air, Wedge Type
	Service brake line	Dual Circuit
	Front wheel brake	Drum
	Rear wheel brake	Drum
	HINO ES (Easy & Smooth) Start System	Yes
Auxiliary Brake	HINO Engine Retarder	Yes
	Transmission Intarder (ZF Intarder IT3)	Yes
Parking Brake	Type	Air Operated Spring Brake
Steering	Type	Telescopic & Tilt Steering Column, Power Steering
	Rack & pinion gear ratio	Variable Gear Ratio
	Turning radius between kerbs (mm)	7200
	Turning radius between walls (mm)	8100
Wheel & Tyre	Tyre size	315/80R22.5
	Wheel size	22.5 x 9
	Load/speed rating	3750-3350/130
	No of wheels (Including spare wheel)	11
	Spare wheel carrier location	Chassis
	Tyre construction	Radial Tubeless
	Attachment	ISO 10-Stud
	Wheel type	Single Steel Piece
Fuel Tank (/)	Capacity	390
	Capacity (Sub tank)	450
Safety & Security	Advanced Safety Features	EBS (Electronic Control Brake System)
		ABS (Anti-Lock Brake System)
		ASR (Anti-Slip Regulation)
		VSC (Vehicle Stability Control)
		PCS (Pre-Collision System)
		ACC (Adaptive Cruise Control)
		LDWS (Lane Departure Warning System)
		Driver Monitor
		Staggering Warning
	Airbags	SRS Airbag System
	Seatbelt	Driver (Pre-tensioner), Passenger (Emergency Locking Retractor)
	Daytime running light	No
	Transponder key immobiliser	Std
	Side impact beams	Std
Comfort & Convenience	Air-conditioner	Yes
	Key activated central locking	Std
	Electric windows	Yes
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval	40 000 km[1,2]
	Vehicle warranty	36 Months, Unlimited kms
	Powertrain warranty	36 Mo nths[2], Unlimited kms
	Cab corrosion warranty	48 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms

1 Dependant on application & operating conditions
2 On-road application
3 Off-road application
** All Chasis modification must be approved by Hino SA*
Please be advised that specifications are subject to change.

HINO 700 SERIES 2841 TIP SPECIFICATIONS

Category type	Model Description	2841 TIP
Dimensions (mm)	BBC - Rear Structure	2035
	OL -Overall Length	7685
	WB - Wheel Base Std	3600 + 1350
	WB - Wheel Base (Min - Max)	No chassis modification allowed*
	CA - Cab to Axle Center	3640
	OVH - Overall Vehicle Height	3025
	HF - Frame Height Front Axle	1015
	HR - Frame Height Rear Axle	1085
	MGC - Minimum Ground Clearance	255
	CW - Cab Width (Excl. mirrors)	2490
	WARW - Width Across Rear Wheels	2540
	FW - Frame Width (Outside)	840
	FOH - Front Overhang	1400
	ROH - Rear Overhang	1335
	FT - Front Track	2030
	RT - Rear Track	1880
	Max. Homologated Body Width	2600
	Max. Body Length	7800
Engine	Make	HINO
	Model	HINO E13C-BG
	4 Stroke compression ignition	Yes
	Aspiration	Turbocharged and Intercooled
	Bore x Stroke (mm)	137 x 146
	Piston displacement (cc)	12913
	Compression ratio (~:1)	17
	Configuration	In-line 6 Cylinder
	Engine oil cooler	Yes
	Euro emission status	Euro 2
	Firing order	1-4-2-6-3-5
	Max engine speed (rpm)	2300
	No of main bearings	7
	Number of cylinders	6
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kW@rpm)	302 @ 1500 - 1800
	Torque (Nm@rpm)	1961 @ 1000 - 1400
	Type of cylinders	Dry Liners
	Valve configuration	Overhead Camshaft
	Hino Stop & Start System	Yes
Clutch	Model	DSF-430
	Facing material	Mold Type (non-asbestos)
	Control	ZF ConAct Pneumatic System
	Clutch automatic gap adjuster	Yes
Transmission	Make	ZF
	Model	ZF16 TX2440TO
	Synchromesh or Automatic	AMT
	No of forward gears	16
	Gearshift operation	Mechanical Auto
	Gear Ratio (1st - Top Gear)	14.682 - 0.821
	Reverse ratio (~:1)	14.138 / 11.602
Mass Data (kg)	A - Front	7500
	A - Rear	21800
	Approx. body + payload allowance	16860
	D/T	65000
	GA - Front	7500
	GA - Rear	21800
	GCM	65000
	GVM	28300
	Tare - Front	4805
	Tare - Rear	3835
	Tare - Total (Incl. spare wheel)	8640
	V - rating	25500
Performance (sea level)	Gradeability tanθ (%)	32
	Geared Speed-km/h (Speed limited)	80

Category type	Model Description	2841 TIP
Front Axle	Model	MF78IR
	Type	I-beam, Reverse Elliot
Rear Axle	Model	THD17
	Type	Full-floating
		Single Reduction
		Single Speed by Hypoid Gearings
	Ratio (~:1)	3,9
Service Brake	Type	Full Air, Wedge Type
	Service brake line	Dual Circuit
	Front wheel brake	Drum
	Rear wheel brake	Drum
	HINO ES (Easy & Smooth) Start System	Yes
Auxiliary Brake	HINO Engine Retarder	Yes
	Transmission Intarder (ZF Intarder IT3)	No
Parking Brake	Type	Air Operated Spring Brake
Steering	Type	Telescopic & Tilt Steering Column, Power Steering
	Rack & pinion gear ratio	Variable Gear Ratio
	Turning radius between kerbs (mm)	7200
	Turning radius between walls (mm)	8100
Wheel & Tyre	Tyre size	315/80R22.5
	Wheel size	22.5 x 9
	Load/speed rating	3750-3350/130
	No of wheels (Including spare wheel)	11
	Spare wheel carrier location	Chassis
	Tyre construction	Radial Tubeless
	Attachment	ISO 10-Stud
	Wheel type	Single Steel Piece
Fuel Tank (/)	Capacity	390
	Capacity (Sub tank)	-
Safety & Security	Advanced Safety Features	EBS (Electronic Control Brake System)
		ABS (Anti-Lock Brake System)
		ASR (Anti-Slip Regulation)
		VSC (Vehicle Stability Control)
		PCS (Pre-Collision System)
		ACC (Adaptive Cruise Control)
		LDWS (Lane Departure Warning System)
		Driver Monitor
		Staggering Warning
	Airbags	SRS Airbag System
	Seatbelt	Driver (pre-tensioner), Passenger (emergency locking retractor)
	Daytime running light	No
	Transponder key immobiliser	Std
	Side impact beams	Std
Comfort & Convenience	Air-conditioner	Yes
	Key activated central locking	Std
	Electric windows	Yes
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval	15 000 km[1,2] I 250 hours[1,2]
	Vehicle warranty	24 Months, Unlimited kms
	Powertrain warranty	24 Months[3], Unlimited kms
	Cab corrosion warranty	48 Months, Unlimited kms
	Chassis frame warranty	24 Months, Unlimited kms

1 Dependant on application & operating conditions
2 On-road application
3 Off-road application
** All Chasis modification must be approved by Hino SA*
Please be advised that specifications are subject to change.

HINO 700 SERIES 2841 FC SPECIFICATIONS

Category type	Model Description	2841 FC
Dimensions (mm)	BBC - Rear Structure	2035
	OL -Overall Length	10835
	WB - Wheel Base Std	5400 + 1350
	WB - Wheel Base (Min - Max)	No chassis modification allowed*
	CA - Cab to Axle Center	5440
	OVH - Overall Vehicle Height	3025
	HF - Frame Height Front Axle	1015
	HR - Frame Height Rear Axle	1085
	MGC - Minimum Ground Clearance	255
	CW - Cab Width (Excl. mirrors)	2490
	WARW - Width Across Rear Wheels	2540
	FW - Frame Width (Outside)	840
	FOH - Front Overhang	1400
	ROH - Rear Overhang	2685
	FT - Front Track	2030
	RT - Rear Track	1880
	Max. Homologated Body Width	2600
	Max. Body Length	11400
Engine	Make	HINO
	Model	HINO E13C-BG
	4 Stroke compression ignition	Yes
	Aspiration	Turbocharged and Intercooled
	Bore x Stroke (mm)	137 x 146
	Piston displacement (cc)	12913
	Compression ratio (~:1)	17
	Configuration	In-line 6 Cylinder
	Engine oil cooler	Yes
	Euro emission status	Euro 2
	Firing order	1-4-2-6-3-5
	Max engine speed (rpm)	2300
	No of main bearings	7
	Number of cylinders	6
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kW@rpm)	302 @ 1500 - 1800
	Torque (Nm@rpm)	1961 @ 1000 - 1400
	Type of cylinders	Dry Liners
	Valve configuration	Overhead Camshaft
	Hino Stop & Start System	Yes
Clutch	Model	DSF-430
	Facing material	Mold Type (non-asbestos)
	Control	ZF ConAct Pneumatic System
	Clutch automatic gap adjuster	Yes
Transmission	Make	ZF
	Model	ZF16 TX2440TO
	Synchromesh or Automatic	AMT
	No of forward gears	16
	Gearshift operation	Mechanical Auto
	Gear Ratio (1st - Top Gear)	14.682 - 0.821
	Reverse ratio (~:1)	14.138 / 11.602
Mass Data (kg)	A - Front	7500
	A - Rear	21800
	Approx. body + payload allowance	16470
	D/T	65000
	GA - Front	7500
	GA - Rear	21800
	GCM	65000
	GVM	28300
	Tare - Front	4980
	Tare - Rear	4050
	Tare - Total (Incl. spare wheel)	9030
	V - rating	25500
Performance (sea level)	Gradeability tanθ (%)	32
	Geared Speed-km/h (Speed limited)	80

Category type	Model Description	2841 FC
Front Axle	Model	MF78IR
	Type	I-beam, Reverse Elliot
Rear Axle	Model	THD17
	Type	Full-floating
		Single Reduction
		Single Speed by Hypoid Gearings
	Ratio (~:1)	3,9
Service Brake	Type	Full Air, Wedge Type
	Service brake line	Dual Circuit
	Front wheel brake	Drum
	Rear wheel brake	Drum
	HINO ES (Easy & Smooth) Start System	Yes
Auxiliary Brake	HINO Engine Retarder	Yes
	Transmission Intarder (ZF Intarder IT3)	Yes
Parking Brake	Type	Air Operated Spring Brake
Steering	Type	Telescopic & Tilt Steering Column, Power Steering
	Rack & pinion gear ratio	Variable Gear Ratio
	Turning radius between kerbs (mm)	7200
	Turning radius between walls (mm)	8100
Wheel & Tyre	Tyre size	315/80R22.5
	Wheel size	22.5 x 9
	Load/speed rating	3750-3350/130
	No of wheels (Including spare wheel)	11
	Spare wheel carrier location	Chassis
	Tyre construction	Radial Tubeless
	Attachment	ISO 10-Stud
	Wheel type	Single Steel Piece
Fuel Tank (/)	Capacity	390
	Capacity (Sub tank)	-
Safety & Security	Advanced Safety Features	EBS (Electronic Control Brake System)
		ABS (Anti-Lock Brake System)
		ASR (Anti-Slip Regulation)
		VSC (Vehicle Stability Control)
		PCS (Pre-Collision System)
		ACC (Adaptive Cruise Control)
		LDWS (Lane Departure Warning System)
		Driver Monitor
		Staggering Warning
	Airbags	SRS Airbag System
	Seatbelt	Driver (pre-tensioner), Passenger (emergency locking retractor)
	Daytime running light	No
	Transponder key immobiliser	Std
	Side impact beams	Std
Comfort & Convenience	Air-conditioner	Yes
	Key activated central locking	Std
	Electric windows	Yes
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval	40 000 km[1,2]
	Vehicle warranty	36 Months, Unlimited kms
	Powertrain warranty	36 Months[2], Unlimited kms
	Cab corrosion warranty	48 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms

1 Dependant on application & operating conditions
2 On-road application
3 Off-road application
** All Chasis modification must be approved by Hino SA*
Please be advised that specifications are subject to change.

HINO 700 SERIES 2841 TT SPECIFICATIONS

Category type	Model Description	2841 TT
Dimensions (mm)	BBC - Rear Structure	2035
	OL -Overall Length	6845
	WB - Wheel Base Std	3150 + 1350
	WB - Wheel Base (Min - Max)	No chassis modification allowed*
	CA - Cab to Axle Center	3190
	OVH - Overall Vehicle Height	3025
	HF - Frame Height Front Axle	1015
	HR - Frame Height Rear Axle	1090
	MGC - Minimum Ground Clearance	255
	CW - Cab Width (Excl. mirrors)	2490
	WARW - Width Across Rear Wheels	2485
	FW - Frame Width (Outside)	840
	FOH - Front Overhang	1400
	ROH - Rear Overhang	945
	FT - Front Track	2030
	RT - Rear Track	1825
	Max. Homologated Body Width	2600
	Max. Body Length	N/A
Engine	Make	HINO
	Model	HINO E13C-BG
	4 Stroke compression ignition	Yes
	Aspiration	Turbocharged and Intercooled
	Bore x Stroke (mm)	137 x 146
	Piston displacement (cc)	12913
	Compression ratio (~:1)	17
	Configuration	In-line 6 Cylinder
	Engine oil cooler	Yes
	Euro emission status	Euro 2
	Firing order	1-4-2-6-3-5
	Max engine speed (rpm)	2300
	No of main bearings	7
	Number of cylinders	6
	Number of valves per cylinder	4
	Power (EEC/ISO NET) (kW@rpm)	302 @ 1500 - 1800
	Torque (Nm@rpm)	1961 @ 1000 - 1400
	Type of cylinders	Dry Liners
	Valve configuration	Overhead Camshaft
	Hino Stop & Start System	Yes
Clutch	Model	DSF-430
	Facing material	Mold Type (non-asbestos)
	Control	ZF ConAct Pneumatic System
	Clutch automatic gap adjuster	Yes
Transmission	Make	ZF
	Model	ZF16 TX2440TO
	Synchromesh or Automatic	AMT
	No of forward gears	16
	Gearshift operation	Mechanical Auto
	Gear Ratio (1st - Top Gear)	14.682 - 0.821
	Reverse ratio (~:1)	14.138 / 11.602
Mass Data (kg)	A - Front	7500
	A - Rear	21800
	Approx. body + payload allowance	15895
	D/T	65000
	GA - Front	7500
	GA - Rear	21800
	GCM	65000
	GVM	28300
	Tare - Front	5010
	Tare - Rear	4595
	Tare - Total (Incl. spare wheel)	9605
	V - rating	25500
Performance (sea level)	Gradeability tanθ (%)	32
	Geared Speed-km/h (Speed limited)	80

Category type	Model Description	2841 TT
Front Axle	Model	MF78IR
	Type	I-beam, Reverse Elliot
Rear Axle	Model	THD17
	Type	Full-floating
		Single Reduction
		Single Speed by Hypoid Gearings
	Ratio (~:1)	3,9
Service Brake	Type	Full Air, Wedge Type
	Service brake line	Dual Circuit
	Front wheel brake	Drum
	Rear wheel brake	Drum
	HINO ES (Easy & Smooth) Start System	Yes
Auxiliary Brake	HINO Engine Retarder	Yes
	Transmission Intarder (ZF Intarder IT3)	Yes
Parking Brake	Type	Air Operated Spring Brake
Steering	Type	Telescopic & Tilt Steering Column, Power Steering
	Rack & pinion gear ratio	Variable Gear Ratio
	Turning radius between kerbs (mm)	7200
	Turning radius between walls (mm)	8100
Wheel & Tyre	Tyre size	315/80R22.5
	Wheel size	22.5 x 9
	Load/speed rating	3750-3350/130
	No of wheels (Including spare wheel)	11
	Spare wheel carrier location	Chassis
	Tyre construction	Radial Tubeless
	Attachment	ISO 10-Stud
	Wheel type	Single Steel Piece
Fuel Tank (/)	Capacity	390
	Capacity (Sub tank)	450
Safety & Security	Advanced Safety Features	EBS (Electronic Control Brake System)
		ABS (Anti-Lock Brake System)
		ASR (Anti-Slip Regulation)
		VSC (Vehicle Stability Control)
		PCS (Pre-Collision System)
		ACC (Adaptive Cruise Control)
		LDWS (Lane Departure Warning System)
		Driver Monitor
		Staggering Warning
	Airbags	SRS Airbag System
	Seatbelt	Driver (pre-tensioner), Passenger (emergency locking retractor)
	Daytime running light	No
	Transponder key immobiliser	Std
	Side impact beams	Std
Comfort & Convenience	Air-conditioner	Yes
	Key activated central locking	Std
	Electric windows	Yes
	AM/FM radio with CD player, USB, AUX, Bluetooth	Std
	Storage facilities	Std
Aftersales	Service interval	40 000 km[1,2]
	Vehicle warranty	36 Months, Unlimited kms
	Powertrain warranty	36 Months[2], Unlimited kms
	Cab corrosion warranty	48 Months, Unlimited kms
	Chassis frame warranty	36 Months, Unlimited kms

1 Dependant on application & operating conditions
2 On-road application
3 Off-road application
** All Chasis modification must be approved by Hino SA*
Please be advised that specifications are subject to change.

HINO VALUE ADDED SERVICES

HOW HINO GOES THE DISTANCE FOR ITS CUSTOMERS

24-HOUR ROADSIDE ASSISTANCE

- Hino dealer service and parts assistance
- Hino's Dealer Network is more than 65 strong in Southern Africa
- 24-hour call centre 0800 878 257 (0800 TRUCKS)
- Technically-trained staff for breakdown assistance
- Roadside security – In the event that your vehicle breaks down in an unsafe area*
- Medical assistance

HINO-CONNECT

- HINO-CONNECT is a telematics fleet management system equipped as standard on all new Hino trucks in South Africa
- It provides vehicle tracking and recovery
- Fuel consumption, oil and water temperatures, as well as fault reporting

SERVICE AND MAINTENANCE PLANS

- These can be tailor-made to your requirements
- Speak to your Hino dealer for more information

HINO CARE

EXTENDED WARRANTY PERIOD

- Hino Superior Extended Warranty: 24 Months
- Hino Basic Extended Warranty: 24 Months

TOWING ASSISTANCE

- Recovery towing services to the nearest Hino dealer for repairs or to a safe location**

SERVICE INTERVALS

- 700 Series – 30 000km

  Dependent on application and operating conditions

  Speak to your Hino dealer for more information

SERVICE AND MAINTENANCE PLANS

Your Hino 700's Service and Maintenance plans can be tailor-made to your requirements. For complete convenience, current plans can be up or downgraded to provide more or less cover, depending on each owner's requirements.

* Can be arranged with the call centre - costs to be paid by customer.
** At customer's cost.

Certain vehicle details and specifications contained in this leaflet may differ from the available models. Hino Motors Limited and Hino South Africa reserves the right to alter any details of specifications and equipment without notice. For the most current information on prices and specifications, as well as comprehensive information about products offered by Hino, contact your dealer, or Hino South Africa. Call 0800 139 111 or visit www.hino.co.za