

Q92

ADVANCED Mobile



Food & Beverage



Fashion & Retail



CLASSIC



Powered by
Prolin



PCI 6
SRED



4"
Display






















0.3MP
Rear



Advanced
Connectivity

SPECIFICATIONS

	Operating System	Prolin
	Processor	Cortex-A53
	Memory	512MB FLASH + 256MB DDR RAM Extended microSD Card Slot Up to 32GB
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Cameras	0.3MP Rear-Facing (optional)
	Display	4" TFT WVGA 480 x 800 Pixels Touch Screen
	Comms Configurations	Wi-Fi® 2.4GHz/5GHz (optional) 4G (TD-LTE / FDD-LTE) 3G (WCDMA) (optional) Bluetooth® (optional)
	Battery	5100mAh 3.6V
	Printer	30 lines/sec Paper Roll Outer Diameter: 40mm
	SIM / SAM	1 Micro SIM + 2 Micro SAMs 2 Micro SIMs + 1 Micro SAM 1 Micro SIM + 1 Micro SAM+ 1 eSIM 1 Mini SIM + 1 eSIM
	Positioning	GPS (optional)
	Keys / Buttons	15 Keys: 0~9 Func Alpha Cancel Clear Enter
	Audio	1 Speaker
	Ports	1 Type-C (USB 2.0) OTG
	Adapter	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
	Physical	165 x 75 x 62mm, 375g (including battery)
	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 93% Relative Humidity, Non-Condensing
	Accessories	Optional B92: Charging Base 1 Power Port (Type-C) 74 x 47 x 21mm
	Certifications	PCI PTS 6.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless UPI qUICS Amex Expresspay Discover D-PAS ABECS Anatel Mastercard TQM CE RoHs

