

04 — Routes & Endpoints

One-line quick-reference table of every HTTP route. For detailed semantics see [01_API_DOCS.md](#) . For React-side routes see the bottom of this file.

Backend HTTP routes (`src/api.py`)

Public

Method	Path	Purpose	Auth
GET	/health	Liveness probe	none
POST	/query	RAG question-answer	worker_session (optional)
GET	/machines	Public machine list	none
GET	/machines/{machine_id}/parameters	Parameter spec for EndShiftModal	none
GET	/machines/{machine_id}/shifts/recent	Recent shift logs (used by HandoffBanner)	none
POST	/shifts/log	Submit a shift log	none (worker session optional)
POST	/shifts/{log_id}/acknowledge	Worker-side ack (dismiss handoff banner)	none
GET	/workstation	IP → machine binding lookup	none
GET	/uploads/icons/{file}	Static-serve admin-uploaded icons	none

Authentication

Method	Path	Purpose
POST	/auth/request-link	Admin requests magic sign-in email
GET	/auth/verify?token=...	Magic-link click target → 302 + cookie
POST	/auth/verify	Programmatic verify (same as GET, different content type)
POST	/auth/worker-session	Worker chooses a domain → cookie
GET	/auth/me	Current session info (401 if anonymous)
POST	/auth/logout	Clear both session cookies

Admin — gated by `require_admin`

Method	Path	Purpose
POST	<code>/admin/machines</code>	Upload + ingest a new machine PDF
GET	<code>/admin/machines</code>	Admin machine list (extra metadata)
PATCH	<code>/admin/machines/{machine_id}</code>	Edit machine metadata in place
DELETE	<code>/admin/machines/{machine_id}</code>	Delete machine + chunks + PDF
POST	<code>/admin/machines/{machine_id}/reingest</code>	Re-run ingestion on archived PDF
PUT	<code>/admin/machines/{machine_id}/parameters</code>	Replace shift-log parameter spec
GET	<code>/admin/jobs/{job_id}</code>	Poll ingestion job status
GET	<code>/admin/shifts</code>	List shift logs (filter: machine_id, phase)
POST	<code>/admin/shifts/{log_id}/acknowledge</code>	Admin-side ack (audited)
POST	<code>/admin/shifts/{log_id}/void</code>	Soft-delete a shift log (with reason)
GET	<code>/admin/alerts</code>	Alert list + threshold + snoozes + dedup window
DELETE	<code>/admin/alerts</code>	Clear all alerts
POST	<code>/admin/alerts/{alert_id}/acknowledge</code>	Mark single alert as handled
POST	<code>/admin/alerts/snooze</code>	Mute alerts for a machine for N minutes
POST	<code>/admin/alerts/test</code>	Inject a synthetic alert for pipeline check
GET	<code>/admin/config</code>	Read runtime-tunable config
PATCH	<code>/admin/config</code>	Update + persist runtime config
GET	<code>/admin/analytics</code>	Aggregated dashboard widgets
GET	<code>/admin/audit</code>	Audit log entries (filter: prefix)
POST	<code>/admin/_seed-analytics</code>	DEMO-ONLY synthetic query injection

Total backend routes: **35** (8 public + 6 auth + 21 admin).

Frontend SPA routes (frontend/src/App.jsx)

Path	Component	Notes
/	LandingPage	Marketing landing + machine carousel
/features	FeaturesPage	Marketing feature page
/integrations	IntegrationsPage	Marketing integrations page
/machines	MachinesPage	Worker-facing machine list (links to /chat)
/chat? machine=...	ChatPage	Worker chat for a specific machine
/contact	ContactPage	Marketing contact page
/admin/login	AdminLogin	Magic-link sign-in form
/admin	AdminDashboard (gated by ProtectedAdminRoute)	All admin tabs
/company-policy	CompanyPolicy	Legal
/privacy-policy	PrivacyPolicy	Legal
/cookie-policy	CookiePolicy	Legal
/data-notice	DataNotice	Legal
/legal-notice	LegalNotice	Legal

Proxy mapping (dev vs prod)

The frontend never calls localhost:8000 directly — same-origin requests are proxied to the backend.

Dev (frontend/vite.config.js)

```
/auth      → :8000
/shifts    → :8000
/query     → :8000
/health    → :8000
/workstation → :8000
/uploads   → :8000
/admin     → :8000 (SPA bypass for text/html → index.html)
/machines  → :8000 (SPA bypass for text/html → index.html)
```

Prod (frontend/nginx.conf)

```
location ~ ^/(auth|admin|machines|shifts|query|health|workstation|uploads)(/|$) {  
    proxy_pass http://smartfix_backend;  
    ...  
}  
location / { try_files $uri $uri/ /index.html; } # SPA fallback
```

Both configs match the same set of prefixes. **When you add a new backend prefix, update both files** — though the dev `/admin` rule is broad enough to cover any new `/admin/*` route automatically.