

Premium brake fluids
Safety doesn't happen by accident

Stay prepared for the unexpected!

HYDRAULAN® 402

BASF is a leading provider of high-performance brake fluids under the HYDRAULAN® brand, known for advanced technology and a strong commitment to safety. The brand represents excellence in brake fluid technology, offering products that meet the stringent demands of modern brake systems. With the introduction of HYDRAULAN® 402, BASF responds to the increasing demand for brake fluids without added borates, delivering reliable performance while improving environmental compatibility. A reliable solution that ensures top-tier safety and supports your sustainability ambitions.

Key Features:

- **No added borates:** A novel composition that enhances safety and environmental compatibility
- **Low kinematic viscosity even at low temperatures:** Ensures short actuation response during braking
- **Reduced water absorption compared to general aftermarket DOT4 products in China:** Reduced risk of vapor lock
- **Thermal stability:** Maintains performance under high-temperature conditions
- **Oxidative stability:** Resists degradation over time
- **Corrosion protection:** Safeguards various metals from corrosion
- **Elastomer compatibility:** Works seamlessly with elastomer materials, preventing wear and tear
- **No deposits:** Keeps braking systems clean and efficient
- Meets all relevant industry standards

Experience the future of braking with HYDRAULAN® 402 – engineered for environmental responsibility and reliable performance.

Customer benefits:

- Faster brake response ensures improved driving safety
- Compliant to all relevant global industry standards, e.g. ISO 4925 Class 4, GB 12981-2013 HZY 4 (China)
- Helps to maintain the durability of brake system parts
- Long-lasting fluid effectiveness that reduces maintenance frequency and operating costs
- Ideal for eco-conscious customers seeking lower environmental impact



BASF
We create chemistry

HYDRAULAN® 402 meets the requirements set by the international standards in all criteria:

Product	International standard	Dry ERBP [°C]	Wet ERBP [°C]	Viscosity at -40°C [mm²/s]
HYDRAULAN® 402		≥ 250	≥ 155	≤ 1.200
	FMVSS No. 116 DOT 4	≥ 230	≥ 155	≤ 1.800
	SAE J1703	≥ 205	≥ 140	≤ 1.500
	ISO 4925 Class 4	≥ 230	≥ 155	≤ 1.500
	GB 12981-2013 HZY 4	≥ 230	≥ 155	≤ 1.500
	IS Indian standard 8654-2019 Type II	≥ 230	≥ 155	≤ 1.800
	JIS K 2233 Class 4	≥ 230	≥ 155	≤ 1.500

Packaging information:

HYDRAULAN® 402 is globally available.
Sizes of packaging and offerings may
differ per region.



Contact us today to learn more about the new HYDRAULAN® 402!



**Safety doesn't happen
by accident.**
Learn more on our website
www.hydraulan.com

The descriptions, designs, data and information contained herein are presented in good faith, and are based on BASF's current knowledge and experience. They are provided for guidance only, and do not constitute the agreed contractual quality of the product or a part of BASF's terms and conditions of sale. Because many factors may affect processing or application/use of the product, BASF recommends that the reader carry out its own investigations and tests to determine the suitability of a product for its particular purpose prior to use. It is the responsibility of the recipient of product to ensure that any proprietary rights and existing laws and legislation are observed. No warranties of any kind, either expressed or implied, including, but not limited to, warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth herein, or that the products, descriptions, designs, data or information may be used without infringing the intellectual property rights of others. Any descriptions, designs, data and information given in this publication may change without prior information. The descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained, all such being given and accepted at the reader's risk. (10/2025)