

Safety data sheet

Page: 1/16

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hydralan® 400 N.V.-1

UFI: GQYD-N19P-F00X-W9DR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: brake fluid

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Fuel and Lubricant Solutions

Telephone: +49 621 60-0

E-mail address: RegXcellenceFuelLubes@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Eye Dam./Irrit. 2	H319 Causes serious eye irritation.
Repr. 1B	H360F May damage fertility.
Repr. 2	H361d Suspected of damaging the unborn child.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H319	Causes serious eye irritation.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P280	Wear eye protection.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
--------------------	--

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

EUH208: May produce an allergic reaction. Contains: bisphenol A
Restricted to professional users.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

Restricted to professional users.

Hazard determining component(s) for labelling: Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate, bisphenol A

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Blend based on: polyglycol, glycol ether, inhibitors, glycoletherborate

Regulatory relevant ingredients

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Content (W/W): $\geq 40\%$ - $\leq 50\%$	Repr. 2 (fertility)
CAS Number: 30989-05-0	Repr. 2 (unborn child)
EC-Number: 250-418-4	H361fd
REACH registration number: 01-2119462824-33	

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Content (W/W): $> 10\%$ - $< 20\%$	Eye Dam./Irrit. 1
EC-Number: 907-996-4	H318
REACH registration number: 01-2119531322-53-0000	EUH066

Specific concentration limit:

Eye Dam. 1: $\geq 30\%$
Eye Irrit. 2: $20 - < 30\%$

2-(2-methoxyethoxy)ethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

Content (W/W): > 1 % - < 3 %
CAS Number: 111-77-3
EC-Number: 203-906-6
REACH registration number: 01-2119475100-52
INDEX-Number: 603-107-00-6

Repr. 1B (unborn child)
H360D

Specific concentration limit:

Repr. 1B, unborn child: >= 3 %

Substance with EU occupational exposure limit

2,2' -oxybisethanol

Content (W/W): > 3 % - < 5 %
CAS Number: 111-46-6
EC-Number: 203-872-2
REACH registration number: 01-2119457857-21
INDEX-Number: 603-140-00-6

Acute Tox. 4 (oral)
H302

1,1'-iminodiprop-2-ol

Content (W/W): < 3 %
CAS Number: 110-97-4
EC-Number: 203-820-9
REACH registration number: 01-2119475444-34
INDEX-Number: 603-083-00-7

Eye Irrit. 2
H319

bisphenol A

Content (W/W): > 0.1 % - < 0.5 %
CAS Number: 80-05-7
EC-Number: 201-245-8
REACH registration number: 01-2119457856-23
INDEX-Number: 604-030-00-0

Eye Dam. 1
Skin Sens. 1
Repr. 1B (fertility)
STOT SE 3 (irr. to respiratory syst.)
Aquatic Acute 1
Aquatic Chronic 1
M-factor acute: 1
M-factor chronic: 10
H318, H317, H335, H360F, H400, H410

Substance with EU occupational exposure limit

Included on the candidate list according to article 59 (1,10) of regulation EC No. 1907/2006 ('REACH').

Substance of concern regarding endocrine disruptive properties

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). First aid personnel should pay attention to their own safety.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

water spray, dry powder, foam

5.2. Special hazards arising from the substance or mixture

Endangering substances: harmful vapours

Advice: Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Breathing protection required.

6.2. Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Exposure estimate and reference to its source

Provide a suitable local exhaust ventilation. Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)

7.2. Conditions for safe storage, including any incompatibilities

Unsuitable materials for containers: Paper/Fibreboard

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydraulan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

80-05-7: bisphenol A

110-97-4: 1,1'-iminodipropyl-2-ol

111-46-6: 2,2' -oxybisethanol

111-77-3: 2-(2-methoxyethoxy)ethanol

112-35-6: 2-(2-(2-Methoxyethoxy)ethoxy)ethanol

30989-05-0: Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

PNEC

Data refer to the lead substance

Components with PNEC

80-05-7: bisphenol A

freshwater: 0.018 mg/l

intermittent release: 0.011 mg/l

marine water: 0.018 mg/l

STP: 320 mg/l

sediment (freshwater): 1.2 mg/l

sediment (marine water): 0.24 mg/l

soil: 3.7 mg/l

oral (secondary poisoning):

No PNEC oral derived, as accumulation in organisms is not to be expected.

DNEL

Data refer to the lead substances

Components with DNEL

30989-05-0: Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

worker: Long-term exposure- systemic effects, Inhalation: 14.8 mg/m³

worker: Long-term exposure- systemic effects, dermal: 4.2 mg/kg

consumer: Long-term exposure- systemic effects, Inhalation: 2.6 mg/m³

consumer: Long-term exposure- systemic effects, dermal: 1.5 mg/kg

consumer: Long-term exposure- systemic effects, oral: 1.5 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Respiratory protection in case of vapour/aerosol release. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

Hand protection:

Wear chemically resistant gloves in combination with specific activity training

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

chemical-protection suit (f.e. according to EN 14605)

General safety and hygiene measures

Wearing of closed work clothing is required additionally to the stated personal protection equipment.

No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	yellow	
Odour:	product specific	
Odour threshold:	not determined	
solidification temperature:	< -50 °C	(DIN 51583)
boiling temperature:	> 260 °C	(ASTM D1120)
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Flash point:	> 130 °C	(DIN 51758)
Auto-ignition temperature:	not determined	(DIN 51794)
Thermal decomposition:	No decomposition if correctly stored and handled.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydraulic® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

pH value:	7.5 - 9	(FMVSS 116, S 6.4)
Viscosity, kinematic:	14 mm ² /s (20 °C)	(DIN 51562)
Thixotropy:	not thixotropic	
Solubility in water:	fully soluble	
Solubility (quantitative) solvent(s):	polar solvents soluble	
Partitioning coefficient n-octanol/water (log K _{ow}):	Study scientifically not justified.	
Vapour pressure:	1 mbar (20 °C) 1 mbar (50 °C)	
Density:	approx. 1.06 g/cm ³ (20 °C)	
Relative vapour density (air):	> 1 (20 °C) Heavier than air.	(estimated)

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

Other Information: If necessary, information on other physical and chemical parameters is indicated in this section.

Evaporation rate: not determined

SECTION 10: Stability and Reactivity

10.1. Reactivity

Corrosion to metals: No corrosive effect on metal.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydraulan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid open flames. Avoid humidity.

10.5. Incompatible materials

Substances to avoid:

strong oxidizing agents, strong bases, strong acids

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products known.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

No data available.

Irritation

Assessment of irritating effects:

Eye contact causes irritation. Not irritating to the skin.

Respiratory/Skin sensitization

Assessment of sensitization:

A sensitizing effect on particularly sensitive individuals cannot be excluded.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

May impair fertility.

Information on: bisphenol A

Assessment of reproduction toxicity:

The results of animal studies suggest a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

May cause harm to the unborn child.

Information on: 2-(2-methoxyethoxy)ethanol

Assessment of teratogenicity:

In animal studies the substance caused malformations.

Specific target organ toxicity (single exposure)

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

The product contains a substance that is identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 or is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

Other information

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydraulan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Elimination information:

> 70 % DOC reduction (28 d) (OECD 302B; ISO 9888; 88/302/EWG, Teil C) Easily eliminated from water.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Endocrine disrupting properties

The product contains a substance that is identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 or is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

12.7. Other adverse effects

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

The product does not contain substances that are listed in Regulation (EU) 2024/590 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydralan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydraulan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 54, 66, 3, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
List entry in regulation: E2

Classification applies for standard conditions of temperature and pressure.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Repr. 2 (unborn child)

Repr. 1B (fertility)

Eye Dam./Irrit. 2A

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Eye Dam./Irrit.

Serious eye damage/eye irritation

Repr.

Reproductive toxicity

Aquatic Chronic

Hazardous to the aquatic environment - chronic

Acute Tox.

Acute toxicity

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025

Version: 9.0

Date / Previous version: 01.07.2024

Previous version: 8.2

Product: **Hydraulan® 400 N.V.-1**

(ID no. 30053073/SDS_GEN_EU/EN)

Date of print 03.12.2025

Eye Irrit.	Eye irritation
Eye Dam.	Serious eye damage
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
H319	Causes serious eye irritation.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H318	Causes serious eye damage.
H360D	May damage the unborn child.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.