

Safety data sheet

Page: 1/11

BASF Safety data sheet
Date / Revised: 04.11.2025
Product: **Hydralan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

1. Substance/preparation and manufacturer/supplier identification

English product name: Hydralan® 400 N.V.-1

Other means of identification: /

Use: brake fluid

Manufacturer/supplier:

BASF Taiwan Ltd.
10th floor, No. 106, Sung Chiang Road
Taipei 10457, TAIWAN
Telephone: +886 2 2518-7600
Telefax number: +886 2 2518-7702
E-mail address: SDS-inquiry-tw@basf.com

Emergency information:

台灣緊急連絡電話
0800-002-119
International emergency number:
Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

Serious eye damage/eye irritation: Cat.2A

Reproductive toxicity: Cat.2 (unborn child)

Reproductive toxicity: Cat.1B (fertility)

Label elements and precautionary statement:

Pictogram:

BASF Safety data sheet
 Date / Revised: 04.11.2025
 Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025



Signal Word:
 Danger

Hazard Statement:

H319 Causes serious eye irritation.
 H360 May damage fertility. Suspected of damaging the unborn child.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face protection.
 P280 Wear eye protection.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical attention.
 P337 + P313 If eye irritation persists: Get medical attention.

Precautionary Statements (Storage):

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
 The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

May produce an allergic reaction. Contains:
 bisphenol A

3. Composition/information on ingredients

State of matter: liquid

Chemical nature

Substance nature: mixture

Blend based on: polyglycol, glycol ether, inhibitors
 , glycoletherborate

Hazardous ingredients

BASF Safety data sheet
Date / Revised: 04.11.2025
Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

Ethanol, 2-[2-(2-methoxyethoxy)ethoxy]-, triester with boric acid (H₃BO₃)

Other means of identification: /

Content (W/W): $\geq 40\%$ - $\leq 50\%$ Repr.: Cat. 2 (fertility)
CAS Number: 30989-05-0 Repr.: Cat. 2 (unborn child)

2-(2-(2-butoxyethoxy)ethoxy)ethanol

Other means of identification: /

Content (W/W): $> 10\%$ - $< 20\%$ Acute Tox.: Cat. 5 (dermal)
CAS Number: 143-22-6 Eye Dam.: Cat. 1

2-(2-methoxyethoxy)ethanol

Other means of identification: /

Content (W/W): $> 1\%$ - $< 3\%$ Flam. Liq.: Cat. 4
CAS Number: 111-77-3 Repr.: Cat. 1B (unborn child)

Diethylene glycol

Other means of identification: /

Content (W/W): $> 3\%$ - $< 5\%$ Acute Tox.: Cat. 4 (oral)
CAS Number: 111-46-6

1,1'-iminodipropan-2-ol

Other means of identification: /

Content (W/W): $< 3\%$ Eye Irrit.: Cat. 2A
CAS Number: 110-97-4

bisphenol A

Other means of identification: /

Content (W/W): $> 0.1\%$ - $< 0.5\%$ Acute Tox.: Cat. 5 (oral)
CAS Number: 80-05-7 Acute Tox.: Cat. 5 (dermal)
Eye Dam.: Cat. 1
Skin Sens.: Cat. 1
Repr.: Cat. 1B (fertility)
STOT SE: Cat. 3 (irr. to respiratory syst.)
Aquatic Acute: Cat. 2
Aquatic Chronic: Cat. 2

3,6,9,12-Tetraoxahexadecan-1-ol

Other means of identification: /

BASF Safety data sheet
Date / Revised: 04.11.2025
Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

Content (W/W): $\geq 2\%$ - $\leq 10\%$ Acute Tox.: Cat. 5 (oral)
CAS Number: 1559-34-8 Eye Irrit.: Cat. 2A

4. First-Aid Measures

General advice:

Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). First aid personnel should pay attention to their own safety.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

water spray, dry powder, foam

Specific hazards:

harmful vapours

Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:

Wear a self-contained breathing apparatus.

Special extinguishing Procedure:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Use personal protective clothing. Breathing protection required.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

Unsuitable materials for containers: Paper/Fibreboard

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure controls and personal protection

Components with occupational exposure limits

No substance specific occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Respiratory protection in case of vapour/aerosol release. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Chemical resistant protective gloves

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g.

BASF Safety data sheet
 Date / Revised: 04.11.2025
 Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

chemical-protection suit (f.e. according to EN 14605)

General safety and hygiene measures:

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	yellow	
Odour:	product specific	
Odour threshold:	not determined	
pH value:	7.5 - 9	(FMVSS 116, S 6.4)
solidification temperature:	< -50 °C	(DIN 51583)
boiling temperature:	> 260 °C	(ASTM D1120)
Flash point:	> 130 °C	(DIN 51758)
Evaporation rate:	not determined	
Flammability (solid/gas):	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	not determined	(DIN 51794)
Thermal decomposition:	No decomposition if correctly stored and handled.	
Self ignition:	not self-igniting	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:	1 mbar (20 °C)	

BASF Safety data sheet
Date / Revised: 04.11.2025
Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

1 mbar
(50 °C)

Density: approx. 1.06 g/cm³
(20 °C)

Relative vapour density (air): > 1 (estimated)
(20 °C)
Heavier than air.

Solubility in water: fully soluble
Solubility (quantitative) solvent(s): polar solvents
soluble

Partitioning coefficient n-octanol/water (log Pow):
Study scientifically not justified.

Viscosity, kinematic: 14 mm²/s (DIN 51562)
(20 °C)

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

10. Stability and Reactivity

Conditions to avoid:

Avoid open flames. Avoid humidity.

Thermal

decomposition:

No decomposition if correctly stored and handled.

Substances to avoid:

strong oxidizing agents, strong bases, strong acids

Corrosion to metals:

No corrosive effect on metal.

Hazardous reactions:

No hazardous reactions when stored and handled according to instructions.

Hazardous decomposition products:

No hazardous decomposition products known.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Symptoms

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
(Further) symptoms and / or effects are not known so far

Irritation

Assessment of irritating effects:
Eye contact causes irritation. Not irritating to the skin.

Respiratory/Skin sensitization

Assessment of sensitization:
A sensitizing effect on particularly sensitive individuals cannot be excluded.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:
May impair fertility.

Information on: bisphenol A

Assessment of reproduction toxicity:
The results of animal studies suggest a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:
May cause harm to the unborn child.

Information on: 2-(2-methoxyethoxy)ethanol

Assessment of teratogenicity:
In animal studies the substance caused malformations.

Specific target organ toxicity (single exposure)

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Mobility

Assessment transport between environmental compartments:

The substance will not evaporate into the atmosphere from the water surface.

Persistence and degradability

Elimination information:

> 70 % DOC reduction (28 d) (OECD 302B; ISO 9888; 88/302/EWG, Teil C) Easily eliminated from water.

Bioaccumulation potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

13. Disposal Considerations

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:

Uncontaminated packaging can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Domestic transport:

BASF Safety data sheet
 Date / Revised: 04.11.2025
 Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

	Not classified as a dangerous good under transport regulations
UN number or ID number	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Further information

Domestic regulations for transport: Please follow Road Safety Rule

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
	Marine pollutant: no
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number	Not applicable
Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

ERG-number: 171

See Section 15 for domestic transport regulations

15. Regulatory Information

BASF Safety data sheet
Date / Revised: 04.11.2025
Product: **Hydraulan® 400 N.V.-1**

Version: 1.0

(30053073/SDS_GEN_TW/EN)

Date of print: 05.12.2025

Other regulations

OCCUPATIONAL SAFETY AND HEALTH ACT, REGULATION OF ROAD SAFETY, and METHODS AND FACILITIES STANDARDS FOR THE STORAGE, CLEARANCE AND DISPOSAL OF INDUSTRIAL WASTE always need to be followed

16. Other Information

Literature references: BASF EHS data

Organization that prepared the SDS: BASF Taiwan Ltd.

Address/telephone: 10th Floor, No. 106, Sung Chiang Rd., 10457 Taipei, Taiwan / +886 2 2518-7600

Person that prepared the SDS: Responsible Department Product Safety and Regulations (PS&R)

Creation date of the SDS: please refer to page head

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.