

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date : 2025/12/03

Version: 2.1

Page: 1/11

(30053073/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Hydralan® 400 N.V.-1

Recommended use of the chemical and restriction on use

Recommended use*: brake fluid

Unsuitable for use: None known

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA
Fuel and Lubricant Solutions

E-mail address: RegXcellenceFuelLubes@basf.com

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: Blend based on: polyglycol, glycol ether, inhibitors

2. Hazards Identification

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Sens.	1	Skin sensitization
Eye Dam.	1	Serious eye damage
Repr.	2 (unborn child)	Reproductive toxicity
Repr.	1B (fertility)	Reproductive toxicity

Safety Data Sheet

Hydraulan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 2/11
(30053073/SDS_GEN_US/EN)

Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H360	May damage fertility. Suspected of damaging the unborn child.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P261	Avoid breathing mist or vapour or spray.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P308 + P313	IF exposed or concerned: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Ethanol, 2-[2-(2-methoxyethoxy)ethoxy]-, triester with boric acid (H3BO3)
CAS Number: 30989-05-0
Content (WW): >= 30.0 - <= 60.0%
Synonym: Ethanol, 2-[2-(2-methoxyethoxy)ethyl]-, triester with boric acid (H3BO3)

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 3/11
(30053073/SDS_GEN_US/EN)

| 2-(2-(2-butoxyethoxy)ethoxy)ethanol

| CAS Number: 143-22-6

| Content (W/W): ≥ 7.0 - $\leq 30.0\%$

| Synonym: 2-[2-(2-Butoxyethoxy)ethoxy]ethanol; Triethylene glycol monobutyl ether

| diethylene glycol

| CAS Number: 111-46-6

| Content (W/W): ≥ 1.0 - $\leq 7.0\%$

| Synonym: 2,2'-Oxybisethanol

| 3,6,9,12-Tetraoxahexadecan-1-ol

| CAS Number: 1559-34-8

| Content (W/W): ≥ 1.0 - $\leq 7.0\%$

| Synonym: No data available.

| 1,1'-iminodipropan-2-ol

| CAS Number: 110-97-4

| Content (W/W): ≥ 1.0 - $\leq 5.0\%$

| Synonym: 1,1'-Iminobis(2-propanol); Diisopropanolamine

| 2-(2-methoxyethoxy)ethanol

| CAS Number: 111-77-3

| Content (W/W): > 0.5 - $< 5.0\%$

| Synonym: 2-(2-Methoxyethoxy)ethanol; Methyl carbitol

| bisphenol A

| CAS Number: 80-05-7

| Content (W/W): ≥ 0.1 - $\leq 1.0\%$

| Synonym: 4,4'-(1-Methylethylidene)bisphenol; 4,4'-Dihydroxydiphenylpropane, Bisphenol A

4. First-Aid Measures

Description of first aid measures

General advice:

| Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). First aid personnel should pay attention to their own safety.

If inhaled:

| Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

| Remove contaminated clothing. Rinse skin immediately with plenty of water for 15 - 20 minutes. If irritation develops, seek medical attention.

If in eyes:

| Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 4/11
(30053073/SDS_GEN_US/EN)

If swallowed:

Rinse mouth immediately with water. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting due to aspiration hazard. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Information on: Ethanol, 2-[2-(2-methoxyethoxy)ethoxy]-, triester with boric acid (H₃BO₃)

Symptoms: Overexposure may cause:, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: 2-(2-(2-butoxyethoxy)ethoxy)ethanol

Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: 3,6,9,12-Tetraoxahexadecan-1-ol

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: diethylene glycol

Symptoms: Overexposure may cause:, vomiting, coma, abdominal cramps, lethargy, nausea, diarrhea, headache

Information on: 1,1'-iminodipropan-2-ol

Symptoms: Overexposure may cause:, abdominal cramps, dyspnea, coughing

Information on: bisphenol A

Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps
Inhalation may provoke the following symptoms:, irritation of respiratory tract, coughing

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours

Safety Data Sheet

Hydraulan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 5/11
(30053073/SDS_GEN_US/EN)

Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Breathing protection required.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).
Dispose of absorbed material in accordance with regulations.
For large amounts: Pump off product.
Place absorbed material in the same container as the spilled substance/product for disposal.

7. Handling and Storage

Precautions for safe handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.
Unsuitable materials for containers: Paper/Fibreboard

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:

No applicable information available.

Safety Data Sheet

Hydraulan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 6/11
(30053073/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Respiratory protection in case of vapour/aerosol release.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure., Protective coverall and/or impermeable apron and boots as necessary.

General safety and hygiene measures:

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Physical state:	liquid	
Form:	liquid	
Odour:	No data available.	
Odour threshold:	not determined	
Colour:	yellow	
pH value:	7.5 - 9	(FMVSS 116, S 6.4)
solidification temperature:	< -50 °C	(DIN 51583)
Melting point:	No data available.	
Freezing point:	No data available.	
boiling temperature:	> 260 °C	(ASTM D1120)
Sublimation point:	No applicable information available.	
Flash point:	> 130 °C	(DIN 51758)
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	not determined	(DIN 51794)
Vapour pressure:	1 mbar (20 °C) 1 mbar (50 °C)	
Density:	approx. 1.06 g/cm3 (20 °C)	
Relative density:	No applicable information available.	
Relative vapour density:	> 1 (20 °C) Heavier than air.	(estimated)

Safety Data Sheet

Hydraulan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 7/11
(30053073/SDS_GEN_US/EN)

Partitioning coefficient n-octanol/water (log Pow):	Study scientifically not justified.
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if correctly stored and handled.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	14 mm ² /s (DIN 51562) (20 °C)
Solubility in water:	fully soluble
Solubility (quantitative):	No applicable information available. polar solvents soluble
Solubility (qualitative):	No data available.
Molecular weight:	No data available.
Evaporation rate:	not determined
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form.

10. Stability and Reactivity

Reactivity

No applicable information available.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

The product is chemically stable.

Conditions to avoid

Avoid open flames. Avoid humidity.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products known.

Thermal decomposition:

No decomposition if correctly stored and handled.

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 8/11
(30053073/SDS_GEN_US/EN)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Based on available data, the classification criteria are not met.

Irritation / corrosion

Assessment of irritating effects: May cause severe damage to the eyes. Not irritating to the skin.

Information on: 2-(2-(2-butoxyethoxy)ethoxy)ethanol

Assessment of irritating effects: Not irritating to the skin. Causes serious eye damage.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Information on: bisphenol A

Assessment of sensitization:

The substance may be photo-sensitizing. May cause sensitization by skin contact.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: Causes impairment of fertility in laboratory animals.

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 9/11
(30053073/SDS_GEN_US/EN)

Information on: bisphenol A

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Information on: Ethanol, 2-[2-(2-methoxyethoxy)ethoxy]-, triester with boric acid (H3BO3)

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Information on: 2-(2-methoxyethoxy)ethanol

Assessment of teratogenicity: In animal studies the substance caused malformations.

Information on: Ethanol, 2-[2-(2-methoxyethoxy)ethoxy]-, triester with boric acid (H3BO3)

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Persistence and degradability

Elimination information

> 70 % DOC reduction (28 d) (OECD 302B; ISO 9888; 88/302/EWG, Teil C) Easily eliminated from water.

Bioaccumulative potential

Assessment bioaccumulation potential

Significant accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 10/11
(30053073/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number

CAS Number	Chemical name
111-77-3	2-(2-methoxyethoxy)ethanol
143-22-6	2-(2-(2-butoxyethoxy)ethoxy)ethanol

State regulations

State RTK

PA

CAS Number

110-97-4

111-46-6

111-77-3

Trade Secret

143-22-6

Chemical name

1,1'-iminodipropyl-2-ol

diethylene glycol

2-(2-methoxyethoxy)ethanol

Polyethylene glycol

2-(2-(2-butoxyethoxy)ethoxy)ethanol

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

Safety Data Sheet

Hydralan® 400 N.V.-1

Revision date: 2025/12/03
Version: 2.1

Page: 11/11
(30053073/SDS_GEN_US/EN)

WARNING: This product can expose you to chemicals including BISPHENOL A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 3^a Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2025/12/03

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Hydralan® 400 N.V.-1 is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Date / Revised: 2025/12/03

Version: 2.1

Date / Previous version: 2019/01/04

Previous version: 2.0

END OF DATA SHEET