

# Safety data sheet

Page: 1/14

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Polymer

Recommended use: Polymer, for industrial processing only

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF SE  
67056 Ludwigshafen  
GERMANY

Contact address:

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

### 1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

No need for classification according to GHS criteria for this product.

## 2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

The product does not require a hazard warning label in accordance with GHS criteria.

## 2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

No specific dangers known, if the regulations/notes for storage and handling are considered.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

---

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Chemical nature

Compound based on: polyamide (PA 66)

additives, fillers

flame retardant, red phosphorus

Hazardous ingredients (GHS)

red phosphorus

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

|                                       |                   |
|---------------------------------------|-------------------|
| Content (W/W): $\geq 3\%$ - $< 4.9\%$ | Flam. Sol. 1      |
| CAS Number: 7723-14-0                 | Aquatic Chronic 3 |
| EC-Number: 231-768-7                  | H228, H412        |
| INDEX-Number: 015-002-00-7            |                   |

zinc oxide

|                                             |                     |
|---------------------------------------------|---------------------|
| Content (W/W): $\geq 0.1\%$ - $\leq 1\%$    | Aquatic Acute 1     |
| CAS Number: 1314-13-2                       | Aquatic Chronic 1   |
| EC-Number: 215-222-5                        | M-factor acute: 1   |
| REACH registration number: 01-2119463881-32 | M-factor chronic: 1 |
| INDEX-Number: 030-013-00-7                  | H400, H410          |

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

Avoid contact with the skin, eyes and clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Burns caused by molten material require hospital treatment.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. If difficulties occur: Seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

Suitable extinguishing media:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

water spray, foam, dry powder

Unsuitable extinguishing media for safety reasons:  
water jet

### 5.2. Special hazards arising from the substance or mixture

Temperature limit: > 310 °C

Endangering substances: ammonia ....%, carbon monoxide, Carbon dioxide, cyclopentanone, hydrogen cyanide, phosphine, amine derivatives, nitriles

Advice: Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

### 5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

### 6.1. Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

### 6.2. Environmental precautions

Prevent releases of this product into the environment. Comprehensive instructions explaining how to prevent releases of plastics pellets, flakes, and powders to the environment during both use and disposal are provided by the industry program 'Operation Clean Sweep' (OCS).

### 6.3. Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

For residues: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Closed containers should only be opened in well-ventilated areas. Ensure thorough ventilation of stores and work areas.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

Any short stoppages in production, it is recommended that you inject material into the mould not purge an air shot. Any molten material drooling from the machine nozzle or hot runner nozzles can self-ignite when in open atmosphere.

It is therefore advisable to dispose of purgings etc into water containers.

For additional guidelines and recommendations see the product-specific "Processing Data Sheet".

Protection against fire and explosion:

Take precautionary measures against static discharges.

## 7.2. Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:

Protect against moisture.

## 7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

#### Components with occupational exposure limits

1314-13-2: zinc oxide

TWA value 10 mg/m<sup>3</sup> (WEL/EH 40 (UK)), Inhalable dust

TWA value 4 mg/m<sup>3</sup> (WEL/EH 40 (UK)), Respirable dust

1333-86-4: Carbon black

TWA value 3.5 mg/m<sup>3</sup> (WEL/EH 40 (UK))

STEL value 7 mg/m<sup>3</sup> (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

65997-17-3: Glass, oxide, chemicals

### 8.2. Exposure controls

#### Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. (Particle filter EN 143 P2 or FFP2)

Hand protection:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

#### General safety and hygiene measures

Do not inhale gases/vapours/aerosols. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. After use of gloves apply skin-cleaning agents and skin cosmetics.

#### Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

|                                   |                                                                    |                            |
|-----------------------------------|--------------------------------------------------------------------|----------------------------|
| Form:                             | granules                                                           |                            |
| Colour:                           | black                                                              |                            |
| Odour:                            | odourless                                                          |                            |
| Odour threshold:                  | not applicable                                                     |                            |
| pH value:                         | not applicable                                                     |                            |
| melting range:                    | 260 °C<br>(1,013 hPa)                                              | (DIN 53765)                |
| Boiling range:                    | The substance / product<br>decomposes therefore not<br>determined. |                            |
| Sublimation point:                | No applicable information available.                               |                            |
| Flash point:                      | not applicable                                                     |                            |
| Evaporation rate:                 | The product is a non-volatile solid.                               |                            |
| Flammability:                     | not self-igniting                                                  | (derived from flash point) |
| Flammability of Aerosol Products: | not applicable, the product does not<br>form flammable aerosoles   |                            |
| Lower explosion limit:            | For solids not relevant for<br>classification and labelling.       |                            |

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

|                                                     |                                                              |                                                           |
|-----------------------------------------------------|--------------------------------------------------------------|-----------------------------------------------------------|
| Upper explosion limit:                              | For solids not relevant for classification and labelling.    |                                                           |
| Ignition temperature:                               | > 350 °C                                                     | (ASTM D1929)                                              |
| Vapour pressure:                                    | not applicable                                               |                                                           |
| Density:                                            | 1.30 - 1.60 g/cm <sup>3</sup><br>(20 °C, 1,013 hPa)          | (EN ISO 1183-1)                                           |
| Relative density:                                   | Study does not need to be conducted.                         |                                                           |
| Relative vapour density (air):                      | not applicable                                               |                                                           |
| Solubility in water:                                | insoluble<br>(20 °C, 1,013 hPa)                              | (OECD Guideline 105)                                      |
| Partitioning coefficient n-octanol/water (log Kow): | not applicable                                               |                                                           |
| Self ignition:                                      | not self-igniting                                            | Test type: Spontaneous self-ignition at room-temperature. |
| Thermal decomposition:                              | > 310 °C<br>To avoid thermal decomposition, do not overheat. |                                                           |
| Viscosity, dynamic:                                 | not applicable, the product is a solid                       |                                                           |
| Viscosity, kinematic:                               | not applicable, the product is a solid                       |                                                           |
| Explosion hazard:                                   | not explosive                                                |                                                           |
| Fire promoting properties:                          | not fire-propagating                                         |                                                           |

## 9.2. Other information

|                          |                                                                                                       |                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------|
| Self heating ability:    | It is not a substance capable of spontaneous heating according to UN transport regulations class 4.2. | (VDI 2263, sheet 1, 1.4.1 (May 1990)) |
| Bulk density:            | 500 - 800 kg/m <sup>3</sup><br>(20 °C, 1,013 hPa)                                                     | (DIN 53466)                           |
| Grain size distribution: | spheroidal                                                                                            |                                       |

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

The product is chemically stable.

### 10.3. Possibility of hazardous reactions

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

No hazardous reactions known.

The product is chemically stable.

#### **10.4. Conditions to avoid**

Temperature: > 310 °C

See SDS section 7 - Handling and storage.

#### **10.5. Incompatible materials**

Substances to avoid:

No substances known that should be avoided.

#### **10.6. Hazardous decomposition products**

Hazardous decomposition products:

ammonia ....%, carbon monoxide, Carbon dioxide, cyclopentanone, hydrogen cyanide, phosphine amines, nitriles

---

## **SECTION 11: Toxicological Information**

### **11.1. Information on toxicological effects**

#### Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

#### Irritation

Assessment of irritating effects:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Experimental/calculated data:

Serious eye damage/irritation

: May cause mechanical irritation.

#### Respiratory/Skin sensitization

Assessment of sensitization:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Germ cell mutagenicity

Assessment of mutagenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Carcinogenicity



BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

#### Assessment of carcinogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Reproductive toxicity

##### Assessment of reproduction toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Developmental toxicity

##### Assessment of teratogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Specific target organ toxicity (single exposure)

##### Assessment of STOT single:

not applicable

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

##### Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

#### Aspiration hazard

No aspiration hazard expected.

#### Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

---

## SECTION 12: Ecological Information

### 12.1. Toxicity

#### Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

### 12.2. Persistence and degradability

#### Assessment biodegradation and elimination (H<sub>2</sub>O):

Experience shows this product to be inert and non-degradable.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Elimination information:

Poorly biodegradable.

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

### **12.3. Bioaccumulative potential**

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

Bioaccumulation potential:

The product will not be readily bioavailable due to its consistency and insolubility in water.

### **12.4. Mobility in soil**

Assessment transport between environmental compartments:

Adsorption in soil: Adsorption to solid soil phase is not expected.

### **12.5. Results of PBT and vPvB assessment**

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

### **12.6. Other adverse effects**

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

### **12.7. Additional information**

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

The product is a polymeric compound.

---

## **SECTION 13: Disposal Considerations**

### **13.1. Waste treatment methods**

Check for possible recycling.

Incinerate in suitable incineration plant, observing local authority regulations.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

The waste codes are manufacturer's recommendations based on the designated use of the product. Other use and special waste disposal treatment on customer's location may require different waste-code assignments.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Waste key:

07 02 13 waste plastic

Contaminated packaging:

Packs must be completely emptied.

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport Information

### Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

### Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

Transport hazard class(es): Not applicable  
 Packing group: Not applicable  
 Environmental hazards: Not applicable  
 Special precautions for user: None known

Transport in inland waterway vessel  
 Not evaluated

### **Sea transport**

IMDG

Not classified as a dangerous good under transport regulations  
 UN number or ID number: Not applicable  
 UN proper shipping name: Not applicable  
 Transport hazard class(es): Not applicable  
 Packing group: Not applicable  
 Environmental hazards: Not applicable  
 Special precautions for user: None known

### **Air transport**

IATA/ICAO

Not classified as a dangerous good under transport regulations  
 UN number or ID number: Not applicable  
 UN proper shipping name: Not applicable  
 Transport hazard class(es): Not applicable  
 Packing group: Not applicable  
 Environmental hazards: Not applicable  
 Special precautions for user: None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

---

### **SECTION 15: Regulatory Information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

Classification applies for standard conditions of temperature and pressure.

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

#### **15.2. Chemical Safety Assessment**

Chemical Safety Assessment not required

Product is not classified as hazardous.

A safety data sheet for this product is legally not required and is provided by us just as a courtesy to our customers.

---

### **SECTION 16: Other Information**

In addition to the information given in the safety data sheet we refer to the product specific 'Technical Information'.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Flam. Sol.

Flammable solids

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 28.10.2025

Version: 14.0

Date / Previous version: 20.01.2025

Previous version: 13.0

Product: **ULTRAMID® A3X2G10 BLACK 23187 POLYAMIDE**

(ID no. 30045150/SDS\_GEN\_GB/EN)

Date of print 18.11.2025

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Aquatic Chronic | Hazardous to the aquatic environment - chronic        |
| Aquatic Acute   | Hazardous to the aquatic environment - acute          |
| H228            | Flammable solid.                                      |
| H412            | Harmful to aquatic life with long lasting effects.    |
| H400            | Very toxic to aquatic life.                           |
| H410            | Very toxic to aquatic life with long lasting effects. |

### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.