



We create chemistry

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2025/12/12
Version: 2.0

Page: 1/11
(30036470/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

**ULTRADUR® B 4300 M5 UNCOLORED
POLYBUTYLENE TEREPHTHALATE**

Recommended use of the chemical and restriction on use

Recommended use*: Polymer

Recommended use*: Polymer; for industrial processing only

Suitable for use in industrial sector: Polymers industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
5025 Creekbank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: polyester resin
Synonyms: Poly(butylene terephthalate)

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2022-272)

Classification of the product

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 2/11
(30036470/SDS_GEN_CA/EN)

Carc. 1A (by inhalation) Carcinogenicity

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:
H350 May cause cancer by inhalation.

Precautionary Statements (Prevention):
P280 Wear protective gloves, protective clothing and eye protection or face protection.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.

Precautionary Statements (Response):
P308 + P313 IF exposed or concerned: Get medical attention.

Precautionary Statements (Storage):
P405 Store locked up.

Precautionary Statements (Disposal):
P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2022-272)

1-Propanamine, 3-(triethoxysilyl)-
CAS Number: 919-30-2
Content (W/W): ≥ 0.1 - $< 1.0\%$
Synonym: (3-Aminopropyl)triethoxysilane; 3-(Triethoxysilyl)-1-propanamine

Quartz (SiO₂)
CAS Number: 14808-60-7
Content (W/W): ≥ 0.1 - $< 1.0\%$

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 3/11
(30036470/SDS_GEN_CA/EN)

| Synonym: Silicon dioxide

| The actual concentration is withheld as a trade secret.

4. First-Aid Measures

Description of first aid measures

General advice:

Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

If inhaled:

| If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

If on skin:

| Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.
| Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink 200-300 ml of water. Ingestion is not likely in the available physical form. If ingested, seek medical attention. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

| *Information on: Quartz (SiO₂)*

| *Symptoms: Overexposure may cause:; rhinitis, irritation of the mucous membranes, irritates the eyes and respiratory tract, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms:; coughing, dyspnea, wheezing, respiratory disorders, kidney damage, Repeated exposure may affect the immune system.*

Indication of any immediate medical attention and special treatment needed

Note to physician

| Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 4/11
(30036470/SDS_GEN_CA/EN)

5. Fire-Fighting Measures

Suitable extinguishing media:
| water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
| water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
| carbon monoxide, tetrahydrofuran, can be emitted at > 290 °C
| Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Advice for fire-fighters

Protective equipment for fire-fighting:
| Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

| Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
| High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

| No special precautions necessary.

Environmental precautions

| Prevent releases of this product into the environment. Comprehensive instructions explaining how to prevent releases of plastics pellets, flakes, and powders to the environment during both use and disposal are provided by the industry program 'Operation Clean Sweep' (OCS).

Methods and material for containment and cleaning up

| For small amounts: Pick up with suitable appliance and dispose of.
| For large amounts: Pick up with suitable appliance and dispose of.
| Reclaim for processing if possible. Place into suitable containers for reuse or disposal in a licensed facility.

7. Handling and Storage

Precautions for safe handling

| Handle in accordance with good industrial hygiene and safety practice. Avoid inhalation of dusts/mists/vapours. Provide good ventilation of working area (local exhaust ventilation if necessary).

Protection against fire and explosion:

| The product is capable of dust explosion. Take precautionary measures against static discharges.

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 5/11
(30036470/SDS_GEN_CA/EN)

Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Wollastonite (Ca(SiO ₃))	ACGIH, US:	TWA value 1 mg/m ³ Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
	ACGIH, US:	TWA value 1 mg/m ³ Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Quartz (SiO ₂)	OSHA, US:	TWA value 0.05 mg/m ³ (Respirable dust);
	OSHA, US:	OSHA Action level 0.025 mg/m ³ (Respirable dust);
	ACGIH, US:	TWA value 0.025 mg/m ³ Respirable fraction ;

Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Wear respiratory protection if ventilation is inadequate. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions., Chemical resistant protective gloves, Suitable materials, rubber, plastic

Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 6/11
(30036470/SDS_GEN_CA/EN)

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions.
Avoid inhalation of dust. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Physical state:	solid	
Form:	pellets	
Odour:	odourless	
Odour threshold:	not applicable	
Colour:	various, depending on the colourant	
pH value:	not applicable	
melting range:	220 - 230 °C (1,013 hPa)	(DIN 53736)
Freezing point:	not applicable	
Boiling range:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable	
Flammability:	not self-igniting	(derived from flash point)
Flammability of Aerosol Products:	not applicable, the product does not form flammable aerosoles	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	350 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	1.3 - 1.8 g/cm3 (20 °C, 1,013 hPa)	(EN ISO 1183-1)
Relative density:	Study does not need to be conducted.	
Bulk density:	600 - 900 kg/m3 (20 °C, 1,013 hPa)	(DIN 53466)
Relative vapour density:	not applicable	
Partitioning coefficient n- octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 300 °C May decompose if overheated and/or subjected to prolonged heating.	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	
Solubility in water:	(20 °C, 1,013 hPa) insoluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	The product is a non-volatile solid.	

Particle characteristics

Particle size distribution:	spheroidal	
Specific Surface Area:	0.0 m²/g	(MSSA, ISO 9227)

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 7/11
(30036470/SDS_GEN_CA/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

The product is chemically stable.

Possibility of hazardous reactions

The product is chemically stable.

No hazardous reactions known.

Conditions to avoid

Temperature: > 290 degrees Celsius

See SDS section 7 - Handling and storage.

Incompatible materials

No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:

Possible decomposition products: carbon monoxide, tetrahydrofuran, terephthalic acid, carbon dioxide, Water, Gaseous products of degradation can be given off if the product is greatly overheated.

Thermal decomposition:

> 300 °C

May decompose if overheated and/or subjected to prolonged heating.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 8/11
(30036470/SDS_GEN_CA/EN)

Inhalation

| Not inhalable due to the physico-chemical properties of the product.

Assessment other acute effects

| No applicable information available.

Irritation / corrosion

| Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization

| Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard

| No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

| Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity

| Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity

| Assessment of carcinogenicity: The substance caused cancer in animal studies.

Information on: Quartz (SiO₂)

| *Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols is classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.*

| *NTP listed carcinogen*

Reproductive toxicity

| Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Teratogenicity

| Assessment of teratogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 9/11
(30036470/SDS_GEN_CA/EN)

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product.
There is a high probability that the product is not acutely harmful to aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.
Experience shows this product to be inert and non-degradable.

Elimination information

Poorly biodegradable.

Assessment of stability in water

According to structural properties, hydrolysis is not expected/probable.

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Bioaccumulation potential

The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

The product is a polymeric compound.

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 10/11
(30036470/SDS_GEN_CA/EN)

13. Disposal considerations

Waste disposal of substance:

| Incinerate in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:

| Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

TDG

| Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA

Contains registered, non-listed substance.
For import, individual registration may be required.
Can be purchased domestically from BASF.
Please contact your BASF representative.

NFPA Hazard codes:

| Health: 1 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2025/12/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in

Safety Data Sheet

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date: 2025/12/12
Version: 2.0

Page: 11/11
(30036470/SDS_GEN_CA/EN)

a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ULTRADUR® B 4300 M5 UNCOLORED POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Canada or BASF SE

Date / Revised: 2025/12/12

Version: 2.0

Date / Previous version: 2011/04/05

Previous version: 1.0

END OF DATA SHEET