



We create chemistry

Issue Date: January 22, 2026

To Whom it May Concern:

BASF **Ultramid® 66 H2 G25 V0KB1 BK3324** material plaques meet the requirements of Federal Motor Vehicle Safety Standard 49CFR571.302 (FMVSS302) and ISO 3795.

Maximum Burning Rates* = **0 mm/minute**

Nominal Thickness= **1.5 mm**

Max. Burning Rate = 102 mm/minute

Test Conditions:

Temperature and Relative Humidity during Test Specimen Preconditioning:
Dry as molded Max. 25°C Min. 21°C: Max. 60% Min. 40%

Temperature and Relative Humidity during Burning Test:
Max. 25°C Min. 21°C: Max. 60% Min. 40%

Specimen Dimensions:

Length 337 mm x Width 102 mm x Thickness 1 mm

Specimen #	Time of Burn (sec)	Extent of Burn (mm)	Rate of Burn (mm/min)
1	0	0	0
2	0	0	0
3	0	0	0
4	0	0	0
5	0	0	0
Average			0

Test Date: October 7, 2020
Test Facility: Intertek
50 Pearl Street, Pittsfield, MA 01201

*** Flammability testing is only performed during initial automotive approval submissions. ***
This test is not performed on an annual basis.

Thank you for your interest in BASF Plastic Materials.
OEM Specifications
BASF Performance Materials

BASF Corporation
1609 Biddle Avenue
Wyandotte, Michigan 48192
Tel: (734) 324-6000
www.basf.com/usa