

Elastollan® TPU

for Hose and Tube

[Elastollan.com](https://www.elastollan.com)

Elastollan® Thermoplastic Polyurethane (TPU) offers a vast portfolio to serve demanding hose and tube applications. Whether it's providing safe drinking water, supporting automation, or powering industrial applications, BASF's TPU solutions has got you covered!

Applications

- Hydraulic & Pneumatic
- Fire & Lay Flat hose
- Conveyance hose
- Sewer hose
- Agriculture
- Beverage tubing
- Medical tubing
- Industrial hose



Key Properties

- Abrasion resistant
- Flexible through a broad temperature range (-40°C to + 125°C)
- Resistant to cuts and tear propagation
- Chemical, ozone, and microbe resistant
- High burst pressure
- Kink resistant
- PVC free

Key Grades

1100 Series: Polyether chemistry that offers excellent hydrolysis resistance, cold temperature flexibility, and long-term durability even in humid environments. It also offers natural resistance to microorganisms.

Antistatic: Antistatic TPU reduces surface adhesion and minimizes the buildup of electrical charge, helping maintain cleaner, more consistent processing.

Matte Finish: TPU can be processed to give a smooth, rubber-like matte look with low gloss and strong color stability for visible parts. It maintains high performance while preserving the classic appearance of rubber.

Flame Retardant: Non-halogenated flame-retardant TPU provides outstanding mechanical properties, excellent hydrolysis and microbe resistance. These grades can achieve UL 94 V0 and V2.

Food Contact Grades: TPU food-contact materials are suited for drinking-water and sensitive applications, delivering clean and reliable performance. NSF-61 certification is achievable.

THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND ARE BASED ON BASF'S CURRENT KNOWLEDGE AND EXPERIENCE. THEY ARE PROVIDED FOR GUIDANCE ONLY, AND DO NOT CONSTITUTE THE AGREED CONTRACTUAL QUALITY OF THE PRODUCT OR A PART OF BASF'S TERMS AND CONDITIONS OF SALE. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE OF THE PRODUCT, BASF RECOMMENDS THAT THE READER CARRY OUT ITS OWN INVESTIGATIONS AND TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR ITS PARTICULAR PURPOSE PRIOR TO USE. IT IS THE RESPONSIBILITY OF THE RECIPIENT OF PRODUCT TO ENSURE THAT ANY PROPRIETARY RIGHTS AND EXISTING LAWS AND LEGISLATION ARE OBSERVED. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH HEREIN. OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. ANY DESCRIPTIONS, DESIGNS, DATA AND INFORMATION GIVEN IN THIS PUBLICATION MAY CHANGE WITHOUT PRIOR INFORMATION. THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

® = registered trademark of BASF. © 2025 BASF Corp, Florham Park, NJ 07932. All rights reserved.