

Helaian Data Keselamatan

Safety data sheet

Mukasurat (Page): 1/27

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

1. Pengenalan bahan kimia dan pembekal

BUTYLDIGLYCOL

Nama bahan kimia: Butyl diglycol

Nombor CAS: 112-34-5

Kegunaan: bahan kimia proses, pelarut

Syarikat:

BASF (Malaysia) Sdn Bhd
Lot 19.02 Level 19, 1 Powerhouse
No 1 Persiaran Bandar Utama
47800 Petaling Jaya
Selangor D.E, MALAYSIA
Nombor Telefon: +60 3 7612 1888
Nombor Telefax: +60 3 7612 1777

Maklumat kecemasan:

Nombor Kecemasan Kebangsaan
+603 7612 1999
Nombor Kecemasan Antarabangsa:
Nombor Telefon: +49 180 2273-112

2. Pengenalan Bahaya

Pengelasan bahan dan campuran:

| Kreng. Mata 2

Bagi pengelasan yang tidak ditulis dengan penuh dalam bahagian ini, teks lengkap boleh didapati di bahagian 16.

Unsur label dan pernyataan berjaga-jaga:

Piktogram:



Kata Isyarat:

Amaran

Pernyataan Bahaya:

H319 Menyebabkan kerengsaan mata yang serius.

Pernyataan Berjaga-jaga (Pencegahan):

P280 Pakai perlindungan mata.

P264 Basuh bahagian badan yang tercemar dengan sepenuhnya selepas pengendalian.

Pernyataan Berjaga-jaga (Tindak Balas):

P305 + P351 + P338 JIKA TERKENA MATA: Bilas berhati-hati dengan air selama beberapa minit. Tanggalkan kanta lekap, jika ada dan dapat dilakukan dengan mudah. Teruskan membilas.

P337 + P313 Jika kerengsaan mata berterusan: Dapatkan nasihat/rawatan perubatan.

Bahaya lain yang tidak menyebabkan pengelasan:

Jika berkenaan, maklumat yang diberikan dalam bahagian ini tentang bahaya lain tidak menyebabkan pengelasan tetapi mungkin menyumbang kepada bahaya bahan atau campuran secara keseluruhan.

Lihat seksyen 12 - Keputusan PBT dan Penilaian vPvB

3. Komposisi dan Maklumat Mengenai Ramuan Bahan Kimia

Kedadaan kimia

2-(2-butoksietoksi)etanol; dietilena glikol monobutil eter
Nombor CAS: 112-34-5

Ramuan berbahaya

2-(2-butoksietoksi)etanol; dietilena glikol monobutil eter

Kandungan (berat/berat): $\geq 75\%$ Kreng. Mata 2
 $\leq 100\%$

Nombor CAS: 112-34-5

Bagi pengelasan yang tidak ditulis dengan penuh dalam bahagian ini, teks lengkap boleh didapati di bahagian 16.

4. Langkah-Langkah Pertolongan Cemas

Nasihat am:

Tanggalkan pakaian yang tercemar.

Jika tersedut:

Tenangkan pesakit, alihkan ke tempat berudara bersih, dapatkan rawatan perubatan.

Apabila terkena kulit:

Basuh bersih-bersih dengan sabun dan air.

Apabila terkena mata:

basuh mata yang terkena bahan selama sekurang-kurangnya 15 minit dibawah air yang mengalir dengan kelopak mata dibuka, rujuk kepada pakar mata.

Apabila tertelan:

Segera berkumur, kemudian minum 200-300 ml air, dapatkan rawatan perubatan.

Nota kepada doktor:

Gejala: Maklumat, iaitu maklumat tambahan mengenai simptom dan kesan boleh termasuk di dalam fasa palabelan GHS yang tersedia ada dalam Seksyen 2 dan di dalam penaksiran Toksikologi yang tersedia ada dalam Seksyen 11.

Nota kepada doktor:

Bahaya: Maklumat, iaitu maklumat tambahan mengenai simptom dan kesan boleh termasuk di dalam fasa palabelan GHS yang tersedia ada dalam Seksyen 2 dan di dalam penaksiran Toksikologi yang tersedia ada dalam Seksyen 11. Simptom dan/atau kesan tidak diketahui setakat ini

Rawatan: Rawat mengikut gejala (nyahcemar, fungsi utama), tiada penawar khusus diketahui.

5. Langkah-Langkah Pemadaman Kebakaran

Bahan pemadam yang sesuai:

serbuk kering, semburan air, karbon dioksida, busa tahan-alkohol

Alat memadam yang tidak sesuai untuk tujuan keselamatan:

pancutan air

Maklumat tambahan:

Gunakan langkah memadam kebakaran yang sesuai dengan persekitaran.

Bahaya tertentu:

Produk mudah terbakar. Sejukkan bekas yang berbahaya dengan semburan air. Lihat MSDS bahagian 7 - Pengendalian dan Penyimpanan.

Peralatan perlindungan khusus:

Gunakan alat pernafasan serba lengkap. Alat kelengkapan perlindungan khas bagi pemadam kebakaran.

Maklumat lanjut:

Kakitangan yang tidak diperlukan hendaklah mengosongkan kawasan. Padamkan api dari jarak yang maksimum.

Memperluas pelaksanaan langkah-langkah pemadaman api ke kawasan sekitar. Lupuskan sisa kebakaran dan air pemadam api yang tercemar menurut peraturan rasmi.

6. Langkah-Langkah Pelepasan Tidak Sengaja

Perlindungan diri, kelengkapan pelindung dan tatacara kecemasan:
Kendalikan mengikut amalan kesihatan dan keselamatan industri yang baik.

Langkah berjaga-jaga untuk alam sekitar:
Pelepasan ke alam sekitar mestilah dielakkan.

Kaedah pembersihan atau penyerapan:
Kutip dengan alat yang sesuai dan lupuskan. Bahan yang tumpah mestilah dibendung, dipejalkan, dan diletakkan didalam bekas yang sesuai untuk pelupusan. Lupuskan bahan yang diserap mengikut peraturan.

Maklumat tambahan: Risiko tergelincir yang tinggi disebabkan oleh kebocoran/tumpahan produk.

Tutup atau hentikan sumber kebocoran. Tutup atau hentikan kebocoran bahan/produk dalam keadaan yang selamat.

Bungkus di dalam bekas yang bertutup rapat untuk dilupuskan.

7. Pengendalian dan Penyimpanan

Pengendalian

Elakkan daripada terkena udara/oksigen (pembentukan peroksida) Pastikan pengalihudaraan menyeluruh di kawasan simpanan dan di tempat kerja. Kendalikan mengikut amalan kesihatan dan keselamatan industri yang baik.

Perlindungan terhadap kebakaran dan letupan:
Ambil langkah berjaga-jaga terhadap luahan statik.

Penyimpanan

Maklumat lanjut tentang keadaan penyimpanan: Bekas hendaklah disimpan tertutup rapat di tempat yang kering.

8. Kawalan pendedahan dan perlindungan diri

Komponen dengan parameter kawalan tempat kerja

| 2-(2-butoksietoksi)etanol; dietilena glikol monobutil eter, 112-34-5;

Peralatan perlindungan peribadi

Perlindungan pernafasan:

Pakai perlindungan pernafasan jika pengalihudaraan tidak mencukupi. Penapis gas bagi gas/wap sebatian organik (takat didih >65°C, cth EN 14387 Jenis A)

Perlindungan tangan:

Sarung tangan pelindung kalis kimia (EN ISO 374-1)

Bahan yang sesuai juga sekiranya terkena produk secara berpanjangan dan langsung. (Syor: Indeks perlindungan 6, bersamaan > 480 minit tempoh penelapan menurut EN ISO 374-1):

getah nitril (NBR) - 0.4 mm ketebalan salutan

Arahan penggunaan pengilang hendaklah dipatuhi kerana jenisnya yang pelbagai.

Nota tambahan : Spesifikasi adalah berdasarkan ujian –ujian, data penerbitan dan maklumat dari pengeluar sarung tangan atau diambil yang serupa secara analogi. Oleh sebab banyak keadaan yang perlu dipertimbangkan (misalnya suhu), perlulah diambil kira, bahawa secara praktikalnya tempoh penggunaan sarung tangan pelindung kimia mungkin lebih pendek daripada tempoh penelapan yang ditentukan menurut ujian.

Perlindungan mata:

Kaca mata keselamatan dengan pelindung sisi (gogal berbingkai) (contohnya EN 166)

Perlindungan badan:

Perlindungan badan mesti dipilih bergantung kepada aktiviti dan pendedahan, contohnya apron, kasut perlindungan, pakaian perlindungan bahan kimia (Berdasarkan DIN-EN 465)

Langkah kebersihan dan keselamatan am:

Kendalikan mengikut amalan kesihatan dan keselamatan industri yang baik. Memakai pakaian kerja yang tertutup diperlukan sebagai tambahan kepada kelengkapan perlindungan diri yang dinyatakan.

9. Sifat Fizikal dan Kimia

Bentuk:	cecair	
Warna:	Tidak berwarna	
Bau:	hampir tiada bau	
Ambang bau:	tidak ditentukan	
nilai pH:	(20 °C)	
	neutral, terlarut campur	
pKA:	14.77	(dikira)
	(25 °C)	
	Bahan tersebut tidak boleh dipisahkan.	
takat lebur:	-68.0 °C	(lain)
	Data penulisan.	
takat didih:	230.5 °C	(lain)
	(1,013.25 hPa)	
Takat kilat:	105 °C	(ASTM D93, cawan tertutup)

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

Tahap penyejatan:

Nilai boleh dianggarkan berdasarkan
Pemalar Hukum Henry atau tekanan
wap.

Kemudahbakaran (pepejal/gas): tidak mudah terbakar (diterbitkan daripada takat kilat)
Had letupan bawah: 0.69 %(V) 46 g/m³ (udara)
(102.2 °C)

Takat bawah letupan
bahan/campuran telah ditentukan.
Takat letupan ini menerangkan suhu
bagi cecair mudah terbakar apabila
kepekatan wap tepu bercampur
dengan udara bersamaan dengan
had bawah letupan.

Had letupan atas: 5.9 %(V) 398 g/m³ (udara)
(143 °C)

Takat atas letupan bahan/campuran
telah ditentukan. Takat letupan ini
menerangkan suhu bagi cecair
mudah terbakar apabila kepekatan
wap tepu bercampur dengan udara
bersamaan dengan had atas letupan.

Suhu pencucuhan: 210 °C (DIN 51794)

Penguraian terma: Tiada penguraian jika disimpan dan
dikendalikan seperti yang
ditetapkan/dinyatakan.

pencucuhan sendiri: Berdasarkan ciri strukturnya produk
tidak dikelaskan sebagai mencucuh-
sendiri. Jenis ujian: Swanyalaan
spontan pada suhu bilik.

Kebolehan swapemanasan sendiri: tidak berkenaan,
produk ialah cecair

Bahaya letupan: Berdasarkan struktur kimia tiada
petunjuk ciri-ciri mudah meletup.

Sifat yang menggalakkan kebakaran: Berdasarkan sifat
strukturnya produk ini tidak
diklasifikasikan sebagai
pengoksida.

Tekanan Wap: 0.03 hPa (diukur)
(25 °C)
Data penulisan.

Kepekatan: dianggarkan 0.9553 g/cm³ (lain)
(20 °C)
Data penulisan.

ketumpatan relatif: 0.9553 (lain)
(20 °C)
Data penulisan.

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

Ketumpatan wap relatif (udara): 5.59 (20 °C) Lebih berat daripada udara	(dikira)
Keterlarutan dalam air: terlarut campur (20 °C)	
Keterlarutan (kualitatif) pelarut: pelarut organik terlarut	
Pekali petakan n-oktanol/air (log Pow): 1 (20 °C; nilai pH: 7)	(Garis panduan OECD 117)
Penjerapan/air-tanah: KOC: 10; log KOC: 1	(dikira)
Tegangan permukaan: Berdasarkan struktur kimia, aktiviti permukaan adalah tidak dijangka.	
Kelikatan, dinamik: 6.49 mPa.s (20 °C) Data penulisan.	
Jisim molar: 162.23 g/mol	

10. Kestabilan dan Kereaktifan

Keadaan yang perlu dielakkan:

Tiada langkah waspada khas selain menyimpan bahan kimia dengan kemas

Penguraian terma:

Tiada penguraian jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Bahan yang perlu dielakkan:

agen pengoksida yang kuat

Kakisan kepada
logam:

Tiada kesan mengakis pada logam

Tindak balas berbahaya:

Bertindak balas dengan agen pengoksida yang kuat. Bertindak balas dengan logam ringan, dengan penghasilan hidrogen.

Bahan penguraian berbahaya:

Tiada produk penguraian yang berbahaya jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Kereaktifan:

Tiada produk penguraian yang berbahaya jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Kestabilan kimia:

Produk adalah stabil jika disimpan dan dikendalikan sebagaimana

11. Maklumat Toksikologi

Ketoksikan akut

Penilaian ketoksikan akut:

Ketoksikan yang rendah selepas sekali tertelan. Ketoksikan rendah selepas terkena kulit untuk jangka pendek. Penyedutan campuran wap-udara yang diperkaya/tepu mungkin tidak menimbulkan bahaya akut.

Data eksperimen/dikira:

LD50 mencit (melalui mulut): 2,410 mg/kg (Garispanduan OECD 401)

LC50 tikus (melalui penyedutan): > 29 ppm 2 h (IRT)

Tiada kematian diperhatikan wap diuji

LD50 arnab (dermal): 2,764 mg/kg (Garispanduan OECD 402)

Kerengsaan

Penilaian kesan merengsa:

Sentuhan dengan mata boleh menyebabkan kerengsaan. Boleh menyebabkan sedikit kerengsaan pada kulit.

Data eksperimen/dikira:

Kakisan/Kerengsaan kulit arnab: tidak merengsa (Garispanduan OECD 404)

Kerosakkan/kerengsaan mata yang serius arnab: Merengsa (similar to OECD guideline 405)

Pemekaan pernafasan/kulit

Penilaian pemekaan:

Kesan pemekaan kulit tidak diperhatikan dalam kajian haiwan.

Data eksperimen/dikira:

Ujian pemaksimum tikus kasturi marmut: Tidak memeka (Garispanduan OECD 406)

Kemutagenan sel germa

Penilaian kemutagenan:

Bahan tidak mutagen dalam bakteria. Bahan tidak mutagen dalam kultur sel mamalia. Bahan tidak mutagen dalam kajian dengan mamalia.

Kekarsinogenan

Penilaian kekarsinogenan:

Tiada data diperoleh tentang aktiviti karsinogen.

Ketoksikan pembiakan

Penilaian ketoksikan pembiakan:

Keputusan kajian haiwan tidak menunjukkan kesan gangguan kesuburan.

Ketoksikan perkembangan

Penilaian keteratogenan:

Tiada petunjuk kesan ketoksikan/teratogen diperhatikan dalam kajian haiwan.

Ketoksikan khusus organ sasaran (sekali pendedahan):

Penilaian sekali STOT:

Berdasarkan maklumat yang ada, ketoksikan organ sasaran yang khusus adalah tidak dijangka selepas sekali pendedahan.

Ketoksikan dos berulang dan Ketoksikan organ sasaran tertentu (pendedahan berulang)

Penilaian ketoksikan dos berulang:

Tiada ketoksikan organ daripada bahan tertentu diperhatikan selepas diberi secara berulang kepada haiwan. Boleh menyebabkan kerengsaan ringan pada kulit jika terkena secara berpanjangan atau berulang.

Bahaya penyedutan

Tidak boleh digunakan

12. Maklumat Ekologi

Keekotoksikan

Penilaian ketoksikan akuatik:

Ada kemungkinan besar produk tidak memudaratkan organisma akuatik secara akut. Perencatan aktiviti degradasi di dalam enap cemar yang diaktifkan tidak dijangka akan berlaku semasa bahan berkepekatan rendah dimasukkan kedalam loji rawatan biologi.

Ketoksikan kepada ikan:

LC50 (96 h) 1,300 mg/l, *Lepomis macrochirus* (Garis panduan OECD 203, statik)

Data penulisan. Kepekatan nominal

Invertebrat air:

EC50 (48 h) > 100 mg/l, *Daphnia magna* (Arahan 92/69/EEC, C.2, statik)

Kepekatan nominal

Tumbuhan akuatik:

EC50 (96 h) > 100 mg/l (kadar pertumbuhan), *Scenedesmus subspicatus* (Garis panduan OECD 201, statik)

Kepekatan nominal

Mikroorganisma/Kesan ke atas enap cemar diaktifkan:

EC10 (30 min) > 1,995 mg/l, Enap cemar diaktifkan, industri (Garis panduan OECD 209, akuatik)

Kepekatan nominal

Ketoksikan kronik kepada ikan:

Tiada data diperoleh tentang ketoksikan kepada ikan.

Ketoksikan kronik kepada invertebrata akuatik:

Tiada data diperoleh tentang ketoksikan kepada daphnid.

Penilaian ketoksikan daratan:

Tiada data didapati berkenaan dengan ketoksikan daratan.

Mobiliti

Penilaian pengangkutan di antara bahagian di persekitaran:

Bahan tidak akan menyejat ke atmosfera daripada permukaan air

Penjerapan kepada fasa tanah pejal tidak dijangka

Keterusan dan boleh keterdegradasikan

Maklumat penyingkiran:

80 - 90 % BOD bagi ThOD (28 hari) (OECD 301C; ISO 9408; 92/69/EEC, C.4-F) (aerobik, Inokulum megikut keperluan MITI (OECD 301C))

Penilaian kestabilan dalam air:

Tiada data diperoleh.

Potensi Biotumpukan

Penilaian potensi bioakumulasi:

Oleh sebab pekali agihan n-oktanol/air (log Pow), tidak dijangka terakumulasi dalam organisma.

Potensi Biotumpukan:

Tiada data diperoleh.

Kesan buruk lain

Halogen terikat secara organik boleh terjerap (AOX):

Produk ini tidak mengandungi halogen yang terikat secara organik.

Maklumat tambahan

Nasihat ekotoksikologi lain:

Jangan lepaskan sisa yang tidak dirawat ke dalam air semula jadi.

13. Maklumat Pelupusan

Kod sisa adalah syor pengilang berdasarkan kegunaan khusus produk. Kegunaan lain dan rawatan pelupusan sisa khas di lokasi pelanggan mungkin memerlukan kod sisa yang berbeza.

Terus hubungi pengeluar jika ada masalah pelupusan sisa dengan kod sisa yang ditetapkan.

Pembungkusan tercemar:

Bungkusan yang tercemar hendaklah dikosongkan sejauh yang boleh; kemudian ia boleh dihantar untuk dikitar semula setelah dibasuh bersih-bersih.

14. Maklumat Pengangkutan

Pengangkutan domestik:

Tidak dikelaskan sebagai berbahaya di bawah peraturan

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

pengangkutan

Pengangkutan laut

IMDG

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan udara

IATA/ICAO

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan secara pukal menurut Lampiran II MARPOL dan IBC

Peraturan:	IBC
Penghantaran yang diluluskan:	1
Nama pencemaran:	Poly(2-8)Alkylene Glykol Monoalkyl (C1-C6)ether
Kategori pencemaran:	Z
Jenis Kapal:	3

15. Maklumat PengawalseliaanInstitut Pembersihan Amerika (ACI) Inventori Ramuan Produk Pembersihan (US)

ACI Ingredient Inventory (US) (09 2012)

tersenarai

Peraturan-Peraturan Keselamatan dan Kesihatan Pekerjaan (Pengelasan, Pelabelan dan Helaian Data Keselamatan Bahan kimia Berbahaya) 2013

Akta OSHA 1994 dan peraturan berkaitan

Akta Kualiti Alam Sekeliling 1974

Maklumat tentang peraturan-peraturan tidak meliputi kesemuanya. Peraturan-peraturan lain mungkin dikenakan kepada bahan ini.

Peraturan lain

Jika maklumat peraturan lain yang berkenaan tidak dinyatakan dibahagian lain didalam risalah data keselamatan ini, ianya akan dinyatakan bahagian ini.

16. Maklumat lain

Tarikh Penyediaan / Tarikh Penyemakan: 11.11.2025

Sumber Maklumat dan Rujukan :

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

SDS ini disediakan dengan menggunakan data dan maklumat tersimpan di dalam sistem berasaskan IT dalaman kami dan dibekalkan oleh pembekal perkhidmatan syarikat kami.

Singkatan Petunjuk:

ATE - Anggaran Ketoksikan Akut

GHS - Sistem Terharmoni Global

IATA / ICAO - Persatuan Pengangkutan Udara Antarabangsa / Organisasi Penerbangan Awam Antarabangsa

IBC - Kontena Pukul Pertengahan

IMDG - Barangan Merbahaya Kelautan Antarabangsa

LC - Kepekatan Maut

LD - Dos Maut

OECD - Organisasi Untuk Kerjasama dan Pembangunan Ekonomi

OEL - Had Pendedahan Pekerjaan

OSHA - Akta Keselamatan dan Kesihatan Pekerjaan

STOT - Ketoksikan Organ Sasaran Khusus

Teks penuh pengelasan, simbol bahaya dan pernyataan bahaya, jika dinyatakan dalam seksyen 2 atau 3:

Bhn. Ltp. T. Stab.	Bahan letup tidak stabil
Bhn. Ltp. 1.1	Bahan letup divisyen 1.1
Bhn. Ltp. 1.2	Bahan letup divisyen 1.2
Bhn. Ltp. 1.3	Bahan letup divisyen 1.3
Bhn. Ltp. 1.4	Bahan letup divisyen 1.4
Bhn. Ltp. 1.5	Bahan letup divisyen 1.5
Bhn. Ltp. 1.6	Bahan letup divisyen 1.6
Gas M. Bkr 1	Gas mudah terbakar kategori 1
Gas M. Bkr 2	Gas mudah terbakar kategori 2
Aerosol M. Bkr1	Aerosol mudah terbakar kategori 1
Aerosol M. Bkr 2	Aerosol mudah terbakar kategori 2
Cec. M. Bkr 1	Cecair mudah terbakar kategori 1
Cec. M. Bkr 2	Cecair mudah terbakar kategori 2
Cec. M. Bkr 3	Cecair mudah terbakar kategori 3
Pep. M. Bkr 1	Pepejal mudah terbakar kategori 1
Pep. M. Bkr 2	Pepejal mudah terbakar kategori 2
Gas Oks. 1	Gas mengoksida kategori 1
Cec. Oks. 1	Cecair mengoksida kategori 1
Cec. Oks. 2	Cecair mengoksida kategori 2
Cec. Oks. 3	Cecair mengoksida kategori 3
Pep. Oks. 1	Pepejal mengoksida kategori 1
Pep. Oks. 2	Pepejal mengoksida kategori 2
Pep. Oks. 3	Pepejal mengoksida kategori 3
Gas Tkn.	Gas di bawah tekanan
Swareak. A	Bahan kimia swareaktif jenis A
Swareak. B	Bahan kimia swareaktif jenis B
Swareak. CD	Bahan kimia swareaktif jenis C dan D
Swareak. EF	Bahan kimia swareaktif jenis E dan F
Swareak. G	Bahan kimia swareaktif jenis G
Cec. Pir. 1	Cecair piroforik kategori 1
Pep. Pir. 1	Pepejal piroforik kategori 1
Swapanas. 1	Bahan kimia swapanasan kategori 1
Swapanas. 2	Bahan kimia swapanasan kategori 2

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

Tdk. Bls. Air 1	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 1
Tdk. Bls. Air 2	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 2
Tdk. Bls. Air 3	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 3
Peroks. Org. A	Peroksida organik jenis A
Peroks. Org. B	Peroksida organik jenis B
Peroks. Org. CD	Peroksida organik jenis C and D
Peroks. Org. EF	Peroksida organik jenis E and F
Peroks. Org. G	Peroksida organik jenis G
Kakis. Log. 1	Mengakis logam kategori 1
Toks. Akut 1	Ketoksikan akut kategori 1
Toks. Akut 2	Ketoksikan akut kategori 2
Toks. Akut 3	Ketoksikan akut kategori 3
Toks. Akut 4	Ketoksikan akut kategori 4
Kks. Kulit 1A	Kakisan atau kerengsaan kulit kategori 1A
Kks. Kulit 1B	Kakisan atau kerengsaan kulit kategori 1B
Kks. Kulit 1C	Kakisan atau kerengsaan kulit kategori 1C
Kreng. Kulit 2	Kakisan atau kerengsaan kulit kategori 2
Kros. Mata 1	Kerosakan mata atau kerengsaan mata yang serius kategori 1
Kreng. Mata 2	Kerosakan mata atau kerengsaan mata yang serius kategori 2
Pem. Naf. 1	Pemekaan pernafasan kategori 1
Pem. Kulit 1	Pemekaan kulit kategori 1
Muta. 1A	Kemutagenan sel germa kategori 1A
Muta. 1B	Kemutagenan sel germa kategori 1B
Muta. 2	Kemutagenan sel germa kategori 2
Kars. 1A	Kekarsinogenan kategori 1A
Kars. 1B	Kekarsinogenan kategori 1B
Kars. 2	Kekarsinogenan kategori 2
Pemb. 1A	Ketoksikan pembiakan kategori 1A
Pemb. 1B	Ketoksikan pembiakan kategori 1B
Pemb. 2	Ketoksikan pembiakan kategori 2
Laktasi	Kesan ke atas atau melalui penyusuan
STOT SE 1	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 1
STOT SE 2	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 2
STOT SE 3	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 3
STOT RE 1	Ketoksikan organ sasaran khusus - pendedahan berulang kategori 1
STOT RE 2	Ketoksikan organ sasaran khusus - pendedahan berulang kategori 2
Bhy. Asp.	Bahaya aspirasi kategori 1
Akuatik Akut 1	Berbahaya kepada persekitaran akuatik – bahaya akut kategori 1
Akuatik Kronik 1	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 1
Akuatik Kronik 2	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 2
Akuatik Kronik 3	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 3
Akuatik Kronik 4	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 4
Ozon	Berbahaya bagi lapisan ozon kategori 1

Garis menegak pada margin sebelah kiri tangan menunjukkan pindaan dari versi sebelumnya.

Data yang terdapat dalam risalah data keselamatan ini adalah berdasarkan pengetahuan dan pengalaman kami, dan menerangkan tentang produk yang berkaitan dengan keperluan keselamatan sahaja. Data tidak menyatakan ciri produk (spesifikasi produk). Data dalam risalah data keselamatan ini juga tidak menyatakan apa-apa ciri khusus atau kesesuaian produk yang dipersetujui untuk apa-apa

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

tujuan tertentu. Penerima produk bertanggungjawab untuk memastikan bahawa apa-apa hak pemilikan serta undang-undang dan perundangan sedia ada dipatuhi.

1. Identification of the chemical and of the supplier

BUTYLDIGLYCOL

Chemical name: Butyl diglycol

CAS Number: 112-34-5

Use: process chemical, solvent(s)

Company:

BASF (Malaysia) Sdn Bhd
Lot 19.02 Level 19, 1 Powerhouse
No 1 Persiaran Bandar Utama
47800 Petaling Jaya
Selangor D.E, MALAYSIA
Telephone: +60 3 7612 1888
Telefax number: +60 3 7612 1777

Emergency information:

National emergency number:

+603 7612 1999

International emergency number:

Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

Eye Irrit. 2

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements and precautionary statement:

Pictogram:



Signal Word:

Warning

Hazard Statement:

H319

Causes serious eye irritation.

Precautionary Statements (Prevention):

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): BUTYLDIGLYCOL

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

P280	Wear eye protection.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
See section 12 - Results of PBT and vPvB assessment.

3. Composition/information on ingredients

Chemical nature

Butyl diglycol

CAS Number: 112-34-5

Hazardous ingredients

Butyl diglycol

Content (W/W): >= 75 % - <= 100 %	Eye Irrit. 2
CAS Number: 112-34-5	

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Note to physician:

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

Specific hazards:

The product is combustible. Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Handle in accordance with good industrial hygiene and safety practice.

Environmental precautions:

Discharge into the environment must be avoided.

Methods for cleaning up or taking up:

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

Additional information: High risk of slipping due to leakage/spillage of product.

Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

7. Handling and Storage

Handling

Prevent contact with air/oxygen (formation of peroxide). Ensure thorough ventilation of stores and work areas. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure controls and personal protection

Components with occupational exposure limits

| Butyl diglycol, 112-34-5;

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

nitrile rubber (NBR) - 0.4 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	colourless	
Odour:	almost odourless	
Odour threshold:	not determined	
pH value:	(20 °C) neutral, miscible	
pKA:	14.77 (25 °C) The substance does not dissociate.	(calculated)
Melting point:	-68.0 °C Literature data.	(other)
Boiling point:	230.5 °C (1,013.25 hPa)	(other)
Flash point:	105 °C	(ASTM D93, closed cup)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability (solid/gas):	hardly combustible	(derived from flash point)
Lower explosion limit:	0.69 %(V) 46 g/m ³ (102.2 °C) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit.	(air)
Upper explosion limit:	5.9 %(V) 398 g/m ³ (143 °C) The upper explosion point of the substance/mixture has been determined. This explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the upper explosion limit.	(air)
Ignition temperature:	210 °C	(DIN 51794)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Self ignition:	Based on its structural properties the product is not classified as self- igniting.	Test type: Spontaneous self- ignition at room-temperature.

Self heating ability:	not applicable, the product is a liquid	
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	
Vapour pressure:	0.03 hPa (25 °C) Literature data.	(measured)
Density:	approx. 0.9553 g/cm3 (20 °C) Literature data.	(other)
Relative density:	0.9553 (20 °C) Literature data.	(other)
Relative vapour density (air):	5.59 (20 °C) Heavier than air.	(calculated)
Solubility in water:	miscible (20 °C)	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Pow):	1 (20 °C; pH value: 7)	(OECD Guideline 117)
Adsorption/water - soil:	KOC: 10; log KOC: 1	(calculated)
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Viscosity, dynamic:	6.49 mPa.s (20 °C) Literature data.	
Molar mass:	162.23 g/mol	

10. Stability and Reactivity

Conditions to avoid:

No special precautions other than good housekeeping of chemicals.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:

strong oxidizing agents

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

Reacts with strong oxidizing agents. Reacts with light metals, with evolution of hydrogen.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:

Of low toxicity after single ingestion. Of low toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Experimental/calculated data:

LD50 mouse (oral): 2,410 mg/kg (OECD Guideline 401)

LC50 rat (by inhalation): > 29 ppm 2 h (IRT)

No mortality was observed. The vapour was tested.

LD50 rabbit (dermal): 2,764 mg/kg (OECD Guideline 402)

Irritation

Assessment of irritating effects:

Eye contact causes irritation. May cause slight irritation to the skin.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (OECD Guideline 404)

Serious eye damage/irritation rabbit: Irritant. (similar to OECD guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (OECD Guideline 406)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

No data was available concerning carcinogenic activity.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure):

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No substance-specific organotoxicity was observed after repeated administration to animals.

Prolonged or repeated contact may cause mild skin irritation.

Aspiration hazard

not applicable

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 1,300 mg/l, *Lepomis macrochirus* (OECD Guideline 203, static)

Literature data. Nominal concentration.

Aquatic invertebrates:

EC50 (48 h) > 100 mg/l, *Daphnia magna* (Directive 92/69/EEC, C.2, static)

Nominal concentration.

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

Aquatic plants:

EC50 (96 h) > 100 mg/l (growth rate), *Scenedesmus subspicatus* (OECD Guideline 201, static)

Nominal concentration.

Microorganisms/Effect on activated sludge:

EC10 (30 min) > 1,995 mg/l, activated sludge, industrial (OECD Guideline 209, aquatic)

Nominal concentration.

Chronic toxicity to fish:

No data available regarding toxicity to fish.

Chronic toxicity to aquatic invertebrates:

No data available regarding toxicity to daphnids.

Assessment of terrestrial toxicity:

No data available concerning terrestrial toxicity.

Mobility

Assessment transport between environmental compartments:

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

Persistence and degradability

Elimination information:

80 - 90 % BOD of the ThOD (28 d) (OECD 301C; ISO 9408; 92/69/EWG, C.4-F) (aerobic, Inoculum conforming to MITI requirements (OECD 301C))

Assessment of stability in water:

No data available.

Bioaccumulation potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

Other adverse effects

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters.

13. Disposal Information

The waste codes are manufacturer's recommendations based on the designated use of the product. Other use and special waste disposal treatment on customer's location may require different waste-code assignments.

Contact the manufacturer directly in case of waste disposal problems with the assigned waste-codes.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transportation Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation: IBC

Shipment approved: 1

Pollution name: Poly(2-8)Alkylene Glykol Monoalkyl (C1-C6)ether

Pollution category: Z

Ship Type: 3

15. Regulatory Information

American Cleaning Institute (ACI) Cleaning Product Ingredient Inventory (US)

ACI Ingredient Inventory (US) (09 2012)

listed

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

OSHA 1994 and relevant regulations

Environmental Quality Act, 1974

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Date of Preparation / Date of Revision: 11.11.2025

Information Source and References:

This SDS is prepared using data and information saved in our internal IT-based system and supplied by our company's service providers.

Key Abbreviations:

ATE - Acute Toxicity Estimates

GHS - Globally Harmonized System

IATA / ICAO - International Air Transport Association / International Civil Aviation Organization

IBC - Intermediate Bulk Container

IMDG - International Maritime Dangerous Goods

LC - Lethal Concentration

LD - Lethal Dose

OECD - Organisation for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OSHA - Occupational Safety and Health Act

STOT - Specific Target Organ Toxicity

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Unst. Expl.	Unstable explosives
Expl. 1.1	Explosives division 1.1
Expl. 1.2	Explosives division 1.2
Expl. 1.3	Explosives division 1.3
Expl. 1.4	Explosives division 1.4
Expl. 1.5	Explosives division 1.5
Expl. 1.6	Explosives division 1.6
Flam. Gas 1	Flammable gases category 1
Flam. Gas 2	Flammable gases category 2
Flam. Aerosol 1	Flammable aerosols category 1
Flam. Aerosol 2	Flammable aerosols category 2
Flam. Liq. 1	Flammable liquids category 1
Flam. Liq. 2	Flammable liquids category 2
Flam. Liq. 3	Flammable liquids category 3
Flam. Sol. 1	Flammable solids category 1
Flam. Sol. 2	Flammable solids category 2
Ox. Gas 1	Oxidizing gases category 1
Ox. Liq. 1	Oxidizing liquids category 1
Ox. Liq. 2	Oxidizing liquids category 2
Ox. Liq. 3	Oxidizing liquids category 3
Ox. Sol. 1	Oxidizing solids category 1
Ox. Sol. 2	Oxidizing solids category 2
Ox. Sol. 3	Oxidizing solids category 3
Press. Gas	Gases under pressure
Self-react. A	Self-reactive chemicals type A

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

Self-react. B	Self-reactive chemicals type B
Self-react. CD	Self-reactive chemicals type C and D
Self-react. EF	Self-reactive chemicals type E and F
Self-react. G	Self-reactive chemicals type G
Pyr. Liq. 1	Pyrophoric liquids category 1
Pyr. Sol. 1	Pyrophoric solids category 1
Self-heat. 1	Self-heating chemicals category 1
Self-heat. 2	Self-heating chemicals category 2
Water-react. 1	Chemicals which, if in contact with water, emits flammable gases category 1
Water-react. 2	Chemicals which, if in contact with water, emits flammable gases category 2
Water-react. 3	Chemicals which, if in contact with water, emits flammable gases category 3
Org. Perox. A	Organic peroxides type A
Org. Perox. B	Organic peroxides type B
Org. Perox. CD	Organic peroxides type C and D
Org. Perox. EF	Organic peroxides type E and F
Org. Perox. G	Organic peroxides type G
Met. Corr. 1	Corrosive to metals category 1
Acute Tox. 1	Acute toxicity category 1
Acute Tox. 2	Acute toxicity category 2
Acute Tox. 3	Acute toxicity category 3
Acute Tox. 4	Acute toxicity category 4
Skin Corr. 1A	Skin corrosion or irritation category 1A
Skin Corr. 1B	Skin corrosion or irritation category 1B
Skin Corr. 1C	Skin corrosion or irritation category 1C
Skin Irrit. 2	Skin corrosion or irritation category 2
Eye Dam. 1	Serious eye damage or eye irritation category 1
Eye Irrit. 2	Serious eye damage or eye irritation category 2
Resp. Sens. 1	Respiratory sensitization category 1
Skin Sens. 1	Skin sensitization category 1
Muta. 1A	Germ cell mutagenicity category 1A
Muta. 1B	Germ cell mutagenicity category 1B
Muta. 2	Germ cell mutagenicity category 2
Carc. 1A	Carcinogenicity category 1A
Carc. 1B	Carcinogenicity category 1B
Carc. 2	Carcinogenicity category 2
Repr. 1A	Reproductive toxicity category 1A
Repr. 1B	Reproductive toxicity category 1B
Repr. 2	Reproductive toxicity category 2
Lact.	Effect on or via lactation
STOT SE 1	Specific target organ toxicity – single exposure category 1
STOT SE 2	Specific target organ toxicity – single exposure category 2
STOT SE 3	Specific target organ toxicity – single exposure category 3
STOT RE 1	Specific target organ toxicity – repeated exposure category 1
STOT RE 2	Specific target organ toxicity – repeated exposure category 2
Asp. Haz.	Aspiration hazard category 1
Aquatic Acute 1	Hazardous to the aquatic environment – acute hazard category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – chronic hazard category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – chronic hazard category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – chronic hazard category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – chronic hazard category 4
Ozone	Hazardous to the ozone layer category 1

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 11.11.2025

Versi (Version): 9.0

Produk (Product): **BUTYLDIGLYCOL**

(30034744/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 12.11.2025

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.