



Benjamin Moore®

SAFETY DATA SHEET

Revision Date: 28-Aug-2023

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name HP ALIPHATIC URETHANE - CATALYST
Product Code HP5000-90
Alternate Product Code UF5790
Product Class CATALYST
Color Light yellow
Recommended use CATALYST
Restrictions on use No information available

Manufactured For
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.benjaminmoore.com

Emergency Telephone
CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2

Label elements

Danger

Hazard statements

Harmful if inhaled
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction

May cause respiratory irritation. May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure



Appearance liquid

Odor slight, odorless

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
If experiencing respiratory symptoms: Call a POISON CENTER or doctor

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Hexane, 1,6-diisocyanato-, homopolymer	28182-81-2	95 - 100

Hexamethylene-1,6-diisocyanate	822-06-0	0.1 - 0.5
--------------------------------	----------	-----------

4. FIRST AID MEASURES

Description of first aid measures

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous combustion products	Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.
Specific Hazards Arising From The Chemical	Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may

rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.

Sensitivity to mechanical impact

No

Sensitivity to static discharge

Yes

Flash Point Data**Flash point (°F)**

460

Flash Point (°C)

238

Method

PMCC

Flammability Limits In Air**Lower flammability limit:**

No data available

Upper flammability limit:

No data available

NFPA**Health hazards**

2

Flammability

1

Stability

1

Special:

Not Applicable

NFPA Legend

0 - Not Hazardous

1 - Slightly

2 - Moderate

3 - High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions

See Section 12 for additional Ecological Information.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

Technical measures/Precautions

Ensure adequate ventilation. Use only where airflow will keep vapors from building up in or near the work area in adjoining rooms. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids.

Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. All equipment should be non-sparking and explosion proof. Use explosion proof electrical equipment for ventilation, lighting and material handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Hexamethylene-1,6-diisocyanate	TWA: 0.005 ppm	-

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Appropriate engineering controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles.

Skin Protection

Long sleeved clothing. Protective gloves.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a

technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	slight odorless
Odor Threshold	No information available
Density (lbs./gal)	9.6 - 10.0
Specific Gravity	1.15 - 1.21
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Relative vapor density	No information available
Wt. % Solids	90 - 100
Vol. % Solids	90 - 100
Wt. % Volatiles	0 - 10
Vol. % Volatiles	0 - 10
VOC Regulatory Limit (g/L)	< 250
Boiling Point (°F)	No information available
Boiling Point (°C)	No information available
Freezing point (°F)	No information available
Freezing Point (°C)	No information available
Flash point (°F)	460
Flash Point (°C)	238
Method	PMCC
Flammability (solid, gas)	Not applicable
Upper flammability limit:	No data available
Lower flammability limit:	No data available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	No data available
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions to avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated

temperature.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors.

Possibility of hazardous reactions

None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information**Information on likely routes of exposure**

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Contact with eyes may cause irritation.
Skin contact	May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
Inhalation	Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
Sensitization	Respiratory sensitizer May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure if inhaled.
STOT - single exposure	May cause disorder and damage to the, Respiratory system, Lungs.
Other adverse effects	No information available.
Aspiration Hazard	May be harmful if swallowed and enters airways. Small amounts of this product

aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 99999 mg/kg
 ATEmix (inhalation-dust/mist) 4.6 mg/l
 ATEmix (inhalation-vapor) 11 mg/l

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane, 1,6-diisocyanato-, homopolymer 28182-81-2	-	-	= 18500 mg/m ³ (Rat) 1 h
Hexamethylene-1,6-diisocyanate 822-06-0	= 746 mg/kg (Rat)	= 7001 mg/kg (Rat)	= 0.06 mg/L (Rat) 4 h

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

Legend

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

Not classified

Component Information**Acute Toxicity to Fish**

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

Hexane, 1,6-diisocyanato-, homopolymer

EC50: > 1000 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS**Waste Disposal Method**

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION**DOT**

Not regulated

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION**International Inventories****TSCA: United States**

Yes - All components are listed or exempt.

DSL: Canada

Yes - All components are listed or exempt.

Federal Regulations**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>Hazardous Air Pollutant (HAP)</u>
Hexamethylene-1,6-diisocyanate	822-06-0	0.1 - 0.5	Listed

US State Regulations**California Proposition 65**

WARNING: Cancer and Reproductive Harm— www.P65Warnings.ca.gov

U.S. State Right-to-Know Regulations

<u>Chemical name</u>	<u>Massachusetts</u>	<u>New Jersey</u>	<u>Pennsylvania</u>
Hexamethylene-1,6-diisocyanate	X	X	

Legend

X - Listed

16. OTHER INFORMATION

HMIS

Health hazards	2*
Flammability	1
Reactivity:	1
Personal protection	-

HMIS Legend

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or

risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 28-Aug-2023
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet