



SAFETY DATA SHEET

Revision Date: 22-Jun-2023

Revision Number: 6

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	COROTECH COMMAND WATERBORNE ACRYLIC URETHANE SATIN BRONZETONE
Product Code	V39262
Alternate Product Code	V39262
Product Class	Water thinned paint
Color	Bronze
Recommended use	Paint
Restrictions on use	No information available

Manufacturer

Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.benjaminmoore.com/Corotech

Emergency Telephone

CHEMTRAC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B

Label elements

Danger

Hazard statements

May cause an allergic skin reaction
May cause genetic defects
Suspected of causing cancer
May damage fertility or the unborn child



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%
Kaolin	1332-58-7	1 - 5
Ethylene glycol mono-2-ethylhexyl ether	1559-35-9	1 - 5
Zinc phosphate	7779-90-0	1 - 5

Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	0.5 - 1
Carbon black	1333-86-4	0.1 - 0.5
Ammonium hydroxide	1336-21-6	0.1 - 0.5
Alcohols, C12 - 14, ethoxylated	68439-50-9	0.1 - 0.5
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl- ylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-h ydroxy-	104810-48-2	0.1 - 0.5
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.1 - 0.5
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl- ylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl- ylethyl)- 4-hydroxyphenyl]-1-oxoprop	104810-47-1	0.1 - 0.5
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	41556-26-7	0.1 - 0.5

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F) 250

Flash Point (°C) 121

Method PMCC

Flammability Limits In Air

Lower flammability limit: Not applicable

Upper flammability limit: Not applicable

NFPA

Health hazards 2

Flammability 1

Stability 0

Special: Not Applicable

NFPA Legend

0 - Not Hazardous

1 - Slightly

2 - Moderate

3 - High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautions See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Kaolin	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	15 mg/m ³ - TWA 5 mg/m ³ - TWA
Iron oxide	TWA: 5 mg/m ³ respirable particulate matter	10 mg/m ³ - TWA 15 mg/m ³ - TWA Rouge 5 mg/m ³ - TWA Rouge
Titanium dioxide	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	15 mg/m ³ - TWA
Carbon black	TWA: 3 mg/m ³ inhalable particulate matter	3.5 mg/m ³ - TWA
Ammonium hydroxide	STEL: 35 ppm TWA: 25 ppm	-

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin Protection

Protective gloves and impervious clothing.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Odor

little or no odor

Odor Threshold

No information available

Density (lbs./gal)

9.1 - 9.5

Specific Gravity

1.09 - 1.14

pH

No information available

Viscosity (cps)

No information available

Solubility(ies)

No information available

Water solubility

No information available

Evaporation Rate

No information available

Vapor pressure @20 °C (kPa)

No information available

Relative vapor density	No information available
Wt. % Solids	40 - 50
Vol. % Solids	30 - 40
Wt. % Volatiles	50 - 60
Vol. % Volatiles	60 - 70
VOC Regulatory Limit (g/L)	< 150
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing point (°F)	32
Freezing Point (°C)	0
Flash point (°F)	250
Flash Point (°C)	121
Method	PMCC
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	May cause slight irritation.
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	May cause an allergic skin reaction
Neurological Effects	No information available.
Mutagenic Effects	Suspected of causing genetic defects.
Reproductive Effects	May damage fertility or the unborn child.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	31696 mg/kg
ATEmix (inhalation-dust/mist)	120.6 mg/l

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Ethylene glycol mono-2-ethylhexyl ether 1559-35-9	= 3080 mg/kg (Rat)	= 2120 mg/kg (Rabbit) = 2120 µL/kg (Rabbit)	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Iron oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	> 5050 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	-
Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester 41556-26-7	= 2615 mg/kg (Rat)	-	-

Chronic Toxicity**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen::

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed

Titanium dioxide	Carcinogen		
Carbon black	2B - Possible Human Carcinogen		Listed

- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer
NTP - National Toxicity Program
OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester
LC50: 0.22 mg/L (water flea - 48 hr.)

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

<u>Chemical name</u>	<u>CAS No</u>	<u>Weight-%</u>	<u>CERCLA/SARA 313 (de minimis concentration)</u>
Zinc phosphate	7779-90-0	1 - 5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

 **WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

U.S. State Right-to-Know Regulations

Chemical name	Massachusetts	New Jersey	Pennsylvania
Water			X
Kaolin	X	X	X
Zinc phosphate		X	X
Iron oxide	X	X	X
Carbon black	X	X	X
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester		X	

Legend

X - Listed

16. OTHER INFORMATION

HMIS

Health hazards	2*
Flammability	1
Reactivity:	0
Personal protection	-

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Issuing Date 03-Dec-2021

Revision Date: 22-Jun-2023
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet