

Safety Data Sheet (SDS)

Section 1 - Chemical Product and Company Information

Product Name: Wash and Wax Product Code: BWASHWAX-5



WARNING

Hazard Statements:
Causes Eye Irritation

Recommended use of the chemical restriction on use:

Relevant uses (Industrial User): Soap Wash, protective Wax finish for cars, truck and trailers

Name, US address, and US telephone number of the chemical manufacturer or other responsible parties:

THE BERKEBILE OIL COMPANY
PO BOX 715, 1216 RED BRANT RD,
SOMERSET, PA 15501 - USA
PHONE: (814)443-1656 - FAX (724)625-1640
Info@Berkebileoil.com
www.BerkebileOil.com

Product Use: Hard surface cleaner
Not recommended for: Children

FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT CONTACT
CHEMTREC (800) 262-8200 CCN# 8297:

Section 2 - Hazards

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

GHS Ratings:

Eye corrosive

2B

Mild eye irritant: Subcategory 2B, Reversible in 7 days

GHS Hazards

H320

Causes eye irritation

GHS Precautions

P233

Keep container tightly closed

P260

Do not breathe dust/fume/gas/mist/vapours/spray

P264

Wash ... thoroughly after handling

P280

Wear protective gloves/protective clothing/eye protection/face protection

P363

Wash contaminated clothing before reuse

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P405

Store locked up

P403+P235

Store in a well ventilated place. Keep cool

Signal Word: Warning



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product.

Section 3 - Composition

Chemical Name	CAS number	Weight Concentration %
dodecyl benzene sulfonic acid	68584-22-5	10.00% - 20.00%
Alcohols, C9-11, ethoxylated	68439-46-3	1.00% - 5.00%
Sodium Hydroxide	1310-73-2	1.00% - 5.00%

Section 4 - First Aid Measures

INHALATION - Take affected persons out into the fresh air. Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. Rinse until skin no longer feels slippery. If skin irritation continues, consult a doctor.

INGESTION - If material is ingested, rinse out mouth with water and seek immediate medical attention. Do not induce vomiting but if vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs. If victim is conscious drink large quantities of water to dilute stomach contents.

Notes to Physician: If swallowed, gastric irrigation with added, activated carbon. If swallowed or in case of vomiting, danger of entering the lungs. If necessary oxygen respiration treatment.

Section 5 - Fire Fighting Measures

Flash Point: None

LEL:

UEL:

EXTINGUISHING MEDIA: This product is not inherently flammable. Use media appropriate for surrounding fire.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Keep nonessential personnel away from the contaminated area. Spilled product may be very slippery!

SMALL SPILLS: Ventilate the contaminated area. Mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Avoid aerosolizing product. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Do not store together with acids.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
dodecyl benzene sulfonic acid 68584-22-5	Not Established	Not Established	Not Established
Alcohols, C9-11, ethoxylated 68439-46-3	Not Established	Not Established	Not Established
Sodium Hydroxide 1310-73-2	OEL Table z-1 TWA 2.00 mg/m3	TLV 2 mg/m3 (Ceiling)	NIOSH 2.00 mg/m3 (Ceiling)

ENGINEERING:

VENTILATION: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Use mechanical ventilation to reduce buildup of vapors in enclosed areas.

ADMINISTRATIVE CONTROLS: Read SDS and follow recommended procedures.

PROTECTIVE EQUIPMENT: Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. If needed, use a NIOSH/MSHA approved respirator equipped with a full facepiece, organic vapor cartridges, and high-efficiency, particulate air (HEPA) filters. Do not use respirators beyond their capabilities. FOR EMERGENCIES AND UNKNOWN CONCENTRATIONS, use supplied-air respiratory protection or a positive-pressure, self-contained breathing apparatus (SCBA).

CONTAMINATED EQUIPMENT: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance: Almost colorless liquid Vapor Pressure: 16.8 mmHg Vapor Density: 0.7 Specific Gravity: 1.02 Freezing point: No Data Boiling range: 100°C Evaporation rate: No Data	Odor: Mild Odor threshold: No Data pH: 8 - 10 Melting point: No Data Solubility: No Data Flash point: None Flammability: No Data
---	---

Explosive Limits: No Data Autoignition temperature: No Data Viscosity: No Data	Partition coefficient (n- octanol/water): Decomposition temperature: No Data Grams VOC less water: No Data
---	---

Section 10 - Stability and Reactivity

Stability: Hazardous polymerization will not occur.

STABLE

Components of this mixture are incompatible with the following materials: Acids and soft metals like aluminum. .

This mixture is likely to exhibit the following combustion products:

Oxides of carbon and sulfur

Section 11 - Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 2,395mg/kg

Component Toxicity

68584-22-5	dodecyl benzene sulfonic acid Oral LD50: 501 mg/kg (rat) Dermal LD50: 2,001 mg/kg (rabbit)
68439-46-3	Alcohols, C9-11, ethoxylated Oral LD50: 2,001 mg/kg (rat) Dermal LD50: 3,300 mg/kg (rat)

Exposure to this material may affect the following organs:

Effects of Overexposure

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

Section 12 - Ecological Information

Ecological information: No data found.

Component Ecotoxicity

dodecyl benzene sulfonic acid	Algae EC50 Algae 47.3 mg/l, 72 hours Crustacea EC50 Daphnia 2.4 mg/l, 48 hours Fish LC50 Fish 1.67 mg/l, 96 hours
-------------------------------	---

Alcohols, C9-11, ethoxylated

Toxicity to fish - Components

Alcohols, C9-11, ethoxylated LC50 (96 h) : 1 - 10 mg/l Species : Fathead minnow (Pimephales promelas).

Toxicity to daphnia - Components

Alcohols, C9-11, ethoxylated EC50 (48 h) : 1 - 10 mg/l Species : Daphnia

Toxicity to algae - Components

Alcohols, C9-11, ethoxylated ErC50 (96 h) : 1 - 10 mg/l Species : Algae.

Sodium Hydroxide

Toxicity to fish LC50 - Gambusia affinis (Mosquito fish) - 125 mg/l - 96 h

LC50 - Oncorhynchus mykiss (rainbow trout) - 45.4 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates Immobilization EC50 - Daphnia (water flea) - 40.38 mg/l - 48 h

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
US DOT	Non Regulated			

Section 15 - Regulatory Information

Additional regulatory listings, where applicable.

The following chemicals are on the NJ RTK list:

1310-73-2 Sodium Hydroxide 1 to 5 %

The following chemicals are on the NY RTK list

1310-73-2 Sodium Hydroxide 1 to 5 %

The following chemicals are on the PA RTK list

1310-73-2 Sodium Hydroxide 1 to 5 %

Country

Canada

US

Regulation

Canadian Domestic Substances List

Toxic Substances Control Act

All Components Listed

Yes

Yes

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH	<input type="text"/>	1
FLAMMABILITY	<input type="text"/>	0
PHYSICAL HAZARD	<input type="text"/>	0
PERSONAL PROTECTION	<input type="text"/>	

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard

0 = INSIGNIFICANT


1 = SLIGHT

2 = MODERATE

3 = HIGH

4 = SEVERE

National Fire Protection Association (NFPA)



DISCLAIMER AND NON-WARRANTY: This Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information came from raw material suppliers, regulatory databases, and/or third parties with expertise in this area. This information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. No warranties of any kind, either expressed or implied, including warranties of the accuracy of the information presented and the suitability of a product for a particular purpose

Reviewer Revision

Date Prepared: 6/9/2015