

# SAFETY DATA SHEET



## DOT 5 Silicone Brake Fluid

Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

### SECTION 1. IDENTIFICATION

Product name                    DOT 5 Silicone Brake Fluid

Product code                    B5900, B5901, B5902, B59055

#### Manufacturer or supplier's details

Company name of supplier    The Berkebile Oil CO. INC.

Address                        1216 Red Brant Road  
Somerset, PA 15501

Telephone                      1 (800) 732-9235

Emergency telephone         : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

#### Recommended use of the chemical and restrictions on use

Recommended use             : fluids and additives

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Carcinogenicity             : Category 2

#### GHS label elements

Hazard pictograms            :



Signal Word                    : Warning

Hazard Statements            : H351 Suspected of causing cancer.

Precautionary Statements    :

#### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

#### Storage:

P405 Store locked up.

#### Disposal:

# SAFETY DATA SHEET



## DOT 5 Silicone Brake Fluid

Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone

### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Tributyl phosphate	126-73-8	>= 1 - < 5

## SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Suspected of causing cancer.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray



## DOT 5 Silicone Brake Fluid

Version  
1.0Revision Date:  
6/21/2017SDS Number:  
B590201

Date of last issue: 6/21/2017

Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Silicon oxides  
Formaldehyde  
Oxides of phosphorus
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

# SAFETY DATA SHEET

## DOT 5 Silicone Brake Fluid



Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid inhalation of vapor or mist.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Tributyl phosphate	126-73-8	TWA (Inhalable fraction and vapor)	5 mg/m <sup>3</sup>	ACGIH
		TWA	0.2 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1

- Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide



## DOT 5 Silicone Brake Fluid

Version  
1.0Revision Date:  
6/21/2017SDS Number:  
B590201

Date of last issue: 6/21/2017

adequate protection.

<b>II Hand protection</b> <b>Material</b>	: Chemical-resistant gloves
<b>Remarks</b>	: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
<b>Eye protection</b>	: Wear the following personal protective equipment: Safety glasses
<b>Skin and body protection</b>	: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
<b>Hygiene measures</b>	: Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ( <a href="http://www.SEHSC.com">www.SEHSC.com</a> ) or contact the Dow Corning customer service group.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: purple
Odor	: slight
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 35 °C

# SAFETY DATA SHEET



## DOT 5 Silicone Brake Fluid

Version 1.0      Revision Date: 6/21/2017      SDS Number: B590201      Date of last issue: 6/21/2017

---

Flash point	:	> 101.1 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	0.95
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	20 cSt
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents



## DOT 5 Silicone Brake Fluid

Version  
1.0Revision Date:  
6/21/2017SDS Number:  
B590201

Date of last issue: 6/21/2017

### Hazardous decomposition products

Thermal decomposition : Formaldehyde

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

- Inhalation
- Skin contact
- Ingestion
- Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Ingredients:

#### Tributyl phosphate:

Acute oral toxicity	: LD50 (Rat): 1,552 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 4.242 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	: LD50 (Rabbit): > 3,100 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

Not classified based on available information.

### Ingredients:

#### Tributyl phosphate:

Result: Skin irritation
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

### Serious eye damage/eye irritation

Not classified based on available information.

### Ingredients:

#### Tributyl phosphate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405



## DOT 5 Silicone Brake Fluid

Version 1.0      Revision Date: 6/21/2017      SDS Number: B590201      Date of last issue: 6/21/2017

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Ingredients:**

##### **Tributyl phosphate:**

Routes of exposure: Skin contact  
Species: Guinea pig  
Result: negative

### **Germ cell mutagenicity**

Not classified based on available information.

#### **Ingredients:**

##### **Tributyl phosphate:**

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	:	Species: Rat Application Route: Ingestion Result: negative

### **Carcinogenicity**

Suspected of causing cancer.

#### **Ingredients:**

##### **Tributyl phosphate:**

Species: Rat  
Application Route: Ingestion  
Exposure time: 24 month(s)  
Result: positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.



## DOT 5 Silicone Brake Fluid

Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

### **Reproductive toxicity**

Not classified based on available information.

#### **Ingredients:**

##### **Tributyl phosphate:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Not classified based on available information.

### **Repeated dose toxicity**

#### **Ingredients:**

##### **Tributyl phosphate:**

Species: Mouse
NOAEL: > 500 ppm
Application Route: Ingestion
Exposure time: 3 Months

### **Aspiration toxicity**

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Ingredients:**

##### **Tributyl phosphate:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 11 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3.65 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): 2.8 mg/l Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 0.92 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET



## DOT 5 Silicone Brake Fluid

Version 1.0      Revision Date: 6/21/2017      SDS Number: B590201      Date of last issue: 6/21/2017

Toxicity to fish (Chronic toxicity)	:	NOEC (Danio rerio (zebra fish)): 13.5 mg/l Exposure time: 10 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 1.3 mg/l Exposure time: 21 d

### Persistence and degradability

#### Ingredients:

##### **Tributyl phosphate:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 89 % Exposure time: 28 d Method: OECD Test Guideline 301E
------------------	---	---

### Bioaccumulative potential

#### Ingredients:

##### **Tributyl phosphate:**

Bioaccumulation	:	Species: Cyprinus carpio (Carp) Bioconcentration factor (BCF): 6.9 - 20
Partition coefficient: n-octanol/water	:	log Pow: 4

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Resource Conservation and Recovery Act (RCRA)	:	This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

#### **International Regulation**

#### **UNRTDG**

# SAFETY DATA SHEET

## DOT 5 Silicone Brake Fluid



Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

Not regulated as a dangerous good

### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Chronic Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9
Di(2-ethylhexyl) sebacate	122-62-3
Tributyl phosphate	126-73-8
Triethylene glycol monomethyl ether	112-35-6

**California Prop. 65** This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### California List of Hazardous Substances

II	Tributyl phosphate	126-73-8
----	--------------------	----------

#### California Permissible Exposure Limits for Chemical Contaminants

II	Tributyl phosphate	126-73-8
----	--------------------	----------

#### The ingredients of this product are reported in the following inventories:

REACH All ingredients (pre-)registered or exempt.

TSCA All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

# SAFETY DATA SHEET

## DOT 5 Silicone Brake Fluid



Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

AICS

All ingredients listed or exempt.

ENCS/ISHL

All components are listed on ENCS/ISHL or exempted from inventory listing.


DSL

All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

### SECTION 16. OTHER INFORMATION

#### Further information

NFPA:



HMIS III:

HEALTH	1*
FLAMMABILITY	1
PHYSICAL HAZARD	0

Special hazard.

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

#### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - Interna-



## DOT 5 Silicone Brake Fluid

Version  
1.0

Revision Date:  
6/21/2017

SDS Number:  
B590201

Date of last issue: 6/21/2017

tional Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 6/21/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8