

SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name R09149A
Product code 467969-BE04
SDS no. 467969
Product type Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Handling and dilution of metal working fluid concentrates-Industrial

Use of the substance/mixture Additive
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier BP Europa SE - BP Belgium / BP Marine
 Amocolaan 2
 2440 Geel
 BELGIE
 Phone: 0032 3 260 89 45
 Fax: 32 (0) 286 82 69
 Poison Control Center: 32 (0)70 245 245
E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER Carechem: +44 (0) 1235 239 670 (24/7)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture
Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]
 Skin Irrit. 2, H315
 Eye Dam. 1, H318
 Repr. 1B, H360F (Fertility)
 Aquatic Chronic 3, H412

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H318 - Causes serious eye damage.
 H315 - Causes skin irritation.
 H360F - May damage fertility.
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201 - Obtain special instructions before use.
 P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection.
 P273 - Avoid release to the environment.

Product name R09149A

Product code 467969-BE04

Page: 1/18

Version 8

Date of issue 15 May 2019

Format Belgium
 (Belgium)

Language ENGLISH

SECTION 2: Hazards identification

Response	P332 + P313 - If skin irritation occurs: Get medical attention. P305 + P351 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or physician.
Storage	P405 - Store locked up.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	Phosphorodithioic acid, mixed O,O-bis(iso-bu and pentyl) esters, zinc salts Phenol, dodecyl-, branched
Supplemental label elements	Not applicable.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Restricted to professional users.
---	-----------------------------------

Special packaging requirements

Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Product definition Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Calcium branched alkyl phenate sulphide (overbased)	Polymer.	≥25 - ≤50	Aquatic Chronic 4, H413	[1]
Base oil - unspecified	Varies - See Key to abbreviations	≥25 - ≤50	Asp. Tox. 1, H304	[1] [2]
Phosphorodithioic acid, mixed O,O-bis (iso-bu and pentyl) esters, zinc salts	REACH #: 01-2119493628-22 EC: 270-608-0 CAS: 68457-79-4	≥10 - ≤25	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411	[1]
Phenol, dodecyl-, branched	REACH #: 01-2119513207-49 EC: 310-154-3 CAS: 121158-58-5 Index: 604-092-00-9	≤3	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F (Fertility) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	[1]
Poly(oxy-1,2-ethanediyl), .alpha.- [(1,1,3,3-tetramethylbutyl)phenyl]-. omega.-hydroxy-	CAS: 9036-19-5	≤3	Eye Irrit. 2, H319 Aquatic Chronic 2, H411	[1] [5]

See Section 16 for the full text of the H statements declared above.

Type

Product name R09149A

Version 8

Date of issue 15 May 2019

Product code 467969-BE04

Format Belgium
(Belgium)

Page: 2/18

Language ENGLISH

SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard
 - [2] Substance with a workplace exposure limit
 - [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
 - [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
 - [5] Substance of equivalent concern
 - [6] Additional disclosure due to company policy
- Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention immediately.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system.
Ingestion	Irritating to mouth, throat and stomach.
Skin contact	Causes skin irritation. Defatting to the skin.
Eye contact	Causes serious eye damage.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed


Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
---------------------------	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Use foam or all-purpose dry chemical to extinguish.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	 Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

SECTION 5: Firefighting measures

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Do not breathe vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid contact of spilt material and runoff with soil and surface waterways. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

SECTION 7: Handling and storage**Not suitable**

Prolonged exposure to elevated temperature.

7.3 Specific end use(s)**Recommendations**

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

Product/ingredient name	Exposure limit values
Base oil - unspecified	Limit values (Belgium). STEL: 10 mg/m ³ 15 minutes. Issued/Revised: 10/2002 Form: Mist TWA: 5 mg/m ³ 8 hours. Issued/Revised: 10/2002 Form: Mist

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls**Appropriate engineering controls**

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures**Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Chemical splash goggles.

Skin protection

SECTION 8: Exposure controls/personal protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Wear suitable gloves.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

SECTION 8: Exposure controls/personal protection**Refer to standards:**

Respiratory protection: EN 529
 Gloves: EN 420, EN 374
 Eye protection: EN 166
 Filtering half-mask: EN 149
 Filtering half-mask with valve: EN 405
 Half-mask: EN 140 plus filter
 Full-face mask: EN 136 plus filter
 Particulate filters: EN 143
 Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	Liquid.
Colour	Not available.
Odour	Not available.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-12 °C
Flash point	Closed cup: 168°C (334.4°F) [Pensky-Martens.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Density	1060 kg/m³ (1.06 g/cm³) at 15.6°C
Solubility(ies)	insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 1650 mm²/s (1650 cSt) at 40°C Kinematic: 70 mm²/s (70 cSt) at 100°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.

Product name R09149A

Product code 467969-BE04

Page: 7/18

Version 8

Date of issue 15 May 2019

Format Belgium
(Belgium)

Language ENGLISH

SECTION 10: Stability and reactivity**10.6 Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**Acute toxicity estimates

N/A

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects**Inhalation**

May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system.

Ingestion

Irritating to mouth, throat and stomach.

Skin contact

Causes skin irritation. Defatting to the skin.

Eye contact

Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics**Inhalation**

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Ingestion

Adverse symptoms may include the following:
stomach pains

Skin contact

Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur

Eye contact

Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Inhalation**

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects**General**

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

May damage fertility.

SECTION 12: Ecological information**12.1 Toxicity****Environmental hazards**

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Partially biodegradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil**Soil/water partition coefficient (K_{oc})**

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

SECTION 12: Ecological information**12.5 Results of PBT and vPvB assessment**

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Other adverse effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 02 08*	other engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Other information At sea, used or unwanted product should be stored for eventual discharge into port approved waste oil disposal facilities.

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not available.

Product name R09149A

Version 8

Date of issue 15 May 2019

Product code 467969-BE04

Format Belgium
(Belgium)

Page: 9/18

Language ENGLISH

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

Substances of very high concern**Substance of equivalent concern for human health**

Ingredient name	Status	Reference number
4-(1,1,3,3-tetramethylbutyl)phenol, ethoxylated [covering well-defined substances and UVCB substances, polymers and homologues]; 4-tert-Octylphenol ethoxylates	Recommended	ED/169/2012

Other regulations**REACH Status**

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b)

All components are listed or exempted.

Australia inventory (AICS)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (ENCS)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information**Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

Product name R09149A**Product code** 467969-BE04**Page:** 10/18**Version** 8**Date of issue** 15 May 2019**Format** Belgium
(Belgium)**Language** ENGLISH

SECTION 16: Other information

OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SADT = Self-Accelerating Decomposition Temperature
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4 / RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 1B, H360F (Fertility) Aquatic Chronic 3, H412	Calculation method Calculation method Calculation method Expert judgment

Full text of abbreviated H statements

H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H360F May damage fertility.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS]

Aquatic Acute 1, H400 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2, H411 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 4, H413 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 1B, H360F REPRODUCTIVE TOXICITY (Fertility) - Category 1B
Skin Corr. 1C, H314 SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

History

Date of issue/ Date of revision 15/05/2019.
Date of previous issue 08/11/2018.
Prepared by Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material,

Product name R09149A	Product code 467969-BE04	Page: 11/18
Version 8	Date of issue 15 May 2019	Format Belgium (Belgium)
		Language ENGLISH

SECTION 16: Other information

from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.



Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition	Mixture
Code	467969-BE04
Product name	R09149A

Section 1: Title

Short title of the exposure scenario	Handling and dilution of metal working fluid concentrates - Industrial - H360-E-E6.1x0.4 (i)
List of use descriptors	Identified use name: Handling and dilution of metal working fluid concentrates-Industrial Process Category: PROC01, PROC02, PROC08b, PROC05 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC02 Specific Environmental Release Category: ATIEL-ATC SPERC 2.Ei.v1

Processes and activities covered by the exposure scenario	Handling and dilution of metal working fluid concentrates. Includes associated product storage, material transfers, sampling and maintenance activities.
---	--

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures (Reproductive toxin):

Consider technical advances and process upgrades (including automation) for the elimination of releases.
Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation.

Drain down systems and clear transfer lines prior to breaking containment.

Clean/flush equipment, where possible, prior to maintenance.

Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely.

Ensure safe systems of work or equivalent arrangements are in place to manage risks.

Regularly inspect, test and maintain all control measures.

Consider the need for risk-based health surveillance.

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Filling of equipment from drums or containers:

Avoid carrying out activities involving exposure for more than 4 hours per day.

Process sampling:

Avoid carrying out activities involving exposure for more than 4 hours per day.

R09149A

Handling and dilution of metal working fluid concentrates - Industrial - H360-E-E6.1x0.4 (i)

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Avoid carrying out activities involving exposure for more than 4 hours per day. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:

Store substance within a closed system.

Section 2.2: Control of environmental exposure

Amounts used:

EU tonnage of risk determining substance per year: 3.02E+02 Tonnes/year

Frequency and duration of use:

Emission days 300

Environment factors not influenced by risk management:

Local freshwater dilution factor 10

Local marine water dilution factor 100

Other conditions affecting environmental exposure: Water-based (oil in water emulsion) or straight oil (contains no water) process

Release fraction to air (after typical onsite RMMs) 5.00E-05

Release fraction to soil from process (after typical onsite RMMs) 0

Release fraction to wastewater from process (after typical onsite RMMs and before sewage treatment plan) 2.00E-11

Technical conditions and measures at process level (source) to prevent release:

Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Prevent discharge of undissolved substance to or recover from onsite wastewater.

User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant

Organisational measures to prevent/limit release from site:

Do not apply industrial sludge to natural soils.

Sewage sludge should be incinerated, contained or reclaimed.

Conditions and measures related to sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment 69

Assumed domestic sewage treatment plant flow rate (m3/d) 2.00E+3

Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal as product: 60.8

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment): Used ECETOC TRA model (May 2010 release).

Exposure estimation and reference to its source - Workers

Exposure assessment (human): The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

