



# صحيفة بيانات السلامة

Hydraulic Oil 46

## القسم 1. الاسم (بيان المنتج)

Hydraulic Oil 46 بيان تعريف المنتج طبقاً للنظام المنسق العالمي GHS

401107-EG01

كود المنتج

401107

صحيفة بيانات سلامة المادة رقم #

سائل.

نوع المنتج

الاستخدامات الهامة المحددة للمادة أو الخليط وأوجه الاستخدام التي لا ينصح بها

استخدام المادة/المستحضر

سائل هيدروليكي.

بالنسبة لجهاز التطبيق المحدد، انظر نشرة البيانات التقنية المعنية أو تشاور مع ممثل شركتنا.

المورد

BP Egypt

42 Road 17

Digla, Maadi

PO Box 1254

Cairo, Egypt

رقم هاتف الطوارئ

خدمة Carechem: +44 (0) 671 239 1235 (اللغة العربية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

+44 (0) 670 239 1235 (اللغة الإنجليزية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

## القسم 2. بيان الأخطار

تصنيف المادة أو الخليط غير مُصنَّعة.

عناصر بطاقة الوسم في النظام المنسق العالمي GHS

كلمة التنبيه

بدون كلمة تنبيه

عبارات المخاطر

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

عبارات التحذير

الوقاية

غير قابل للتطبيق.

الاستجابة

غير قابل للتطبيق.

التخزين

غير قابل للتطبيق.

التخلص من النفايات

غير قابل للتطبيق.

الأخطار الأخرى التي لا تؤدي إلى تصنيف

يزيل دهون الجلد.

ملاحظة: تطبيقات الضغط العالي

عمليات الحقن عبر الجلد التي تنتج عن ملامسة المنتج بضغط مرتفع تمثل حالة طبية خطيرة. انظر 'ملاحظات الطبيب' في موضوع إجراءات الإسعافات الأولية، القسم 4 من نشرة البيانات هذه.

## القسم 3. التركيب/معلومات عن المكونات

مادة/مستحضر خليط

زيت أساسي عالي النقاوة (خلاصة IP 346 DMSO > 3%). إضافات خاصة للأداء.

اسم المكون	%	رقم CAS
مواد مقطرة (بترول)، معالجة بالهيدروجين بدرجة خفيفة، بارافينية	≥50 - ≤75	64742-55-8
مواد مقطرة (بترول)، معالجة بالهيدروجين بارافينية بدرجة كثيفة	≥25 - ≤50	64742-54-7
2,6-دي-تيرت-بيوتيل فينول	<0.25	128-39-2

الصفحة: 16/1	اسم المنتج	Hydraulic Oil 46	Product name
Page: 1/16	تاريخ الإصدار	01/09/2023.	Date of issue
اللغة	Format	Egypt	Version
العربية	ENGLISH	2	نسخة
اللغة	Product code	401107-EG01	كود المنتج

### القسم 3. التركيب/معلومات عن المكونات

على حد علم المورد في هذه اللحظة وطبقاً للتركيزات المستخدمة، لا توجد أية مكونات أو مكونات إضافية مصنفة كمواد خطرة على الصحة أو على البيئة تستدعي الإبلاغ عنها في هذا القسم.

القسم الثامن يعرض حدود التعرض المهني، في حال توفرها.

### القسم 4. تدبير الإسعاف الأولي

#### وصف إجراءات الإسعافات الأولية اللازمة

ملازمة العين	في حالة الملازمة، يُراعى دفع الماء فوراً على العين لمدة لا تقل عن 15 دقيقة. يجب إبعاد الجفون عن مقلات العين لضمان الشطف الكامل. يُراعى التحقق من عدم وجود عدسات لاصقة أو إزالتها إن وجدت. يُراعى الحصول على الرعاية الطبية.
استنشاق	في حالة الاستنشاق، يُراعى نقل المصاب إلى الهواء الطلق. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
ملازمة الجلد	يراعى غسل البشرة غسلاً جيداً بالماء والصابون أو بأحد منظفات الجلد المعترف بها. أزل الثياب والأحذية الملوثة. يُراعى غسل الثياب قبل إعادة استخدامها. يُراعى تنظيف الحذاء تنظيفاً جيداً قبل ارتدائه ثانية. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
الابتلاع	لا تحرض على القيء إلا إن طلب أحد أعضاء الطاقم الطبي منك أن تقوم بهذا. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.

#### أهم الأعراض/التأثيرات، الحادة والمتأخرة

انظر القسم 11 لمزيد من المعلومات عن التأثيرات الصحية والأعراض.

#### بيان الرعاية الطبية الفورية والمعالجة الخاصة إذا كانت ضرورية

ملاحظات للطبيب	يجب أن تتم المعالجة حسب الأعراض بشكل عام ويتم إجراؤها لتخفيف حدة التأثيرات.
معالجات خاصة	ملاحظة: تطبيقات الضغط العالي عمليات الحقن عبر الجلد التي تنتج عن ملازمة المنتج بضغط مرتفع تمثل حالة طبية خطيرة. الإصابات قد لا تبدو خطيرة في البداية، ولكن خلال ساعات قليلة يمكن أن يظهر تورم أو تغير لوني أو آلام شديدة في الأنسجة مع حدوث نخر ممتد تحت الجلد. يجب إجراء فحص جراحي على الفور. ومن الضروري إجراء عملية إنضار شاملة ودقيقة للجرح والأنسجة الموجودة أسفله للحد من خطورة فقدان الأنسجة ولمنع أو الحد من حدوث تلف دائم. يُراعى أن الضغط المرتفع يمكن أن يؤدي إلى توغل المنتج لمسافات كبيرة بطول طبقات الأنسجة. لا يوجد علاج محدد. يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب.
حماية فريق الإسعافات الأولية	

### القسم 5. تدابير مكافحة الحريق

#### وسائل الإطفاء

وسائل الإطفاء المناسبة	في حالة نشوب حريق، استخدم الرغوة والمواد الكيميائية الجافة أو طفاية حريق أو بخاخة بها ثاني أكسيد الكربون.
وسائل الإطفاء غير المناسبة	لا تستخدم المياه النفاثة.
مخاطر خاصة ناشئة عن المادة الكيميائية	سوف يحدث تزايد في الضغط وقد تنفجر الحاوية في حالة حدوث حريق أو تسخين.
نواتج تحليل حراري خطيرة	نواتج الاحتراق قد تشمل ما يلي: أكاسيد الكربون (CO, CO <sub>2</sub> )
معدات الحماية الشخصية والاحتياطات اللازمة لعمال الإطفاء	يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يُراعى عزل المكان على الفور وذلك بإخلاء الأفراد المتواجدين على مقربة من الحادث في حالة نشوب حريق.
معدات الحماية الشخصية والاحتياطات اللازمة لعمال الإطفاء	يجب على فريق مكافحة الحريق أن يرتدوا جهاز تنفس مكتفي ذاتياً SCBA إيجابي الضغط والزي الواقي كلاً.

Product name	Hydraulic Oil 46	اسم المنتج	الصفحة: 16/2
Product code	401107-EG01	كود المنتج	Date of issue
Version	2	نسخة	01/09/2023.
		Format	Page: 2/16
		Egypt	تاريخ الإصدار
			اللغة
			ENGLISH
			العربية

## القسم 6. تدابير مواجهة التسرب العارض

### احتياطات الشخصية ومعدات الحماية وإجراءات الطوارئ

#### لأفراد من خارج فريق الطوارئ

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى إخلاء المناطق المجاورة. يراعى عدم السماح بالدخول لكل من لا يرتدي مهمات الوقاية أو من لا حاجة لك بهم من الأفراد. يراعى تجنب ملامسة المادة المنسكبة أو السير عليها. ارتدي مهمات الوقاية الشخصية الملائمة. قد تكون الأرضيات زلقة؛ يجب توخي العناية لتجنب السقوط.

#### لمسعفي الطوارئ

إذا لزم الأمر ارتداء ثياباً خاصة للتعامل مع الانسكاب، يُرجى أخذ ما ورد في القسم 8 من معلومات حول المواد المناسبة وغير المناسبة في الحسبان. راجع كذلك المعلومات الواردة في قسم "للأفراد من خارج فريق الطوارئ".

### الاحتياطات البيئية

تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف. يُراعى إبلاغ السلطات المعنية لو تسبب المنتج في تلوث البيئة (مجري الصرف، المجاري المائية، التربة أو الهواء).

### طرائق ومواد الاحتواء والتنظيف

#### انسكاب صغير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يُراعى امتصاصها بمادة خاملة، ثم إيداعها إحدى الحاويات الملائمة للتخلص من النفايات. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

#### انسكاب كبير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. امنع دخولها في البالوعات والصرف، و المجاري المائية، أو البدرومات، أو المناطق المغلقة. يُراعى احتواء الانسكاب وجمعه بمادة ماصة غير قابلة للاحتراق مثل الرمل، أو التراب، أو الفرميكيوليت، أو تراب دياتومي، ثم وضعها في إحدى الحاويات للتخلص منها بما يتفق واللوائح المحلية. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

## القسم 7. المناولة والتخزين

### احتياطات للمناولة الآمنة

#### احتياطات للمناولة الآمنة

#### إرشادات حول الصحة المهنية العامة

يراعى ارتداء أجهزة الوقاية الشخصية الملائمة(انظر القسم 8).

يحظر تناول الطعام، والشراب، والتدخين في الأماكن التي يجري التعامل فيها مع هذه المادة سواء بالمناولة، التخزين أو المعالجة. يُراعى الإغتسال جيداً بعد مناولتها. اخلع الثياب الملوثة والتجهيزات الوقائية قبل دخول الأماكن المخصصة للطعام. انظر القسم 8 لمزيد من المعلومات حول إجراءات الحفاظ على الصحة.

### متطلبات التخزين الآمنة، بما في ذلك ما يتعلق بحالات عدم توافق المواد

خزن المادة وفقاً لتعليمات السلطات المحلية. خزن المادة في حاويتها الأصلية مع حمايتها من التعرض لحرارة الشمس المباشرة في منطقة جافة، وباردة، وجيدة التهوية بعيداً عن المواد غير المطابقة (انظر القسم 10)، وعن الطعام، والشراب. يراعى غلق الوعاء غلقاً تاماً محكماً إلى أن يُعد للاستخدام. يجب أن يتم التخزين والاستعمال فقط في معدات/حاويات مصممة للاستخدام مع هذا المنتج. لا بد من إحكام غلق الأوعية التي قد قُتحت و تركها في وضع قائم و ذلك لتلافي حدوث تسريب. يُحظر التخزين في حاويات لا تحمل كتابة توضيحية. يُراعى استخدام طرق احتواء سليمة لتجنب تلوث البيئة.

التعرض لدرجات الحرارة العالية لفترات طويلة

#### غير ملائمة

## القسم 8. ضوابط التعرض/الحماية الشخصية

### تدابير التحكم

#### حدود التعرض المهني

اسم المكون	حدود التعرض
مواد مقطرة (بنترول)، معالجة بالهيدروجين بدرجة خفيفة، بارافينية	TLV ACGIH (الولايات المتحدة). Oil [Mineral refined] severely and highly, pure TWA: 5 مج / م <sup>3</sup> 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشق
مواد مقطرة (بنترول)، معالجة بالهيدروجين بارافينية بدرجة كثيفة	TLV ACGIH (الولايات المتحدة). Oil [Mineral refined] severely and highly, pure TWA: 5 مج / م <sup>3</sup> 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشق

الصفحة: 16/3	اسم المنتج	Hydraulic Oil 46	Product name
Page: 3/16	تاريخ الإصدار	01/09/2023.	Date of issue
اللغة	Format	Egypt	كود المنتج
العربية	Version	2	نسخة
ENGLISH	Product code	401107-EG01	اللغة

## القسم 8. ضوابط التعرض/الحماية الشخصية

### الضوابط الهندسية المناسبة

يجب تقييم جميع الأنشطة المرتبطة بالمواد الكيميائية من حيث مخاطرها على الصحة، وذلك لضمان التحكم في معدلات التعرض بالشكل المناسب. لا يجوز تحديد معدات الوقاية الشخصية إلا بعد تقييم الأشكال الأخرى لإجراءات التحكم (على سبيل المثال عمليات التحكم الهندسية) بالشكل المناسب. يجب أن تتوافق معدات الوقاية الشخصية مع المواصفات المعنية وأن تكون مناسبة للاستخدام، ويجب الحفاظ عليها في حالة جيدة وصيانتها بشكل سليم. يجب التشاور مع مورد معدات الوقاية الشخصية لطلب المشورة بشأن الاختيار والمواصفات المعنية. لمزيد من المعلومات، اتصل بالهيئة المحلية للمواصفات.

احرص على توفير تهوية للعوامل أو الوسائل الهندسية الأخرى للحماية، وذلك للإبقاء على مستويات التركيز المعنية للمواد العالقة بالهواء دون حدود التعرض المقبولة لها على الصعيد المهني. القرار النهائي لاختيار معدات الوقاية يعتمد على تقييم المخاطر. ومن المهم التأكد من ملاءمة جميع عناصر معدات الوقاية الشخصية.

ننصح بفحص الانبعاثات الصادرة من أجهزة العمل والتهوية، للتأكد من استيفائها لمتطلبات قانون حماية البيئة. في بعض الحالات، قد يكون من الضروري استخدام أجهزة إمتصاص الدخان، أو المرشحات أو إجراء تعديلات هندسية للمعدات، كي يتسنى تقليل الانبعاثات إلى مستويات مقبولة.

### ضوابط التعرض البيئي

### تدابير الحماية الفردية

### إجراءات النظافة الشخصية

اغسل اليدين، والذراعين، والوجه غسلاً تاماً بعد مناولة المنتجات الكيميائية، وعند الأكل والتدخين، وفي نهاية فترة العمل. يتوجب استخدام طرق ملائمة لنزع الثياب التي يُحتمل تلوثها. يُراعى غسل الثياب الملوثة قبل ارتدائها مرة ثانية. تأكد من وجود محطات غسيل الأعين وأدشاش الطوارئ على مقربة من موقع العمل. نظارات أمان ذات سائرات جانبية.

### أدوات حماية الوجه/العين

### حماية للجلد

### حماية يديوية

احرص على ارتداء القفازات الواقية من الماء إذا كان من المحتمل حدوث ملامسات متكررة وطويلة. قم بارتداء القفازات المقاومة للمواد الكيميائية. يُنصح باستخدام قفازات نيتريل. يعتمد الاختيار الصحيح لقفازات الحماية على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة القفازات (حتى أفضل القفازات المقاومة للمواد الكيميائية تتآكل بفعل التعرض المتكرر للمواد الكيميائية). معظم القفازات توفر الحماية لفترة زمنية قصيرة فقط وبعدها يجب التخلص منها واستبدالها. نظراً للظروف الخاصة لبيئات العمل واختلاف ممارسات التعامل مع المواد، فيجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار القفازات بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

### أدوات حماية الجسم

استخدام الملابس الواقية يعتبر من الممارسات الجيدة في المجال الصناعي. يجب انتقاء التجهيزات الشخصية الواقية للجسم بما يتفق والمهمة التي يجري القيام بها والمخاطر التي تنطوي عليها، كما يجب أن يعتمدوا أحد المختصين قبل التعامل مع هذا المنتج. أفرولات العمل المصنوعة من القطن أو البوليستر/القطن توفر الحماية فقط من التلوث السطحي الخفيف الذي لا يصل إلى الجلد. ويجب غسل أفرولات العمل بصفة منتظمة. عندما تزداد خطورة تعرض الجلد للمواد (على سبيل المثال عند تنظيف المواد المنسكبة أو في حالة وجود خطورة من تناثر الرذاذ)، فيجب ارتداء مريلة مقاومة للمواد الكيميائية و/أو أحذية وسترات غير منفذة للمواد الكيميائية.

### حماية تنفسية

في حالة عدم كفاية التهوية، يُراعى ارتداء تجهيزات تنفسية ملائمة. يعتمد الاختيار الصحيح لتجهيزات حماية الجهاز التنفسي على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة تجهيزات حماية الجهاز التنفسي. يجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار تجهيزات حماية الجهاز التنفسي بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

## القسم 9. الخصائص الفيزيائية والكيميائية

ظروف قياس جميع الخصائص تتم في ظل الضغط ودرجة الحرارة القياسيين ما لم تتم الإشارة إلى غير ذلك.

### المظهر

### الحالة الفيزيائية

### اللون

### الرائحة

### عتبة الرائحة

### الأس الهيدروجيني pH

### نقطة الانصهار/نقطة التجمد

### نقطة الغليان، والنقطة الأولية، ومعدل الغليان

### نقطة السقوط

### نقطة الوميض

### معدل التبخر

سائل.

كهرومان. [فاتح]

غير متوفرة.

غير متوفرة.

غير قابل للتطبيق.

غير متوفرة.

غير متوفرة.

غير متوفرة.

غير متوفرة.

كأس مغلق: <190°C (<374 ف) [جهاز بنسكي-مارتينز]

جهاز الكأس المفتوحة: <185°C (<365 ف) [جهاز كليفلاند 2592 ISO EN DIN]

غير متوفرة.

Product name	Hydraulic Oil 46	اسم المنتج	الصفحة: 16/4
Product code	401107-EG01	Date of issue	Page: 4/16 تاريخ الإصدار
Version	2 نسخة	Format	اللغة
		Egypt	العربية
			ENGLISH

القسم 9. الخصائص الفيزيائية والكيميائية

القابلية على الاشتعال

القابلية للالتهاب (مادة صلبة، غاز)  
الحد الأعلى/الأدنى للانفجار أو القابلية للاشتعال

الضغط البخاري

كثافة البخار النسبية

الكثافة النسبية

الكثافة

الذوبانية (نيات)

غير قابل للتطبيق. اعتمادًا على - الحالة الفيزيائية  
غير متوفرة.

غير متوفرة.

غير متوفرة.

>1000 كجم/م<sup>3</sup> (g/cm<sup>3</sup> 1>) عند 15°C

النتيجة	وسائل الإعلام
غير قابل للذوبان	الماء

معامل تفريق الأوكتانول/الماء

غير قابل للتطبيق.

درجة حرارة الاشتعال الذاتي

غير متوفرة.

درجة حرارة الانحلال

غير متوفرة.

اللزوجة

كينماتي: 43.88 /S<sup>2</sup>mm (43.88 سنتي ستوك) عند 40°C  
كينماتي: 6.54 /S<sup>2</sup>mm (6.54 سنتي ستوك) عند 100°C (445 D ASTM)

خصائص الجسيمات

حجم الجسيمات المتوسط

غير قابل للتطبيق.

القسم 10. الثبات الكيميائي والقابلية للتفاعل

التفاعلية

غير متاح بيانات اختبار أخرى معينة لهذا المنتج. ارجع إلى الظروف التي يجب تجنبها والمواد غير المتوافقة لمزيد من المعلومات.

الثبات الكيميائي

المُنتج ثابت.

إمكانية التفاعلات الخطرة

لن تحدث تفاعلات خطيرة في ظروف التخزين والاستخدام العادية.  
لن تحدث بلمرة خطيرة في ظروف التخزين والاستخدام العادية.

الظروف التي ينبغي تجنبها

يجب تجنب جميع مصادر الاشتعال الممكنة (شرر أو لهب).

المواد غير المتوافقة

تتفاعل أو غير متطابقة مع المواد التالية: مواد مؤكسدة.

نواتج الانحلال الخطرة

في ظروف التخزين والاستخدام العادية، من غير المنتظر أن تتولد نواتج تحلل خطيرة.

القسم 11. المعلومات السمية

معلومات حول الآثار السمية

خطر الاستنشاق على الجهاز التنفسي

غير متوفرة.

معلومات عن سُبل التعرض المرجحة

سُبل التعرض المُرتقبة: جلدي، استنشاق، الأغين.

آثار صحية حادة كامنة

ملامسة العين

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

استنشاق

استنشاق الأبخرة في الظروف المحيطة لا يمثل مشكلة في المعتاد، وذلك لانخفاض ضغط الأبخرة.

ملامسة الجلد

يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيجه.

الابتلاع

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

أعراض متعلقة بالخواص السمية والكيميائية والفيزيائية

ملامسة العين

ليست هناك بيانات معينة.

استنشاق

ليست هناك بيانات معينة.

Product name	Hydraulic Oil 46	اسم المنتج	16/5 الصفحة:
Product code	401107-EG01	كود المنتج	Date of issue
Version	2	نسخة	01/09/2023.
		Format	Egypt
		Language	ENGLISH
		اللغة	العربية
		Page:	5/16
		تاريخ الإصدار	

## القسم 11 . المعلومات السمية

ملامسة الجلد

الأعراض الضائرة قد تشمل ما يلي:  
تهيج  
الجفاف  
التشقق  
ليست هناك بيانات معينة.

الابتلاع

### التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

ملامسة العين

هناك خطورة محتملة من حدوث لسعة عابرة أو احمرار عابر في حالة حدوث ملامسة العين بشكل عرضي.  
التعرض الزائد لاستنشاق الجزيئات المتطايرة في الهواء أو الإيروسولات قد يتسبب في تهيج الجهاز التنفسي.  
الملامسة المطوّلة أو المتكررة بإمكانها أن تتسبب في إزالة دهون الجلد وتهيج وتشققه و/أو التهابه.  
ابتلاع كميات كبيرة يمكن أن يؤدي إلى الغثيان والإسهال.

استنشاق

ملامسة الجلد

الابتلاع

### آثار صحية مزمنة كامنة

عامة

السرطنة

التأثير على الجينات

القابلية على التسبب في المسخ

التأثيرات النمانية

التأثيرات الخصوبية

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.  
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.  
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.  
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.  
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.  
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

### القياسات الرقمية للسمية

#### تقديرات السمية الحادة

غير متوفرة.

## القسم 12 . المعلومات الإيكولوجية

تأثيرات بيئية

الثبات والتحلل

يُتوقع أن يكون قابلاً للتحلل الحيوي.

القدرة على التراكم الأحيائي

لا يُتوقع أن يتراكم هذا المنتج حيوياً في البيئة من خلال السلاسل الغذائية.

القابلية على التحرك عبر التربة

معامل تقاسم التربة/الماء (Koc)

التحركة

غير متوفرة.

المواد المنسكبة يمكن أن تتوغل في التربة وتتسبب في تلوث المياه الجوفية.

التأثيرات الضارة الأخرى

معلومات بيئية أخرى

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.  
قد تتسبب السوائل المنسكبة في تكوين طبقة على أسطح الماء، وقد تتسبب في ضرر مادي للكائنات الحية. وقد يتم إعاقة نقل الأكسجين أيضاً.

## القسم 13 . الاعتبارات المتعلقة بتصريف المواد والتخلص منها

طرائق التصريف

ينبغي تجنب توليد النفايات أو التقليل منها حيثما أمكن. ينبغي عدم التخلص من الكميات الكبرى من فضالة نفاية المنتج عبر شبكة الصرف الصحي وإنما معالجتها في محطة مناسبة لمعالجة مياه الصرف. يُراعى التخلص من الفائض والمنتجات غير القابلة لإعادة التدوير من خلال أحد المقاولين المرخص لهم بذلك. يراعى أن يجري دوماً التخلص من هذا المنتج، و المحاليل و المنتجات الثانوية بما يتفق و متطلبات الحماية البيئية و تشريعات التخلص من النفايات و غيرها من متطلبات السلطة الإقليمية و المحلية. ينبغي أن يُعاد تدوير نفاية التغليف. ينبغي عدم أخذ الحرق أو الطمر في الاعتبار إلا إذا كانت إعادة التدوير غير مُجدية. لا بد أن يجري التخلص من هذا المنتج وحاويته بطريقة آمنة. قد تظل بعض رواسب المنتج عالقة بالحاويات الفارغة أو قمصانها. تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف.

Product name

Hydraulic Oil 46

اسم المنتج

الصفحة: 6/16

Product code

401107-EG01

Date of issue كود المنتج

01/09/2023.

Page: 6/16 تاريخ الإصدار

Version

نسخة 2

Format Egypt

Language

اللغة

ENGLISH

العربية

## القسم 14. المعلومات المتعلقة بالنقل

IATA	IMDG	
غير مقننة.	غير مقننة.	رقم الأمم المتحدة
-	-	اسم الشحن الصحيح الخاص بالأمم المتحدة
-	-	فئة/فئات مخاطر النقل
-	-	مجموعة التعبئة
لا.	لا.	الأخطار البيئية
-	-	معلومات إضافية

احتياجات خاصة للمستخدم غير متوفرة.

النقل سائناً بحسب اتفاقيات المنظمة البحرية الدولية (IMO) غير متوفرة.

## القسم 15. المعلومات التنظيمية

القواعد المتعلقة بالسلامة والصحة والبيئة، لا توجد لوائح وطنية و/أو إقليمية معروفة تنطبق على هذا المنتج (بما في ذلك مكوناته). المنطبقة على المنتج

### قائمة الجرد الوطنية

أستراليا

كندا

الصين.

الوضع وفق REACH (النظام المتعلق بتسجيل وتقييم وترخيص المواد الكيميائية)

اليابان

الفلبين

جمهورية كوريا

تايبوان

الولايات المتحدة

مكون واحد على الأقل غير مُدرَج.

مكون واحد على الأقل غير مُدرَج.

مكون واحد على الأقل غير مُدرَج.

للتعرف على حالة REACH لهذا المنتج، يرجى التواصل مع جهة الاتصال في شركتكم، كما هو محدد في القسم 1.

مكون واحد على الأقل غير مُدرَج.

مكون واحد على الأقل غير مُدرَج.

مكون واحد على الأقل غير مُدرَج.

مكون واحد على الأقل غير مُدرَج.

لم تُحدّد.

## القسم 16. المعلومات الأخرى

### السيرة

تاريخ الإصدار/تاريخ المراجعة 01/09/2023.

تاريخ الإصدار السابق 11/08/2023.

نسخة 2

Product Stewardship من إعداد

Product name	Hydraulic Oil 46	اسم المنتج	الصفحة: 16/7
Product code	401107-EG01	كود المنتج	Date of issue 01/09/2023.
Version	2	نسخة	Page: 7/16 تاريخ الإصدار
		Format Egypt	اللغة Language
			ENGLISH العربية





## Section 2. Hazards identification

### GHS Classification

Not classified.

### GHS label elements

#### Signal word

No signal word.

#### Hazard statements

No known significant effects or critical hazards.

#### Precautionary statements

##### Prevention

Not applicable.

##### Response

Not applicable.

##### Storage

Not applicable.

##### Disposal

Not applicable.

### Other hazards which do not result in classification

Defatting to the skin.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

## Section 3. Composition/information on ingredients

### Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light paraffinic	≥50 - ≤75	64742-55-8
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	64742-54-7
2,6-di-tert-butylphenol	<0.25	128-39-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

#### Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

#### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

Product name	Hydraulic Oil 46	اسم المنتج	16/9: الصفحة
Product code	401107-EG01	كود المنتج	Date of issue تاريخ الإصدار Page: 9/16
Version	2 نسخة	Format Egypt	Language اللغة
			ENGLISH العربية

## Section 4. First aid measures

### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

### Specific treatments

No specific treatment.

### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

## Section 5. Firefighting measures

### Extinguishing media

#### Suitable

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

#### Unsuitable extinguishing media

Do not use water jet.

### Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

### Hazardous thermal decomposition products

Combustion products may include the following:  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

#### For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Product name	Hydraulic Oil 46	اسم المنتج	16/10: الصفحة
Product code	401107-EG01	كود المنتج	Date of issue تاريخ الإصدار Page: 10/16
Version	2 نسخة	Format Egypt	Language اللغة
			ENGLISH العربية

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8).

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Not suitable

Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic	<b>ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Distillates (petroleum), hydrotreated heavy paraffinic	<b>ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

#### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

Safety glasses with side shields.

#### Skin protection

Product name	Hydraulic Oil 46	اسم المنتج	16/11	الصفحة:
Product code	401107-EG01	كود المنتج	Date of issue	01/09/2023.
Version	2	نسخة	Format	Egypt
			Language	ENGLISH
			اللغة	العربية

## Section 8. Exposure controls/personal protection

### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

### Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

#### Physical state

Liquid.

#### Colour

Amber. [Light]

#### Odour

Not available.

#### Odour threshold

Not available.

#### pH

Not applicable.

#### Melting point/freezing point

Not available.

#### Boiling point, initial boiling point, and boiling range

Not available.

#### Drop Point

Not available.

#### Flash point

Closed cup: >190°C (>374°F) [Pensky-Martens]  
Open cup: >185°C (>365°F) [Cleveland DIN EN ISO 2592]

#### Evaporation rate

Not available.

#### Flammability

Not available.

#### Lower and upper explosion limit/flammability limit

Not available.

#### Vapour pressure

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated light paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			

#### Relative vapour density


Not available.

Product name	Hydraulic Oil 46	اسم المنتج	16/12: الصفحة
Product code	401107-EG01	كود المنتج	Date of issue
Version	2	نسخة	01/09/2023.
		Format	ENGLISH
		Language	العربية

## Section 9. Physical and chemical properties

**Relative density** Not available.  
**Density** <1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C  
**Solubility(ies)**

Media	Result
water	Not soluble

**Partition coefficient: n-octanol/water** Not applicable.  
**Auto-ignition temperature** Not available.  
**Decomposition temperature** Not available.  
**Viscosity**  Kinematic: 43.88 mm<sup>2</sup>/s (43.88 cSt) at 40°C  
Kinematic: 6.54 mm<sup>2</sup>/s (6.54 cSt) at 100°C (ASTM D 445)

### Particle characteristics

**Median particle size**

غير قابل للتطبيق.

## Section 10. Stability and reactivity

**Reactivity** No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

**Chemical stability** The product is stable.

**Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerisation will not occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

**Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Aspiration hazard

Not available.

**Information on likely routes of exposure** Routes of entry anticipated: Dermal, Inhalation, Eyes.

### Potential acute health effects

**Eye contact** No known significant effects or critical hazards.

**Inhalation** Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** No specific data.

**Inhalation** No specific data.

**Skin contact** Adverse symptoms may include the following:  
irritation  
dryness  
cracking

**Ingestion** No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** Potential risk of transient stinging or redness if accidental eye contact occurs.

<b>Product name</b>	Hydraulic Oil 46	اسم المنتج	16/13 الصفحة:
<b>Product code</b>	401107-EG01	كود المنتج	Date of issue تاريخ الإصدار Page: 13/16
<b>Version</b>	2 نسخة	Format Egypt	Language اللغة
			ENGLISH العربية

## Section 11. Toxicological information

<b>Inhalation</b>	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
<b>Skin contact</b>	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
<b>Ingestion</b>	Ingestion of large quantities may cause nausea and diarrhoea.
<b><u>Potential chronic health effects</u></b>	
<b>General</b>	No known significant effects or critical hazards.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.
<b><u>Numerical measures of toxicity</u></b>	
<b>Acute toxicity estimates</b>	Not available.

## Section 12. Ecological information

<b>Environmental effects</b>	No known significant effects or critical hazards.
<b><u>Persistence and degradability</u></b>	Expected to be biodegradable.
<b><u>Bioaccumulative potential</u></b>	This product is not expected to bioaccumulate through food chains in the environment.
<b><u>Mobility in soil</u></b>	
<b>Soil/water partition coefficient (<math>K_{oc}</math>)</b>	Not available.
<b>Mobility</b>	Spillages may penetrate the soil causing ground water contamination.
<b>Other adverse effects</b>	No known significant effects or critical hazards.
<b>Other ecological information</b>	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

<b>Disposal methods</b>	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
-------------------------	--

<b>Product name</b>	Hydraulic Oil 46	اسم المنتج	16/14	الصفحة:
<b>Product code</b>	401107-EG01	كود المنتج	01/09/2023.	تاريخ الإصدار Page: 14/16
<b>Version</b>	2	نسخة	Format	الغة
		Egypt	Language	العربية
			ENGLISH	

## Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

## Section 15. Regulatory information

### Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

### International lists

#### National inventory

Australia

At least one component is not listed.

Canada

At least one component is not listed.

China

At least one component is not listed.

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Japan

At least one component is not listed.

Philippines

At least one component is not listed.

Republic of Korea

At least one component is not listed.

Taiwan

At least one component is not listed.

United States

Not determined.

## Section 16. Other information

### History

Date of issue/Date of revision 01/09/2023.

Date of previous issue 11/08/2023.

Version 2

Prepared by Product Stewardship

Product name	Hydraulic Oil 46	اسم المنتج	16/15: الصفحة
Product code	401107-EG01	كود المنتج	01/09/2023. تاريخ الإصدار Page: 15/16
Version	2 نسخة	Format	Egypt اللغة
			ENGLISH العربية



## Section 16. Other information

### Key to abbreviations

ACGIH = American Conference of Industrial Hygienists  
CAS Number = Chemical Abstracts Service Registry Number  
GHS = Global Harmonised System  
IATA = International Air Transport Association, the organisation  
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.  
OEL = Occupational Exposure Limit  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
SDS = Safety Data Sheet  
STEL = Short term exposure limit  
TWA = Time weighted average  
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.  
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### Procedure used to derive the classification

Classification	Justification
Not classified.	

Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Hydraulic Oil 46	اسم المنتج	16/16 الصفحة
Product code	401107-EG01	كود المنتج	01/09/2023. تاريخ الإصدار Page: 16/16
Version	2 نسخة	Format Egypt	Language اللغة ENGLISH العربية