SAFETY DATA SHEET



(ENGLISH)

1. Identification of the substance/preparation and company/undertaking

1.1 Identification of the substance or mixture

Product name Enersyn RC-S 68

SDS no. 402053

1.2 Use of the Compressor lubricant

substance/mixture NOTE: This product should not be used in compressors producing breathable air.

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Company/undertaking identification

Supplier BP Petrolleri A.Ş.

Sarı Kanarya Sokak No:14 K2 Plaza

34742 Kozyatağı, İstanbul

TURKEY

Telephone: 0216 5712800 Fax: 0216 5712950

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE BP Access Line: 0 212 473 27 27

NUMBER Carechem: +44 (0) 1235 239 670 (24 hours)

2. Composition/information on ingredients

Substance/preparation

Poly-alpha-olefin Proprietary performance additives.

This product does not contain any hazardous ingredients at or above regulated thresholds.

3. Hazards identification

This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Additional hazards Defatting to the skin.

NOTE: This product should not be used in compressors producing breathable air.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

4. First-aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be

held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get

medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated

clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical

attention if irritation develops.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms appear.

IngestionDo not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Fire-fighting measures

First issue date 1 December 2009

Extinguishing media

Suitable In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Not suitable Do not use water iet.

Hazardous decomposition Decomposition products may include the following materials:

products carbon dioxide carbon monoxide

Unusual fire/explosion hazards raire or if heated, a pressure increase will occur and the container may burst.

Conforms to the regulation on preparation and distribution of safety data sheets on hazardous materials and preparations 26.12.2008 – 27092.

Substance/preparation Name Enersyn RC-S 68 Product code 402053-FR01 Page: 1/5

Date of revision 20 September 2011 Number of Revisions 2 Format Turkey Language ENGLISH

Build 1.0.1

(Turkey)

Special fire-fighting procedures

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Protection of fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Accidental release measures

Personal precautions - For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

Personal precautions - For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

Immediately contact emergency personnel. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Reference to other sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

7. Handling and storage

7.1 Handling

Fut on appropriate personal protective equipment.

Handling - Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Storage

Store and use only in equipment/containers designed for use with this product. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10).

Not suitable

Prolonged exposure to elevated temperature.

7.3 Specific uses

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

8. Exposure controls/personal protection

8.1 Occupational exposure limits

This product does not have any assigned OELs.

8.2.1 Occupational exposure controls

8.2 Exposure controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

8.2.1.1 Respiratory protection

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Conforms to the regulation on preparation and distribution of safety data sheets on hazardous materials and preparations 26.12.2008 – 27092.

Substance/preparation Name Enersyn RC-S 68

Product code 402053-FR01

Page: 2/5

Date of revision 20 September 2011

Number of Revisions 2

Format Turkey

Language ENGLISH

First issue date 1 December 2009

Build 1.0.1 (Turkey)

(ENGLISH)

8.2.1.2 Hand protection Wear protective gloves if prolonged or repeated contact is likely

Wear chemical resistant gloves. Recommended: Nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

8.2.1.3 Eye protection Safety glasses with side shields.

8.2.1.4 Skin protection Use of protective clothing is good industrial practice.

> Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Environmental exposure 8.2.2

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Physical and chemical properties

9.1 General information

9.1.1 Appearance

Physical state Liquid. Colour Amber. 9.1.2 Odour Oily.

9.2 Important health, safety and environmental information

Flash point Closed cup: 220°C (428°F) [Pensky-Martens.]

Kinematic: 68 mm²/s (68 cSt) at 40°C **Viscosity**

-33 °C **Pour point** 0.839 **Relative Density**

Solubility insoluble in water.

Partition coefficient

(LogKow)

9.3 Other information Not available.

10. Stability and reactivity

Stability The product is stable.

10.1 Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.2 Materials to avoid

Reactive or incompatible with the following materials: oxidising materials.

10.3 Hazardous

decomposition products

Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Acute toxicity

Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.

Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.

At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Chronic toxicity

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. **Chronic effects**

Effects and symptoms

Conforms to the regulation on preparation and distribution of safety data sheets on hazardous materials and preparations 26.12.2008 -

Substance/preparation Name Enersyn RC-S 68 Product code 402053-FR01 Page: 3/5 **Number of Revisions 2** Date of revision 20 September 2011 Format Turkey Language ENGLISH (ENGLISH) First issue date 1 December 2009 Build 1.0.1 (Turkey)

Eyes Potential risk of transient stinging or redness if accidental eye contact occurs.

Skin May cause skin dryness and irritation.

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition

products occurs

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

12 . Ecological information

12.1 Ecotoxicity

12.2 Environmental hazards Not classified as dangerous.

12.3 Mobility Spillages may penetrate the soil causing ground water contamination.

12.4 Persistence/degradability Biodegradable

12.5 Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer

could also be impaired.

13. Disposal considerations

Disposal considerations / Waste information

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Refer to all national, regional, and local regulations for disposal requirements

14. Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

15. Regulatory information

Classification and labelling have been performed according to EU directive 1999/45/EC as amended and adapted and Regulation on classification, packaging and labelling of Hazardous materials and preparations (26.12.2008-27092).

Label requirements

Risk phrasesThis product is not classified according to EU legislation.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current

requirements of REACH.

All components are listed or exempted.

United States inventory

(TSCA 8b)

Australia inventory (AICS)

Canada inventory

China inventory (IECSC)

Japan inventory (ENCS)

Korea inventory (KECI)

Philippines inventory

All components are listed or exempted.

(PICCS)

Conforms to the regulation on preparation and distribution of safety data sheets on hazardous materials and preparations 26.12.2008 – 27092.

Substance/preparation Name Enersyn RC-S 68 Product code 402053-FR01 Page: 4/5

Date of revision 20 September 2011 Number of Revisions 2 Format Turkey Language ENGLISH

First issue date 1 December 2009 Build 1.0.1 (Turkey) (ENGLISH)

16. Other information

History

Date of issue/ Date of 9/20/2011.

revision

Date of previous issue 9/14/2011.

Prepared by Product Stewardship

Notice to reader

Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Conforms to the regulation on preparation and distribution of safety data sheets on hazardous materials and preparations 26.12.2008 – 27092.

Substance/preparation Name Enersyn RC-S 68 Product code 402053-FR01 Page: 5/5

Date of revision 20 September 2011 Number of Revisions 2 Format Turkey Language ENGLISH

First issue date 1 December 2009 Build 1.0.1 (Turkey) (ENGLISH)