



صحيفة بيانات السلامة

AUTRAN SYN 295

القسم 1. الاسم (بيان المنتج)

AUTRAN SYN 295

بيان تعريف المنتج طبقاً للنظام

المنسق العالمي GHS

464239-US65

كود المنتج

464239

صحيفة بيانات سلامة المادة رقم #

سائل.

نوع المنتج

الاستخدامات الهامة المحددة للمادة أو الخليط وأوجه الاستخدام التي لا ينصح بها

استخدام المادة/المستحضر

سائل ناقل الحركة الأوتوماتيكي.

بالنسبة لجهاز التطبيق المحدد، انظر نشرة البيانات التقنية المعنية أو تشاور مع ممثل شركتنا.

BP Middle East

المورد

Standard Chartered Tower

8th Floor, Down Town Burj Khalifa

By Emaar Square

P.O. Box 1699, Dubai, United Arab Emirates

Main : (971) 4 331 7999

Fax : (971) 4 331 8530

خدمة Carechem : +44 (0) 671 239 1235 (اللغة العربية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

رقم هاتف الطوارئ

+44 (0) 670 239 1235 (اللغة الإنجليزية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

القسم 2. بيان الأخطار

الخطورة البيئية المائتية (الحادة) - الفئة 2
الخطورة البيئية المائتية (طويلة الأمد) - الفئة 3

تصنيف المادة أو الخليط

عناصر بطاقة الوسم في النظام المنسق العالمي GHS

بدون كلمة تنبيه

كلمة التنبيه

H401 - سام للحياة المائية.

عبارات المخاطر

H412 - ضار للحياة المائية مع تأثيرات طويلة الأمد.

عبارات التحذير

P102 - ضع المنتج بعيداً عن متناول الأطفال.

عامة

P101 - في حالة استشارة الطبيب : اصطحب معك وعاء المنتج أو بطاقة التعريف

الوقاية

P273 - تجنب انتشار المادة في البيئة.

الاستجابة

غير قابل للتطبيق.

التخزين

غير قابل للتطبيق.

P501 - تخلص من المحتويات والوعاء وفقاً لكافة اللوائح المحلية، والإقليمية، والوطنية، والدولية.

التخلص من النفايات

يزيل دهون الجلد.

الأخطار الأخرى التي لا تؤدي إلى تصنيف

القسم 3. التركيب/معلومات عن المكونات

خليط

مادة/مستحضر

مخزون أساسي اصطناعي. إضافات خاصة للأداء.

Product name	AUTRAN SYN 295	اسم المنتج	الصفحة: 17/1
Product code	464239-US65	Date of issue	03/08/2022.
Version	3.01	Format	Oman
تسعة		اللغة	ENGLISH
		العربية	

Page: 1/17 تاريخ الإصدار

كود المنتج

القسم 3. التركيب/معلومات عن المكونات

اسم المكون	%	رقم التسجيل في دائرة المستخلصات الكيميائية CAS
ديك-1-ين، بوليمر متجانس، ديك-1-ين مهدرج، أوليجمرز، مهدرج مواد مقطرة (بنترول)، معالجة بالهيدروجين بارافينيكية بدرجة كثيفة	$\geq 10 - \leq 25$	68037-01-4
2,6-دي-تيرت-بيوتيل فينول	≤ 3	64742-54-7
ثنائي (2-هيدروكسي إيثيل) شحم الكليل الأمين	< 1	128-39-2
3-(أيزو ديلسيلوكسي) أمين البروبيل	≤ 0.3	61791-44-4
	< 0.1	30113-45-2

على حد علم المورد في هذه اللحظة وطبقاً للتركيزات المستخدمة، لا توجد أية مكونات أو مكونات إضافية مصنفة كمواد خطرة على الصحة أو على البيئة تستدعي الإبلاغ عنها في هذا القسم.

القسم الثامن يعرض حدود التعرض المهني، في حال توفرها.

القسم 4. تدبير الإسعاف الأولي

وصف إجراءات الإسعافات الأولية اللازمة

ملامسة العين	في حالة الملامسة، يُراعى دفع الماء فوراً على العين لمدة لا تقل عن 15 دقيقة. يجب إبعاد الجفون عن مقلات العين لضمان الشطف الكامل. يراعى التحقق من عدم وجود عدسات لاصقة أو إزالتها إن وجدت. يُراعى الحصول على الرعاية الطبية.
استنشاق	في حالة الاستنشاق، يُراعى نقل المصاب إلى الهواء الطلق. في حالة استنشاق مخلفات التحلل عند نشوب حريق، قد تظهر الأعراض ظهوراً آجلاً. قد يكون من الضروري أن يظل الشخص المعرض تحت الملاحظة الطبية لـ 48 ساعة. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
ملامسة الجلد	يراعى غسل البشرة غسلاً جيداً بالماء والصابون أو بأحد منظفات الجلد المعترف بها. أزل الثياب والأحذية الملوثة. يُراعى غسل الثياب قبل إعادة استخدامها. يراعى تنظيف الحذاء تنظيفاً جيداً قبل ارتدائه ثانية. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
الابتلاع	لا تحرض على القيء إلا إن طلب أحد أعضاء الطاقم الطبي منك أن تقوم بهذا. يُحظر إعطاء أي شيء عن طريق الفم لشخص فاقد الوعي. في حالة فقدان الوعي، ضع المتعرض في وضعية الإفاقة واطلب الرعاية الطبية على الفور. يُراعى الحصول على الرعاية الطبية إذا استمرت التأثيرات الصحية الضارة أو إن كانت شديدة.

أهم الأعراض/التأثيرات، الحادة والمتأخرة

انظر القسم 11 لمزيد من المعلومات عن التأثيرات الصحية والأعراض.

بيان الرعاية الطبية الفورية والمعالجة الخاصة إذا كانت ضرورية

ملاحظات للطبيب	يجب أن تتم المعالجة حسب الأعراض بشكل عام ويتم إجراؤها لتخفيف حدة التأثيرات. في حالة استنشاق مخلفات التحلل عند نشوب حريق، قد تظهر الأعراض ظهوراً آجلاً. قد يكون من الضروري أن يظل الشخص المعرض تحت الملاحظة الطبية لـ 48 ساعة.
معالجات خاصة	لا يوجد علاج محدد.
حماية فريق الإسعافات الأولية	يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. قد تنطوي عملية الإنعاش من الفم إلى الفم على خطورة ما للشخص الذي يقدم المساعدة عند قيامه بها.

القسم 5. تدابير مكافحة الحريق

وسائل الإطفاء

وسائل الإطفاء المناسبة	يستخدم الرغوة أو مادة كيميائية الجافة متعددة الأغراض لإخماد الحريق.
وسائل الإطفاء غير المناسبة	لا تستخدم المياه النفاثة.
مخاطر خاصة ناشئة عن المادة الكيميائية	يجب إحتواء ماء الإطفاء الملوثة بهذه المادة للحيلولة دون تسربها إلى المجاري المائية أو المصارف أو المجاري الصحية. سوف يحدث تزايد في الضغط وقد تنفجر الحاوية في حالة حدوث حريق أو تسخين. هذه المادة سامة للحياة المائية. هذه المادة ضارة بالحياة المائية وتأثيراتها طويلة الأمد.
نواتج تحلل حراري خطيرة	نواتج الاحتراق قد تشمل ما يلي: أكاسيد الكربون (CO, CO ₂) أكاسيد النيتروجين (NO, NO ₂) (إلخ)

معدات الحماية الشخصية والاحتياطات اللازمة لعمال الإطفاء

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى عزل المكان على الفور و ذلك بإخلاء الأفراد المتواجدين على مقربة من الحادث في حالة نشوب حريق.

Product name	AUTRAN SYN 295	اسم المنتج	الصفحة: 17/2
Product code	464239-US65	Date of issue	03/08/2022.
Version	3.01	كود المنتج	تاريخ الإصدار Page: 2/17
نسخة		Format Oman	اللغة
			ENGLISH
			العربية

القسم 5. تدابير مكافحة الحريق

معدات الحماية الشخصية والاحتياطات
اللازمة لعمال الإطفاء

يجب على فريق مكافحة الحريق أن يرتدوا جهاز تنفس مكتفي ذاتياً SCBA إيجابي الضغط والزي الواقي كملأ.

القسم 6. تدابير مواجهة التسرب العارض

لاحتياطات الشخصية ومعدات الحماية وإجراءات الطوارئ

للأفراد من خارج فريق الطوارئ

اتصل بفريق الطوارئ. يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى إخلاء المناطق المجاورة. يراعى عدم السماح بالدخول لكل من لا يرتدي مهمات واقية أو من لا حاجة لك بهم من الأفراد. يراعى تجنب ملامسة المادة المنسكبة أو السير عليها. تجنب استنشاق البخار أو الرذاذ. يُراعى توفير تهوية كافية. ارتدي مهمات الواقية الشخصية الملائمة. قد تكون الأرضيات زلقة؛ يجب توخي العناية لتجنب السقوط.

لمسعفي الطوارئ

الدخول إلى مكان مقفل أو منطقة رديئة التهوية ملوثة بالأبخرة أو الرذاذ أو العادم يمثل خطورة بالغة في حالة عدم استخدام معدات الحماية المناسبة للجهاز التنفسي وعدم الاستعانة بنظام عمل آمن. قم بارتداء جهاز تنفس مستقل بذاته. احرص على ارتداء سترة مناسبة واقية من المواد الكيميائية. أحذية برقبة مقاومة للمواد الكيميائية. راجع كذلك المعلومات الواردة في قسم "للأفراد من خارج فريق الطوارئ".

الاحتياطات البيئية

تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف. يُراعى إبلاغ السلطات المعنية لو تسبب المنتج في تلوث البيئة (مجري الصرف، المجاري المائية، التربة أو الهواء). مادة ملوثة للماء. قد تكون ضارة بالبيئة إذا انتشرت بكميات كبيرة.

طرائق ومواد الاحتواء والتنظيف

انسكاب صغير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يُراعى امتصاصها بمادة خاملة، ثم إيداعها إحدى الحاويات الملائمة للتخلص من النفايات. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

انسكاب كبير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يتم الاقتراب من الناحية التي تهب منها الرياح إلى المكان. منع دخولها في البالوعات والصرف، و المجاري المائية، أو البدرومات، أو المناطق المغلقة. يُراعى احتواء الانسكاب وجمعه بمادة ماصة غير قابلة للاحتراق مثل الرمل، أو التراب، أو الفرميكيوليت، أو تراب دياتومي، ثم وضعها في إحدى الحاويات للتخلص منها بما يتفق واللوائح المحلية. المادة الماصة الملوثة قد تشكل خطراً مماثلاً لخطر المنتج المنسكب. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

القسم 7. المناولة والتخزين

احتياطات للمناولة الآمنة

احتياطات للمناولة الآمنة

يراعى ارتداء أجهزة الوقاية الشخصية الملائمة (انظر القسم 8). يحظر ابتلاعها. يُراعى تجنب ملامستها العين و الجلد و الثياب. تجنب استنشاق البخار أو الرذاذ. يُراعى الحفظ في الحاوية الأصلية أو في حاوية بديلة معتمدة مصنوعة من مادة متوافقة وإغلاقها بإحكام عند عدم استخدامها. الأوعية الفارغة تحتوي على بقايا قد تكون خطرة. لاتعيد استخدام الحاوية. يُراعى تجنب ملامسة المادة المنسكبة، و وصولها إلى التربة، و المجاري المائية السطحية.

إرشادات حول الصحة المهنية العامة

يحظر تناول الطعام، والشراب، والتدخين في الأماكن التي يجري التعامل فيها مع هذه المادة سواء بالمناولة، التخزين أو المعالجة. يُراعى الإغتسال جيداً بعد تناولها. اخلع الثياب الملوثة والتجهيزات الوقائية قبل دخول الأماكن المخصصة للطعام. انظر القسم 8 لمزيد من المعلومات حول إجراءات الحفاظ على الصحة.

متطلبات التخزين الآمنة، بما في ذلك ما

يتعلق بحالات عدم توافق المواد

خزن المادة وفقاً لتعليمات السلطات المحلية. خزن المادة في حاويتها الأصلية مع حمايتها من التعرض لحرارة الشمس المباشرة في منطقة جافة، وباردة، وجيدة التهوية بعيداً عن المواد غير المطابقة (انظر القسم 10)، وعن الطعام، والشراب. يراعى غلق الوعاء غلقاً تاماً محكماً إلى أن يُعد للاستخدام. يجب أن يتم التخزين والاستعمال فقط في معدات/حاويات مصممة للاستخدام مع هذا المنتج. لابد من إحكام غلق الأوعية التي قد قُطعت و تركها في وضع قائم و ذلك لتلافي حدوث تسريب. يُحظر التخزين في حاويات لا تحمل كتابة توضيحية. يُراعى استخدام طرق احتواء سليمة لتجنب تلوث البيئة.

التعرض لدرجات الحرارة العالية لفترات طويلة

غير ملائمة

القسم 8. ضوابط التعرض/الحماية الشخصية

تدابير التحكم

حدود التعرض المهني

اسم المُكوّن	حدود التعرض
مواد مقطرة (بنترول)، معالجة بالهيدروجين بارافينية بدرجة كثيفة	TLV ACGIH (الولايات المتحدة). TWA: 5 مج / م ³ 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشَق

الصفحة: 17/3	اسم المنتج	AUTRAN SYN 295	Product name
Page: 3/17 تاريخ الإصدار	Date of issue	03/08/2022.	Product code
اللغة	Format Oman	3.01 نسخة	Version
العربية	ENGLISH		

القسم 8. ضوابط التعرض/الحماية الشخصية

الضوابط الهندسية المناسبة

يجب تقييم جميع الأنشطة المرتبطة بالمواد الكيميائية من حيث مخاطرها على الصحة، وذلك لضمان التحكم في معدلات التعرض بالشكل المناسب. لا يجوز تحديد معدات الوقاية الشخصية إلا بعد تقييم الأشكال الأخرى لإجراءات التحكم (على سبيل المثال عمليات التحكم الهندسية) بالشكل المناسب. يجب أن تتوافق معدات الوقاية الشخصية مع المواصفات المعنية وأن تكون مناسبة للاستخدام، ويجب الحفاظ عليها في حالة جيدة وصيانتها بشكل سليم.

يجب التشاور مع مورد معدات الوقاية الشخصية لطلب المشورة بشأن الاختيار والمواصفات المعنية. لمزيد من المعلومات، اتصل بالهيئة المحلية للمواصفات.

احرص على توفير تهوية للعوامل أو الوسائل الهندسية الأخرى للحماية، وذلك للإبقاء على مستويات التركيز المعنية للمواد العالقة بالهواء دون حدود التعرض المقبولة لها على الصعيد المهني.

القرار النهائي لاختيار معدات الوقاية يعتمد على تقييم المخاطر. ومن المهم التأكد من ملاءمة جميع عناصر معدات الوقاية الشخصية.

ننصح بفحص الانبعاثات الصادرة من أجهزة العمل والتهوية، للتأكد من استيفائها لمتطلبات قانون حماية البيئة. في بعض الحالات، قد يكون من الضروري استخدام أجهزة إمتصاص الدخان، أو المرشحات أو إجراء تعديلات هندسية للمعدات، كي يتسنى تقليل الانبعاثات إلى مستويات مقبولة.

ضوابط التعرض البيئي

تدابير الحماية الفردية

إجراءات النظافة الشخصية

اغسل اليدين، والذراعين، والوجه غسلاً تاماً بعد مناولة المنتجات الكيميائية، وعند الأكل والتدخين، وفي نهاية فترة العمل. يتوجب استخدام طرق ملائمة لنزع الثياب التي يُحتمل تلوثها. يُراعى غسل الثياب الملوثة قبل ارتدائها مرة ثانية. تأكد من وجود محطات غسيل الأعين وأدشاش الطوارئ على مقربة من موقع العمل.

نظارات أمان ذات سائرات جانبية.

أدوات حماية الوجه/العين

حماية للجلد

حماية يديوية

احرص على ارتداء القفازات الواقية من الماء إذا كان من المحتمل حدوث ملامسات متكررة وطويلة. قم بارتداء القفازات المقاومة للمواد الكيميائية. يُنصح باستخدام قفازات نيتريل. يعتمد الاختيار الصحيح لقفازات الحماية على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة القفازات (حتى أفضل القفازات المقاومة للمواد الكيميائية تتآكل بفعل التعرض المتكرر للمواد الكيميائية). معظم القفازات توفر الحماية لفترة زمنية قصيرة فقط وبعدها يجب التخلص منها واستبدالها. نظراً للظروف الخاصة لبيئات العمل واختلاف ممارسات التعامل مع المواد، فيجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار القفازات بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

أدوات حماية الجسم

استخدام الملابس الواقية يعتبر من الممارسات الجيدة في المجال الصناعي. يجب انتقاء التجهيزات الشخصية الواقية للجسم بما يتفق والمهمة التي يجري القيام بها والمخاطر التي تنطوي عليها، كما يجب أن يعتمدوا أحد المختصين قبل التعامل مع هذا المنتج. أفرولات العمل المصنوعة من القطن أو البوليستر/القطن توفر الحماية فقط من التلوث السطحي الخفيف الذي لا يصل إلى الجلد. ويجب غسل أفرولات العمل بصفة منتظمة. عندما تزداد خطورة تعرض الجلد للمواد (على سبيل المثال عند تنظيف المواد المنسكبة أو في حالة وجود خطورة من تناثر الرذاذ)، فيجب ارتداء مريلة مقاومة للمواد الكيميائية و/أو أحذية وسترات غير منفذة للمواد الكيميائية.

حماية تنفسية

في حالة عدم كفاية التهوية، يُراعى ارتداء تجهيزات تنفسية ملائمة. يعتمد الاختيار الصحيح لتجهيزات حماية الجهاز التنفسي على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة تجهيزات حماية الجهاز التنفسي. يجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار تجهيزات حماية الجهاز التنفسي بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

القسم 9. الخصائص الفيزيائية والكيميائية

ظروف قياس جميع الخصائص تتم في ظل الضغط ودرجة الحرارة القياسيين ما لم تتم الإشارة إلى غير ذلك.

المظهر

الحالة الفيزيائية

اللون

الرائحة

عتبة الرائحة

الأس الهيدروجيني pH

نقطة الانصهار/نقطة التجمد

نقطة الغليان، والنقطة الأولية، ومعدل الغليان

نقطة السقوط

نقطة الوميض

معدل التبخر

القابلية على الاشتعال

سائل.

أحمر.

غير متوفرة.

غير متوفرة.

غير قابل للتطبيق.

غير متوفرة.

غير متوفرة.

غير متوفرة.

غير متوفرة.

جهاز الكأس المفتوحة: <235°C (455°F) [جهاز كليفلاند]

غير متوفرة.

Product name	AUTRAN SYN 295	اسم المنتج	الصفحة: 17/4
Product code	464239-US65	Date of issue	Page: 4/17
Version	3.01	Format Oman	تاريخ الإصدار
نسخة		اللغة	ENGLISH
		العربية	

القسم 9. الخصائص الفيزيائية والكيميائية

غير قابل للتطبيق. اعتمادًا على - الحالة الفيزيائية
غير متوفرة.

القابلية للاشتعال (مادة صلبة، غاز)
الحد الأعلى/الأدنى للانفجار أو القابلية
للاشتعال
الضغط البخاري

ضغط البخار عند 20 درجة مئوية			ضغط البخار عند 50 درجة مئوية		
اسم المكون	مم زئبق	كيلوباسكال	طريقة	مم زئبق	كيلوباسكال
ديك-1-ين، بوليمر متجانس، ديك-1-ين مهدرج، أوليجمرز، مهدرج	0	0	ASTM E 1194-87		
ديك-1-ين، بوليمر متجانس، ديك-1-ين مهدرج، أوليجمرز، مهدرج	0	0	ASTM E 1194-87		
diisooctyl adipate	0	0			
1-Dodecene, polymer with 1-decene, hydrogenated	0	0	EU A.4		
مواد مقطرة (بنترول)، معالجة بالبهروجين بارافينيية بدرجة كثيفة	<0.08	<0.011	ASTM D 5191		

غير متوفرة.

غير متوفرة.

>1000 كجم/م³ (g/cm³ >1) عند 15°C

غير ذوب في الماء.

غير متوفرة.

غير قابل للتطبيق.

كثافة البخار النسبية

الكثافة النسبية

الكثافة

الذوبانية

الذوبانية

معامل تفريق الأوكتانول/الماء

درجة حرارة الاشتعال الذاتي

اسم المكون	°	ف	طريقة
ديك-1-ين، بوليمر متجانس، ديك-1-ين مهدرج، أوليجمرز، مهدرج	343 إلى 369	649.4 إلى 696.2	ASTM D 2159
ديك-1-ين، بوليمر متجانس، ديك-1-ين مهدرج، أوليجمرز، مهدرج	343 إلى 369	649.4 إلى 696.2	ASTM D 2159

غير متوفرة.

درجة حرارة الانحلال

اللزوجة

كينماتي: 37.64 /S²mm (37.64 سنتي ستوك) عند 40°C
كينماتي: 7 إلى 8 /S²mm (7 إلى 8 سنتي ستوك) عند 100°C

خصائص الجسيمات

حجم الجسيمات المتوسط

غير قابل للتطبيق.

القسم 10. الثبات الكيميائي والقابلية للتفاعل

التفاعلية
غير متاح بيانات اختبار أخرى معينة لهذا المنتج. ارجع إلى الظروف التي يجب تجنبها والمواد غير المتوافقة لمزيد من المعلومات.

المنتج ثابت.

لن تحدث تفاعلات خطيرة في ظروف التخزين والاستخدام العادية.
لن تحدث بلمرة خطيرة في ظروف التخزين والاستخدام العادية.

يجب تجنب جميع مصادر الاشتعال الممكنة (شرر أو لهب).

تتفاعل أو غير متطابقة مع المواد التالية: مواد مؤكسدة.

في ظروف التخزين والاستخدام العادية، من غير المنتظر أن تتولد نواتج تحليل خطيرة.

نواتج الانحلال الخطرة

الثبات الكيميائي

إمكانية التفاعلات الخطرة

الظروف التي ينبغي تجنبها

المواد غير المتوافقة

Product name	AUTRAN SYN 295	اسم المنتج	الصفحة: 17/5
Product code	464239-US65	Date of issue	03/08/2022.
Version	3.01	Format	Oman
اللغة	ENGLISH	اللغة	العربية
تاريخ الإصدار	Page: 5/17	كود المنتج	03/08/2022.
نسخة	3.01	Format	Oman

القسم 11 . المعلومات السمية

معلومات حول الآثار السمية

خطر الاستنشاق على الجهاز التنفسي

الاسم

النتيجة
خطر السمية الإستنشاق - الفئة 1

ديك-1-ين، بوليمر متجانس، ديك-1-ين مهدرج، أوليجمرز، مهدرج

معلومات عن سُبُل التعرض المرجحة سُبُل التعرض المُرتقبة: جلدي، استنشاق.

آثار صحية حادة كامنة

ملامسة العين

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

استنشاق

التعرض لمنتجات التحلل قد يشكل خطورة صحية. قد تتأجل بعض التأثيرات الخطيرة عقب التعرض.

ملامسة الجلد

يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيجه.

الابتلاع

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

أعراض متعلقة بالخواص السمية والكيميائية والفيزيائية

ملامسة العين

ليست هناك بيانات معينة.

استنشاق

قد يؤدي إلى ضرر في حالة الاستنشاق في حالة التعرض للأبخرة أو الرذاذ أو العوادم الناتجة عن التحلل الحراري للمنتجات.

ملامسة الجلد

الأعراض الضائرة قد تشمل ما يلي:

تهيج

الجفاف

التشقق

الابتلاع

ليست هناك بيانات معينة.

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

ملامسة العين

هناك خطورة محتملة من حدوث لسعة عابرة أو احمرار عابر في حالة حدوث ملامسة العين بشكل عرضي.

ملامسة الجلد

اللامسة المطوّلة أو المتكررة بإمكانها أن تتسبب في إزالة دهون الجلد وتهيجه وتشققه و/أو التهابه.

الابتلاع

ابتلاع كميات كبيرة يمكن أن يؤدي إلى الغثيان والإسهال.

آثار صحية مزمنة كامنة

عامة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

السرطنة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثير على الجنينات

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

القابلية على التسبب في المسخ

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات النمائية

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات الخصوبية

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

القياسات الرقمية للسمية

تقديرات السمية الحادة

غير متوفرة.

القسم 12. المعلومات الإيكولوجية

تأثيرات بيئية

هذه المادة سامة للحياة المائية. هذه المادة ضارة بالحياة المائية وتأثيراتها طويلة الأمد.

الثبات والتحلل

لا يُتوقع أن تكون قابلة للتحلل السريع.

القدرة على التراكم الأحيائي

لا يُتوقع أن يتراكم هذا المنتج حيوياً في البيئة من خلال السلاسل الغذائية.

القابلية على التحرك عبر التربة

Product name	AUTRAN SYN 295	اسم المنتج	الصفحة: 17/6
Product code	464239-US65	Date of issue	03/08/2022.
Version	3.01	Format	Oman
اللغة	ENGLISH	تاريخ الإصدار	Page: 6/17
العربية	ENGLISH	كود المنتج	03/08/2022.
نسخة	3.01	Format	Oman

القسم 12. المعلومات الإيكولوجية

مُعامل تقاسم التربة/الماء (Koc) غير متوفرة.
التحريك

المواد المنسكبة يمكن أن تتوغل في التربة وتتسبب في تلوث المياه الجوفية.

التأثيرات الضارة الأخرى

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.
قد تتسبب السوائل المنسكبة في تكوين طبقة على أسطح الماء، وقد تتسبب في ضرر مادي للكائنات الحية. وقد يتم إعاقة نقل الأكسجين أيضاً.

معلومات بيئية أخرى

القسم 13. الاعتبارات المتعلقة بتصريف المواد والتخلص منها

طرائق التصريف

ينبغي تجنب توليد النفايات أو التقليل منها حيثما أمكن. ينبغي عدم التخلص من الكميات الكبرى من فضالة نفاية المُنتج عبر شبكة الصرف الصحي وإنما مُعالجتها في محطة مُناسبة لمعالجة مياه الصرف. يُراعى التخلص من الفائض والمنتجات غير القابلة لإعادة التدوير من خلال أحد المقاولين المرخص لهم بذلك. يراعى أن يجري دوماً التخلص من هذا المنتج، و المحاليل و المنتجات الثانوية بما يتفق و متطلبات الحماية البيئية و تشريعات التخلص من النفايات و غيرها من متطلبات السلطة الإقليمية و المحلية. ينبغي أن يُعاد تدوير نفاية التغليف. ينبغي عدم أخذ الحرق أو الطمر في الاعتبار إلا إذا كانت إعادة التدوير غير مُجدية. لا بد أن يجري التخلص من هذا المنتج وحايثته بطريقة آمنة. ينبغي الحذر عند مناولة الحاويات المُفرّغة التي لم تُنظف ولم تُغسل. قد تظل بعض رواسب المنتج عالقة بالحاويات الفارغة أو قُمصانها. تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية و البالوعات و مجاري الصرف.

القسم 14. المعلومات المتعلقة بالنقل

IATA	IMDG	
غير مقننة.	غير مقننة.	رقم الأمم المتحدة
-	-	اسم الشحن الصحيح الخاص بالأمم المتحدة
-	-	فئة/فئات مخاطر النقل
-	-	مجموعة التعبئة
لا.	لا.	الأخطار البيئية
-	-	معلومات إضافية

احتياطات خاصة للمستخدم غير متوفرة.

النقل سائناً بحسب اتفاقيات المنظمة البحرية الدولية (IMO) غير متوفرة.

القسم 15. المعلومات التنظيمية

القواعد المتعلقة بالسلامة والصحة والبيئة، لا توجد لوائح وطنية و/أو إقليمية معروفة تنطبق على هذا المنتج (بما في ذلك مكوناته). المنطقة على المنتج

قائمة الجرد الوطنية

أستراليا

كندا

الصين.

الوضع وفق REACH (النظام المتعلق بتسجيل وتقييم وترخيص المواد الكيميائية)

اليابان

كافة المُكونات مُدرجة بالقائمة أو مُستثناة منها.

كافة المُكونات مُدرجة بالقائمة أو مُستثناة منها.

مُكوّن واحد على الأقل غير مُدرَج.

للتعرف على حالة REACH لهذا المنتج، يرجى التواصل مع جهة الاتصال في شركتك، كما هو محدد في القسم 1.

مُكوّن واحد على الأقل غير مُدرَج.

Product name	AUTRAN SYN 295	اسم المنتج	الصفحة: 17/7
Product code	464239-US65	Date of issue	03/08/2022.
Version	3.01	Format	Oman
اللغة	ENGLISH	اللغة	العربية

القسم 15. المعلومات التنظيمية

الفلبين	كافة المكونات مُدرجة بالقائمة أو مُستثناة منها.
جمهورية كوريا	كافة المكونات مُدرجة بالقائمة أو مُستثناة منها.
تايبان	كافة المكونات مُدرجة بالقائمة أو مُستثناة منها.
الولايات المتحدة	جميع المكونات تحمل الصفة "فعالة" أو الصفة "مستثناة".

القسم 16. المعلومات الأخرى

السيرة

تاريخ الإصدار/تاريخ المراجعة	03/08/2022.
تاريخ الإصدار السابق	03/08/2022.
نسخة	3.01
من إعداد	Product Stewardship
مفتاح الاختصارات	ACGIH = المؤتمر الأمريكي للمتخصصين في الصحة الصناعية CAS = رقم سجل دائرة المستخلصات الكيميائية GHS = النظام المنسق العالمي IATA = اتحاد النقل الجوي الدولي، المنظمة IMDG = قوانين المنظمة البحرية الدولية والقواعد الحاكمة لشحن البضائع عن طريق المياه. OEL = حد التعرض المهني REACH = التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيميائية [نظام (المفوضية الأوروبية) رقم [1907/2006 SDS = نشرة بيانات الأمان STEL = حد التعرض على المدى القصير TWA = المتوسط المرجح للوقت

رقم UN = رقم الأمم المتحدة، رقم من أربعة أرقام يتم تعيينه من قبل لجنة الأمم المتحدة لخبراء نقل البضائع الخطرة.
متنوع = قد يحتوي على واحد أو أكثر من المكونات التالية 64741-88-4, 64741-89-5, 64741-95-3, 64742-53-6, 64742-52-5, 64742-45-6, 64742-44-5, 64742-01-4, 64741-96-4, 64742-62-7, 64742-58-1, 64742-57-0, 64742-56-9, 64742-55-8, 64742-54-7, 72623-87-1, 72623-86-0, 72623-85-9, 64742-70-7, 64742-65-0, 64742-63-8

الإجراء المتبع للحصول على التصنيف

التصنيف	التبرير
طريقة الحساب	طريقة الحساب
طريقة الحساب	طريقة الحساب

تشير إلى معلومات تم تغييرها مقارنة بالنسخة التي سبق إصدارها.

ملاحظة للقارئ الكريم

تم اتخاذ جميع الخطوات المتاحة المعقولة لضمان دقة نشرة البيانات هذه والمعلومات المتعلقة بالصحة والأمان والبيئة حسب البيانات الموضحة أدناه. لا يوجد ضمان أو تفويض، صريح أو ضمني، بشأن دقة أو اكتمال البيانات والمعلومات الواردة في نشرة البيانات هذه.

تسري البيانات والنصائح المعطاة في حالة بيع المنتج للتطبيق المذكور أو التطبيقات المذكورة. لا يجوز لك استخدام المنتج في غير التطبيق المذكور أو التطبيقات المذكورة دون طلب المشورة من شركة Group BP.

يجب على المستخدم تقييم هذا المنتج واستخدامه بشكل آمن بما يتوافق مع جميع القوانين والتشريعات المعمول بها. لا تتحمل شركة Group BP أية مسؤولية عن أي ضرر أو إصابة تنتج عن الاستخدام، أو أي استخدام آخر بخلاف استخدام المنتج المذكور للخامة، أو في حالة عدم مراعاة التوصيات، أو المخاطر المتأصلة في طبيعة الخامة. القارئون بشراء المنتج لتوريده إلى طرف ثالث للاستخدام في العمل عليهم اتخاذ جميع الخطوات اللازمة للتأكد من أن أي شخص يستخدم المنتج يكون على دراية بالمعلومات الواردة في هذه النشرة. يجب على أصحاب العمل إبلاغ الموظفين لديهم وغيرهم من الأشخاص المعنيين بالمخاطر الموضحة في هذه النشرة وعن الاحتياطات الواجب اتخاذها. يمكنك الاتصال بشركة Group BP للتأكد من أن هذا المستند على أحدث وضع. ممنوع منعًا باتًا إجراء تغيير على هذا المستند.

SAFETY DATA SHEET

AUTRAN SYN 295



Section 1. Identification

GHS product identifier	Autran Syn 295
Product code	464239-US65

Product name	AUTRAN SYN 295	اسم المنتج	17/8 الصفحة
Product code	464239-US65	Date of issue	03/08/2022.
Version	3.01	Format	Oman
Language	ENGLISH	اللغة	العربية

Section 1. Identification

SDS no. 464239

Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/
mixture** Automatic transmission fluid.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Manufacturer

Supplier BP Middle East
Standard Chartered Tower
8th Floor, Down Town Burj Khalifa
By Emaar Square
P.O. Box 1699, Dubai, United Arab Emirates

Main : (971) 4 331 7999

Fax : (971) 4 331 8530

EMERGENCY TELEPHONE NUMBER

Carechem: +44 (0) 1235 239 671 (Arabic language 24/7)

+44 (0) 1235 239 670 (English language 24/7)

Section 2. Hazards identification

GHS Classification SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements

Signal word No signal word.

Hazard statements H401 - Toxic to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention P273 - Avoid release to the environment.

Response Not applicable.

Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not
result in classification** Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture Mixture

Synthetic base stock. Proprietary performance additives.

Ingredient name	%	CAS number
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	≥10 - ≤25	68037-01-4
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	64742-54-7
2,6-di-tert-butylphenol	<1	128-39-2
Bis (2-hydroxyethyl) tallow alkylamine	≤0.3	61791-44-4
3-(isodecyloxy)propylamine	<0.1	30113-45-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name	AUTRAN SYN 295	اسم المنتج	17/9: الصفحة
Product code	464239-US65	كود المنتج	Date of issue 03/08/2022. تاريخ الإصدار Page: 9/17
Version 3.01	نسخة	Format Oman	Language اللغة
			ENGLISH العربية

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable	Use foam or all-purpose dry chemical to extinguish.
Unsuitable extinguishing media	Do not use water jet.

Specific hazards arising from the chemical	Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects.
---	---

Hazardous thermal decomposition products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)
---	--

Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
---	---

Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
---	--

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
------------------------------------	---

Product name	AUTRAN SYN 295	اسم المنتج	17/10	الصفحة:
Product code	464239-US65	كود المنتج	Date of issue	03/08/2022.
Version	3.01	نسخة	Format	Oman
			Language	اللغة
			ENGLISH	العربية

Section 6. Accidental release measures

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

Product name	AUTRAN SYN 295	اسم المنتج	17/11: الصفحة
Product code	464239-US65	كود المنتج	Date of issue 03/08/2022. تاريخ الإصدار Page: 11/17
Version 3.01	نسخة	Format Oman	اللغة Language ENGLISH العربية

Section 8. Exposure controls/personal protection

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name	AUTRAN SYN 295	اسم المنتج	17/12: الصفحة
Product code	464239-US65	كود المنتج	Date of issue
Version	3.01	نسخة	Format Oman
			Language
			ENGLISH
			اللغة
			العربية

03/08/2022.

تاريخ الإصدار Page: 12/17

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	Liquid.
Colour	Red.
Odour	Not available.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Boiling point, initial boiling point, and boiling range	Not available.
Drop Point	Not available.
Flash point	Open cup: >235°C (>455°F) [Cleveland]
Evaporation rate	Not available.
Flammability	Not available.
Lower and upper explosion limit/flammability limit	Not available.
Vapour pressure	

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	0	0	ASTM E 1194-87			
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	0	0	ASTM E 1194-87			
diisooctyl adipate	0	0				
1-Dodecene, polymer with 1-decene, hydrogenated	0	0	EU A.4			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			

Relative vapour density	Not available.
Relative density	Not available.
Density	<1000 kg/m³ (<1 g/cm³) at 15°C
Solubility	insoluble in water.
Solubility	Not available.
Partition coefficient: n-octanol/water	Not applicable.
Auto-ignition temperature	

Ingredient name	°C	°F	Method
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

Decomposition temperature	Not available.
---------------------------	----------------

Section 9. Physical and chemical properties

Viscosity Kinematic: 37.64 mm²/s (37.64 cSt) at 40°C
Kinematic: 7 to 8 mm²/s (7 to 8 cSt) at 100°C

Particle characteristics

Median particle size

غير قابل للتطبيق.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated

Result

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

No specific data.

Inhalation

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Skin contact

Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion

No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Product name	AUTRAN SYN 295	اسم المنتج	17/14: الصفحة
Product code	464239-US65	كود المنتج	Date of issue 03/08/2022. تاريخ الإصدار Page: 14/17
Version 3.01	نسخة	Format Oman	Language اللغة
			ENGLISH العربية

Section 11. Toxicological information

Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Environmental effects	This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects.
------------------------------	---

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition coefficient (K_{oc})	Not available.
--	----------------

Mobility	Spillages may penetrate the soil causing ground water contamination.
-----------------	--

Other adverse effects	No known significant effects or critical hazards.
------------------------------	---

Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
-------------------------------------	--

Section 13. Disposal considerations

Disposal methods	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
-------------------------	--

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-

Product name	AUTRAN SYN 295	اسم المنتج	17/15 الصفحة:
Product code	464239-US65	كود المنتج	Date of issue 03/08/2022. تاريخ الإصدار Page: 15/17
Version 3.01	نسخة	Format Oman	Language اللغة
			ENGLISH العربية

Section 14. Transport information

Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product No known specific national and/or regional regulations applicable to this product (including its ingredients).

International lists

National inventory

Australia All components are listed or exempted.

Canada All components are listed or exempted.

China At least one component is not listed.

REACH Status For the REACH status of this product please consult your company contact, as identified in Section 1.

Japan At least one component is not listed.

Philippines All components are listed or exempted.

Republic of Korea All components are listed or exempted.

Taiwan All components are listed or exempted.

United States All components are active or exempted.

Section 16. Other information

History

Date of issue/Date of revision 03/08/2022.

Date of previous issue 03/08/2022.

Version 3.01

Prepared by Product Stewardship

Key to abbreviations
ACGIH = American Conference of Industrial Hygienists
CAS Number = Chemical Abstracts Service Registry Number
GHS = Global Harmonised System
IATA = International Air Transport Association, the organisation
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.
OEL = Occupational Exposure Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
SDS = Safety Data Sheet
STEL = Short term exposure limit
TWA = Time weighted average
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Product name	AUTRAN SYN 295	اسم المنتج	17/16 الصفحة
Product code	464239-US65	كود المنتج	Date of issue 03/08/2022. تاريخ الإصدار Page: 16/17
Version 3.01	نسخة	Format Oman	Language اللغة ENGLISH العربية

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
	Calculation method Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	AUTRAN SYN 295	اسم المنتج	17/17 الصفحة:
Product code	464239-US65	كود المنتج	03/08/2022. تاريخ الإصدار Page: 17/17
Version	3.01	نسخة	Format Oman
			Language اللغة
			ENGLISH العربية