

صحيفة بيانات السلامة

Energear 140

القسم 1. الاسم (بيان المنتج)

بيان تعريف المنتج طبقا للنظام النظام

المنسق العالمي GHS

عود المنتج 467139-AE02

صحيفة بيانات سلامة المادة رقم #

نوع المنتج سائل.

الاستخدامات الهامة المُحددة للمادة أو الخليط وأوجه الاستخدام التي لا يُنصَح بها

استخدام المادة/المستحضر سائل ناقل الحركة اليدوي.

بالنسبة لجهاز التطبيق المحدد، انظر نشرة البيانات التقنية المعنية أو تشاور مع ممثل شركتنا.

المورّد BP Egypt 14

Road 252 Diglaamaadi

Cairo

Tel +20 2 25199915

رقم هاتف الطوارئ خدمة Carechem: 44 (Carechem) في اليوم/7 أيام على مدار الأسبوع)

44+ (0) 1235 (239 670 (اللغة الإنجليزية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

القسم 2. بيان الأخطار

تصنيف المادة أو الخليط غير مُصنَّفة.

عناصر بطاقة الوسم في النظام النظام المنسق العالمي GHS

كلمة التنبيه بدون كلمة تنبيه

عبارات المخاطر كرجة معروفة.

عبارات التحذير

 الوقاية
 غير قابل التطبيق.

 الاستجابة
 غير قابل التطبيق.

 التخزين
 غير قابل التطبيق.

 التخلص من النفاية
 غير قابل التطبيق.

الأخطار الأخرى التي لا تؤدي إلى تصنيف يزيل دهون الجلد.

القسم 3. التركيب/معلومات عن المكونات

مادة/مستحضر خليط

زيت أساسي عالي النقاوة (خلاصة DMSO 346 IP). إضافات خاصة للأداء.

الصفحة: 161 | Product name | Energear 140 | الصفحة: 161 | Product code | 467139-AE02 | كود المنتج | Page: 1/16 | Pormat Egypt | Language | كاللغة | Product code | كاللغة | Product code | كود المنتج | كود المنتج | كود المنتج | Product code | Prod

العربية ENGLISH العربية

القسم 3. التركيب/معلومات عن المكونات

اسم المُكوَن	%	رقم CAS
زيت متبقى (نفط)، منزوعة الشحم بمذيب	≥25 - ≤50	64742-62-7
زيت متبقي (نفط)، زيوت متبقية (نفط)، معالجة بالماء	≥25 - ≤50	64742-57-0
مواد مقطرة (بترول)، معالجة بالهيدروجين بارافينيية بدرجة كثيفة	≤3	64742-54-7
مواد مقطرة (بترول)، خالية من الشمع بالمذيب، بارافينيية بدرجة كثيفة	≤3	64742-65-0
1-Propene, 2-methyl-, sulfurized	≤3	68511-50-2
(Z)-أو كتاديك-9-إينيلامين	<0.025	112-90-3

على حد علم المورّد في هذه اللحظة وطبقاً للتركيزات المستخدمة، لا توجد أية مكوّنات أو مكوّنات إضافية مصنفة كمواد خطِرة على الصحة أو على البيئية تستدعيّ الإبلاغ عنها في هذا القسم.

القسم الثامن يعرض حدود التعرض المهني، في حال توفرها.

القسم 4. تدبير الإسعاف الأولى

وصف إجراءات الإسعافات الأولية اللازمة

ملامسة العين

في حالة الملامسة، يُراعى دفق الماء فوراً على الأعين لمدة لا تقل عن 15 دقيقة. يجب إبعاد الجفون عن مقلات الأعين لضمان الشطف الكامل. يراعى التحقق من عدم وجود عدسات لاصقة أو إزالتها إن وُجدت. يُراعى الحصول على الرعاية الطبية.

في حالة الإستنشاق، يُراعى نقل المصاب إلى الهواء الطلق. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض. يراعى غسل البشرة غسلا جيدا بالماء و الصابون أو بأحد منظفات الجلد المعترف بها. أزل الثياب و الأحذية الملوثة. يُراعى غسل الثياب قبل إعادة استخدامها. يراعى تنظيف الحذاء تنظيفا جيدا قبل ارتدائه ثانية. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض. إذا حدث تهيج أو طفح جلدي: تطلب استشارة الطبيب/رعاية طبية.

لا تحرض على القيء إلا إن طلب أحد أعضاء الطاقم الطبي منك أن تقوم بهذا. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.

أهم الأعراض/التأثيرات، الحادة والمتأخرة

انظر القسم 11 لمزيد من المعلومات عن التأثيرات الصحية والأعراض.

بيان الرعاية الطبية الفورية والمعالجة الخاصة إذا كانت ضرورية

ملاحظات للطبيب يجب أن تتم المعالجة حسب الأعراض بشكل عام ويتم إجراؤها لتخفيف حدة التأثيرات.

معالجات خاصة لا يوجد علاج محدد.

حماية فريق الإسعافات الأولية يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب.

القسم 5. تدابير مكافحة الحريق

معدات الحماية الشخصية والاحتياطات

ENGLISH

اللازمة لعمال الإطفاء

العربية

وسائل الإطفاء

استنشاق

الابتلاع

ملامسة الجلد

وسائل الإطفاء المناسبة في حالة نشوب حريق، استخدم الرغوة والمواد الكيميائية الجافة أو طفاية حريق أو بخاخة بها ثاني أكسيد الكربون.

وسائل الإطفاء غير المناسبة لا تستخدم المياه النفاثة.

مخاطر خاصة ناشئة عن المادة الكيميائية سوف يحدث تزايد في الضغط وقد تنفجر الحاوية في حالة حدوث حريق أو تسخين.

نواتج تحلل حراري خطِرة نواتج الاحتراق قد تشمل ما يلي: أكاسيد الكربون (CO₂,CO)

يُحظِر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعي عزل المكان على الفور و ذلك بإخلاء

الأفراد المتواجدين على مقربةً من الحادث في حالة نشوب حريق.

معدات الحماية الشخصية والاحتياطات يجب على فريق مُكافحة الحريق أن يرتدوا جهاز تنفس مكتفيّ ذاتياً SCBA إيجابي الضغط والزي الواقي كاملاً. اللازمة لعمال الإطفاء

الصفحة: £16/2 الصفحة: 16/2 | Product name | Energear 140 | اسم المنتج | Product code | 467139-AE02 | كود المنتج | Page: 2/16 | Version 3,02 | اللغة | Format Egypt | Language

القسم 6. تدابير مواجهة التسرب العارض

لاحتياطات الشخصية ومعدات الحماية وإجراءات الطوارئ

للأفراد من خارج فريق الطوارئ

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى إخلاء المناطق المجاورة. يراعى عدم السماح بالدخول لكل من لا يرتدي مهمات الواقية أو من لا حاجة لك بهم من الأفراد. يراعى تجنب ملامسة المادة المنسكبة أو السير عليها. ارتدي مهمات الواقية الشخصية المُلائمة. قد تكون الأرضيات زلقة؛ يجب توخي العناية المنسكبة أو السير عليها.

جنب السقوط.

إذا لزم الأمر ارتداء ثيابًا خاصة للتعامل مع الانسكاب، يُرجى أخذ ما ورد في القسم 8 من معلومات حول المواد المناسبة وغير المناسبة في الحسبان. راجع كذلك المعلومات الواردة في قسم "للأفراد من خارج فريق الطوارئ". لمسعفي الطوارئ

الاحتياطات البيئية

تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف. يُراعى إبلاغ السلطات المعنية لو تسبب المنتج في تلوث البيئة (مجاري الصرف، المجاري المائية، التربة أو الهواء).

طرائق ومواد الاحتواء والتنظيف

يُراعى وقف النسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يُراعى امتصاصها بمادة خاملة، ثم إيداعها إحدى الحاويات المُلائمة للتخلص من النفاياة. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المدخورين.

انسكاب كبير

انسكاب صغير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. امنع دخولها في بالوعات الصرف، و المجاري المائية، أو البدرومات، أو المناطق المغلقة. يُراعى احتواء الانسكاب وجمعه بمادة ماصةٍ غير قابلة للاحتراق مثل الرمل، أو التراب، أو الفرميكيوليت، أو تراب دياتومي، ثم وضعها في إحدى الحاويات للتخلص منها بما يتفق واللوائح المحلية. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

القسم 7. المناولة والتخزين

احتياطات للمناولة المأمونة

احتياطات للمناولة الآمنه

إرشادات حول الصحة المهنية العامة

يراعى ارتداء أجهزة الوقاية الشخصية الملائمة(انظر القسم 8).

يحظر تناول الطعام، والشراب، والتدخين في الأماكن التي يجري التعامل فيها مع هذه المادة سواء بالمناولة، التخزين أو المعالجة. يُراعى الإغتسال جيداً بعد مناولتها. اخلع الثياب المُلوَّثة والتجهيزات الوقائية قبل دخول الأماكن المخصصة للطعام. لا يسمح بارتداء ملابس العمل الملوثة خارج مكان العمل. انظر القسم 8 لمزيد من المعلومات حول إجراءات الحفاظ على الصحة.

متطلبات التخزين الآمنه، بما في ذلك ما يتعلق بحالات عدم توافق المواد

خزن المادة وفقاً لتعليمات السلطات المحلية. خزن المادة في حاويتها الأصلية مع حمايتها من التعرض لحرارة الشمس المباشرة في منطقة جافة، وباردة، وجيدة التهوية بعيداً عن المواد غير المطابقة (انظر القسم 10)، وعن الطعام، والشراب. يراعى غلق الوعاء غلقا تاما محكما إلى أن يُعدّ للاستخدام. يجب أن يتم التخزين والاستعمال فقط في معدات/حاويات مصممة للاستخدام مع هذا المنتج. لابد من إحكام غلق الأوعية التي قد فتحت و تركها في وضع قائم و ذلك لتلافي حدوث تسريب. يُحظر التخزين في حاويات لا تحمل كتابة توضيحية. يُراعى استخدام طرق احتواء سليمة لتجنب تلوث البيئة.

غير ملائمة

التعرض لدرجات الحرارة العالية لفترات طويلة

القسم 8. ضوابط التعرض/الحماية الشخصية

ندابير التحكم

حدود التعرض المهنى

حدود التعرض	اسم المُكوَرَن
TLV ACGIH (الولايات المتحدة). Oil [Mineral,	زيت متبقى (نفط)، منزوعة الشحم بمذيب
refined] severely and highly ,pure	
TWA: 5 مج / م ³ 8 ساعات. صدرت/روجعت:	
11/2009 الشكل: النسبة التي قد تُستَنشق	
TLV ACGIH (الولايات المتحدة). Oil [Mineral,	زيت متبقي (نفط)، زيوت متبقية (نفط)، معالجة بالماء
refined] severely and highly ,pure	
TWA: 5 مج / م ³ 8 ساعات. صدرت/روجعت:	
11/2009 الشكل: النسبة التي قد تُستَنشق	
TLV ACGIH (الولايات المتحدة). Oil [Mineral,	مواد مقطرة (بترول)، معالجة بالهيدروجين بارافينيية بدرجة كثيفة
refined] severely and highly ,pure	
TWA: 5 مّج / م ³ 8 سأعات. صدرت/روجعت:	
11/2009 الشكل: النسبة التي قد تُستَنشق	
TLV ACGIH (الولايات المتحدة). Oil [Mineral,	مواد مقطرة (بترول)، خالية من الشمع بالمذيب، بارافينيية بدرجة كثيفة
refined] severely and highly ,pure	• , ,
-	

Product name Energear 140 اسم المنتج 16/3

Product code 467139-AE02 كود المنتج Page: 3/16 كود المنتج 22/07/2025. كالله Page: 3/16 كود المنتج Page: 3/16 كالله Page: 3/16 كالله كالله

القسم 8. ضوابط التعرض/الحماية الشخصية

TWA: 5 مج / م 8 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستَشق

الضوابط الهندسية المناسبة

يجب تقييم جميع الأنشطة المرتبطة بالمواد الكيميائية من حيث مخاطر ها على الصحة، وذلك لضمان التحكم في معدلات التعرض بالشكل المناسب. لا يجوز تحديد معدات الوقاية الشخصية إلا بعد تقييم الأشكال الأخرى لإجراءات التحكم (على سبيل المثال عمليات التحكم الهندسية) بالشكل المناسب. يجب أن تتوافق معدات الوقاية الشخصية مع المواصفات المعنية وأن تكون مناسبة للاستخدام، وبحب الحفاظ عليها في حالة حددة وصدانتها بشكل سليم.

وأن تكون مناسبة للاستخدام، ويجب الحفاظ عليها في حالة جيدة وصيانتها بشكل سليم. يجب التشاور مع مورد معدات الوقاية الشخصية لطلب المشورة بشأن الاختيار والمواصفات المعنية. لمزيد من المعلومات، اتصل بالهيئة المحلية للمواصفات.

احرص على توفير تهوية للعوادم أو الوسائل الهندسية الاخرى للحماية، وذلك للإبقاء على مستويات التركيز المعنية للمواد العالقة بالهواء دون حدود التعرض المقبولة لها على الصعيد المهني.

القرار النهائي لاختيار معدات الوقاية يعتمد على تقييم المخاطر. ومن المهم التاكد من ملاءمة جميع عناصر معدات الوقاية الشخصية

اغسل اليدين، والذراعين، والوجه غسلاً تاماً بعد مناولة المنتجات الكيميائية، وعند الأكل والتدخين، وفي نهاية فترة

ننصح بفحص الإنبعاثات الصادرة من أجهزة العمل والتهوية، للتأكد من استيفائها لمتطلبات قانون حماية البيئة. في بعض الحالات، قد يكون من الضروري استخدام أجهزة إمتصاص الدُّخان، أو المُرشِّحات أو إجراء تعديلاتٍ هندسية للمُعِدَّات، كي يتسنى تقليل الانبعاثات إلى مستويات مقبولة.

ضوابط التعرض البيئي

تدابير الحماية الفردية

إجراءات النظافة الشخصية

العمل. يتوجب استخدام طرق ملائمة لنزع الثياب التي يُحتمل نلوَّ ثها. يُراعى غسل الثياب الملوثة قبل ارتدائها مرة ثانية. تأكد من وجود محطات غسيل الأعين وأدشاش الطوارئ على مقربة من موقع العمل. نظار ات أمان ذات ساتر ات جانبية.

أدوات حماية الوجه/العين

<u>حماية للجلد</u>

احرص على ارتداء القفازات الواقية من الماء إذا كان من المحتمل حدوث ملامسات متكررة وطويلة. قم بارتداء القفازات المقاومة للمواد الكيميائية. يُنصح باستخدام: قفازات نيتريل. يعتمد الاختيار الصحيح لقفازات الحماية على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة القفازات (حتى أفضل القفازات المقاومة للمواد

يجب التخلص منها واستبدالها. نظرًا للظروف الخاصة لبيئات العمل واختلاف ممارسات التعامل مع المواد، فيجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار القفازات بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

أدوات حماية الجسم

الكيميائية تتأكل بفعل التعرض المتكرر للمواد الكيميائية). معظم القفازات توفر الحماية لفترة زمنية قصيرة فقط وبعدها

يجب أن يعتمدها أحد المختصين قبل التعامل مع هذا المنتج.

أفرولات العمل المصنوعة من القطن أو البوليستر/القطن توفر الحماية فقط من التلوث السطحي الخفيف الذي لا يصل إلى الجلد. ويجب غسل أفرولات العمل بصفة منتظمة. عندما تزداد خطورة تعرض الجلد للمواد (على سبيل المثال عند تنظيف المواد المنسكبة أو في حالة وجود خطورة من تناثر الرذاذ)، فيجب ارتداء مريلة مقاومة للمواد الكيميائية و/أو أحذية وسترات غير منفذة للمواد الكيميائية.

حماية تنفسية في حالة عدم كفاية التهوية، يُراعى ارتداء تجهيزات تنفسية ملائمة.

يعتمد الاختيار الصحيح لتجهيزات حماية الجهاز التنفسي على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة تجهيزات حماية الجهاز التنفسي. يجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار تجهيزات حماية الجهاز التنفسي بالتشاور مع المورد/الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

القسم 9. الخصائص الفيزيائية والكيميائية

ظروف قياس جميع الخصائص تتم في ظل الضغط ودرجة الحرارة القياسيين ما لم تتم الإشارة إلى غير ذلك.

المظهر

الحالة الفيزيانية سان

 اللون
 کهرمان. [داکن]

 الرائحة
 غیر متوفرة.

 عتبة الرائحة
 غیر متوفرة.

الأس الهيدروجيني pH غير قابل التطبيق. نقطة الانصهار/نقطة التجمد غير متوفرة.

نقطة الغليان، والنقطة الأولية، ومعدل غير متوفرة.

الغليان

نقطة السقوط غير متوفرة.

Product name Energear 140 اسم المنتج 16/4

Product code 467139-AE02 كود المنتج Page: 4/16 كود المنتج 22/07/2025. كود المنتج Page: 4/16 كود المنتج Page: 4/16 كاللغة Page: 4/16

القسم 9. الخصائص الفيزيائية والكيميائية

نقطة الوميض جهاز الكأس المفتوحة: >350 C°180 ف) [جهاز كليفلاند 92 D ASTM]

معدل التبخر غير متوفرة.

القابلية على الاشتعال غير متوفرة.

الحد الأعلى/الأدنى للانفجار أو القابلية غير متوفرة.

الضغط البخاري

درجة منوية	خار عند 50	ضغط الب	ز درجة منوية	بخار عند 20	ضغط ال	
الطريقة	كيلوباسكال	مم زئبق	لطريقة	كيلوباسكال	مم زنبق	اسم المُكوِّن
			ASTM D 5191	<0.01	<0.07501	زیت متبقی (نفط)، منزوعة الشحم بمذیب
			ASTM D 5191	<0.01	<0.07501	زيت متبقي (نفط)، زيوت متبقية (نفط)، معالجة بالماء
			ASTM D 5191	<0.01	<0.07501	مواد مقطرة (بترول)، معالجة بالهيدروجين بارافينيية بدرجة كثيفة
			ASTM D 5191	<0.01	<0.07501	مواد مقطرة (بنترول)، خالية من الشمع بالمذيب، بار افينيية بدرجة كثيفة

كثافة البخار النسبية غير متوفرة.

الكثافة النسبية غير متوفرة.

الكثافة (g/cm³ 1>) m³/ عند 1000>

وسائل الإعلام	النتيجة
الماء	غير قابل للذوبان

معامل تفريق الأوكتانول/الماء غير قابل للتطبيق.

درجة حرارة الاشتعال الذاتي غير متوفرة.

درجة حرارة الاتحلال غير متوفرة.

اللزوجة كينماني: S²mm 418/ (418 سنتي سنوك) عند C°40

 $^{\circ}$ 20 الى 30 سنتي سنوك) عند $^{\circ}$ 27 الى 30 سنتي سنوك) عند $^{\circ}$

<u>خصائص الجسيمات</u>

الذوبانية (نيات)

حجم الجسيمات المتوسط غير قابل للتطبيق.

القسم 10. الثبات الكيميائي والقابلية للتفاعل

التفاعلية غير متاح بيانات اختبار أخرى معينة لهذا المنتج. ارجع إلى الظروف التي يجب تجنبها والمواد غير المتوافقة لمزيد من

الثبات الكيميائي المُنتَج ثابت.

ENGLISH

إمكانية التفاعلات الخطرة للم لن تحدث تفاعلات خطِرة في ظروف التخزين والاستخدام العادية.

لن تحدث بلمرة خطِرة في ظروف التخزين والاستخدام العادية.

الظروف التي ينبغي تجنبها يجب تجنب جميع مصادر الاشتعال الممكنة (شرر أو الهب).

المواد غير المتوافقة

العربية

تتفاعل أو غير متطابقة مع المواد التالية: مواد مؤكسِدة.

 Product name
 Energear 140
 # Indicated product code
 Energear 140
 # Indicated product code
 # Indicate

القسم 11 . المعلومات السمية

معلومات حول الآثار السمية

خطر الإستنشاق على الجهاز التنفسي

النتيجة

(Z)-أو كتاديك-9-إينيلامين خطر السمية الإستنشاق - الفئة 1

> سُبُل التعرض المُرتقبة: بالفمر جلدي استنشاق الأعْين. معلومات عن سئبل التعرض المرجحة

> > آثار صحية حادة كامنة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. ملامسة العين

استنشاق استنشاق الأبخرة في الظروف المحيطة لا يمثل مشكلة في المعتاد، وذلك لانخفاض ضغط الأبخرة.

> يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيُّجه. ملامسة الجلد

> لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. الابتلاع

أعراض متعلقة بالخواص السمية والكيميانية والفيزيانية

ملامسة العين ليست هناك بيانات معينة.

قد يؤدي إلى ضرر في حالة الاستنشاق في حالة التعرض للأبخرة أو الرذاذ أو العوادم الناتجة عن التحلل الحراري استنشاق

الأعراض الضائرة قد تشمل ما يلي: ملامسة الجلد

تهيُّج التشقق

ليست هناك بيانات معينة. الابتلاع

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

هناك خطورة محتملة من حدوث لسعة عابرة أو احمر ار عابر في حالة حدوث ملامسة العين بشكل عرضي. ملامسة العين استنشاق التعرض الزائد لاستنشاق الجزيئات المتطايرة في الهواء أو الإيروسولات قد يتسبب في تهيج الجهاز التنفسي. الملامسة المطوَّلة أو المتكررة بإمكانها أن تتسبب في إزالة دهون الجلد وتهيُّجه وتشققه و/أو التهابه. ملامسة الجلد

ابتلاع كميات كبيرة يمكن أن يؤدى إلى الغثيان والإسهال.

آثار صحبة مزمنة كامنة

الابتلاع

لا توجد تأثير ات شديدة أو مخاطر حرجة معروفة. لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. السرطنة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. التأثير على الجينات لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. القابلية على التسبب في المسخ

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. التأثيرات النمائية التأثيرات الخصوبية لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

القياسات الرقمية للسمية

تقديرات السمية الحادة

غير متوفرة.

القسم 12. المعلومات الإيكولوجية

تأثيرات بيئية لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

الثبات والتحلل

يُتوقع أن يكون قابلاً للتحلل الحيوي.

القدرة على التراكم الأحيائي

لا يُتوقع أن يتراكم هذا المنتَج حيوياً في البيئة من خلال السلاسل الغذائية.

Product name اسم المنتج الصفحة: 16/6 Energear 140 **Product code** 467139-AE02 Date of issue کود المنتج Page: 6/16 تاريخ الإصدار 22/07/2025. Version 3.02 نسخة Format Egypt Language اللغة **ENGLISH** العربية

القسم 12. المعلومات الإيكولوجية

القابلية على التحرك عبر التربة

مُعامل تقاسم التربة/الماء (Koc) غير متوفرة.

المواد المنسكبة يمكن أن تتوغل في التربة وتتسبب في تلوث المياه الجوفية.

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة. التأثيرات الضارة الأخرى

قد تتسبب السوائل المنسكبة في تكوين طبقة على أسطح الماء، وقد تتسبب في ضرر مادي للكائنات الحية. وقد يتم إعاقة معلومات بيئية أخرى نقل الإكسجين أيضًا.

القسم 13. الاعتبارات المتعلقة بتصريف المواد والتخلص منها

طرائق التصريف

التحركية

ينبغي تجنب توليد النفايات أو التقليل منها حيثما أمكن. ينبغي عدم التخلص من الكميات الكبرى من فضالة نفاية المُنتَج عبر شبكة الصرف الصحي وإنما مُعالجتها في محطة مُناسبةً لمعالجة مياه الصرف. يُراعى التخلص من الفائض والمنتجات غير القابلة لإعاَّدة التدوير من خلالً أحد المقاولين المرخص لهم بذلك. يراعي أن يجري دوما التخلص من هذا المنتج، و المحاليل و المنتجات الثانوية بما يتفق و متطلبات الحماية البيئية و تشريعات التخلص من النفايات و غيرها من متطلبات السلطة الإقليمية و المحلية. ينبغي أن يُعاد تدوير نفاية التغليف. ينبغي عدم أخذ الحرق أو الطمر في الاعتبار إلا إذا كانت إعادة التدوير غير مُجديةً. لابد أن يجري التخلص من هذا المنتج وحاويته بطريقة آمنة. قد تظل بعض رُواسبُ المنتج عالقة بالحاويات الفارغة أو قُمصانها. تَجنب تناثر المادة المنسكّبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف.

القسم 14. المعلومات المتعلقة بالنقل

	IMDG	IATA
رقم الأمم المتحدة	غير مقننة.	غير مقننة.
اسم الشدن الصحيح الخاص - بالأمم المتحدة	-	-
فنة/فنات مخاطر النقل	-	-
مجموعة التعبنة	-	-
الأخطار البيئية لا	. У.	. У
معلومات إضافية	-	-

احتياطات خاصة للمستخدم غير متوفرة.

النقل سائباً بحسب اتفاقيات المنظمة غير متوفرة.

البحرية الدولية (IMO)

القسم 15. المعلومات التنظيمية

القواعد المتعلقة بالسلامة والصحة والبيئة، لا توجد لوائح وطنية و/أو إقليمية معروفة تنطبق على هذا المنتج (بما في ذلك مكوناته). المنطبقة على المنتوج

قائمة الجرد الوطنية

كافة المُكوِّ نات مُدر جة بالقائمة أو مُستثناة منها. أستر البا

كافة المُكوِّ نات مُدرجة بالقائمة أو مُستثناة منها. كندا كافة المُكوِّنات مُدرجة بالقائمة أو مُستثناة منها.

الوضع وفق REACH (النظام المتعلق للتعرف على حالة REACH لهذا المنتج، يرجى التواصل مع جهة الاتصال في شركتك، كما هو محدد في القسم 1. بتسجيل وتقييم وترخيص المواد

الكيماوية)

Product name الصفحة: 16/7 اسم المنتج Energear 140 Page: 7/16 تاريخ الإصدار **Product code** 467139-AE02 Date of issue کود المنتج 22/07/2025. نسخة Version 3.02 Format Egypt Language اللغة **ENGLISH** العربية

القسم 15. المعلومات التنظيمية

كافة المُكوِّنات مُدرجة بالقائمة أو مُستثناة منها. القلبين كافة المُكوِّ نات مُدرجة بالقائمة أو مُستثناة منها.

كافة المُكوِّ نات مُدرجة بالقائمة أو مُستثناة منها. جمهورية كوريا

كافة المُكوِّ نات مُدرجة بالقائمة أو مُستثناة منها. تايوان جميع المكونات تحمل الصفة "فعالة" أو الصفة "مستثناة". الولايات المتحدة

القسم 16. المعلومات الأخرى

22/07/2025. تاريخ الإصدار/تاريخ المراجعة

22/07/2025. تاريخ الإصدار السابق

> ئسخة 3.02

Product Stewardship من إعداد

ACGIH = المؤتمر الأمريكي للمتخصصين في الصحة الصناعية مفتاح الإختصارات

رقم CAS = رقم سجل دائرة المستخلصات الكيميائية

GHS = النظام المنسق العالمي

IATA = اتحاد النقل الجوي الدولي، المنظمة

IMDG = قوانين المنظمة البحرية الدولية والقواعد الحاكمة لشحن البضائع عن طريق المياه.

OEL = حد التعرض المهني

REACH = التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيماوية إنظام (المفوضية الأوروبية) رقم

[1907/2006

SDS = نشرة بيانات الأمان

STEL = حد التعرض على المدى القصير TWA = المتوسط المرجح للوقت

رقم UN = رقم الأمم المتحدة، رقم من أربعة أعداد يتم تعبينه من قبل لجنة الأمم المتحدة لخبراء نقل البضائع الخطرة.

متنوع = قد يحتوي على واحد أو أكثر من المكونات التالية 4-88-64741, 5-89-64741, 3-95, 6-95-64741,

,64742-53-6 ,64742-52-5 ,64742-45-6 ,64742-44-5 ,64742-01-4 ,64741-96-4

,64742-62-7 ,64742-58-1 ,64742-57-0 ,64742-56-9 ,64742-55-8 ,64742-54-7

72623-87-1 ,72623-86-0 ,72623-85-9 ,64742-70-7 ,64742-65-0 ,64742-63-8

الإجراء المتبع للحصول على التصنيف

التبرير	التصنيف
	غير مُصنَّفة.

تشير إلى معلومات تم تغييرها مقارنة بالنسخة التي سبق إصدارها.

ملاحظة للقارىء الكريم

تم اتخاذ جميع الخطوات المتاحة المعقولة لضمان دقة نشرة البيانات هذه والمعلومات المتعلقة بالصحة والأمان والبيئة حسب البيانات الموضحة أدناه. لا يوجد ضمان أو تغويض، صريح أو ضمني، بشأن دقة أو اكتمال البيانات والمعلومات الواردة في نشرة البيانات هذه.

تسري البيانات والنصائح المعطاة في حالة بيع المنتج للتطبيق المذكور أو التطبيقات المذكورة. لا يجوز لك استخدام المنتج في غير التطبيق المذكور أو التطبيقات المذكورة دون طلب المشورة من شركة Group BP.

يجب على المستخدم تقييم هذا المنتج واستخدامه بشكل آمن بما يتوافق مع جميع القوانين والتشريعات المعمول بها. لا تتحمل شركة Group BP أية مسؤولية عن أي ضرر أو إصابة تنتج عن الاستخدام، أو أي استخدام آخر بخلاف استخدام المنتج المذكور للخامة، أو في حالة عدم مراعاة التوصيات، أو المخاطر المتأصلة في طبيعة الخامة. القائمون بشراء المنتج لتوريده إلى طرف ثالث للاستخدام في العمل عليهم اتخاذ جميع الخطوات اللازمة للتأكد من أن أي شخص يستخدم المنتج يكون على دراية بالمعلومات الواردة في هذه النشرة. يجب على أصحاب العمل إبلاغ الموظفين لديهم وغيرهم من الأشخاص المعنيين بالمخاطر الموضحة في هذه النشرة وعن الاحتياطات الواجب اتخاذها. يمكنك الاتصال بشركة Group BP للتأكد من أن هذا المستند على أحدث وضع. ممنوع منعًا باتًا إجراء تغيير على هذا المستند.

SAFETY DATA SHEET

Language

Energear 140

Section 1. Identification

GHS product identifier Energear 140 **Product code** 467139-AE02

Product name اسم المنتج Energear 140 الصفحة: 16/8

Product code 467139-AE02 Date of issue کود المنتج 22/07/2025. Page: 8/16 تاريخ الإصدار نسخة 3.02 كسخة Format Egypt اللغة

ENGLISH العربية

Section 1. Identification

SDS no. 467139

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Manual transmission fluid.

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer

Supplier BP Egypt 14

Road 252 Diglaamaadi Cairo

Tel +20 2 25199915

EMERGENCY TELEPHONE Carechem: +44 (0) 1235 239 671 (Arabic language 24/7)

NUMBER +44 (0) 1235 239 670 (English language 24/7)

Section 2. Hazards identification

GHS Classification Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Other hazards which do not

result in classification

Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number
Residual oils (petroleum), solvent-dewaxed	≥25 - ≤50	64742-62-7
Residual oils (petroleum), hydrotreated	≥25 - ≤50	64742-57-0
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0
1-Propene, 2-methyl-, sulfurized	≤3	68511-50-2
(Z)-octadec-9-enylamine	<0.025	112-90-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

الصفحة: 16/9 | Product name | Energear 140 | اسم المنتج | Product code | 467139-AE02 | Date of issue | 22/07/2025. | Version 3.02 | كاللغة | Pormat Egypt | Language

ENGLISH

العربية

Section 4. First aid measures

Description of necessary first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin

irritation or rash occurs: Get medical advice/attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physicianTreatment should in general be symptomatic and directed to relieving any effects.

Specific treatments No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

Section 5. Firefighting measures

Extinguishing media

Suitable In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising

from the chemical

Hazardous thermal

decomposition products

In a fire or if heated, a pressure increase will occur and the container may burst.

Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions

for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus

(SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal

protective equipment. Floors may be slippery; use care to avoid falling.

information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

ENGLISH

pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

الصفحة: 16/10 الصفحة: 16/10 Product code 467139-AE02 ود المنتج الإصدار 22/07/2025. كود المنتج الإصدار 13.02 Pormat Egypt Language

Section 6. Accidental release measures

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures
Advice on general
occupational hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Residual oils (petroleum), solvent-dewaxed	ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined]
	TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Residual oils (petroleum), hydrotreated	ACGIH TLV (United States). [Mineral Oil,
, , , , , , , , , , , , , , , , , , ,	pure, highly and severely refined]
	TWA: 5 mg/m³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States). [Mineral Oil,
	pure, highly and severely refined]
	TWA: 5 mg/m ³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States). [Mineral Oil,
,	pure, highly and severely refined]
	TWA: 5 mg/m³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on

Section 8. Exposure controls/personal protection

selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

Eye/face protection Skin protection

Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons

and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>

Physical state Liquid.

ColourAmber. [Dark]OdourNot available.Odour thresholdNot available.pHNot applicable.Melting point/freezing pointNot available.

الصفحة: 16/12 الصفحة: 16/12 | Product code | 467139-AE02 | كود المنتج | Date of issue | 22/07/2025. | Version 3.02 | النغة | Format Egypt | Language

فعربية ENGLISH

Section 9. Physical and chemical properties

Boiling point, initial boiling point, and boiling range

Not available.

Drop Point

Not available.

Flash point

Open cup: >180°C (>356°F) [Cleveland ASTM D 92]

Flammability Lower and upper explosion Not available. Not available.

limit/flammability limit

Not available.

Vapour pressure

Evaporation rate

	Vapou	Vapour Pressure at 20°C			ur pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Residual oils (petroleum), solvent- dewaxed	<0.07501	<0.01	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191			

Relative vapour density

Not available.

Relative density

Not available.

Density

<1000 kg/m3 (<1 g/cm3) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature Decomposition temperature

Not available. Not available.

Viscosity

Kinematic: 418 mm²/s (418 cSt) at 40°C

Kinematic: 27 to 30 mm²/s (27 to 30 cSt) at 100°C

Particle characteristics

Median particle size Not applicable.

Section 10. Stability and reactivity

No specific test data available for this product. Refer to Conditions to avoid and Reactivity

Incompatible materials for additional information.

Chemical stability

The product is stable.

Possibility of hazardous

Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

الصفحة: 16/13 **Product name** اسم المنتج Energear 140 Page: 13/16 تاريخ الإصدار **Product code** 467139-AE02 Date of issue کود المنتج 22/07/2025. Version 3.02 Format Egypt Language اللغة

> **ENGLISH** العربية

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name Result

(Z)-octadec-9-enylamine ASPIRATION HAZARD - Category 1

Information on likely routes

of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact No known significant effects or critical hazards.

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Environmental effects No known significant effects or critical hazards.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

الصفحة: 16/14 الصفحة: 16/14 | Product code | 467139-AE02 | كود المنتج | Date of issue | 22/07/2025. | Version 3.02 | للغة | Format Egypt | Language | اللغة |

Section 12. Ecological information

Soil/water partition coefficient (Koc)

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user

Not available.

Transport in bulk according

Not available.

to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

International lists

National inventory

Australia All components are listed or exempted.

Canada All components are listed or exempted.

China All components are listed or exempted.

الصفحة: 16/15 | Product name | Energear 140 | اسم المنتج | Product code | 467139-AE02 | كود المنتج | Date of issue | 22/07/2025 | كود المنتج | Page: 15/16 | Version 3.02 | النغة | Format Egypt | Language

Section 15. Regulatory information

REACH Status For the REACH status of this product please consult your company contact, as

identified in Section 1.

JapanAll components are listed or exempted.PhilippinesAll components are listed or exempted.Republic of KoreaAll components are listed or exempted.TaiwanAll components are listed or exempted.United StatesAll components are active or exempted.

Section 16. Other information

History

Date of issue/Date of

revision

Date of previous issue

22/07/2025.

22/07/2025.

Version

3.02

Prepared by

Product Stewardship

Key to abbreviations

ACGIH = American Conference of Industrial Hygienists
CAS Number = Chemical Abstracts Service Registry Number

GHS = Global Harmonised System

IATA = International Air Transport Association, the organisation

IMDG = International Maritime Organization Rules, rules governing shipment of

goods by water.

OEL = Occupational Exposure Limit

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation [Regulation (EC) No. 1907/2006]

SDS = Safety Data Sheet

STEL = Short term exposure limit TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

Procedure used to derive the classification

Classification	Justification
Not classified.	

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.