

# SAFETY DATA SHEET

## 1. Product and company identification

Product name Super V 5W-30  
Product code 467311-JP03  
SDS # 467311  
Original preparation date 31/12/2009  
Supplier BP Castrol K.K.  
1-11-2, Osaki, Shinagawaku, Tokyo, 141-0032  
East Tower 20F, Gate City Osaki  
Telephone : 03-5719-7860 (days & hours of operation : Monday - Friday, 09:00 - 17:00)  
Carechem: +81 50 5057 7850 (Operation time: 24 hrs)

EMERGENCY TELEPHONE NUMBER

### Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine Oils.  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

### Uses advised against

Use advised against: Consult with experts for use other than relevant identified use

## 2. Hazards identification

GHS Classification Not classified.

### GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

### Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Other hazards which do not result in classification Defatting to the skin.  
USED ENGINE OILS  
Used engine oil may contain hazardous components which have the potential to cause skin cancer.  
See Toxicological Information, section 11 of this Safety Data Sheet.

### 3. Composition/information on ingredients

#### Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number	Official Gazette notice reference number	
			CSCL	ISHL
Distillates (petroleum), hydrotreated heavy paraffinic	≥50 - ≤75	CAS: 64742-54-7	Not available.	Not available.
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	CAS: 64742-54-7	(9)-1692	Not available.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤5.0	CAS: 64742-65-0	Not available.	Not available.
Distillates (petroleum), hydrotreated light paraffinic	≤3.0	CAS: 64742-55-8	Not available.	Not available.
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3.0	CAS: 64742-56-9	Not available.	Not available.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Applicability to local regulations are determined with consideration of reactions of constituents included in the formulation. Please see section 15 for regulatory information.

### 4. First aid measures

#### Description of necessary first aid measures

##### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

##### Inhalation

If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

##### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

##### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

##### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

##### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

##### Specific treatments

No specific treatment.

**Product name** Super V 5W-30

**Product code** 467311-JP03

Page: 2/18

**Version** 11.01 **Date of issue** 2026 January 9

**Format** Japan

**Language**

**ENGLISH**

**Date of** 2025 October 16.

**Build** 6.2

**(Japan)**

**(ENGLISH)**

**previous issue**

**Original preparation date**

7/5/2018

## 5. Firefighting measures

### Extinguishing media

Suitable	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO <sub>2</sub> etc.)
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.  In the case of spillage at sea approved dispersants may be used where authorised by the appropriate government/regulatory authorities.

## 7. Handling and storage

Protective measures	Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

<b>Product name</b>	Super V 5W-30	<b>Product code</b>	467311-JP03	Page: 3/18
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9	<b>Format Japan</b>
		<b>Date of previous issue</b>	2025 October 16.	<b>Language</b>
		<b>Original preparation date</b>	7/5/2018	<b>ENGLISH</b>
			Build 6.2 (Japan)	<b>(ENGLISH)</b>

## 7. Handling and storage

### Conditions for safe storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### Not suitable

Prolonged exposure to elevated temperature

## 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	<b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b> OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist. Issued/Revised: 5/2010.
Distillates (petroleum), hydrotreated heavy paraffinic	<b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b> OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist. Issued/Revised: 5/2010.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b> OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist. Issued/Revised: 5/2010.
Distillates (petroleum), hydrotreated light paraffinic	<b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b> OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist. Issued/Revised: 5/2010.
Distillates (petroleum), solvent-dewaxed light paraffinic	<b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1. <b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b> OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist.

**Product name** Super V 5W-30

**Product code** 467311-JP03

Page: 4/18

**Version** 11.01 **Date of issue** 2026 January 9  
**Date of previous issue** 2025 October 16.  
**Original preparation date** 7/5/2018

**Format Japan** **Language** **ENGLISH**  
Build 6.2 **(Japan)** **(ENGLISH)**

## 8. Exposure controls/personal protection

Issued/Revised: 5/2010.

### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Biological exposure indices

No exposure indices known.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Eye protection

Safety glasses with side shields.

<b>Product name</b>	Super V 5W-30		<b>Product code</b>	467311-JP03		Page: 5/18
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9	<b>Format Japan</b>	<b>Language</b>	<b>ENGLISH</b>
		<b>Date of previous issue</b>	2025 October 16.	Build 6.2	(Japan)	(ENGLISH)
		<b>Original preparation date</b>	7/5/2018			

## 8. Exposure controls/personal protection

### Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

#### Physical state

Liquid.

#### Colour

Brown. [Light]

#### Odour

Mild.

#### pH

Not applicable.

#### Melting point/freezing point

Not available.

#### Softening point

Not available.

#### Boiling point or initial boiling point and boiling range

Not available.

#### Flash point

Closed cup: 202.5°C (396.5°F) [Pensky-Martens ASTM D 93]  
Open cup: >200°C (>392°F) [Cleveland ASTM D 92]

#### Fire point

Not available.

#### Evaporation rate

Not available.

#### Flammability

Not available.

#### Lower and upper explosive (flammable) limits

Not available.

#### Vapour pressure

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed light paraffinic	<0.07501	<0.01	ASTM D 5191			

**Product name** Super V 5W-30

**Version** 11.01 **Date of issue** 2026 January 9

**Date of previous issue** 2025 October 16.

**Original preparation date** 7/5/2018

**Product code** 467311-JP03

**Format Japan**  
Build 6.2 (Japan)

**Language** ENGLISH  
(ENGLISH)

Page: 6/18

## 9. Physical and chemical properties

Relative vapour density Not available.  
Relative Density Not available.  
Density <1 g/cm<sup>3</sup> [15°C (59°F)]  
Auto-ignition temperature Not available.

Ingredient name	°C	°F	Method
bis(nonylphenyl)amine	440	824	EU A.15

Decomposition temperature Not available.  
Lower and upper explosion limit/flammability limit Not available.  
Critical temperature Not available.  
Oxidising properties Not available.  
Viscosity Kinematic: 59.14 mm<sup>2</sup>/s (59.14 cSt) at 40°C  
Kinematic: 9.8 to 12.5 mm<sup>2</sup>/s (9.8 to 12.5 cSt) at 100°C  
Drop Point Not available.  
Density <1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C  
Solubility(ies)

Media	Result
water	Not soluble

Solubility at room temperature (g/l) Not available.  
Partition coefficient (LogKow) Not applicable.  
Remarks Not available.

### Particle characteristics

Median particle size Not applicable.

## 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.  
Chemical stability The product is stable.  
Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerisation will not occur.  
Conditions to avoid Avoid all possible sources of ignition (spark or flame).  
Incompatible materials Reactive or incompatible with the following materials: oxidising materials.  
Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

### Acute toxicity

Product/ingredient name	Result
-------------------------	--------



## 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

### **Rat - Oral - LD50**

>5000 mg/kg

OECD 401

### **Rabbit - Dermal - LD50**

>5000 mg/kg

OECD 402

### **Rat - Inhalation - LC50 Dusts and mists**

>5 mg/l [4 hours]

OECD 403

Distillates (petroleum), hydrotreated heavy paraffinic

### **Rat - Oral - LD50**

>5000 mg/kg

OECD 401

### **Rabbit - Dermal - LD50**

>5000 mg/kg

OECD 402

### **Rat - Inhalation - LC50 Dusts and mists**

>5 mg/l [4 hours]

OECD 403

Distillates (petroleum), solvent-dewaxed heavy paraffinic

### **Rat - Oral - LD50**

>5000 mg/kg

OECD 401

### **Rat - Dermal - LD50**

>2000 mg/kg

OECD 402

### **Rat - Inhalation - LC50 Dusts and mists**

>5.53 mg/l [4 hours]

OECD 403

Distillates (petroleum), hydrotreated light paraffinic

### **Rat - Oral - LD50**

>5000 mg/kg

OECD 401

### **Rabbit - Dermal - LD50**

>5000 mg/kg

OECD 402

### **Rat - Inhalation - LC50 Dusts and mists**

>5.53 mg/l [4 hours]

OECD 403

Distillates (petroleum), solvent-dewaxed light paraffinic

### **Rat - Oral - LD50**

>5000 mg/kg

OECD 401

### **Rabbit - Dermal - LD50**

>5000 mg/kg

OECD 402

### **Rat - Inhalation - LC50 Dusts and mists**

>2.18 mg/l [4 hours]

OECD 403

### [Acute toxicity estimates](#)

N/A

### [Skin corrosion/irritation](#)

Product/ingredient name

Result

**Product name** Super V 5W-30

**Version** 11.01 **Date of issue** 2026 January 9

**Date of previous issue** 2025 October 16.

**Original preparation date** 7/5/2018

**Product code** 467311-JP03

**Format Japan**  
**(Japan)**

Build 6.2

**Language** **ENGLISH**  
**(ENGLISH)**

Page: 8/18



## 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic  
Distillates (petroleum), hydrotreated heavy paraffinic  
Distillates (petroleum), solvent-dewaxed heavy paraffinic  
Distillates (petroleum), hydrotreated light paraffinic  
Distillates (petroleum), solvent-dewaxed light paraffinic

**Rabbit - Skin - Mild irritant**  
OECD 404  
**Rabbit - Skin - Mild irritant**  
OECD 404  
**Rabbit - Skin - Non-irritant to skin.**  
  
**Rabbit - Skin - Non-irritant to skin.**  
  
**Rabbit - Skin - Non-irritant to skin.**

### [Serious eye damage/eye irritation](#)

#### **Product/ingredient name**

Distillates (petroleum), hydrotreated heavy paraffinic  
Distillates (petroleum), hydrotreated heavy paraffinic  
Distillates (petroleum), solvent-dewaxed heavy paraffinic  
Distillates (petroleum), hydrotreated light paraffinic  
Distillates (petroleum), solvent-dewaxed light paraffinic

#### **Result**

**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405  
**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405  
**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405  
**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405  
**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405

### [Respiratory corrosion/irritation](#)

Not available.

### [Respiratory or skin sensitization](#)

#### **Product/ingredient name**

Distillates (petroleum), hydrotreated heavy paraffinic  
  
Distillates (petroleum), hydrotreated heavy paraffinic  
  
Distillates (petroleum), solvent-dewaxed heavy paraffinic  
  
Distillates (petroleum), hydrotreated light paraffinic  
  
Distillates (petroleum), solvent-dewaxed light paraffinic

#### **Result**

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising  
**Guinea pig - skin**  
OECD 406  
Result: Not sensitising  
**Guinea pig - skin**  
OECD 406  
Result: Not sensitising  
**Guinea pig - skin**  
OECD 406  
Result: Not sensitising  
**Guinea pig - skin**  
OECD 406  
Result: Not sensitising

## 11. Toxicological information

### [Germ cell mutagenicity](#)

#### [Product/ingredient name](#)

Distillates (petroleum), hydrotreated heavy paraffinic

#### [Result](#)

##### **In vitro - Bacteria**

Bacterial Reverse Mutation Test

Result: Negative

##### **In vitro - Mammal - species unspecified**

In vitro Mammalian Chromosomal Aberration Test

Result: Negative

##### **In vivo - Mammal - species unspecified**

Mammalian Erythrocyte Micronucleus Test

Result: Negative

##### **In vitro - Mammal - species unspecified**

In vitro Mammalian Cell Gene Mutation Test

Result: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

##### **In vitro - Bacteria**

Bacterial Reverse Mutation Test

Result: Negative

##### **In vitro - Mammal - species unspecified**

In vitro Mammalian Chromosomal Aberration Test

Result: Negative

##### **In vivo - Mammal - species unspecified**

Mammalian Erythrocyte Micronucleus Test

Result: Negative

##### **In vitro - Mammal - species unspecified**

In vitro Mammalian Cell Gene Mutation Test

Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

##### **In vitro - Bacteria**

OECD [Bacterial Reverse Mutation Test]

Result: Negative

##### **In vitro - Mammal - species unspecified**

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

Distillates (petroleum), hydrotreated light paraffinic

##### **In vitro - Bacteria**

OECD [Bacterial Reverse Mutation Test]

Result: Negative

##### **In vitro - Mammal - species unspecified**

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

Distillates (petroleum), solvent-dewaxed light paraffinic

##### **In vitro - Bacteria**

OECD [Bacterial Reverse Mutation Test]

Result: Negative

##### **In vitro - Mammal - species unspecified**

In vitro Mammalian Chromosomal Aberration Test

Result: Negative

### [Carcinogenicity](#)

#### [Product/ingredient name](#)

#### [Result](#)

<b>Product name</b>	Super V 5W-30		<b>Product code</b>	467311-JP03		Page: 10/18
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9		<b>Format</b>	Japan
		<b>Date of previous issue</b>	2025 October 16.		<b>Language</b>	ENGLISH
		<b>Original preparation date</b>	7/5/2018			(ENGLISH)

## 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

### Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

### Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

### Mouse - Dermal - Unspecified

OECD 451

Result: Negative

### Reproductive toxicity

#### Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

#### Result

##### **Rat - Oral**

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

##### **Rat - Oral**

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

##### **Rat - Oral**

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Distillates (petroleum), hydrotreated light paraffinic

##### **Rat - Oral**

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Distillates (petroleum), solvent-dewaxed light paraffinic

##### **Rat - Oral**

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

#### Product/ingredient name

#### Result

<b>Product name</b>	Super V 5W-30		<b>Product code</b>	467311-JP03	Page: 11/18
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9	<b>Format Japan</b>	<b>Language</b> <b>ENGLISH</b>
		<b>Date of previous issue</b>	2025 October 16.	Build 6.2 <b>(Japan)</b>	<b>(ENGLISH)</b>
	<b>Original preparation date</b>	7/5/2018			

## 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1

[Information on likely routes of exposure](#) Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### [Potential acute health effects](#)

<a href="#">Eye contact</a>	No known significant effects or critical hazards.
<a href="#">Inhalation</a>	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
<a href="#">Skin contact</a>	Defatting to the skin. May cause skin dryness and irritation.
<a href="#">Ingestion</a>	No known significant effects or critical hazards.

### [Symptoms related to the physical, chemical and toxicological characteristics](#)

<a href="#">Eye contact</a>	No specific data.
<a href="#">Inhalation</a>	No specific data.
<a href="#">Skin contact</a>	Adverse symptoms may include the following: irritation dryness cracking
<a href="#">Ingestion</a>	No specific data.

### [Delayed and immediate effects as well as chronic effects from short and long-term exposure](#)

<a href="#">Eye contact</a>	Potential risk of transient stinging or redness if accidental eye contact occurs.
<a href="#">Skin contact</a>	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
<a href="#">Ingestion</a>	Ingestion of large quantities may cause nausea and diarrhoea.

### [Potential chronic health effects](#)

<a href="#">General</a>	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
<a href="#">Carcinogenicity</a>	No known significant effects or critical hazards.
<a href="#">Mutagenicity</a>	No known significant effects or critical hazards.
<a href="#">Developmental effects</a>	No known significant effects or critical hazards.
<a href="#">Fertility effects</a>	No known significant effects or critical hazards.

<b>Product name</b>	Super V 5W-30	<b>Product code</b>	467311-JP03	Page: 12/18
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9	<b>Format Japan</b>
		<b>Date of previous issue</b>	2025 October 16.	<b>Language</b>
		<b>Original preparation date</b>	7/5/2018	<b>ENGLISH</b>
			Build 6.2 (Japan)	<b>(ENGLISH)</b>

## 12. Ecological information

### Environmental effects

No known significant effects or critical hazards.

### Ecotoxicity

#### Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

#### Result

##### Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

##### Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

##### Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

##### Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

##### Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

##### Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

##### Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

##### Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

##### Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

##### Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

##### Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

##### Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

##### Acute - LL50

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Product name		Super V 5W-30		Product code		467311-JP03		Page: 13/18					
Version		11.01		Date of issue		2026 January 9		Format Japan		Language		ENGLISH	
				Date of previous issue		2025 October 16.		Build 6.2		(Japan)		(ENGLISH)	
				Original preparation date		7/5/2018							

## 12. Ecological information

Distillates (petroleum), hydrotreated light paraffinic

OECD 203  
Fish  
>100 mg/l [96 hours]  
**Chronic - NOEL**  
OECD 201  
Algae  
≥100 mg/l [72 hours]  
**Chronic - NOEL**  
OECD 211  
Daphnia  
10 mg/l [21 days]  
**Acute - EL50**  
OECD 201  
Algae  
>100 mg/l [72 hours]  
**Acute - EL50**  
OECD 202  
Daphnia  
>10000 mg/l [48 hours]  
**Acute - LL50**  
OECD 203  
Fish  
>100 mg/l [96 hours]  
**Chronic - NOEL**  
OECD 201  
Algae  
≥100 mg/l [72 hours]  
**Chronic - NOEL**  
OECD 211  
Daphnia  
10 mg/l [21 days]  
**Acute - EL50**  
OECD 201  
Algae  
>100 mg/l [72 hours]  
**Acute - EL50**  
OECD 202  
Daphnia  
>10000 mg/l [48 hours]  
**Acute - LL50**  
OECD 203  
Fish  
>100 mg/l [96 hours]  
**Chronic - NOEL**  
OECD 201  
Algae  
≥100 mg/l [72 hours]  
**Chronic - NOEL**  
OECD 211  
Daphnia  
10 mg/l [21 days]

Distillates (petroleum), solvent-dewaxed light paraffinic

OECD 203  
Fish  
>100 mg/l [96 hours]  
**Chronic - NOEL**  
OECD 201  
Algae  
≥100 mg/l [72 hours]  
**Chronic - NOEL**  
OECD 211  
Daphnia  
10 mg/l [21 days]  
**Acute - EL50**  
OECD 201  
Algae  
>100 mg/l [72 hours]  
**Acute - EL50**  
OECD 202  
Daphnia  
>10000 mg/l [48 hours]  
**Acute - LL50**  
OECD 203  
Fish  
>100 mg/l [96 hours]  
**Chronic - NOEL**  
OECD 201  
Algae  
≥100 mg/l [72 hours]  
**Chronic - NOEL**  
OECD 211  
Daphnia  
10 mg/l [21 days]

## 12. Ecological information

**Persistence and degradability** Not expected to be rapidly degradable.

**Product/ingredient name**

**Result**

Distillates (petroleum), hydrotreated heavy paraffinic

OECD 301F  
31% [28 days] - Not readily

Distillates (petroleum), hydrotreated heavy paraffinic

OECD 301F  
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed heavy paraffinic

OECD 301F  
31% [28 days] - Not readily

Distillates (petroleum), hydrotreated light paraffinic

OECD 301F  
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed light paraffinic

OECD 301F  
31% [28 days] - Not readily

**Bioaccumulative potential**

**Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

**Mobility**

Spillages may penetrate the soil causing ground water contamination.

**Hazardous to the ozone layer**

Not applicable.

**Other ecological information**

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## 13. Disposal considerations

**Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	-	-
<b>Transport hazard class(es)</b>	-	-
<b>Packing group</b>	-	-
<b>Environmental hazards</b>	No.	No.

**Product name** Super V 5W-30

**Product code** 467311-JP03

Page: 15/18

**Version** 11.01 **Date of issue** 2026 January 9

**Format** Japan

**Language**

**ENGLISH**

**Date of** 2025 October 16.

**Build** 6.2

**(Japan)**

**(ENGLISH)**

**previous issue**

**Original preparation date**

7/5/2018



## 14. Transport information

### Additional information

-

-

Special precautions for user Not available.

[Transport in bulk according to IMO instruments](#)

Not available.

## 15. Regulatory information

### [Fire Service Law](#)

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Category IV	Class IV petroleum	III	Flammable - Keep Fire Away	6000 L

Fire Service Law - Listed  
Obstructive materials

### [Industrial Safety and Health Act](#)

Special Organic Solvents, etc. Not applicable.

### [Substances requiring labelling](#)

Ingredient name	Name on list	CAS no.	Conc.	Status
-	Mineral oil	-	90 - 100	Listed

\*Chemicals damaging skin/eye and Skin-absorbable harmful substances based on Article 594-2 are disclosed in the above table.

### [Chemicals requiring notification](#)

Ingredient name	Name on list	CAS no.	Conc.	Status
-	Mineral oil	-	90 - 100	Listed

### [Carcinogens based on Article 577-2 of the Ordinance on ISH](#)

Ingredient name	%	Status	Reference number
None of the components are listed.			

### [Carcinogens based on Paragraph 3, Article 28 of the Law](#)

Ingredient name	%	Status	Reference number
None of the components are listed.			

### [Poisonous and Deleterious Substances](#)

Ingredient name	%	Status	Reference number
Ethylene oxide and preparations containing it	0.0000007	Deleterious	2-1-14-7

### [Pollutant Release and Transfer Registers \(PRTR\)](#)

None of the components are listed.

### [Other regulations](#)

<b>Product name</b>	Super V 5W-30	<b>Product code</b>	467311-JP03	Page: 16/18
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9	<b>Format Japan</b>
		<b>Date of previous issue</b>	2025 October 16.	<b>Language</b>
		<b>Original preparation date</b>	7/5/2018	<b>ENGLISH (ENGLISH)</b>
			Build 6.2 (Japan)	

## 15. Regulatory information

Australia inventory (AIIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.
United States inventory (TSCA 8b)	All components are active or exempted.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

## 16. Other information

### History

Date of issue/Date of revision	2026 January 9.
Date of previous issue	2025 October 16.
Prepared by	Product Stewardship
	The Japan key to abbreviations is as follows:
	GHS = Global Harmonized System
	CAS Number = Chemical Abstracts Service Registry Number
	ISHL = Industrial Safety and Health Law
	OSHL = Occupational Safety and Health Law
	PRTR = Law Concerning Reporting of the Release into the Environment of Specific Chemical Substances and Promoting Improvements in Their Management
	ENCS = Existing and New Chemical Substances
	METI = Ministry of Economy, Trade and Industry
	OEL = Occupational Exposure Limit
	JSOH = Japan Society for Occupational Health
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
	TWA = Time weighted average
	STEL = Short term exposure limit
	IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.
	IATA = International Air Transport Association, the organization
	UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.
	Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### Procedure used to derive the classification

Classification	Justification
Not classified.	

Indicates information that has changed from previously issued version.

### Notice to reader

<b>Product name</b>		Super V 5W-30		<b>Product code</b>		467311-JP03		Page: 17/18	
<b>Version</b>	11.01	<b>Date of issue</b>	2026 January 9		<b>Format Japan</b>	<b>Language</b>	<b>ENGLISH</b>		
		<b>Date of previous issue</b>	2025 October 16.		Build 6.2	<b>(Japan)</b>	<b>(ENGLISH)</b>		
		<b>Original preparation date</b>	7/5/2018						

16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name		Super V 5W-30	Product code		467311-JP03	Page: 18/18
Version	11.01	Date of issue	2026 January 9	Format Japan	Language	ENGLISH
		Date of previous issue	2025 October 16.	Build 6.2 (Japan)		(ENGLISH)
Original preparation date		7/5/2018				