



# صحيفة بيانات السلامة

Super V 15W-40

## القسم 1. الاسم (بيان المنتج)

Super V 15W-40

بيان تعريف المنتج طبقاً للنظام ن م

470020-AE02

كود المنتج

470020

صحيفة بيانات سلامة المادة رقم #

سائل.

نوع المنتج

الاستخدامات الهامة المحددة للمادة أو الخليط وأوجه الاستخدام التي لا ينصح بها

استخدام المادة/المستحضر

مادة تزييق علية مرافق محركات السيارات.

بالنسبة لجهاز التطبيق المحدد، انظر نشرة البيانات التقنية المعنية أو تشاور مع ممثل شركتنا.

BP Middle East

المورد

Standard Chartered Tower

8th Floor, Down Town Burj Khalifa

By Emaar Square

P.O. Box 1699, Dubai, United Arab Emirates

Main : (971) 4 331 7999

Fax : (971) 4 331 8530

رقم هاتف الطوارئ

خدمة Carechem : +44 (0) 671 239 1235 (اللغة العربية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

+44 (0) 670 239 1235 (اللغة الإنجليزية 24 ساعة في اليوم/7 أيام على مدار الأسبوع)

## القسم 2. بيان الأخطار

غير مُصنَّفة.

تصنيف المادة أو الخليط

عناصر بطاقة الوسم في النظام ن م

كلمة التنبيه

بدون كلمة تنبيه

عبارات المخاطر

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

عبارات التحذير

الوقاية

غير قابل للتطبيق.

الاستجابة

غير قابل للتطبيق.

التخزين

غير قابل للتطبيق.

التخلص من النفاية

غير قابل للتطبيق.

الأخطار الأخرى التي لا تؤدي إلى تصنيف

يزيل دهون الجلد.

زيوت المحركات المستعملة

قد يحتوي زيت المحرك المستعمل على مكونات خطيرة من الممكن ان تتسبب في سرطان الجلد.

انظر معلومات التسمم، القسم 11 من نشرة البيانات هذه.

## القسم 3. التركيب/معلومات عن المكونات

خليط

مادة/مستحضر

زيت أساسي عالي النقاوة (خلاصة 346 IP DMSO > 3%) . إضافات خاصة للأداء.

Product name	Super V 15W-40	اسم المنتج	الصفحة: 16/1
Product code	470020-AE02	كود المنتج	Date of issue 03/07/2019.
Version 1.01	نسخة	Format Oman	Page: 1/16 تاريخ الإصدار
			Language ENGLISH
			العربية

### القسم 3. التركيب/معلومات عن المكونات

اسم المكون	%	رقم التسجيل في دائرة المستخلصات الكيميائية CAS
مواد مقطرة (بترول)، معالجة بالهيدروجين بارافينية بدرجة كثيفة زيت أساسي - عالي النقاوة	90 - 75 ≥ - 10 ≤	64742-54-7 يتنوع - انظر مفتاح الاختصارات
مواد مقطرة (بترول)، معالجة بالهيدروجين بدرجة خفيفة، بارافينية	5 ≤	64742-55-8
مواد مقطرة (بترول)، خالية من الشمع بالمذيب، بارافينية بدرجة كثيفة	3 ≤	64742-65-0
فينول ألكيلي	0.1 ≤	74499-35-7 / 121158-58-5

على حد علم المورد في هذه اللحظة وطبقاً للتركيزات المستخدمة، لا توجد أية مكونات أو مكونات إضافية مصنفة كمواد خطرة على الصحة أو على البيئة تستدعي الإبلاغ عنها في هذا القسم.

القسم الثامن يعرض حدود التعرض المهني، في حال توفرها.

### القسم 4. تدبير الإسعاف الأولي

#### وصف إجراءات الإسعافات الأولية اللازمة

ملامسة العين	في حالة الملامسة، يُراعى دفع الماء فوراً على العين لمدة لا تقل عن 15 دقيقة. يجب إبعاد الجفون عن مقلات العين لضمان الشطف الكامل. يراعى التحقق من عدم وجود عدسات لاصقة أو إزالتها إن وجدت. يُراعى الحصول على الرعاية الطبية.
استنشاق	في حالة الاستنشاق، يُراعى نقل المصاب إلى الهواء الطلق. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
ملامسة الجلد	يراعى غسل البشرة غسلاً جيداً بالماء والصابون أو بأحد منظفات الجلد المعترف بها. أزل الثياب والأحذية الملوثة. يُراعى غسل الثياب قبل إعادة استخدامها. يراعى تنظيف الحذاء تنظيفاً جيداً قبل ارتدائه ثانية. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
الابتلاع	لا تحرض على القيء إلا إن طلب أحد أعضاء الطاقم الطبي منك أن تقوم بهذا. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.

#### أهم الأعراض/التأثيرات، الحادة والمتأخرة

انظر القسم 11 لمزيد من المعلومات عن التأثيرات الصحية والأعراض.

#### بيان الرعاية الطبية الفورية والمعالجة الخاصة إذا كانت ضرورية

ملاحظات للطبيب	يجب أن تتم المعالجة حسب الأعراض بشكل عام ويتم إجراؤها لتخفيف حدة التأثيرات.
معالجات خاصة	لا يوجد علاج محدد.
حماية فريق الإسعافات الأولية	يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب.

### القسم 5. تدابير مكافحة النار

#### وسائل الإطفاء

وسائل الإطفاء المناسبة	في حالة نشوب حريق، استخدم الرغوة والمواد الكيميائية الجافة أو مطفأة حريق أو بخاخة بها ثاني أكسيد الكربون.
وسائل الإطفاء غير المناسبة	لا تستخدم المياه النفاثة.

#### مخاطر خاصة ناشئة عن المادة الكيميائية

سوف يحدث تزايد في الضغط وقد تنفجر الحاوية في حالة حدوث حريق أو تسخين.

#### نواتج تحليل حراري خطرة

نواتج الاحتراق قد تشمل ما يلي:  
أكاسيد الكربون (CO, CO<sub>2</sub>)

#### معدات الحماية الشخصية والاحتياطات اللازمة لعمال الإطفاء

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى عزل المكان على الفور وذلك بإخلاء الأفراد المتواجدين على مقربة من الحادث في حالة نشوب حريق.

#### معدات الحماية الشخصية والاحتياطات اللازمة لعمال الإطفاء

يجب على فريق مكافحة الحريق أن يرتدوا جهاز تنفس مكتفي ذاتياً SCBA إيجابي الضغط والزي الواقي كلاً.

Product name	Super V 15W-40	اسم المنتج	الصفحة: 16/2
Product code	470020-AE02	كود المنتج	Date of issue
Version	1.01	نسخة	03/07/2019.
		Format Oman	تاريخ الإصدار
		Language	Page: 2/16
		ENGLISH	العربية

## القسم 6. تدابير مواجهة التسرب العارض

### لاحتياطات الشخصية ومعدات الحماية وإجراءات الطوارئ

#### للأفراد من خارج فريق الطوارئ

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى إخلاء المناطق المجاورة. يراعى عدم السماح بالدخول لكل من لا يرتدي الثياب الواقية أو من لا حاجة لك بهم من الأفراد. يراعى تجنب ملامسة المادة المنسكبة أو السير عليها. ارتدي التجهيزات الواقية الشخصية الملائمة. قد تكون الأرضيات زلقة؛ يجب توخي العناية لتجنب السقوط.

#### لمسعفي الطوارئ

إذا لزم الأمر ارتداء ثياباً خاصة للتعامل مع الانسكاب، يُرجى أخذ ما ورد في القسم 8 من معلومات حول المواد المناسبة وغير المناسبة في الحسبان. راجع كذلك المعلومات الواردة في قسم "للأفراد من خارج فريق الطوارئ".

### الاحتياطات البيئية

تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف. يُراعى إبلاغ السلطات المعنية لو تسبب المنتج في تلوث البيئة (مجري الصرف، المجاري المائية، التربة أو الهواء).

### طرائق ومواد الاحتواء والتنظيف

#### انسكاب صغير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يُراعى امتصاصها بمادة خاملة، ثم إيداعها إحدى الحاويات الملائمة للتخلص من النفايات. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

#### انسكاب كبير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. امنع دخولها في البالوعات والصرف، و المجاري المائية، أو البدرومات، أو المناطق المحصورة. يُراعى احتواء الانسكاب وجمعه بمادة ماصة غير قابلة للاحتراق مثل الرمل، أو التراب، أو الفرميكيوليت، أو تراب دياتومي، ثم وضعها في إحدى الحاويات للتخلص منها بما يتفق واللوائح المحلية. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

## القسم 7. المناولة والتخزين

### احتياطات للمناولة الآمنة

#### إجراءات للحماية

#### إرشادات حول الصحة المهنية العامة

يراعى ارتداء أجهزة الوقاية الشخصية الملائمة(انظر القسم 8).

يحظر تناول الطعام، والشراب، والتدخين في الأماكن التي يجري التعامل فيها مع هذه المادة سواء بالمناولة، التخزين أو المعالجة. يُراعى الإغتسال جيداً بعد مناولتها. اخلع الثياب الملوثة والتجهيزات الوقائية قبل دخول الأماكن المخصصة للطعام. انظر القسم 8 لمزيد من المعلومات حول إجراءات الحفاظ على الصحة.

متطلبات التخزين الآمن، بما في ذلك ما يتعلق بحالات عدم توافق المواد

خزن المادة وفقاً لتعليمات السلطات المحلية. خزن المادة في حاويتها الأصلية مع حمايتها من التعرض لحرارة الشمس المباشرة في منطقة جافة، وباردة، وجيدة التهوية بعيداً عن المواد غير المطابقة (انظر القسم 10)، وعن الطعام، والشراب. يراعى غلق الوعاء غلقاً تاماً محكماً إلى أن يُعد للاستخدام. يجب أن يتم التخزين والاستعمال فقط في معدات/حاويات مصممة للاستخدام مع هذا المنتج. لا بد من إحكام غلق الأوعية التي قد قُفِّحت و تركها في وضع قائم و ذلك لتلافي حدوث تسريب. يُحظر التخزين في حاويات لا تحمل كتابة توضيحية. يُراعى استخدام طرق احتواء سليمة لتجنب تلوث البيئة.

التعرض لدرجات الحرارة العالية لفترات طويلة.

غير ملانمة

## القسم 8. ضوابط التعرض/الحماية الشخصية

### إزامترات التحكم

#### حدود التعرض المهني

اسم المكون	حدود التعرض
مواد مقطرة (بنترول)، معالجة بالهيدروجين بارافينية بدرجة كثيفة	TLV ACGIH (الولايات المتحدة). TWA: 5 مج / م <sup>3</sup> 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشق
زيت أساسي - عالي النقاوة	TLV ACGIH (الولايات المتحدة). TWA: 5 مج / م <sup>3</sup> 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشق
مواد مقطرة (بنترول)، معالجة بالهيدروجين بدرجة خفيفة، بارافينية	TLV ACGIH (الولايات المتحدة). TWA: 5 مج / م <sup>3</sup> 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشق
مواد مقطرة (بنترول)، خالية من الشمع بالمذيب، بارافينية بدرجة كثيفة	TLV ACGIH (الولايات المتحدة). TWA: 5 مج / م <sup>3</sup> 8 ساعات. صدرت/روجعت: 11/2009 الشكل: النسبة التي قد تُستنشق

## القسم 8. ضوابط التعرض/الحماية الشخصية

### الضوابط الهندسية المناسبة

يجب تقييم جميع الأنشطة المرتبطة بالمواد الكيميائية من حيث مخاطرها على الصحة، وذلك لضمان التحكم في معدلات التعرض بالشكل المناسب. لا يجوز فحص معدات الوقاية الشخصية إلا بعد تقييم الأشكال الأخرى لإجراءات التحكم (على سبيل المثال عمليات التحكم الهندسية) بالشكل المناسب. يجب أن تتوافق معدات الوقاية الشخصية مع المواصفات المعنية وأن تكون مناسبة للاستخدام، ويجب الحفاظ عليها في حالة جيدة وصيانتها بشكل سليم.

يجب التشاور مع مورد معدات الوقاية الشخصية لطلب المشورة بشأن الاختيار والمواصفات المعنية. لمزيد من المعلومات، اتصل بالهيئة المحلية للمواصفات.

احرص على توفير تهوية للعوامل أو الوسائل الهندسية الأخرى للحماية، وذلك للإبقاء على مستويات التركيز المعنية للمواد العالقة بالهواء دون حدود التعرض المقبولة لها على الصعيد المهني.

القرار النهائي لاختيار معدات الوقاية يعتمد على تقييم المخاطر. ومن المهم التأكد من ملائمة جميع عناصر معدات الوقاية الشخصية.

### ضوابط التعرض البيئي

ننصح بفحص الانبعاثات الصادرة من أجهزة العمل والتهوية، للتأكد من استيفائها لمتطلبات قانون حماية البيئة. في بعض الحالات، قد يكون من الضروري استخدام أجهزة غسل الدخان، أو المرشحات أو إجراء تعديلات هندسية للمعدات، كي يتسنى تقليل الانبعاثات إلى مستويات مقبولة.

### تدابير الحماية الفردية

#### إجراءات النظافة الشخصية

اغسل اليدين، والذراعين، والوجه غسلاً تاماً بعد مناولة المنتجات الكيميائية، وعند الأكل والتدخين، وفي نهاية فترة العمل. يتوجب استخدام طرائق ملائمة لنزع الثياب التي يُحتمل تلوثها. يُراعى غسل الثياب الملوثة قبل ارتدائها مرة ثانية. تأكد من وجود محطات غسيل الأعين وأدشاش الأمان على مقربة من موقع العمل.

نظارات أمان ذات سائرات جانبية.

#### أدوات حماية الوجه/العين

#### حماية للجلد

#### حماية يديوية

احرص على ارتداء القفازات الواقية من الماء إذا كان من المحتمل حدوث ملامسات متكررة وطويلة. قم بارتداء القفازات المقاومة للمواد الكيميائية. يُنصح باستخدام قفازات نيتريل. يعتمد الاختيار الصحيح لقفازات الحماية على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة القفازات (حتى أفضل القفازات المقاومة للمواد الكيميائية تتآكل بفعل التعرض المتكرر للمواد الكيميائية). معظم القفازات توفر الحماية لفترة زمنية قصيرة فقط وبعدها يجب التخلص منها واستبدالها. نظراً للظروف الخاصة لبيئات العمل واختلاف ممارسات التعامل مع المواد، فيجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار القفازات بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

#### أدوات حماية الجسم

استخدام الملابس الواقية يعتبر من الممارسات الجيدة في المجال الصناعي.

يجب انتقاء التجهيزات الشخصية الواقية للجسم بما يتفق والمهمة التي يجري القيام بها والمخاطر التي تنطوي عليها، كما يجب أن يعتمد عليها أحد المختصين قبل التعامل مع هذا المنتج.

بدلات العمل المصنوعة من القطن أو البوليستر/القطن توفر الحماية فقط من التلوث السطحي الخفيف الذي لا يصل إلى الجلد. ويجب غسل بدلات العمل بصفة منتظمة. عندما تزداد خطورة تعرض الجلد للمواد (على سبيل المثال عند تنظيف المواد المنسكبة أو في حالة وجود خطورة من تناثر الرذاذ)، فيجب ارتداء إزارات مقاومة للمواد الكيميائية و/أو أحذية وسترات غير منفذة للمواد الكيميائية.

#### حماية تنفسية

في حالة عدم كفاية التهوية، يُراعى ارتداء تجهيزات تنفسية ملائمة.

يعتمد الاختيار الصحيح لتجهيزات حماية الجهاز التنفسي على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة تجهيزات حماية الجهاز التنفسي. يجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار تجهيزات حماية الجهاز التنفسي بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

## القسم 9. الخصائص الفيزيائية والكيميائية

### المظهر

#### الحالة الفيزيائية

#### اللون

#### الرائحة

#### عتبة الرائحة

#### الأس الهيدروجيني pH

#### نقطة الانصهار

#### نقطة الغليان

#### نقطة السقوط

#### نقطة الوميض

#### معدل التبخر

#### القابلية للالتهاب (مادة صلبة، غاز)

#### الحدود العليا/الدنيا للقابلية للالتهاب أو الانفجار

سائل.

كهرومان. [فاتح]

غير متوفرة.

غير متوفرة.

غير متوفرة.

غير متوفرة.

غير متوفرة.

غير متوفرة.

كأس مغلق: 204°C (399.2 ف) [جهاز بنسكي-مارتينز. (القيمة بالضبط)]

جهاز الكأس المفتوحة: <210°C (<410 ف) [جهاز كليفلاند].

غير متوفرة.

غير قابل للتطبيق. اعتماداً على - الحالة الفيزيائية

غير متوفرة.

Product name	Super V 15W-40	اسم المنتج	الصفحة: 16/4
Product code	470020-AE02	Date of issue	Page: 4/16 تاريخ الإصدار
Version	1.01 نسخة	Format Oman	Language
			ENGLISH العربية

## القسم 9. الخصائص الفيزيائية والكيميائية

الضغط البخاري	غير متوفرة.
الكثافة البخارية	غير متوفرة.
الكثافة النسبية	غير متوفرة.
الكثافة	$1000 \text{ كجم/م}^3 > 1 \text{ g/cm}^3$ عند $15^\circ\text{C}$
الذوبانية	غير ذوب في الماء.
الذوبانية	غير متوفرة.
معامل تفريق الأوكتانول/الماء	غير متوفرة.
درجة حرارة الاشتعال الذاتي	غير متوفرة.
درجة حرارة الانحلال	غير متوفرة.
اللزوجة	كينماتي: $109 \text{ S}^2\text{mm}$ (109 سنتي ستوك) عند $40^\circ\text{C}$ كينماتي: $14.2$ إلى $15.5 \text{ S}^2\text{mm}$ (14.2 إلى 15.5 سنتي ستوك) عند $100^\circ\text{C}$

## القسم 10. الثبات الكيميائي والقابلية للتفاعل

التفاعلية	لا تتاح بيانات اختبار أخرى معينة لهذا المنتج. ارجع إلى الظروف التي يجب تجنبها والمواد غير المتوافقة لمزيد من المعلومات.
الثبات الكيميائي	المنتج ثابت.
إمكانية التفاعلات الخطرة	لن تحدث تفاعلات خطيرة في ظروف التخزين والاستخدام العادية. لن تحدث بلمرة خطيرة في ظروف التخزين والاستخدام العادية.
الظروف التي ينبغي تجنبها	يجب تجنب جميع مصادر الاشتعال الممكنة (شرر أو لهب).
المواد غير المتوافقة	تتفاعل أو غير متطابقة مع المواد التالية: مواد مؤكسدة.
نواتج الانحلال الخطرة	في ظروف التخزين والاستخدام العادية، من غير المنتظر أن تتولد نواتج تحلل خطيرة.

## القسم 11. المعلومات السمية

معلومات حول الآثار السمية	خطر الشفط في الجهاز التنفسي
الاسم	زيت أساسي - عالي النقاوة
مواد مقطرة (بترو)، معالجة بالهيدروجين بدرجة خفيفة، بارافينية	مواد مقطرة (بترو)، معالجة بالهيدروجين بدرجة خفيفة، بارافينية
معلومات عن سُبُل التعرض المرجحة	سُبُل الدخول المُرتقبة: جلدي، استنشاق.
آثار صحية حادة كامنة	لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.
ملامسة العين	استنشاق
ملامسة الجلد	لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.
الابتلاع	لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.
أعراض متعلقة بالخواص السمية والكيميائية والفيزيائية	أعراض متعلقة بالخواص السمية والكيميائية والفيزيائية
ملامسة العين	ليست هناك بيانات معينة.
استنشاق	ليست هناك بيانات معينة.
ملامسة الجلد	الأعراض الضائرة قد تشمل ما يلي: تهيج الجفاف التشقق ليست هناك بيانات معينة.
الابتلاع	ليست هناك بيانات معينة.

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

Product name	Super V 15W-40	اسم المنتج	الصفحة: 16/5
Product code	470020-AE02	Date of issue	03/07/2019.
Version	1.01	Format	Oman
تسعة	تسعة	Language	ENGLISH
		العربية	

## القسم 11. المعلومات السمومية

ملامسة العين

استنشاق

ملامسة الجلد

الابتلاع

آثار صحية مزمنة كامنة

عامة

زيوت المحركات المستعملة

نواتج الاحتراق التي تنتج من تشغيل محركات الاحتراق الداخلي تلوث زيت المحرك أثناء الاستخدام. وقد يحتوي زيت المحرك المستعمل على مكونات خطيرة من الممكن أن تتسبب في سرطان الجلد. لذلك يجب تجنب ملامسة جميع أنواع وماركات زيوت المحركات المستعملة بشكل متكرر أو لفترات طويلة، ويجب الالتزام بالموصفات القياسية العالية للتنظيف الصحية على مستوى الأفراد.

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

السرطنة

التأثير على الجينات

القابلية على التسبب في المسخ

التأثيرات النمائية

التأثيرات الخصوبية

القياسات الرقمية للسمية

تقديرات السمية الحادة

غير متوفرة.

## القسم 12. المعلومات الإيكولوجية

تأثيرات بيئية

الثبات والتحلل

يُتوقع أن يكون قابلاً للتحلل الحيوي.

القدرة على التراكم الأحيائي

لا يُتوقع أن يتراكم هذا المنتج حيوياً في البيئة من خلال السلاسل الغذائية.

القابلية على التحرك عبر التربة

معامل تقاسم التربة/الماء (Koc)

التحررية

غير متوفرة.

المواد المنسكبة يمكن أن تتوغل في التربة وتتسبب في تلوث المياه الجوفية.

لا توجد تأثيرات شديدة أو مخاطر حرجية معروفة.

قد تتسبب السوائل المنسكبة في تكوين طبقة على أسطح الماء، وقد تتسبب في ضرر مادي للكائنات الحية. وقد يتم إعاقة نقل الأكسجين أيضاً.

التأثيرات الضارة الأخرى

معلومات بيئية أخرى

## القسم 13. الاعتبارات المتعلقة بتصريف المواد والتخلص منها

طرائق التصريف

ينبغي تجنب توليد النفايات أو التقليل منها حيثما أمكن. ينبغي عدم التخلص من الكميات الكبرى من فضالة نفاية المُنتج عبر شبكة الصرف الصحي وإنما مُعالجتها في محطة مُناسبة لمعالجة مياه الصرف. يُراعى التخلص من الفائض والمنتجات غير القابلة لإعادة التدوير من خلال أحد المقاولين المرخص لهم بذلك. يراعى أن يجري دوماً التخلص من هذا المنتج، و المحاليل و المنتجات الثانوية بما يتفق و متطلبات الحماية البيئية و تشريعات التخلص من النفايات و غيرها من متطلبات السلطة الإقليمية و المحلية. ينبغي أن يُعاد تدوير نفاية التغليف. ينبغي عدم أخذ الترميد أو الطمر في الاعتبار إلا إذا كانت إعادة التدوير غير مُجدية. لا بد أن يجري التخلص من هذا المنتج وحاويته بطريقة آمنة. قد تظل بعض رواسب المنتج عالقة بالحاويات الفارغة أو مُصانها. تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية و البالوعات و مجاري الصرف.

Product name	Super V 15W-40	اسم المنتج	الصفحة: 6/16
Product code	470020-AE02	Date of issue	03/07/2019.
Version	1.01	Format	ENGLISH
تسعة		Oman	العربية

## القسم 14. المعلومات المتعلقة بالنقل

IATA	IMDG	
غير مقننة.	غير مقننة.	رقم الأمم المتحدة
-	-	اسم الشحن الصحيح الخاص بالأمم المتحدة
-	-	فئة/فئات مخاطر النقل
-	-	مجموعة التعبئة
لا.	لا.	الأخطار البيئية
-	-	معلومات إضافية

احتياطات خاصة للمستخدم غير متوفرة.

النقل سائناً بحسب الملحق الثاني من اتفاقية ماريبول MARPOL (بشأن منع التلوث الناجم عن السفن) وكود حاوية السوانب الوسيطة (IBC)

غير متوفرة.

## القسم 15. المعلومات التنظيمية

القواعد المتعلقة بالسلامة والصحة والبيئة، لا توجد لوائح وطنية و/أو إقليمية معروفة تنطبق على هذا المنتج (بما في ذلك مكوناته). المنطبقة على المنتج

### قائمة الجرد الوطنية

أستراليا

كندا

الصين.

الوضع وفق REACH (النظام المتعلق بتسجيل وتقييم وترخيص المواد الكيميائية)

اليابان

الفلبين

جمهورية كوريا

تايلاند

الولايات المتحدة

كافة المكونات مدرجة بالقائمة أو مُستثناة منها.

كافة المكونات مدرجة بالقائمة أو مُستثناة منها.

مُكوّن واحد على الأقل غير مُدرَج.

للتعرف على حالة REACH لهذا المنتج، يرجى التواصل مع جهة الاتصال في شركتكم، كما هو محدد في القسم 1.

مُكوّن واحد على الأقل غير مُدرَج.

كافة المكونات مدرجة بالقائمة أو مُستثناة منها.

كافة المكونات مدرجة بالقائمة أو مُستثناة منها.

كافة المكونات مدرجة بالقائمة أو مُستثناة منها.

جميع المكونات تحمل الصفة "فعالة" أو الصفة "مستثناة".

## القسم 16. المعلومات الأخرى

### السيرة

تاريخ الإصدار/تاريخ المراجعة 03/07/2019.

تاريخ الإصدار السابق 03/07/2019.

نسخة 1.01

من إعداد Product Stewardship

Product name	Super V 15W-40	اسم المنتج	الصفحة: 16/7
Product code	470020-AE02	Date of issue	03/07/2019.
Version	1.01	Format	Oman
نسخة		Language	ENGLISH
		العربية	

كود المنتج

03/07/2019.

Page: 7/16 تاريخ الإصدار

Format Oman

Language

ENGLISH

العربية

ACGIH = المؤتمر الأمريكي للمتخصصين في الصحة الصناعية  
 رقم CAS = رقم سجل دائرة المستخلصات الكيميائية  
 GHS = النظام المنسق العالمي  
 IATA = اتحاد النقل الجوي الدولي، المنظمة  
 IMDG = قوانين المنظمة البحرية الدولية والقواعد الحاكمة لشحن البضائع عن طريق المياه.  
 OEL = حد التعرض المهني  
 REACH = التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيميائية [نظام (المفوضية الأوروبية) رقم  
 1907/2006]  
 SDS = نشرة بيانات الأمان  
 STEL = حد التعرض على المدى القصير  
 TWA = المتوسط المرجح للوقت  
 رقم UN = رقم الأمم المتحدة، رقم من أربعة أرقام يتم تعيينه من قبل لجنة الأمم المتحدة لخبراء نقل البضائع الخطرة.  
 متنوع = قد يحتوي على واحد أو أكثر من المكونات التالية 4-6, 64741-88-5, 64741-89-5, 64741-95-3, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 64742-72-8, 72623-85-9, 72623-86-0, 72623-87-1

## الإجراء المتبع للحصول على التصنيف

التصنيف	التبرير
غير مُصنَّفة.	

تشير إلى معلومات تم تغييرها مقارنة بالنسخة التي سبق إصدارها.

## ملاحظة للقارئ الكريم

تم اتخاذ جميع الخطوات المتاحة المعقولة لضمان دقة نشرة البيانات هذه والمعلومات المتعلقة بالصحة والأمان والبيئة حسب البيانات الموضحة أدناه. لا يوجد ضمان أو تفويض، صريح أو ضمني، بشأن دقة أو اكتمال البيانات والمعلومات الواردة في نشرة البيانات هذه.

تسري البيانات والنصائح المعطاة في حالة بيع المنتج للتطبيق المذكور أو التطبيقات المذكورة. لا يجوز لك استخدام المنتج في غير التطبيق المذكور أو التطبيقات المذكورة دون طلب المشورة من شركة Group BP.

يجب على المستخدم تقييم هذا المنتج واستخدامه بشكل آمن بما يتوافق مع جميع القوانين والتشريعات المعمول بها. لا تتحمل شركة Group BP أية مسؤولية عن أي ضرر أو إصابة تنتج عن الاستخدام، أو أي استخدام آخر بخلاف استخدام المنتج المذكور للخامة، أو في حالة عدم مراعاة التوصيات، أو المخاطر المتأصلة في طبيعة الخامة. القارئون بشراء المنتج لتوريده إلى طرف ثالث للاستخدام في العمل عليهم اتخاذ جميع الخطوات اللازمة للتأكد من أن أي شخص يستخدم المنتج يكون على دراية بالمعلومات الواردة في هذه النشرة. يجب على أصحاب العمل إبلاغ الموظفين لديهم وغيرهم من الأشخاص المعنيين بالمخاطر الموضحة في هذه النشرة وعن الاحتياطات الواجب اتخاذها. يمكنك الاتصال بشركة Group BP للتأكد من أن هذا المستند على أحدث وضع. ممنوع منعاً باتاً إجراء تغيير على هذا المستند.

## SAFETY DATA SHEET



Super V 15W-40

## Section 1. Identification

GHS product identifier	Super V 15W-40
Product code	470020-AE02
SDS no.	470020
<b>Relevant identified uses of the substance or mixture and uses advised against</b>	
Use of the substance/ mixture	Automotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer Supplier	BP Middle East Standard Chartered Tower 8th Floor, Down Town Burj Khalifa By Emaar Square P.O. Box 1699, Dubai, United Arab Emirates  Main : (971) 4 331 7999 Fax : (971) 4 331 8530

Product name	Super V 15W-40	اسم المنتج	16/8 الصفحة
Product code	470020-AE02	كود المنتج	Date of issue 03/07/2019.
Version 1.01	نسخة	Format Oman	تاريخ الإصدار Page: 8/16
			Language ENGLISH
			العربية



## Section 1. Identification

### EMERGENCY TELEPHONE NUMBER

Carechem: +44 (0) 1235 239 671 (Arabic language 24/7)  
+44 (0) 1235 239 670 (English language 24/7)

## Section 2. Hazards identification

### GHS Classification

Not classified.

### GHS label elements

#### Signal word

No signal word.

#### Hazard statements

No known significant effects or critical hazards.

#### Precautionary statements

##### Prevention

Not applicable.

##### Response

Not applicable.

##### Storage

Not applicable.

##### Disposal

Not applicable.

### Other hazards which do not result in classification

Defatting to the skin.  
USED ENGINE OILS  
Used engine oil may contain hazardous components which have the potential to cause skin cancer.  
See Toxicological Information, section 11 of this Safety Data Sheet.

## Section 3. Composition/information on ingredients

### Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥75 - ≤90	64742-54-7
Base oil - unspecified	≤10	Varies - See Key to abbreviations
Distillates (petroleum), hydrotreated light paraffinic	≤5	64742-55-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0
Alkylated phenol	≤0.1	74499-35-7 / 121158-58-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

#### Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

#### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Product name	Super V 15W-40	اسم المنتج	16/9: الصفحة
Product code	470020-AE02	كود المنتج	03/07/2019. تاريخ الإصدار Page: 9/16
Version 1.01	نسخة	Format Oman	Language
			ENGLISH العربية

## Section 4. First aid measures

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

## Section 5. Firefighting measures

### Extinguishing media

Suitable	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

### Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

### Hazardous thermal decomposition products

Combustion products may include the following:  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training.  
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Product name	Super V 15W-40	اسم المنتج	16/10: الصفحة
Product code	470020-AE02	كود المنتج	03/07/2019. تاريخ الإصدار Page: 10/16
Version	1.01	نسخة	Format Oman
			Language
			ENGLISH
			العربية

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8).

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Not suitable

Prolonged exposure to elevated temperature.

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Base oil - unspecified	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Distillates (petroleum), hydrotreated light paraffinic	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

#### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

Product name		Super V 15W-40		اسم المنتج		الصفحة: 16/11	
Product code		470020-AE02		كود المنتج		Date of issue	
Version		1.01		نسخة		03/07/2019.	
				Format		Oman	
						Language	
						ENGLISH	
						العربية	
						Page: 11/16	

## Section 8. Exposure controls/personal protection

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection

Safety glasses with side shields.

### Skin protection

#### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

### Appearance

Physical state	Liquid.
Colour	Amber. [Light]
Odour	Not available.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point	Not available.
Drop Point	Not available.
Flash point	Closed cup: 204°C (399.2°F) [Pensky-Martens. (typical value)] Open cup: >210°C (>410°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower and upper explosive (flammable) limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Density	<1000 kg/m <sup>3</sup> (<1 g/cm <sup>3</sup> ) at 15°C
Solubility	insoluble in water.

Product name	Super V 15W-40	اسم المنتج	16/12: الصفحة
Product code	470020-AE02	كود المنتج	Date of issue
Version	1.01	نسخة	03/07/2019.
		Format	Language
		Oman	ENGLISH
			العربية

## Section 9. Physical and chemical properties

<b>Solubility</b>	Not available.
<b>Partition coefficient: n-octanol/water</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Kinematic: 109 mm <sup>2</sup> /s (109 cSt) at 40°C Kinematic: 14.2 to 15.5 mm <sup>2</sup> /s (14.2 to 15.5 cSt) at 100°C

## Section 10. Stability and reactivity

<b>Reactivity</b>	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame).
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidising materials.
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Aspiration hazard

##### **Name**

Base oil - unspecified  
Distillates (petroleum), hydrotreated light paraffinic

##### **Result**

ASPIRATION HAZARD - Category 1  
ASPIRATION HAZARD - Category 1

<b>Information on likely routes of exposure</b>	Routes of entry anticipated: Dermal, Inhalation.
---	--

### Potential acute health effects

#### **Eye contact**

No known significant effects or critical hazards.

#### **Inhalation**

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

#### **Skin contact**

Defatting to the skin. May cause skin dryness and irritation.

#### **Ingestion**

No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

#### **Eye contact**

No specific data.

#### **Inhalation**

No specific data.

#### **Skin contact**

Adverse symptoms may include the following:  
irritation  
dryness  
cracking

#### **Ingestion**

No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Eye contact**

Potential risk of transient stinging or redness if accidental eye contact occurs.

#### **Inhalation**

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

#### **Skin contact**

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

#### **Ingestion**

Ingestion of large quantities may cause nausea and diarrhoea.

<b>Product name</b>	Super V 15W-40	اسم المنتج	16/13: الصفحة
<b>Product code</b>	470020-AE02	كود المنتج	03/07/2019. تاريخ الإصدار Page: 13/16
<b>Version</b>	1.01	نسخة	Format Oman
			Language
			ENGLISH
			العربية

## Section 11. Toxicological information

### Potential chronic health effects

#### General

#### USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

#### Carcinogenicity

No known significant effects or critical hazards.

#### Mutagenicity

No known significant effects or critical hazards.

#### Teratogenicity

No known significant effects or critical hazards.

#### Developmental effects

No known significant effects or critical hazards.

#### Fertility effects

No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## Section 12. Ecological information

### Environmental effects

No known significant effects or critical hazards.

### Persistence and degradability

Expected to be biodegradable.

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

### Mobility in soil

#### Soil/water partition coefficient ( $K_{oc}$ )

Not available.

#### Mobility

Spillages may penetrate the soil causing ground water contamination.

#### Other adverse effects

No known significant effects or critical hazards.

#### Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

Product name	Super V 15W-40	اسم المنتج	16/14: الصفحة
Product code	470020-AE02	كود المنتج	Date of issue 03/07/2019. تاريخ الإصدار Page: 14/16
Version 1.01	نسخة	Format Oman	Language ENGLISH العربية

## Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Transport in bulk according to Annex II of Marpol and the IBC Code Not available.

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

### International lists

#### National inventory

Australia

All components are listed or exempted.

Canada

All components are listed or exempted.

China

At least one component is not listed.

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Japan

At least one component is not listed.

Philippines

All components are listed or exempted.

Republic of Korea

All components are listed or exempted.

Taiwan

All components are listed or exempted.

United States

All components are active or exempted.

## Section 16. Other information

### History

Date of issue/Date of revision 03/07/2019.

Date of previous issue 03/07/2019.

Version 1.01

Prepared by Product Stewardship

Product name	Super V 15W-40	اسم المنتج	16/15 الصفحة
Product code	470020-AE02	كود المنتج	03/07/2019. تاريخ الإصدار Page: 15/16
Version 1.01	نسخة	Format Oman	Language
			ENGLISH العربية



## Section 16. Other information

### Key to abbreviations

ACGIH = American Conference of Industrial Hygienists  
CAS Number = Chemical Abstracts Service Registry Number  
GHS = Global Harmonised System  
IATA = International Air Transport Association, the organisation  
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.  
OEL = Occupational Exposure Limit  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
SDS = Safety Data Sheet  
STEL = Short term exposure limit  
TWA = Time weighted average  
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.  
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### Procedure used to derive the classification

Classification	Justification
Not classified.	

Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Super V 15W-40	اسم المنتج	16/16 الصفحة
Product code	470020-AE02	كود المنتج	03/07/2019. تاريخ الإصدار Page: 16/16
Version	1.01	نسخة	Format Oman
			Language
			ENGLISH
			العربية