CADDXFPV

– Kangaroo MANUAL –

1 3.3–5.5V	**2** GND	**3** VIDEO	**4** OSD	**5** GND

kangaroo

control panel

GND
OSD

Model	Kangaroo
Image Sensor	SONY STARVIS sensor
Horizontal resolution	1000TVL
Television system	NTSC and PAL(can be changed)
Image	16:9 and 4:3 (can be changed)
WDR	Super WDR

Hey.illumination	0.001Lux@F1.8
Lens	2.1mm
Synchronize	Internal
Electronic shutter	PAL:1/50~100,000;NTSC:1/60~100,000
Signal to noise ratio	>60dB(AGC OFF)
Video output	CVBS
Camera OSD	Progress menu
Fly OSD	Support
DNR	3-DNR
Language	ENG/France/RUS/SPA/PU Korea/CHN/JAPAN
Morning and evening	Auto/Color/Black&White/EXT
Dimensions	14mm/19mm
Operating temperature	-20℃~+60℃

EXIT

SAVE ALL	↵
NOT SAVE	↵
CANCEL	↵
RETURN	↵

SETUP MENU

PICT ADJUST	↵
DAY/NIGHT	AUTO
WHITE BAL	ATW↵
LANGUAGE	ENGLISH
CAMERA RESET	YES↵
EXIT	↵

PICT ADJUST

FLIP	OFF	
BRIGHTNESS		128
CONTRAST		128
SHARPNESS		064
HUE		090
COLOR GAIN		128
RETURN	↵	