



PRODUCT BULLETIN

Motor Flush

PRODUCT #041

CAM2 MOTOR FLUSH is a fast-acting engine cleaning additive formulated to remove harmful deposits and sludge from gasoline and diesel engines prior to an oil change. Its advanced detergent and dispersant chemistry helps dissolve varnish, gum, and carbon buildup that can restrict oil flow and reduce engine efficiency. When added to used motor oil and circulated at idle, CAM2 Motor Flush helps suspend contaminants so they can be drained with the old oil. Regular use promotes improved lubrication, smoother engine operation, and extended engine life.

FEATURES

- Removes Sludge & Varnish
- Improves Oil Flow
- Reduces Engine Noise
- Enhances Engine Efficiency
- Compatible with Gasoline & Diesel Engines

DIRECTIONS

1. Ensure engine is at normal operating temperature.
2. Add entire contents of CAM2 Motor Flush to the crankcase oil (do not overfill).
3. Idle engine for 5–10 minutes. Do not drive vehicle during treatment.
4. Shut off engine and immediately drain oil while warm.
5. Replace oil filter and refill with recommended motor oil.

SPECIAL HANDLING

- For crankcase use only. Do not add to fuel tank.
- Do not operate vehicle under load or drive while product is in crankcase.
- Use only as directed; overuse may affect oil viscosity.
- Avoid contact with skin and eyes; wash thoroughly after handling.
- Keep away from heat, sparks, and open flame.
- Dispose of used oil and flush solution in accordance with local, state, and federal regulations.
- KEEP OUT OF REACH OF CHILDREN.

APPLICATIONS

- Passenger cars and light trucks (gasoline and diesel engines)
- High-mileage engines with sludge or varnish buildup
- Preventative maintenance prior to scheduled oil changes
- Engines with noisy lifters due to deposit formation
- Fleet maintenance programs requiring internal engine cleaning



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 833-715-0016

www.CAM2.com