



PRODUCT BULLETIN

Solvent 140

PRODUCT #808

CAM2 SOLVENT 140 is a high-quality hydrocarbon solvent produced from carefully selected petroleum streams and refined through controlled distillation to deliver consistent performance. It offers strong solvency power with a moderate evaporation rate, making it well suited for applications that require effective dissolving of oils, resins, and other non-polar materials while maintaining good working time. With its relatively high flash point and low sulfur content, CAM2 Solvent 140 provides a balance of safety, stability, and efficiency, and is commonly used in industrial cleaning, coatings, adhesives, rubber processing, and general manufacturing applications where reliable, repeatable solvent performance is critical.

FEATURES

With proper agitation in cleaning equipment, CAM2 Solvent 140 removes from metal surfaces:

- Grease
- Lubricating Oils
- Metal working fluids
- Fines

APPLICATIONS

- Replace low flash solvent
- Compatible with most materials and plastics
- Use in a variety of parts cleaning equipment
- Contains NO hazardous substances (no TLV's, PEL's)

TYPICAL PROPERTIES

Product Code	ASTM	808
Density (lb/gal)	1250	6.508
Flash Point °F	56	142
Viscosity cSt @ 100°F	445	4.21

RECOMMENDATIONS/ SPECIFICATIONS

- CAM2 140 Solvent is NOT SARA (Superfund Amendments Reauthorization Act) reportable
- Less solvent monitoring and paperwork.E
- Exceeds the VOC (Volatile Organic Compound) requirements of SCAQMD (South Coast Air Quality Management District) rule 1171 for use as a "Clean Air Solvent" in California.

SPECIAL HANDLING, NOTICES OR WARNINGS

Product contacting the eye may cause irritation. Prolonged or repeated skin exposure causes mild irritation, dermatitis and defatting.



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 833-715-0016
www.CAM2.com