

PRODUCT BULLETIN**SuperHD Brake Fluid DOT 3**

PRODUCT #410

CAM2 SuperHD Brake Fluid DOT 3 is a glycol based hydraulic brake fluid meeting both the Department of Transportation (DOT 3) & the Federal Motor Vehicle requirements for hydraulic brake fluid. **CAM2 SuperHD Brake Fluid DOT 3** surpasses specifications SAE J1703.

- Engineered to provide excellent performance in today's high temperature braking systems
- Low moisture formulation provides maximum wet boiling point protection against vapor lock brake failure.

STANDARDS

SAE J-1703

ISO-4925

FMVSS-116 (Federal Motor Vehicle Safety Standards)

APPLICATIONS:

- Recommended for all anti-lock braking systems (ABS), hydraulic drum and disc braking systems and hydraulic clutches requiring DOT 3 Fluid.
- Provides superior fluidity at low temperatures for optimum braking response
- Exceeds DOT 3 and all leading auto manufacturer's requirements where a DOT 3 brake fluid is specified. This product is compatible with DOT 4 fluids but is NOT compatible with DOT 5 fluids.

TECHNICAL DATA

| | |
|----------------------------|-----------|
| Product Code | 410 |
| Viscosity @ -40°F, cSt | 1200-1300 |
| Viscosity @ 212°F, cSt | 2.1 |
| pH Value | 10.0-11.0 |
| Wet boiling Point, °F | 284 min |
| Dry boiling Point, °F | 401 min |
| Seal Swell & Hardness Test | PASS |
| Corrosion Test | PASS |

