

Fulvic Acid

CONTAINS NON-PLANT FOOD INGREDIENT

ACTIVE INGREDIENT:

Hydrophobic Fulvic Acids from Sub-Bituminous Coals..... 3.00%

INACTIVE INGREDIENTS:

(Carboxylic Acid and Water) 97.00%

100.00%

F3445

GENERAL INFORMATION

Fulvic Acid is an organic acid-based fertilizer additive formulated to improve fertilizer application and compatibility.

This product may alter the pH of certain solutions. This product may be applied with various irrigation water systems.

DIRECTIONS FOR USE

Consult your local agronomist for rates specific to your crop and conditions.

Do not apply near water, storm drains, or drainage ditches, or to any impervious surface. Do not apply if heavy rain is expected. Apply this product only to the intended application site.

FOLIAR: Apply 1-2 pints per acre with sufficient water for thorough coverage by ground or air application.

SOIL: Apply 1-2 pints per acre with fertilizer or with water. Repeated applications may be beneficial. This product may require agitation when mixed with fertilizer for prolonged periods.

COMPATIBILITY: Fulvic Acid can be mixed with most fertilizers and pesticides. However, to reduce risk of incompatibility, always jar test new combinations prior to field mixing.

KEEP OUT OF REACH OF CHILDREN



WARNING: Causes serious eye irritation. Causes skin irritation.

PRECAUTIONARY STATEMENT: Wear eye/face protection and protective gloves. Wash thoroughly after handling.

FIRST AID: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention. If on skin: Wash with plenty of water. If skin irritation occurs, get medical attention. Take off contaminated clothing and wash it before reuse.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Store in original container only and keep tightly sealed when not in use. Store away from incompatible materials. Dispose of contents/container in accordance with federal, state and local regulations.

LIMITATION OF WARRANTY AND LIABILITY

To access Red Zone Technologies' warranty statement, please go to rztproducts.com/warranty.

All trademarks, service marks, trade names, trade dress, product names and logos appearing on this label are the property of their respective owners.

RZT233008



RED ZONE TECHNOLOGIES
PO BOX 5471, FRESNO, CA 93755

NET CONTENTS: 2.5 GALLONS (9.46 Liters)

DENSITY: 8.4 lb/gal at 68°F