

# Supplemental Labeling



Dow AgroSciences LLC

9330 Zionsville Road

Indianapolis, IN 46268-1054 USA

## Tordon\* 22K

EPA Reg. No. 62719-6

### Revised Equipment Requirements for Aerial Application

#### ATTENTION

- It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
- This labeling must be in the possession of the user at the time of application.
- Read the label affixed to the container for Tordon 22K before applying. Carefully follow all precautionary statements and applicable use directions.
- Except as described in this supplemental labeling, use of Tordon 22K is subject to all use precautions and limitations imposed by the label affixed to the product container.

#### Directions for Use

**The current drift management requirements in label for Tordon 22K specify the following:** The distance of the outer most operating nozzles on the boom must not exceed 3/4 the length of the wingspan or rotor.

**Under this supplemental labeling, this requirement for Tordon 22K has been revised to allow the following:** For aerial applications, the boom width must not exceed 75% of the wingspan or 90% of the rotor width.

All other equipment and spray drift requirements remain as specified in the label booklet for Tordon 22K.

\*Trademark of Dow AgroSciences LLC

EPA-accepted: 06-10-2003

**Revisions:** Modifies aerial boom width specifications to be consistent with EPA's draft PR Notice on spray and dust drift label statements.