

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

SECTION 1. IDENTIFICATION

Product name : PRIME + EC
Design code : A6623C

Product Registration number : 100-640

Manufacturer or supplier's details

Company name of supplier : Syngenta Crop Protection, LLC
Address : Post Office Box 18300
Greensboro NC 27419
United States of America (USA)

Telephone : 1 800 334 9481
Telefax : 1 336 632 2192

E-mail address : sds.requests@syngenta.com
Emergency telephone : 1 800 888 8372

Recommended use of the chemical and restrictions on use

Recommended use : Plant growth regulator

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3
Serious eye damage : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure
Specific target organ toxicity : Category 2 (Central nervous system, Kidney, Liver, hearing
- repeated exposure organs)
Aspiration hazard : Category 1

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system, Kidney, Liver, hearing organs) through prolonged or repeated exposure.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6	$\geq 50 - < 70$
1,2,4-trimethylbenzene	95-63-6	$\geq 20 - < 30$
xylene	1330-20-7	$\geq 10 - < 20$
flumetralin (ISO)	62924-70-3	13.8462
poly(oxy-1,2-ethanediyl), alpha-[4-(1,1,3,3-tetramethylbutyl)phenyl]-omega-hydroxy-	9036-19-5	$\geq 10 - < 20$
ethylbenzene	100-41-4	$\geq 5 - < 10$
calcium bis(dodecylbenzenesulphonate), branched	68953-96-8	$\geq 1 - < 5$
2-ethylhexan-1-ol	104-76-7	$\geq 1 - < 5$
toluene	108-88-3	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.

If inhaled : Take the victim into fresh air.
If breathing is irregular or stopped, administer artificial respiration.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

In case of skin contact	: Keep patient warm and at rest. Call a physician or poison control center immediately. Take off all contaminated clothing immediately. Wash off immediately with plenty of water. If skin irritation persists, call a physician. Wash contaminated clothing before re-use.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.
If swallowed	: If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.
Most important symptoms and effects, both acute and delayed	: Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Notes to physician	: There is no specific antidote available. Treat symptomatically. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Extinguishing media - small fires Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Extinguishing media - large fires Alcohol-resistant foam
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.
Specific hazards during fire fighting	: As the product contains combustible organic ingredients, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Flash back possible over considerable distance.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NOx) Chlorine compounds Fluorine compounds Sulfur oxides

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Further information : Do not allow run-off from fire fighting to enter drains or water courses.
Cool closed containers exposed to fire with water spray.

Special protective equipment for fire-fighters : Wear full protective clothing and self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
Keep people away from and upwind of spill/leak.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Remove all sources of ignition.
Pay attention to flashback.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Clean with detergents. Avoid solvents.
Retain and dispose of contaminated wash water.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.
When using do not eat, drink or smoke.
Use only in an area containing flame proof equipment.
Take precautionary measures against static discharges.
For personal protection see section 8.

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
Keep out of the reach of children.
Keep away from combustible material.
Keep in an area equipped with sprinklers.
Keep away from food, drink and animal feedingstuffs.
No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version 2.1 Revision Date: 05/06/2025 SDS Number: S00047442629 Date of last issue: 11/28/2017
Date of first issue: 11/28/2017

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
		TWA	10 ppm	ACGIH
xylene	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	20 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
flumetralin (ISO)	62924-70-3	TWA	5 mg/m3	Syngenta
poly(oxy-1,2-ethanediyl), al-pha-[4-(1,1,3,3-tetramethylbutyl)phenyl]-omega-hydroxy-	9036-19-5	TWA	10 mg/m3	Supplier
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
2-ethylhexan-1-ol	104-76-7	TWA	5 ppm	ACGIH
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version 2.1 Revision Date: 05/06/2025 SDS Number: S00047442629 Date of last issue: 11/28/2017
Date of first issue: 11/28/2017

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
xylene	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g cre-atinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

Engineering measures : THE FOLLOWING RECOMMENDATIONS FOR EXPOSURE CONTROLS/PERSONAL PROTECTION ARE INTENDED FOR THE MANUFACTURE, FORMULATION AND PACKAGING OF THE PRODUCT. FOR COMMERCIAL APPLICATIONS AND/OR ON-FARM APPLICATIONS CONSULT THE PRODUCT LABEL.

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated.

The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Where necessary, seek additional occupational hygiene advice.

Personal protective equipment

Respiratory protection : Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wear protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The break through time depends amongst other things from the material, the thickness and the type of glove and therefore has to be measured for each case. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Tightly fitting safety goggles
Face-shield

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Remove and wash contaminated clothing before re-use.
Wear as appropriate:
Impervious clothing

Protective measures : The use of technical measures should always have priority over the use of personal protective equipment.
When selecting personal protective equipment, seek appropriate professional advice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : No data available

Odor : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	106 °F / 41 °C
		Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.04 g/cm ³ (77 °F / 25 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	698 °F / 370 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	2.17 mPa.s (68 °F / 20 °C)
		1.49 mPa.s (104 °F / 40 °C)
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : None reasonably foreseeable.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
Conditions to avoid : No decomposition if used as directed.
Incompatible materials : None known.
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Ingestion
Inhalation
Skin contact
Eye contact

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : LD50 (Rat, female): 4,130 mg/kg
Acute inhalation toxicity : LC50 (Rat, male and female): > 2.36 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity : LD50 (Rabbit, male and female): 2,010 mg/kg

Components:

1,2,4-trimethylbenzene:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

xylene:

Acute oral toxicity : LD50 (Rat, female): 3,523 mg/kg
Acute inhalation toxicity : LC50 (Rat): 27.124 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rabbit): 12,126 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

flumetralin (ISO):

- Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat, male and female): > 2.41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
- LD50 (Rabbit, male and female): > 2,000 mg/kg
Assessment: The component/mixture is minimally toxic after single contact with skin.

poly(oxy-1,2-ethanediyl), alpha-[4-(1,1,3,3-tetramethylbutyl)phenyl]-omega-hydroxy-:

- Acute oral toxicity : LD50 (Rat): 1,900 - 5,000 mg/kg

ethylbenzene:

- Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

calcium bis(dodecylbenzenesulphonate), branched:

- Acute dermal toxicity : LD50 (Rat, male and female): > 1,000 - 1,600 mg/kg

2-ethylhexan-1-ol:

- Acute oral toxicity : LD50 (Rat): 2,047 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 0.89 - 5.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : LD50 (Rat): > 3,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

toluene:

- Acute oral toxicity : LD50 (Rat, male): 5,580 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male): 25.7 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male): > 5,000 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Result : Mild skin irritation

Components:

1,2,4-trimethylbenzene:

Result : Irritating to skin.

xylene:

Species : Rabbit
Result : Irritating to skin.

flumetralin (ISO):

Species : Rabbit
Result : No skin irritation

calcium bis(dodecylbenzenesulphonate), branched:

Result : Irritating to skin.

2-ethylhexan-1-ol:

Species : Rabbit
Result : Irritating to skin.

toluene:

Species : Rabbit
Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Species : Rabbit
Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Components:

1,2,4-trimethylbenzene:

Result : Eye irritation

xylene:

Species : Rabbit
Result : Eye irritation

flumetralin (ISO):

Species : Rabbit
Result : No eye irritation

poly(oxy-1,2-ethanediyl), alpha-[4-(1,1,3,3-tetramethylbutyl)phenyl]-omega-hydroxy-:

Result : Risk of serious damage to eyes.

calcium bis(dodecylbenzenesulphonate), branched:

Result : Risk of serious damage to eyes.

2-ethylhexan-1-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

toluene:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Product:

Species : Guinea pig
Result : May cause sensitization by skin contact.

Components:

xylene:

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Result : Not a skin sensitizer.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

flumetralin (ISO):

Test Type	: Local lymph node assay (LLNA)
Result	: Does not cause skin sensitization.

2-ethylhexan-1-ol:

Species	: Humans
Result	: Not a skin sensitizer.

toluene:

Species	: Guinea pig
Result	: Does not cause skin sensitization.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

xylene:

Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.
-------------------------------------	--

flumetralin (ISO):

Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.
-------------------------------------	--

2-ethylhexan-1-ol:

Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.
-------------------------------------	--

toluene:

Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.
-------------------------------------	--

Carcinogenicity

Suspected of causing cancer.

Components:

xylene:

Carcinogenicity - Assessment	: No evidence of carcinogenicity in animal studies.
------------------------------	---

flumetralin (ISO):

Carcinogenicity - Assessment	: No evidence of carcinogenicity in animal studies.
------------------------------	---

2-ethylhexan-1-ol:

Carcinogenicity - Assessment	: No evidence of carcinogenicity in animal studies.
------------------------------	---

toluene:

Carcinogenicity - Assessment	: No evidence of carcinogenicity in animal studies.
------------------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

IARC	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

Components:

xylene:

Reproductive toxicity - Assessment : No toxicity to reproduction, No effects on or via lactation

flumetralin (ISO):

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

2-ethylhexan-1-ol:

Reproductive toxicity - Assessment : No toxicity to reproduction, No effects on or via lactation

toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

May cause respiratory irritation.

Components:

1,2,4-trimethylbenzene:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

xylene:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

2-ethylhexan-1-ol:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

toluene:

Routes of exposure : Inhalation
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure

May cause damage to organs (Central nervous system, Kidney, Liver, hearing organs) through prolonged or repeated exposure.

Components:

xylene:

Target Organs : Central nervous system, Kidney, Liver
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

flumetralin (ISO):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

ethylbenzene:

Target Organs : hearing organs
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

2-ethylhexan-1-ol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

toluene:

Routes of exposure : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

May be fatal if swallowed and enters airways.

1,2,4-trimethylbenzene:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

xylene:

May be fatal if swallowed and enters airways.

ethylbenzene:

May be fatal if swallowed and enters airways.

toluene:

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 6.26 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 27.7 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Navicula pelliculosa (Freshwater diatom)): 0.0254 mg/l Exposure time: 72 h NOEC (Navicula pelliculosa (Freshwater diatom)): 0.01 mg/l End point: Growth rate Exposure time: 72 h ErC50 (Raphidocelis subcapitata (freshwater green alga)): 25 mg/l Exposure time: 72 h NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.097 mg/l End point: Growth rate Exposure time: 72 h

Components:

1,2,4-trimethylbenzene:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 7.72 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3.6 mg/l Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.
--------------------------	---	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

xylene:

Toxicity to algae/aquatic plants : EC50: 2.2 mg/l
Exposure time: 72 h

NOEC: 0.44 mg/l
Exposure time: 72 h

flumetralin (ISO):

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.023 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Americamysis): 0.094 mg/l
Exposure time: 96 h

EC50 (Daphnia magna (Water flea)): > 0.16 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 0.000135 mg/l
Exposure time: 96 h

EC10 (Skeletonema costatum (marine diatom)): 0.000047 mg/l
End point: Growth rate
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): > 0.0011 - < 0.0023 mg/l
Exposure time: 38 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 0.0088 mg/l
Exposure time: 21 d

poly(oxy-1,2-ethanediyl), alpha-[4-(1,1,3,3-tetramethylbutyl)phenyl]-omega-hydroxy-:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4 - 8.9 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 18 - 26 mg/l
Exposure time: 48 h

Toxicity to microorganisms : IC50 (Bacteria): 5,000 mg/l
Exposure time: 16 h

ethylbenzene:

Toxicity to fish : LC50 (Marine species): 5.1 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): 2.6 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (Water flea)): 0.96 mg/l
Exposure time: 7 d

calcium bis(dodecylbenzenesulphonate), branched:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-ethylhexan-1-ol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 17.1 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 16.6 mg/l
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 5.3 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : EC10 (Danio rerio (zebra fish)): 0.28 mg/l
Exposure time: 35 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 1.5 mg/l

toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (Water flea)): 0.74 mg/l
Exposure time: 7 d

Persistence and degradability

Components:

xylene:

Biodegradability : Result: Readily biodegradable.

flumetralin (ISO):

Biodegradability : Result: Not readily biodegradable.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

Stability in water : Remarks: Product is not persistent.

poly(oxy-1,2-ethanediyl), alpha-[4-(1,1,3,3-tetramethylbutyl)phenyl]-omega-hydroxy-:

Biodegradability : Result: Readily biodegradable.

ethylbenzene:

Biodegradability : Result: Readily biodegradable.

2-ethylhexan-1-ol:

Biodegradability : Result: Readily biodegradable.

toluene:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

flumetralin (ISO):

Bioaccumulation : Remarks: Bioaccumulates

Partition coefficient: n-octanol/water : log Pow: 5.53 (77 °F / 25 °C)

toluene:

Bioaccumulation : Remarks: Does not bioaccumulate.

Mobility in soil

Components:

flumetralin (ISO):

Distribution among environmental compartments : Remarks: immobile

Stability in soil : Remarks: Product is not persistent.

Other adverse effects

Components:

2-ethylhexan-1-ol:

Results of PBT and vPvB assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).

toluene:

Results of PBT and vPvB assessment : Substance is not persistent, bioaccumulative, and toxic (PBT).
Substance is not very persistent and very bioaccumulative (vPvB).

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste Code : D001: Ignitability

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.
Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.
This product will be a RCRA characteristic hazardous waste when discarded. Please see section 15 for applicable CERCLA reportable quantities

Contaminated packaging : Empty remaining contents.
Triple rinse containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(PSEUDOCUMENE, XYLENES)
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(PSEUDOCUMENE, XYLENES)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(PSEUDOCUMENE, XYLENES)
Class : 3
Packing group : III
Labels : 3

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(PSEUDOCUMENE, XYLENES)
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

Danger

Corrosive

Causes irreversible eye damage.

Do not get in eyes, on skin, or on clothing.

Wear protective eyewear, goggles, or face shields.

Causes skin irritation.

Avoid contact with skin, eyes or clothing.

Harmful if swallowed.

Harmful if absorbed through skin.

Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

Remove and wash contaminated clothing before re-use.

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylene	1330-20-7	100	557

A characteristic waste RQ of 100 lbs applies to this product in a waste form: D001

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

1,2,4-trimethylbenzene	95-63-6	>= 20 - < 30 %
xylene	1330-20-7	>= 10 - < 20 %
ethylbenzene	100-41-4	>= 5 - < 10 %


California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Syngenta	:	Syngenta Occupational Exposure Limits
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-2 / CEIL	:	Acceptable ceiling concentration
OSHA Z-2 / Peak	:	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
Syngenta / TWA	:	Time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Con-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



PRIME + EC

Version	Revision Date:	SDS Number:	Date of last issue: 11/28/2017
2.1	05/06/2025	S00047442629	Date of first issue: 11/28/2017

trol Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/06/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN