

130 S. 100 W. **BURLEY, IDAHO, USA 83318** 208.678.2610 WWW.REDOXCHEM.COM MANUFACTURED BY:





VÍA A MATAMOROS NO. 1501, SAN NICOLÁS DE LOS GARZA, N.L., MÉXICO C.P. 66484 TEL. +52 (8I) 8625-3100 WWW.COSMOCEL.COM SERVICIOACLIENTES@COSMOCEL.COM

Soilex

CONTAINS NON PLANT FOOD INGREDIENTS

6.00% Alcohols, C9-16, ethoxylated

F001388

KEEP OUT OF REACH OF CHILDREN

SHAKE OR AGITATE WELL BEFORE USE

GENERAL INFORMATION:

the root zone, early in the plant life cycle or applied as a pre-plant.

APPLICATION GUIDELINES:

- Proper application rates and frequency should be determined by specific
- Agitate container prior to usage.
- Always jar test before adding to a spray tank or injection tank.
- be made with sufficient water, 50 mesh screens, and agitation throughout the
- When tank mixing with other chemicals, it is the responsibility of the end-user to assume compatibility and safety.
- Poly in-line filters should be replaced with stainless steel, if possible.
- Always consult your agronomist.

DIRECTIONS FOR USE:

Soilex applications can be done through any irrigation system (drip, microjets, etc.) or with furrow

For best results, utilize and understand the soil problems through soil analysis, combined with good agronomic

APPLICATION RATES:

APPLICATION	RATE
Soil	0.25 - 3 gal./acre

Redox products should be stored in a cool dry place, out of direct sunlight. To maintain product quality, storage temperatures should be between 50°F and 90°F. Always store liquid products on lower shelves and dry products on higher shelves. Do not stack palletized products. Open containers must be resealed for storage. Strictly adhering to Redox storage guidelines will ensure efficacy and performance for the life of the product. If you have a question about the storage, disposal, or shelf-life of your Redox product, contact your local Redox representative or call 1-208-678-2610.

LIMITED WARRANTY AND DISCLAIMER

Limited Warranty: Redox Chemicals, LLC ("Redox") warrants that: (a) the product referred to therein, when it is used in accordance with such directions. Tests have

Limitation of Remedies: Buyer's exclusive remedy and Redox's obligation under this

exclusive agreement between the parties, superseding all prior agreements, oral or matter of this agreement. No employee of Redox or any other party is authorized to may be varied only by agreement in writing signed an authorized representative of

Disclaimer of Warranty: THE ABOVE LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH EXTENDS BEYOND THE WARRANTY SPECIFIED ABOVE, AND IN NO EVENT SHALL THIS WARRANTY BE DEEMED TO COVER INCIDENTAL OR

Venue and Choice of Law: Any claims arising from this limited warranty shall be resolved in the State of Idaho and Idaho law will apply to any dispute.


distributors. To insure proper mixing and application, consult with trained Redox

NET CONTENTS & NET WEIGHT

Weight per gallon at 68° Farhenheit: 8.83 Lbs.



(18.9 Lts.) 44.15 Lbs. (20.07 Kgs.)



03/18

N.P. 1404142 Rev. 3