according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

SECTION 1. IDENTIFICATION

Product name : Suspend PolyZone

Product code : Article/SKU: 84941190 UVP: 84493910 Specification:

102000030997 EPA Registration No: 101563-143

Manufacturer or supplier's details

Company name of supplier : Environmental Science U.S. LLC.

Address : 5000 Centregreen Way, Suite 400

Cary NC 27513

Telephone : 1-800-331-2867

Emergency telephone : +1 703-741-5970

E-mail address : uscontact@envu.com

Recommended use of the chemical and restrictions on use

Recommended use : Insecticide

Restrictions on use : See product label for restrictions.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR

1910.1200)

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary Statements : Prevention:

P264 Wash skin thoroughly after handling.

according to the OSHA Hazard Communication Standard



Suspend PolyZone

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/17/2023

 2.0
 01/31/2024
 11247147-00002
 Date of first issue: 07/17/2023

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves, eye protection and face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see supplemental first aid instructions on this label).

P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Suspension concentrate (=flowable concentrate)(SC)

Components

Chemical name CAS-No.		Concentration (% w/w)	
Propylene glycol	57-55-6	>= 10 - < 20	
Deltamethrin	52918-63-5	>= 1 - < 5	
Silicon, amorphous	112945-52-5	>= 1 - < 5	

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version SDS Number: Date of last issue: 07/17/2023 Revision Date: 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

> Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed If swallowed, DO NOT induce vomiting unless directed to do

so by medical personnel. Get medical attention.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No symptoms known or expected.

Harmful if swallowed. Causes skin irritation.

Causes serious eye irritation. This product contains a pyrethroid.

Pyrethroid poisoning should not be confused with carbamate

or organophosphate poisoning.

Protection of first-aiders First Aid responders should pay attention to self-protection,

> and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

There is no specific antidote available. Notes to physician

Treat symptomatically.

In case of ingestion gastric lavage should be considered in cases of significant ingestions only within the first 2 hours. However, the application of activated charcoal and sodium

sulphate is always advisable.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Bromine compounds

Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers.

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Remove undamaged containers from fire area if it is safe to do

SO

Evacuate area.

Special protective equipment

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid inhalation of vapor or mist.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propylene glycol	57-55-6	TWA	10 mg/m ³	US WEEL
Silicon, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m³ (Silica)	NIOSH REL

Engineering measures: Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : light beige, white

Odor : characteristic

Odor Threshold : No data available

pH : <= 7 (73 °F / 23 °C)

Concentration: 100 %

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

flammability limit

Vapor pressure : No data available

Relative vapor density : No data available

Density : ca. 1.05 g/cm³ (68 °F / 20 °C)

Solubility(ies)

Water solubility : dispersible

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 700,000 - 1,700,000 mPa.s (77 °F / 25 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : Not applicable

Particle size : $\leq 3 \mu m$

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: 2.0 01/31/2024 11247147-00002

Date of last issue: 07/17/2023 Date of first issue: 07/17/2023

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,833 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 18.96 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Propylene glycol:

Acute oral toxicity : LD50 (Rat): 22,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 44.9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Deltamethrin:

Acute oral toxicity : LD50 (Rat, female): 87 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0.6 mg/l

Exposure time: 6 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Silicon, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit
Result : Skin irritation

Components:

Propylene glycol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Deltamethrin:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Silicon, amorphous:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Components:

Propylene glycol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Deltamethrin:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Silicon, amorphous:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Species : Guinea pig

Result : Does not cause skin sensitization.

Components:

Propylene glycol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Deltamethrin:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Propylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Deltamethrin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 473

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro) Method: OECD Test Guideline 482

Result: negative

Silicon, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Propylene glycol:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Deltamethrin:

Species : Rat Application Route : Ingestion

Method : OECD Test Guideline 453

Result : negative

Silicon, amorphous:

Species : Rat

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Propylene glycol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: negative

Deltamethrin:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Silicon, amorphous:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version SDS Number: Date of last issue: 07/17/2023 Revision Date: 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Deltamethrin:

Assessment No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Propylene glycol:

: Rat, male Species NOAEL >= 1,700 mg/kg

Application Route : Ingestion : 2 y Exposure time

Deltamethrin:

Dog Species NOAEL 1 mg/kg LOAEL 10 mg/kg Application Route : Ingestion : 52 Weeks Exposure time

Method : OECD Test Guideline 452

Silicon, amorphous:

Species Rat NOAEL 1.3 mg/l

inhalation (dust/mist/fume)13 Weeks Application Route

Exposure time

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propylene glycol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Ceriodaphnia dubia (water flea)): 18,340 mg/l

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version SDS Number: Date of last issue: 07/17/2023 Revision Date: 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Skeletonema costatum (marine diatom)): 19,300 mg/l

plants Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEC (Ceriodaphnia dubia (water flea)): 13,020 mg/l aquatic invertebrates (Chron-

ic toxicity)

NOEC (Pseudomonas putida): > 20,000 mg/l Toxicity to microorganisms

Exposure time: 18 h

Deltamethrin:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0.15 µg/l

Exposure time: 7 d

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Gammarus fasciatus (freshwater shrimp)): 0.0003 μg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

ErC50 (Chlorella vulgaris (Fresh water algae)): > 0.47 mg/l

Exposure time: 96 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.017 µg/l

Exposure time: 260 d

aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.0041 µg/l

Exposure time: 21 d

Toxicity to microorganisms : EC50 (activated sludge): > 0.3 mg/l

Exposure time: 3 h

Silicon, amorphous:

Toxicity to fish LC50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000

mg/l

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version SDS Number: Date of last issue: 07/17/2023 Revision Date: 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Persistence and degradability

Components:

Propylene glycol:

Biodegradability Result: Readily biodegradable.

Biodegradation: 98.3 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Deltamethrin:

Result: Not readily biodegradable. Biodegradability

> Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

Propylene glycol:

Partition coefficient: n-

log Pow: -1.07

octanol/water

Method: Regulation (EC) No. 440/2008, Annex, A.8

Deltamethrin:

Bioaccumulation Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1,400

Partition coefficient: n-

octanol/water

log Pow: 6.4

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues It is best to use all of the product in accordance with label

> directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local

guidelines.

Do not dispose of waste into sewer.

Contaminated packaging Follow advice on product label and/or leaflet.

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version SDS Number: Date of last issue: 07/17/2023 Revision Date: 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Empty containers retain residue and can be dangerous.

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Deltamethrin)

9 Class Ш Packing group Labels 9 Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(Deltamethrin)

9 Class Ш Packing group

Miscellaneous Labels

Packing instruction (cargo 964

aircraft)

Packing instruction (passen-

ger aircraft)

964

Environmentally hazardous yes

IMDG-Code

UN 3082 **UN** number

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Deltamethrin)

Class 9 Packing group Ш Labels EmS Code F-A, S-F Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(Deltamethrin)

Class 9 Packing group Ш CLASS 9 Labels **ERG Code** 171

Marine pollutant yes(Deltamethrin)

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Water7732-18-5Propylene glycol57-55-6Non-hazardousNot AssignedDeltamethrin52918-63-5Silicon, amorphous112945-52-5

California Permissible Exposure Limits for Chemical Contaminants

Silicon, amorphous 112945-52-5

Product Type : Insecticides, acaricides and products to control other arthro-

pods

Active substance : 4.7477 %

Deltamethrin

SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



Suspend PolyZone

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 2.0 01/31/2024 11247147-00002 Date of first issue: 07/17/2023

NFPA 704:

Flammability Health 2 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic sub-

according to the OSHA Hazard Communication Standard



Suspend PolyZone

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/17/2023

 2.0
 01/31/2024
 11247147-00002
 Date of first issue: 07/17/2023

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 01/31/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8