

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15
Version: 4.0

Page: 1/10
(30587723/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Sepiret 4350 Green

Recommended use of the chemical and restriction on use

Recommended use*: Seed coating

Recommended use*: colouring component

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932
USA
Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Carc.	1A (by inhalation)	Carcinogenicity

Label elements

Pictogram:

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15
Version: 4.0

Page: 2/10
(30587723/SDS_GEN_US/EN)



Signal Word:
Danger

Hazard Statement:
H350 May cause cancer by inhalation.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P201 Obtain special instructions before use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P202 Do not handle until all safety precautions have been read and understood.
P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

Labeling of special preparations (GHS):

May produce an allergic reaction. Contains: 1,2-benzisothiazol-3(2H)-one, mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
12001-26-2	5.0 - 15.0%	Mica-group minerals
13463-67-7	5.0 - 15.0%	Titanium dioxide
57-55-6	5.0 - 15.0%	Propylene glycol
14808-60-7	0.1 - 1.0%	crystalline silica

4. First-Aid Measures

Description of first aid measures

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15

Version: 4.0

Page: 3/10
(30587723/SDS_GEN_US/EN)

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

If on skin:

Wash thoroughly with soap and water.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:

Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam, carbon dioxide

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon monoxide, carbon dioxide, nitrogen oxides
The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Keep containers cool by spraying with water if exposed to fire. In case of fire and/or explosion do not breathe fumes. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/spray. Use personal protective clothing. Avoid contact with the skin, eyes and clothing.

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15
Version: 4.0

Page: 4/10
(30587723/SDS_GEN_US/EN)

Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr).

For large amounts: Dike spillage. Pump off product.

Dispose of absorbed material in accordance with regulations. Collect waste in suitable containers, which can be labeled and sealed. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations.

7. Handling and Storage

Precautions for safe handling

No special measures necessary if stored and handled correctly. Ensure thorough ventilation of stores and work areas. When using do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift.

Protection against fire and explosion:

No special precautions necessary. The substance/product is non-combustible. Product is not explosive.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Further information on storage conditions: Keep away from heat. Protect from direct sunlight.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Rutile (TiO ₂)	OSHA PEL	PEL 15 mg/m ³ Total dust ; TWA value 10 mg/m ³ Total dust ;
C.I. Pigment Green 7	ACGIH TLV	TWA value 1 mg/m ³ Dust and mist (copper (Cu)); TWA value 0.2 mg/m ³ fumes/smoke (copper (Cu));
Mica-group minerals	OSHA PEL	TWA value 3 mg/m ³ Respirable dust ; TWA value 20 millions of particles per cubic foot of air ;
	ACGIH TLV	TWA value 3 mg/m ³ Respirable fraction ;
Titanium dioxide	OSHA PEL	PEL 15 mg/m ³ Total dust ; TWA value 10 mg/m ³ Total dust ;
	ACGIH TLV	TWA value 10 mg/m ³ ;

Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15
Version: 4.0

Page: 5/10
(30587723/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas and vapours. For situations where the airborne concentrations may exceed the level for which an air purifying respirator is effective, or where the levels are unknown or Immediately Dangerous to Life or Health (IDLH), use NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Store work clothing separately. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

Form:	liquid
Odour:	slight odour
Odour threshold:	Not determined due to potential health hazard by inhalation.
Colour:	green
pH value:	approx. 8 - 9 (20 °C)
Melting temperature:	approx. 0 °C Information applies to the solvent.
boiling temperature:	approx. 100 °C Information applies to the solvent.
Flash point:	> 100 °C
Flammability:	not applicable
Lower explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Upper explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Autoignition:	Based on the water content the product does not ignite.

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15

Version: 4.0

Page: 6/10

(30587723/SDS_GEN_US/EN)

Vapour pressure:	approx. 23.4 hPa (20 °C) Information applies to the solvent.
Density:	approx. 1.2 g/cm3 (20 °C)
Vapour density:	not applicable
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, kinematic:	Forms a viscous solution.
Solubility in water:	dispersible
Evaporation rate:	not applicable
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15
Version: 4.0

Page: 7/10
(30587723/SDS_GEN_US/EN)

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral

Type of value: ATE
Value: > 5,000 mg/kg

Inhalation

Type of value: ATE
Value: > 20.0000 mg/l
Determined for vapor

Type of value: ATE
Value: > 5.0000 mg/l
Determined for mist

Dermal

Type of value: ATE
Value: > 5,000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

The product has not been tested. The statement has been derived from the properties of the individual components.

Irritation / corrosion

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Genetic toxicity

Assessment of mutagenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components. The results of animal studies gave no indication of a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Other Information

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15

Version: 4.0

Page: 8/10

(30587723/SDS_GEN_US/EN)

Misuse can be harmful to health.

Symptoms of Exposure

Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Toxicity to fish

No data available.

Aquatic invertebrates

No data available.

Aquatic plants

No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

The product has not been tested. The statement has been derived from the properties of the individual components. Colourants are by their nature very stable and are therefore not readily biodegradable under conditions prevailing in surface water or in effluent treatment plants.

Bioaccumulative potential

Assessment bioaccumulation potential

The product has not been tested. The statement has been derived from the properties of the individual components.

Bioaccumulation potential

Significant accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is expected.

The product has not been tested. The statement has been derived from the properties of the individual components.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control.

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15
Version: 4.0

Page: 9/10
(30587723/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Must be disposed of or incinerated in accordance with local regulations.

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Hazard class: 9
ID number: UN 8888
Hazard label:
Proper shipping name: LOCKED FOR IATA TRANSPORT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
PA	12001-26-2	Mica-group minerals
	13463-67-7	Titanium dioxide
	14808-60-7	crystalline silica
	57-55-6	Propylene glycol
MA	12001-26-2	Mica-group minerals
	14808-60-7	crystalline silica
	13463-67-7	Titanium dioxide
	12001-26-2	Mica-group minerals
NJ	13463-67-7	Titanium dioxide
	1328-53-6	C.I. Pigment Green 7
	57-55-6	Propylene glycol

Safety Data Sheet

Sepiret 4350 Green

Revision date : 2019/10/15

Version: 4.0

Page: 10/10

(30587723/SDS_GEN_US/EN)

14808-60-7

crystalline silica

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including FORMALDEHYDE (GAS), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2019/10/15

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET