




## SPI227 - Hydro Detail Interior Ceramic

### SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** SPI227 - Hydro Detail Interior Ceramic  
**Other means of identification:**  
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses: Chemical cleaning products  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
Chemical Guys  
3501 Sepulveda Blvd  
90505 Torrance - California - United States  
Phone: 866-822-3670 - Fax: 310-988-1061  
info@ChemicalGuys.com  
www.ChemicalGuys.com
- 1.4 Emergency phone number:** INFOTRAC Acct. #116262  
US: 1-800-535-5053 International: +1-352-323-3500

### SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**29 CFR 1910.1200:**  
While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
- 2.2 Label elements:**  
**29 CFR 1910.1200:**  
**Hazard statements:**  
Not applicable (N/A)  
**Precautionary statements:**  
P101: If medical advice is needed, have product container or label at hand.  
P102: Keep out of reach of children.  
P501: Dispose of the contents/containers according to the local, state and federal regulations.  
**Additional labeling:**
- 
- WARNING**  
Keep out of the reach of children  
This product can expose you to chemicals including methanol, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).
- 2.3 Hazards not otherwise classified (HNOC):**  
Not applicable (N/A)

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substances:**  
Non-applicable
- 3.2 Mixtures:**  
**Chemical description:** Aqueous mixture composed of additives  
**Components:**  
Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification	Concentration
CAS: 67-63-0	<b>propan-2-ol</b> Eye Irrit. 2A: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	1 - <2.5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### SECTION 4: FIRST-AID MEASURES

#### 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

##### By inhalation:

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

##### By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

##### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

##### By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS of this product.

#### 4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1 Suitable (and unsuitable) extinguishing media:

##### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

##### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

##### Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

#### 6.1 Personal precautions, protective equipment and emergency procedures:

##### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

##### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### 6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

##### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

##### B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

##### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

##### D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

##### A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 6 Months

##### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
propan-2-ol CAS: 67-63-0	8-hour TWA PEL	400 ppm	980 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
propan-2-ol CAS: 67-63-0	TLV-TWA	200 ppm	
	TLV-STEL	400 ppm	

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
propan-2-ol CAS: 67-63-0	PEL	400 ppm	980 mg/m <sup>3</sup>
	STEL	500 ppm	1225 mg/m <sup>3</sup>

#### Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
propan-2-ol CAS: 67-63-0	40 mg/L	Acetone in urine	End of shift at end of workweek

#### 8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Not applicable (N/A)

D.- Eye and face protection

Not applicable (N/A)

E.- Bodily protection

Not applicable (N/A)

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

##### Appearance:

Physical state at 68 °F:

Liquid

Appearance:

Transparent

Color:

 Yellow

Odor:

Characteristic

\*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour threshold:	Not applicable (N/A) *
<b>Volatility:</b>	
Boiling point at atmospheric pressure:	211 °F
Vapour pressure at 68 °F:	2370 Pa
Vapour pressure at 122 °F:	12474.09 Pa (12.47 kPa)
Evaporation rate at 68 °F:	Not applicable (N/A) *
<b>Product description:</b>	
Density at 68 °F:	1025.1 kg/m <sup>3</sup>
Relative density at 68 °F:	1.025
Dynamic viscosity at 68 °F:	Not applicable (N/A) *
Kinematic viscosity at 68 °F:	Not applicable (N/A) *
Kinematic viscosity at 104 °F:	Not applicable (N/A) *
Concentration:	Not applicable (N/A) *
pH:	5.2
Vapour density at 68 °F:	Not applicable (N/A) *
Partition coefficient n-octanol/water 68 °F:	Not applicable (N/A) *
Solubility in water at 68 °F:	Not applicable (N/A) *
Solubility properties:	Not applicable (N/A) *
Decomposition temperature:	Not applicable (N/A) *
Melting point/freezing point:	Not applicable (N/A) *
<b>Flammability:</b>	
Flash Point:	Non Flammable (>199.4 °F)
Flammability (solid, gas):	Not applicable (N/A) *
Autoignition temperature:	437 °F
Lower flammability limit:	Not applicable (N/A) *
Upper flammability limit:	Not applicable (N/A) *
<b>Particle characteristics:</b>	
Median equivalent diameter:	Non-applicable

#### 9.2 Other information:

##### Information with regard to physical hazard classes:

Explosive properties:	Not applicable (N/A) *
Oxidising properties:	Not applicable (N/A) *
Corrosive to metals:	Not applicable (N/A) *
Heat of combustion:	Not applicable (N/A) *
Aerosols-total percentage (by mass) of flammable components:	Not applicable (N/A) *

##### Other safety characteristics:

Surface tension at 68 °F:	Not applicable (N/A) *
Refraction index:	Not applicable (N/A) *

\*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 10: STABILITY AND REACTIVITY (continued)

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: propan-2-ol (3); d-limonene (3); Coumarin (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

#### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Not applicable (N/A)

#### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
propan-2-ol CAS: 67-63-0	LD50 oral	5280 mg/kg	Rat
	LD50 dermal	12800 mg/kg	Rat
	LC50 inhalation	72.6 mg/L (4 h)	Rat

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### 12.1 Ecotoxicity (aquatic and terrestrial, where available):

##### Acute toxicity:

Identification	Concentration		Species	Genus
propan-2-ol CAS: 67-63-0	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

#### 12.2 Persistence and degradability:

##### Substance-specific information:

Identification	Degradability		Biodegradability	
propan-2-ol CAS: 67-63-0	BOD5	1.19 g O2/g	Concentration	100 mg/L
	COD	2.23 g O2/g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %

#### 12.3 Bioaccumulative potential:

##### Substance-specific information:

Identification	Bioaccumulation potential	
propan-2-ol CAS: 67-63-0	BCF	3
	Pow Log	0.05
	Potential	Low

#### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
propan-2-ol CAS: 67-63-0	Koc	1.5	Henry	8.207E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.24E-2 N/m (77 °F)	Moist soil	Yes

#### 12.5 Results of PBT and vPvB assessment:

Non-applicable

#### 12.6 Other adverse effects:

Not described

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Disposal methods:

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

#### Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

#### Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

### SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:

- |  |                      |
|--|----------------------|
| <b>14.1 UN number:</b>   | Not applicable (N/A) |
| <b>14.2 UN proper shipping name:</b>   | Not applicable (N/A) |
| <b>14.3 Transport hazard class(es):</b>  | Not applicable (N/A) |
| Labels:  | Not applicable (N/A) |
| <b>14.4 Packing group, if applicable:</b>  | Not applicable (N/A) |
| <b>14.5 Marine pollutant:</b>  | No                   |
| <b>14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises</b> |                      |
| Physico-Chemical properties:   | see section 9        |
| <b>14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):</b>  | Not applicable (N/A) |

#### Transport of dangerous goods by sea:

With regard to IMDG 41-22:

- |  |                      |
|--|----------------------|
| <b>14.1 UN number:</b>   | Not applicable (N/A) |
| <b>14.2 UN proper shipping name:</b>   | Not applicable (N/A) |
| <b>14.3 Transport hazard class(es):</b>  | Not applicable (N/A) |
| Labels:  | Not applicable (N/A) |
| <b>14.4 Packing group, if applicable:</b>  | Not applicable (N/A) |
| <b>14.5 Marine pollutant:</b>  | No                   |
| <b>14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises</b> |                      |
| Special regulations:   | Not applicable (N/A) |
| EmS Codes:   |                      |
| Physico-Chemical properties:   | see section 9        |
| Limited quantities:  | Not applicable (N/A) |
| Segregation group:   | Not applicable (N/A) |
| <b>14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):</b>  | Not applicable (N/A) |

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- CONTINUED ON NEXT PAGE -





## SPI227 - Hydro Detail Interior Ceramic

### SECTION 14: TRANSPORT INFORMATION (continued)

- |  |                      |
|--|----------------------|
| <b>14.1 UN number:</b>   | Not applicable (N/A) |
| <b>14.2 UN proper shipping name:</b>   | Not applicable (N/A) |
| <b>14.3 Transport hazard class(es):</b>  | Not applicable (N/A) |
| Labels:  | Not applicable (N/A) |
| <b>14.4 Packing group, if applicable:</b>  | Not applicable (N/A) |
| <b>14.5 Marine pollutant:</b>  | No                   |
| <b>14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises</b> |                      |
| Physico-Chemical properties:   | see section 9        |
| <b>14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):</b>  | Not applicable (N/A) |

### SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations specific for the product in question:**

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *propan-2-ol (67-63-0)* ; *Acetic acid (64-19-7)* ; *methanol (67-56-1)* ; *potassium hydroxide (1310-58-3)* ; *Diethyl phthalate (84-66-2)* ; *Coumarin (91-64-5)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *methanol (67-56-1)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Not applicable (N/A)
- CANADA-Domestic Substances List (DSL): *All components of this product comply with the inventory requirements administered by the governing country.*
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *Acetic acid (64-19-7) - 5000 lb* ; *methanol (67-56-1) - U154* ; *potassium hydroxide (1310-58-3) - 1000 lb* ; *Diethyl phthalate (84-66-2) - U088*
- Hazardous Air Pollutants (Clean Air Act): *methanol (67-56-1)*
- NTP (National Toxicology Program): Not applicable (N/A)
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Not applicable (N/A)
- The Toxic Substances Control Act (TSCA) : *All components of this product comply with the inventory requirements administered by the governing country.*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *propan-2-ol (67-63-0)* ; *methanol (67-56-1)* ; *Magnesium nitrate (10377-60-3)*

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

**Other legislation:**

Take into consideration other applicable federal, state, and local laws and local regulations.

- CONTINUED ON NEXT PAGE -



## SPI227 - Hydro Detail Interior Ceramic

### SECTION 16: OTHER INFORMATION

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**29 CFR 1910.1200:**

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Advice related to training:**

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

**Principal bibliographical sources:**

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 8/19/2024

Revised: 8/23/2024

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET